



## Surge Suppression Receptacles



- 125V
- Power On indicator light

Provide point-of-use protection that can cause premature electronic equipment failure. Audible alarm alerts occupants when device needs replacement. Features a high-impact, nylon face that resists damage. Isolated ground-grade models protect equipment from effects of noise on the ground circuit. For use in accordance with NEC/NFPA Article 250-74, Exception 2. UL Listed and CSA Certified.



6C132

Amps	NEMA Recept. Config.	Application Environment	Special Features	Mr. Model	BLUE Item No.	IVORY Item No.	ORANGE Item No.
<b>Hubbell Wiring Device-Kellems</b>							
15 A	5-15R	Commercial	—	HBL5260SA	3D184	3D183	—
15 A	5-15R	Harsh and Heavy Use Industrial	Audible Alarm	HBL5262SA	6C132	—	—
15 A	5-15R	Industrial	Audible Alarm	IG5262SA	6C134	—	—
20 A	5-20R	Commercial	—	HBL5360SA	3D205	3D204	—
20 A	5-20R	Harsh and Heavy Use Industrial	Audible Alarm	HBL5362SA	6C133	6C605	—
20 A	5-20R	Hospital Grade	Audible Alarm	HBL8362SA	6C136	3D287	—
20 A	5-20R	Hospital Grade	Audible Alarm	IG8362SA	3D407	4D331	—
20 A	5-20R	Industrial	Audible Alarm	IG5362SA	6C135	—	—
<b>Bryant</b>							
15 A	5-15R	Commercial	Audible Alarm	SP52A	49YZ33	52HE21	—
15 A	5-15R	Hospital Grade	Audible Alarm	SP82A	49YZ36	52HE25	—
15 A	5-15R	Hospital Grade	Audible Alarm	SP821GA	49YZ37	52HE26	52HE27
20 A	5-20R	Commercial	Audible Alarm	SP53A	49YZ34	52HE23	—
20 A	5-20R	Commercial	Audible Alarm	SP531GA	49YZ35	52HE24	—
20 A	5-20R	Hospital Grade	Audible Alarm	SP83A	49YZ38	52HE31	—
20 A	5-20R	Hospital Grade	Audible Alarm	SP831GA	49YZ39	52HE33	52HE34

## Isolated Ground Receptacles

- 125V

Insulation-barrier construction isolates ground contacts from mounting strap for a noise-free ground. Reinforced thermoplastic polyester base with impact-resistant nylon face. For use in accordance with NEC/NFPA Article 250-74, Exception 4.



4FTW7



3D400

Amps	NEMA Recept. Config.	Outlet Type	Description	Brand	Mr. Model	GRAY Item No.	IVORY Item No.	LIGHT ALMOND Item No.	ORANGE Item No.	RED Item No.	WHITE Item No.
<b>Commercial</b>											
15 A	5-15R	Standard Duplex	Smooth	Hubbell	IG15CR	—	4ENH5	—	4ENH2	—	4ENH7
15 A	5-15R	Standard Duplex	—	Bryant	CR151G	—	—	—	49YZ19	—	—
15 A	5-15R	Decorator Duplex	—	Hubbell	IG15DR	4ENJ1	4ENJ2	—	—	—	4ENJ4
20 A	5-20R	Standard Duplex	Smooth	Hubbell	IG20CR	4FTW5	4FTW6	4FTW7	4ENJ5	—	4FTW8
20 A	5-20R	Decorator Duplex	—	Hubbell	IG20DR	—	4FTX3	—	—	—	4FTX5
<b>Harsh and Heavy Use Industrial</b>											
15 A	5-15R	Standard Duplex	—	Bryant	BRY5262G	52HD11	—	—	49Y203	—	52HD13
15 A	5-15R	Standard Duplex	—	Bryant	BRY5262GI	—	52HD12	—	—	—	—
20 A	5-20R	Standard Duplex	—	Bryant	BRY5362IG	—	52HD25	—	49Y205	—	—
<b>Industrial</b>											
15 A	5-15R	Standard Duplex	—	Hubbell	IG5262	3D401	—	—	5A075	49YK86	—
15 A	5-15R	Single	—	Hubbell	IG5261	—	—	—	3D400	—	—
15 A	5-15R	Single	—	Bryant	52611G	—	—	—	49YV68	—	—
20 A	5-20R	Standard Duplex	—	Hubbell	IG5362	—	3D406	—	5A083	—	—
20 A	5-20R	Standard Duplex	Smooth	Hubbell	IG5352	4FTY5	4FTY6	4FTY7	4FTY3	—	4FTY8
20 A	5-20R	Single	—	Bryant	53611G	—	—	—	49YY72	—	—
20 A	5-20R	Single	—	Hubbell	IG5361	—	—	—	3D404	—	—

## USB Charger Tamper-Resistant Receptacles



- 125VAC
- LED indicates USB power

- USB charging 5.0A @ 5VDC

Devices combine USB DC power and tamper-resistant AC electrical power in a standard single-gang opening, so you can charge personal electronics and power appliances from the same receptacle. Back and side wire for solid or stranded wire. UL and C-UL Listed.



437K89



437K70

Amps	NEMA Recept. Config.	Outlet Type	No. of USB Ports	USB Connector	Brand	BROWN Item No.	BLACK Item No.	GRAY Item No.	IVORY Item No.	WHITE Item No.	RED Item No.
<b>USB Charger Receptacle, Commercial Environments</b>											
15	5-15R	Decorator Duplex	2	Type A	Hubbell	437K36	437K37	437K38	437K39	437K40	—
	5-15R	Decorator Duplex	2	Type A and C	Hubbell	437K63	437K61	437K60	437K58	437K59	—
	5-15R	Decorator Duplex	2	Type C	Hubbell	437K87	437K85	437K84	437K82	437K83	437K86
	5-20R	Decorator Duplex	2	Type A	Hubbell	437K41	437K42	437K43	437K44	437K45	—
	5-20R	Decorator Duplex	2	Type A and C	Hubbell	437K69	437K67	437K66	437K64	437K65	—
20	5-20R	Decorator Duplex	2	Type C	Hubbell	437K93	437K91	437K90	437K88	437K89	437K92
<b>USB Charger Receptacle, General Purpose</b>											
15	5-15R	Decorator Duplex	2	Type A and C	Legrand	56FM95	56FM94	56FM96	—	56FM99	—
<b>USB Charger Receptacle, Hospital Grade</b>											
15	5-15R	Decorator Duplex	2	Type A	Hubbell	437K46	437K47	437K48	437K49	437K51	437K50
	5-15R	Decorator Duplex	2	Type C	Hubbell	437K99	437K97	437K96	437K94	437K95	437K98
	5-15R	Decorator Duplex	2	Type A and C	Hubbell	437K75	437K73	437K72	437K70	437K71	437K74
	5-20R	Decorator Duplex	2	Type A and C	Hubbell	437K81	437K79	437K78	437K76	437K77	437K80
	5-20R	Decorator Duplex	2	Type C	Hubbell	437L06	437L04	437L03	437L01	437L02	437L05
20	5-20R	Decorator Duplex	2	Type A	Hubbell	437K52	437K53	437K54	437K55	437K57	437K56



5Z841



5Z893



## High-Ampere Receptacles

UL Listed and CSA Certified.

\* See page 326 for NEMA plug configurations.

Amps	NEMA Recept. Config.*	No. of Poles	No. of Wires	Voltage	HUBBELL Mr. Model	HUBBELL Item No.	BRYANT Mr. Model	BRYANT Item No.
20 A	10-20R	3	3	250V AC	HBL6810	5Z839	9326	49YV66
	14-20R	3	4	125/250V AC	HBL8410	6C630	—	—
	15-20R	3	4	250V AC	HBL8420	5C793	—	—
30 A	5-30R	2	3	125V AC	HBL9308	5Z904	9530FR	49YV94
	6-30R	2	3	250V AC	HBL9330	5Z895	9630FR	49YV96
	10-30R	3	3	125/250V AC	HBL9350	5Z841	9303	49YV64
	14-30R	3	4	125/250V AC	HBL9430A	5Z883	9430FR	49YV92
	15-30R	3	4	250V AC	HBL8430A	5Z889	8430FR	49YV88
	TT-30R	2	3	125V AC	HBLT30R	54DY13	—	—
50 A	5-50R	2	3	125V AC	HBL9360	5Z896	9550FR	49YV95
	6-50R	2	3	250V AC	HBL9367	5Z897	9650FR	49YV97
	10-50R	3	3	125/250V AC	HBL7962	5Z840	9306	49YV65
	14-50R	3	4	125/250V AC	HBL9450A	5Z885	9450FR	49YV93
	15-50R	3	4	250V AC	HBL8450A	5Z891	8450FR	49YV89
60 A	14-60R	3	4	250V AC	HBL9460A	5Z887	—	—
	15-60R	3	4	250V AC	HBL8460A	5Z893	8460FR	49YV90
	18-60R	4	4	120/208V AC	HBL7301A	3D240	8360FR	49YV87