

1-800-GRAINGER (472-4643)



Hospital Grade Receptacles

These hospital grade receptacles are designed to withstand the severe conditions unique to hospital environments. Nickel-plated bypass contacts help increase contact pressure and lower operating temperature. Four-point grounding system provides redundant grounding for low resistance ground continuity, and thermoplastic polyester (RTP) back is tough and heat-resistant.

Note: To qualify for the hospital grade designation and use of the green dot symbol, UL requires product performance to specific levels. These levels form an established baseline below which no manufacturer can fall and still carry a green dot.



52HD38



5A078

Amps	NEMA Recept. Config.	Outlet Type	Tamper Resistant	Weather Resistant	Wiring Method	Voltage	Special Features	Brand	BLACK Item No.	BROWN Item No.	GRAY Item No.	IVORY Item No.	ORANGE Item No.	RED Item No.	WHITE Item No.	
Straight Blade Receptacle, Hospital Grade																
15 A	5-15R	Standard Duplex	No	No	Back and Side	125V AC	—	Bryant	—	—	—	52HC77	—	52HC79	—	
	5-15R	Standard Duplex	Yes	No	Back and Side	125V AC	—	Bryant	—	52HC80	—	52HC78	—	—	—	
	5-15R	Single	No	No	Back and Side	125V AC	—	Bryant	—	52HC32	—	49Y75	—	—	—	
	5-15R	Decorator Duplex	No	No	Back and Side	125V AC	—	Bryant	—	49YV63	52HC92	52HC93	—	52HC94	52HC95	
	5-20R	Standard Duplex	No	No	Back and Side	125V AC	—	Bryant	—	49YV76	49YV77	49YV78	49YV91	49YV81	49YV84	
	5-20R	Standard Duplex	No	No	Back and Side	125V AC	—	Bryant	—	—	—	49YV79	—	49YV82	49YV85	
20 A	5-20R	Standard Duplex	No	No	Back and Side	125V AC	Illuminated	Hubbell	—	—	—	—	—	30C268 †	—	
	5-20R	Standard Duplex	Yes	No	Back and Side	125V AC	—	Hubbell	—	—	—	—	—	52HC87	52HC88	
	5-20R	Standard Duplex	No	No	Back and Side	125V AC	—	Bryant	—	49YV83	—	52HC86	—	52HC87	52HC88	
	5-20R	Standard Duplex	Yes	No	Back and Side	125V AC	—	Hubbell	—	—	—	—	—	30C273 †	—	
	5-20R	Decorator Duplex	No	No	Back and Side	125V AC	—	Hubbell	—	—	49YL02	52HF28	—	49K75	49YK75	
	Straight Blade Receptacle, Heavy Use Hospital Grade															
15 A	5-15R	Standard Duplex	No	No	Back and Side	125V AC	—	Hubbell	—	1XC01	5Z825	5A078	5Z827	5Z823	3D285	
	5-15R	Standard Duplex	No	No	Back and Side	125V AC	—	Bryant	—	49Y206	52HD38	52HD41	49Y207	52HD43	52HD46	
	5-15R	Standard Duplex	No	No	Back and Side	125V AC	Illuminated	Hubbell	—	—	2LBX2	3D283	—	3D284	2LBX3	
	5-15R	Standard Duplex	No	No	Back and Side	125V AC	—	Hubbell	—	—	4D035	4D036	—	4D038	4D040	
	5-15R	Standard Duplex	No	No	Back and Side	125V AC	—	Hubbell	—	—	—	—	—	—	2LBV5	—
	5-15R	Standard Duplex	Yes	No	Wire Lead	125V AC	—	Bryant	—	—	—	52HD40	—	52HD45	52HD48	
20 A	5-15R	Standard Duplex	Yes	No	Wire Lead	125V AC	—	Hubbell	—	6C656	3D453	5Z829	—	3D454	3D455	
	5-15R	Standard Duplex	No	No	Back and Side	125V AC	—	Hubbell	—	—	2LBX4	3D286	—	4D045	2LBX5	
	5-20R	Standard Duplex	No	No	Back and Side	125V AC	—	Bryant	—	49Y209	52HD49	—	49Y210	—	52HD52	
	5-20R	Standard Duplex	No	No	Back and Side	125V AC	—	Hubbell	—	4D056	4D057	4D058	—	16R066	3D288	
	5-20R	Standard Duplex	No	No	Back and Side	125V AC	Illuminated	Hubbell	—	—	2LBX7	3D289	—	3D290	2LBX8	
	5-20R	Standard Duplex	No	No	Back and Side	125V AC	—	Hubbell	—	1XC02	5Z826	5A084	5Z828	5Z824	3D291	
GFCI Receptacle, Heavy Use Hospital Grade																
15 A	5-15R	Decorator Duplex	No	No	Back and Side	125V AC	—	Hubbell	39EA33	39EA36	39EA34	39EA35	—	39EA37	39EA38	
	5-15R	Decorator Duplex	No	No	Modular	125V AC	—	Hubbell	—	—	—	45UD97	—	45UD99	45UE01	
	5-15R	Decorator Duplex	Yes	Yes	Modular	125V AC	—	Hubbell	—	—	—	45UE48	—	45UE50	—	
	5-15R	Decorator Duplex	Yes	Yes	Back and Side	125V AC	—	Hubbell	39EA46	39EA49	39EA47	39EA48	—	39EA51	39EA52	
	5-15R	Decorator Duplex	Yes	No	Back and Side	125V AC	Nightlight	Hubbell	45UG10	45UG13	45UG11	45UG12	—	45UG15	45UG16	
	5-20R	Decorator Duplex	No	No	Modular	125V AC	—	Hubbell	45UE22	45UE20	45UE23	45UE24	—	45UE26	45UE27	
20 A	5-20R	Decorator Duplex	No	No	Back and Side	125V AC	—	Hubbell	39EA39	39EA42	39EA40	39EA41	—	39EA43	39EA44	
	5-20R	Decorator Duplex	Yes	No	Back and Side	125V AC	Nightlight	Hubbell	45UG18	45UG21	45UG19	45UG20	—	45UG23	45UG24	
	5-20R	Decorator Duplex	Yes	Yes	Back and Side	125V AC	—	Hubbell	39EA54	39EA57	39EA55	39EA56	—	39EA59	39EA60	
	6-20R	Standard Duplex	No	No	Back and Side	250V AC	—	Hubbell	—	—	—	4D076	—	—	—	

* Slender/compact version. † Includes green LED power indicators.

Amps AC	Switch Type	Switch Style	Mr. Model	WHITE Item No.	RED Item No.	IVORY Item No.	BLACK Item No.	
Wall Switch								
15 A	1-Pole	Toggle	SNAP1201_NA	31A352	31A413	31A350	31A410	
	3-Way	Toggle	SNAP1203_NA	31A354	—	31A353	31A415	
20 A	1-Pole	Toggle	SNAP1221_NA	31A357	31A422	31A355	31A420	
	1-Pole	Rocker	SNAP2121_NA	—	—	31A468	31A465	
Pilot Light Wall Switch								
15 A	1-Pole	Toggle	SNAP1201_PL_NA	31A433	31A432	31A431	31A430	
	1-Pole	Rocker	SNAP2101_PL_NA	—	—	—	31A452	
20 A	1-Pole	Toggle	SNAP1221_PL_NA	31A447	31A446	31A445	31A444	
	1-Pole	Rocker	SNAP2121_PL_NA	31A479	—	31A477	—	
Illuminated Wall Switch								
15 A	1-Pole	Toggle	SNAP1201_IL_NA	31A362	31A429	31A361	31A428	
	1-Pole	Rocker	SNAP2101_IL_NA	31A451	—	—	31A448	
	3-Way	Toggle	SNAP1203_IL_NA	31A440	—	—	—	
20 A	1-Pole	Toggle	SNAP2121_IL_NA	31A460	31A443	31A442	—	
Amps	NEMA Recept. Config.	Tamper Resistant	Weather Resistant	Mr. Model	WHITE Item No.	RED Item No.	IVORY Item No.	BROWN Item No.
Receptacles								
15 A	5-15R	No	No	SNAP5262A	31A338	—	31A336	—
Receptacles, Self Testing								
15 A	5-15R	No	No	GFRST15SNAP	39EA64	—	39EA61	39EA63
	5-15R	Yes	Yes	GFTWRST15SNAP	45UE35	—	—	45UE28
20 A	5-20R	No	No	GFRST20SNAP	39EA68	45UD74	39EA65	39EA67
Receptacles								
20 A	5-20R	No	No	SNAP5362A	—	—	31A339	31A392
	5-20R	Yes	No	SNAP8300ITA	—	—	49YK63	—
Receptacles, Self Testing								
20 A	5-20R	Yes	Yes	GFTWRST20SNAP	—	—	45UE40	45UE36
Description				Mr. Model	SOLID WIRE Item No.	STRANDED WIRE Item No.		
Pigtail Connectors for 15 or 20A Devices, 6" Leads								
Receptacles				SNAP_RA	31A326	—		
Receptacles, Buy American Compliant				SNAP_RNA	31A380	31A381		
Single Pole Switches				SNAPSP_NA	31A348	31A349		
3-Way Switches				SNAP3W_NA	31A334	31A335		
Single Pole Switch with Pilot Light				SNAPSPP_NA	31A408	31A409		

31A355



31A336



31A326



SNAPConnect II Wiring Devices

Suitable for use in commercial construction and in healthcare applications. Great for installations with potential for frequent device change-outs. Additional hospital grade versions are available; see Grainger.com. UL Listed and CSA Certified.

clip. Illuminated Switches have light On with load Off. Pilot Light Switches have light On with load On. 120 to 277VAC.

RECEPTACLES

Abuse-resistant nylon for heavy-duty applications. SNAPConnect feature eliminates exposed energized parts. Stainless steel autoground clip. 120VAC.

Note: SNAPConnect II is not compatible with SNAPConnect. Please check Mr. Model number before ordering.

SWITCHES

Feature an abuse-resistant thermoplastic rocker for heavy-duty applications. Design eliminates exposed energized parts. Stainless steel autoground

PIGTAILED CONNECTORS

1-phase, 2-pole, 3-wire clear polycarbonate pigtails are made for use with the devices listed, and are required for all switches and receptacles.