

1-800-GRAINGER (472-4643)



## High-Ampere Plugs

UL Listed and CSA Certified.

Note: See page 326 for NEMA configurations.

### HUBBELL® PLUGS

Heavy-duty cord clamps handle a wide range of cable sizes and hold conductors securely in place. Nylon bodies withstand severe abuse.

4-position angle plugs allow cord to enter from top, bottom, or either side and stay close to wall.

### BRYANT® PLUGS

Durable wall construction protects critical wiring from abusive environments. Reinforced thermoplastic polyester provides high impact and heat resistance.

Amps	No. of Poles	No. of Wires	Voltage	NEMA Plug Config.	Brand	STRAIGHT PLUG		ANGLE PLUG	
						Mfr. Model	Item No.	Mfr. Model	Item No.
20 A	3	3	125/250V AC	10-20P	Hubbell	HBL9977C	5Z842	—	—
20 A	3	4	125/250V AC	14-20P	Hubbell	—	—	HBL8411C	6C631
20 A	3	4	250V AC	15-20P	Hubbell	—	—	HBL8421C	5C794
30 A	2	3	125V AC	5-30P	Hubbell	—	—	HBL9309	5Z911
30 A	2	3	125V AC	5-30P	Bryant	9530NP	49YY44	—	—
30 A	2	3	250V AC	6-30P	Hubbell	—	—	HBL9331	5Z985
30 A	2	3	250V AC	6-30P	Bryant	—	—	9630ANPB	49YY46
30 A	3	3	125/250V AC	10-30P	Hubbell	HBL9337C	5Z843	HBL9333	4D086
30 A	3	4	125/250V AC	14-30P	Bryant	—	—	9432ANPB	49YY41
30 A	3	4	125/250V AC	14-30P	Hubbell	HBL9431C	5Z884	HBL9432C	5C790
30 A	3	4	250V AC	15-30P	Bryant	—	—	8432ANPB	49YY37
30 A	3	4	250V AC	15-30P	Hubbell	HBL8431C	5Z890	HBL8432C	5C795
50 A	2	3	125V AC	5-50P	Hubbell	—	—	HBL9361	6C118
50 A	2	3	125V AC	5-50P	Bryant	—	—	9550ANPB	49YY45
50 A	2	3	250V AC	6-50P	Hubbell	—	—	HBL9368	6C119
50 A	2	3	250V AC	6-50P	Bryant	—	—	9650ANPB	49YY47
50 A	3	3	125/250V AC	10-50P	Bryant	7513NP	49YY32	—	—
50 A	3	3	125/250V AC	10-50P	Hubbell	HBL7513C	5Z844	HBL7977	3D282
50 A	3	4	125/250V AC	14-50P	Bryant	—	—	9452ANPB	49YY42
50 A	3	4	125/250V AC	14-50P	Hubbell	HBL9451C	5Z886	HBL9452C	5C791
50 A	3	4	250V AC	15-50P	Hubbell	HBL8451C	5Z892	HBL8452C	5C796
50 A	3	4	250V AC	15-50P	Bryant	—	—	8452ANPB	49YY38
60 A	3	4	125/250V AC	14-60P	Bryant	—	—	9462ANPB	49YY43
60 A	3	4	125/250V AC	14-60P	Hubbell	HBL9461C	5Z888	HBL9462C	5C792
60 A	3	4	250V AC	15-60P	Bryant	—	—	8462ANPB	49YY39
60 A	3	4	250V AC	15-60P	Hubbell	HBL8461C	5Z894	HBL8462C	5C797
60 A	4	4	120/208V AC	18-60P	Hubbell	HBL7303C	3D242	HBL7302C	3D241
60 A	4	4	120/208V AC	18-60P	Bryant	—	—	8362ANPB	49YY35



**NEMA 5-30P**  
49YY44



**NEMA 10-30P**  
5Z843



**NEMA 10-50P**  
49YY32



**NEMA 5-30P**  
5Z911



**NEMA 15-50P**  
5C796



**NEMA 18-60P**  
49YY35

## Plug Adapters

Warning: Where adapters have different ratings on blade and slot ends, the following precautions must be exercised in their use:

- Overcurrent protection is determined by blade end.
- Adapter use should be limited to lowest rated end of adapter to prevent overheating.



Slot End Rating	NEMA Connector	Slot End Style	Blade End Rating	Plug Configuration	Blade End Style	Mfr. Model	Item No.
3 Wire 15A 125V	—	Straight Blade	3 Wire 10A 250V 15A 125V	—	Twist-Lock(R)	9053A	3D294
20A 125V	5-20R	Straight Blade	20A 125V	L5-20P	Locking	HBL2129	3D021
15A 125V	L5-15R	Locking	15A 125V	5-15P	Straight Blade	HBL2271	3D024
20A 125V	5-20R	Straight Blade	30A 125V	L5-30P	Locking	HBL31CM29	3D106
10A 250V/15A 125V	Non-NEMA	Locking	15A 125V	5-15P	Straight Blade	9054A	3D295
20A 125V	L5-20R	Locking	15A 125V	5-15P	Straight Blade	HBL21CM28	3D536
20A 125V	5-15R	Straight Blade	20A 125V	L5-20P	Locking	HBL21CM29	3D537
30A 125V	L5-30R	Locking	15A 125V	5-15P	Straight Blade	HBL31CM28	1UKB5 *
30A 125V	L5-30R	Twist-Lock®	15A 125V	NEMA 5-15P	Straight Blade	HBL61CM22	1UKB6 *†

\* Marine rated. † Straight adapter cord.



3D294



3D295

## Locking Blade NEMA Configurations

