



## NEMA Twist-Lock® Devices

Premium-quality industrial wiring devices feature a powerful cord grip, 1-pc. integrated dust shield, tough nylon housing, visible product identification, and roomy wiring chamber.

Note: See page 327 for NEMA configurations. For boots, see page 329.



**Receptacle  
4A258**



**Connector  
4A260**



**Plug  
4A259**



**Flanged Inlet  
3D034**



**Flanged Receptacle  
3D035**



**Corrosion Resistant Plug  
3D564**

Amps	NEMA Plug Config.	No. of Poles	No. of Wires	HP	Voltage	SINGLE RECEPTACLE (BLACK) Mfr. Model Item No.	CONNECTOR BODY (BLACK AND WHITE) Mfr. Model Item No.	PLUG (BLACK AND WHITE) Mfr. Model Item No.	
<b>1-Phase</b>									
15	L1-15	2	2	0.5	125V AC	HBL7535 3D260	HBL7506C 3D258	HBL7545C 3D261	
15	L5-15	2	3	0.5	125V AC	HBL4710 5A072	HBL4729C 5A074	HBL4720C 5A073	
15	L5-15	2	3	0.5	125V AC	—	HBL4729CBK 1DJ2	HBL4720CBK 1DJ1	
15	L6-15	2	3	2.0	250V AC	HBL4560 6C576	HBL4579C 6C579	HBL4570C 6C578	
15	L7-15	2	3	2.0	277V AC	HBL4750 5Z899	—	—	
15	L7-15	2	3	2.0	277V AC	HBL4760 6C122	HBL4779C 1X986	HBL4770C 1X985	
20	L2-20	2	2	2.0	250V AC	HBL7210B 3D239	HBL7101C 3D237	HBL7102C 3D238	
20	L5-20	2	3	1.0	125V AC	HBL2310 4A258	HBL2313 4A260	HBL2311BK 4A259	
20	L5-20	2	3	1.0	125V AC	—	HBL2313BK 1DJJA	HBL2311BK 1DJJJ	
20	L5-20	2	3	1.0	125V AC	—	HBL23CM13 3D046	HBL23CM11 3D045	
20	L6-20	2	3	2.0	250V AC	HBL2320 5A080	HBL2323 5A082	HBL2321 5A081	
20	L6-20	2	3	2.0	250V AC	—	HBL2323BK 1DJJB	HBL2321BK 1DJJJ	
20	L7-20	2	3	2.0	277V AC	HBL2330 1X978	HBL2333 5Z901	HBL2331 1X979	
20	L8-20	2	3	5.0	480V AC	HBL2340 5Z902	HBL2343 6C124	HBL2341 6C123	
20	L9-20	2	3	5.0	600V AC	HBL2350 3D040	HBL2353 3D042	HBL2351 3D041	
20	L14-20	3	4	1 Line to Neutral, 2 Line to Line	125/250V AC	HBL2410 4A264	HBL2413 4A266	HBL2411 4A265	
20	L14-20	3	4	1 Line to Neutral, 2 Line to Line	125/250V AC	—	HBL2413BK 1DJK7	HBL2411BK 1DJK6	
30	L5-30	2	3	1.0	125V AC	HBL2610 4A261	HBL2613 4A263	HBL2611 4A262	
30	L5-30	2	3	1.0	125V AC	—	HBL2613BK 1DJJ6	HBL2611BK 1DJJ5	
30	L5-30	2	3	1.0	125V AC	—	HBL26CM13 3D089	HBL26CM11 3D088	
30	L6-30	2	3	2.0	250V AC	HBL2620 5A086	HBL2623 5A088	HBL2621 5A087	
30	L6-30	2	3	2.0	250V AC	—	HBL2623BK 1DJK1	HBL2621BK 1DJJ9	
30	L8-30	2	3	5.0	480V AC	HBL2640 6C546	HBL2643 6C548	HBL2641 6C547	
30	L14-30	3	4	2.0	125/250V AC	HBL2710 6A655	HBL2713 6A657	HBL2711 6A656	
30	L14-30	3	4	2.0	125/250V AC	—	HBL2713BK 1DJK9	HBL2711BK 1DJK8	
<b>3-Phase</b>									
20	L15-20	3	4	3.0	250V AC	HBL2420 4A267	HBL2423 4A269	HBL2421 4A268	
20	L16-20	3	4	5.0	480V AC	HBL2430 6A661	HBL2433 6A663	HBL2431 6A662	
20	L18-20	4	4	2.0	120/208V AC	HBL2440 3D053	HBL2443 5C972	HBL2441 5C971	
20	L21-20	4	5	2.0	120/208V AC	—	HBL2513 5Z906	HBL2511 1X981	
20	L21-20	4	5	2.0	120/208V AC	—	HBL2513FC 1DNW1	HBL2511FC 1DNV9	
20	L21-20	4	5	2.0	120/208V AC	—	HBL2513BK 1DJK3	HBL2511BK 1DJK2	
20	L22-20	4	5	10.0	277/480V AC	HBL2520 6C153	HBL2523 6C545	HBL2521 6C544	
30	L15-30	3	4	3.0	250V AC	HBL2720 4A270	HBL2723 4A272	HBL2721 4A271	
30	L16-30	3	4	10.0	480V AC	HBL2730 6A658	HBL2733 6A660	HBL2731 6A659	
30	L17-30	3	4	10.0	600V AC	HBL2740 3D095	HBL2743 3D097	HBL2741 3D096	
30	L18-30	4	4	3.0	120/208V AC	HBL2750 3D099	HBL2753 5C970	HBL2751 5C969	
30	L19-30	4	4	10.0	277/480V AC	HBL2760 3D100	HBL2763 3D102	HBL2761 3D101	
30	L21-30	4	5	3.0	120/208V AC	HBL2810 1X982	HBL2813 1X984	HBL2811 1X983	
30	L21-30	4	5	3.0	120/208V AC	—	HBL2813FC 1DNW3	HBL2811FC 1DNW2	
30	L21-30	4	5	3.0	120/208V AC	—	HBL2813BK 1DJK5	HBL2811BK 1DJK4	
30	L22-30	4	5	10.0	277/480V AC	HBL2820 5Z908	HBL2823 6C549	HBL2821 6C789	
<b>Three-Phase</b>									
20	L21-20	4	5	2.0	120/208V AC	HBL2510 1X980	—	—	
						<b>FLANGED INLET (WHITE NYLON)</b>		<b>FLANGED RECEPTACLE (WHITE NYLON)</b>	
						Mfr. Model	Item No.	Mfr. Model	Item No.
						<b>PLUG (YELLOW, MARINE RATED)</b>			
						Mfr. Model	Item No.	Mfr. Model	Item No.
<b>1-Phase</b>									
15	L5-15	2	3	0.5	125V AC	HBL4716C 3D170	HBL4715C 3D168	—	
15	L6-15	2	3	2.0	250V AC	HBL4586 3D785	HBL4585C 3D153	—	
20	L2-20	2	2	2.0	250V AC	—	HBL3226 3D693	—	
20	L5-20	2	3	1.0	125V AC	HBL2315 3D034	HBL2316 3D035	HBL23CM11 3D045	
20	L6-20	2	3	2.0	250V AC	HBL2325 3D036	HBL2326 3D037	HBL23CM21 3D564	
20	L7-20	2	3	2.0	277V AC	—	HBL2336 3D038	—	
20	L8-20	2	3	5.0	480V AC	—	HBL2346 3D039	—	
20	L9-20	2	3	5.0	600V AC	—	HBL2356 3D043	—	
20	L14-20	3	4	1 Line to Neutral, 2 Line to Line	125/250V AC	HBL2415 3D047	HBL2416 3D048	—	
30	L5-30	2	3	—	125V AC	HBL303NM 4D351	—	—	
30	L5-30	2	3	—	125V AC	HBL303SS 3D954	—	—	
30	L5-30	2	3	1.0	125V AC	HBL2615 3D072	HBL2616 3D073	HBL26CM11 3D088	
30	L6-30	2	3	2.0	250V AC	HBL2625 3D074	HBL2626 3D075	HBL26CM21 3D639	
30	L8-30	2	3	5.0	480V AC	—	HBL2646 3D632	—	
30	L14-30	3	4	2.0	125/250V AC	HBL2715 3D090	HBL2716 3D091	—	
<b>3-Phase</b>									
20	L15-20	3	4	3.0	250V AC	HBL2425 3D566	HBL2426 3D049	—	
20	L16-20	3	4	5.0	480V AC	HBL2435 3D572	HBL2436 3D052	—	
20	L18-20	4	4	2.0	120/208V AC	—	HBL2446 3D574	—	
20	L21-20	4	5	2.0	120/208V AC	HBL2515 5C995	HBL2516 5C996	—	
30	L15-30	3	4	3.0	250V AC	HBL2725 3D092	HBL2726 3D093	—	
30	L16-30	3	4	10.0	480V AC	HBL2735 3D641	HBL2736 3D094	—	
30	L17-30	3	4	10.0	600V AC	HBL2745 3D642	HBL2746 3D098	—	
30	L18-30	4	4	3.0	120/208V AC	HBL2755 3D643	HBL2756 3D644	—	
30	L19-30	4	4	10.0	277/480V AC	HBL2765 3D645	HBL2766 3D646	—	
30	L21-30	4	5	3.0	120/208V AC	HBL2815 3D103	HBL2816 3D104	—	
30	L22-30	4	5	10.0	277/480V AC	HBL2825 3D660	HBL2826 3D661	—	

\* Flush duplex receptacle, brown. † Stainless steel housing. ‡ Nonmetallic housing and cover, marine rated. # Stainless steel housing and cover, marine rated. \*\* All black. †† Designed for use with flat cable. ††† Yellow, marine rated.



**4D579**

## Insulgrip® Plug and Connector Twist-Lock® Latching Kit



Latch with locking slide provides double-locking feature for plug and connector bodies to prevent unintentional disconnection even under high vibration.

For Use With		Color	Mfr. Model	Item No.
All 3-Wire 20A or 30A Locking Plugs/Insulgrip Plugs and Connectors		White	SK2	6PFN8
All 4- and 5-Wire 20A or 30A Twist-Lock Insulgrip Plugs and Connectors		White	SK3	4D579