



**Receptacle
3D017**



**Connector Body
3D018**



**Plug
3D019**



Hubbellock Devices

Spring-loaded safety shutter ejects plug if not properly locked into connector/receptacle; shutter snuffs out arcs when devices are connected or disconnected under load. Key/detent ensures positive lock. UL Listed.

Amps	No. of Poles	No. of Wires	Voltage	Color	RECEPTACLE		CONNECTOR BODY			PLUG		Item No.
					Mfr. Model	Item No.	Color	Mfr. Model	Item No.	Color	Mfr. Model	
Industrial Hubbellock												
20	2	3	125VAC	—	—	—	—	—	Black	HBL23035B	3D553	
20/10/10	2	3	125VAC/DC, 250VDC, 480VAC	—	—	—	—	Gray	HBL23005GB	3D031		
20/10/10	2	3	125V AC/DC, 250V DC, 480V AC	Black	HBL23000G	3D026	—	—	Gray	HBL23005GB	3D031	
30	3	4	480VAC	—	—	—	—	—	Red	HBL20444B	3D018	
30	3	4	480V AC	Black	HBL20443	3D017	—	—	Red	HBL20445B	3D019	
30/20	3	4	600VAC/250VDC	—	—	—	—	—	Black	HBL21414B	5C993	
30/20	3	4	600V AC/250V DC	Black	HBL20403	3D015	—	—	Black	HBL21415B	5C994	
30/20	4	5	600VAC/250VDC	—	—	—	—	—	Black	HBL25414B	3D058 †	
30/20	4	5	600V AC/250V DC	Blue	HBL25403	3D057 †	—	—	Black	HBL25415B	3D059 †	
60	3	4	600VAC	—	—	—	—	—	Yellow	HBL26418	3D080	
60	3	4	600V AC	Black	HBL26410	3D079	—	—	Yellow	HBL26419	3D081	
60	4	5	600VAC	—	—	—	—	—	Blue	HBL26516	3D083	
60	4	5	600V AC	Blue	HBL26520	2AXH9	—	—	Blue	HBL26519	3D084	
Hospital Hubbellock												
20	2	3	125VAC	—	—	—	—	Gray	HBL23001HGB	3D028	—	
20	2	3	125VAC	—	—	—	—	—	Gray	HBL23004HG	3D030 **	
20	2	3	125V AC	Black	HBL23000HG	3D027 #	—	—	Gray	HBL23014HGB	3D033	
50	2	3	250VAC	—	—	—	—	—	—	—	—	
50	2	3	250V AC	—	—	—	—	—	Gray	HBL25525	3D062	
50	2	3	250V AC	Black	HBL25503	3D061	—	—	—	—	—	
Flanged Inlet												
30/20	3	4	600V AC/250V DC	—	—	—	—	—	Gray	HBL20418	3D505 †	
50	3	4	600V AC/250V DC	—	—	—	—	—	Gray	HBL3775	3D735	
50	3	4	600V AC/250V DC	—	—	—	—	—	Gray	HBL3768	3D734 ‡	
Accessories and Other Hubbellock Devices												
Weatherproof Plate for No. 3D015 (for FS/FD box mounting)										Aluminum	HBL20405	3D016
Receptacle Box for Nos. 3D085 and 3D086 Only										Aluminum	HBL26401	3D076
Adapter Plate, For Use with Receptacle Box No. 3D076										Aluminum	HBL26402	2AXJ1
45° Adapter for Receptacle Box No. 3D076										Aluminum	HBL26404	3D078
Explosionproof Plug with Epoxy Kit, 2-Pole, 3-Wire, 20A, 125V, Hospital Rated										Gray	HBL24312	3D051

* Includes FS/FD indoor cover. † 30A at 600VAC, 20A at 250VDC. ‡ Includes lift cover. ** Epoxy filled. # Weatherproof plate for FS/FD box mounting available, use 6C615, see page 301.

BRYANT®

IEC Nonmetallic Watertight Pin and Sleeve Devices

Feature a tough, nylon housing that protects against cracking, warping, corrosion, and chemical abrasion. Neoprene sealing glands provide a water-tight seal. Solid brass pins provide contact reliability and superior conductivity.



Amps	Color	Voltage	Phase	CONNECTOR		PLUG		RECEPTACLE	
				Mfr. Model	Item No.	Mfr. Model	Item No.	Mfr. Model	Item No.
2 Pole, 3 Wire									
20	Blue	250VAC	1	—	—	BRY320P6W	49YX88	BRY320R6W	49Y01
3 Pole, 4 Wire									
20	Red	480VAC	3	BRY420C7W	49YX81	BRY420P7W	49YX92	BRY420R7W	49Y05
20	Blue	250VAC	3	—	—	BRY430P9W	49YX94	—	—
30	Red	480VAC	3	BRY430C7W	49YX82	BRY430P7W	49YX93	BRY430R7W	49Y06
60	Blue	250VAC	3	BRY460C9W	49YX85	BRY460P9W	49YX97	BRY460R9W	49Y08
60	Red	480VAC	3	BRY460C7W	49YX84	BRY460P7W	49YX96	—	—
60	Black	600VAC	3	BRY460C5W	49YX83	BRY460P5W	49YX95	—	—
100	Orange	125/250VAC	1	—	—	BRY4100P12W	49YX89	BRY4100R12W	49Y02
100	Blue	250VAC	3	BRY4100C9W	49YX80	BRY4100P9W	49YX91	BRY4100R9W	49Y04
100	Red	480VAC	3	BRY4100C7W	49YX79	BRY4100P7W	49YX90	BRY4100R7W	49Y03
4 Pole, 5 Wire									
60	Blue	120/208VAC	3Y	BRY560C9W	49YX87	BRY560P9W	49YX99	BRY560R9W	49Y11
100	Blue	120/208VAC	3Y	BRY5100C9W	49YX86	BRY5100P9W	49YX98	BRY5100R9W	49Y10



Hubbell Single-Pole Connectors

Nonmetallic retaining screw locks contacts in place so they don't move within the housing. Special screw thread prevents installation 180° out of rotation and requires fewer turns, reducing the chance of a conductive screw being substituted. Multiple guides ease cutting to correct cable size. Large raised alignment arrow eases mating of devices. 600VAC/250VDC. Rated NEMA 3R, 4X and 12K. UL and C-UL Listed.

Amps AC/DC	Cable Range	Terminal Connec.	FEMALE					MALE				
			Black Item No.	Blue Item No.	Green Item No.	Red Item No.	White Item No.	Black Item No.	Blue Item No.	Green Item No.	Red Item No.	White Item No.
Connectors												
300AC/DC	6 to 2/0	Double Set Screw	2XB25	2XB26	2XB27	2XB28	2XB29	2XB30	2XB31	2XB32	2XB33	2XB34
400AC/DC	2/0 to 4/0	Double Set Screw	2XB35	2XB36	2XB37	2XB38	2XB39	2XB40	2XB41	2XB42	2XB43	2XB44
Receptacles												
400AC/DC	4 to 4/0	Double Set Screw	2XB50	2XB51	2XB52	2XB53	2XB59	2XB65	2XB66	2XB67	2XB68	2XB74
400AC/DC	N/A	Threaded Stud	2XB54	2XB55	2XB56	2XB57	2XB58	2XB69	2XB70	2XB71	2XB72	2XB73
Accessories												
Protective Caps for Connectors			2XB45	2XB46	2XB47	2XB48	2XB49	2XB60	2XB61	2XB62	2XB63	2XB64
Snap Back Covers for Receptacles, Fits Male and Female			2XB75	2XB76	2XB77	2XB78	2XB79	2XB75	2XB76	2XB77	2XB78	2XB79