



MONOPRICE

Fiber Optic Patch Cables

- Clad dimension: 125µm
- Attenuation and bandwidth: 10 GB



			LENGTH			
Fiber Optic Connector Type	Core Dim.	Jacket Color	15m Item No.	20m Item No.	30m Item No.	40m Item No.
Extended Length Patch Cables						
LC/LC	50	Aqua	13U492	13U493	13U494	13U496

Fiber Optic Connector Type	Core Dim.	Jacket Color	LENGTH				
			1m Item No.	2m Item No.	3m Item No.	5m Item No.	10m Item No.
Patch Cables							
LC/LC	9	Yellow	13U509	13U510	13U511	13U498	13U512
	50	Aqua	13U463	13U464	13U465	13U466	13U467
	62.5	Orange	13U421	13U422	—	—	—
LC/SC	9	Yellow	13U515	—	—	—	—
	50	Aqua	13U468	13U469	—	—	—
	62.5	Orange	13U433	13U434	13U435	13U436	13U437
LC/ST	50	Aqua	13U472	—	—	—	—
	62.5	Orange	13U427	13U428	13U429	13U430	13U431
SC/SC	9	Yellow	13U519	13U501	—	—	—
	62.5	Orange	14C133	—	—	—	—
SC/ST	9	Yellow	13U520	—	—	—	—
	62.5	Orange	13U521	—	—	—	—
ST/ST	9	Yellow	13U512	—	—	—	—
	62.5	Orange	14C123	14C124	—	—	14C127



Core Dim.	Attenuation	Fiber Count	
		6 Item No.	12 Item No.
Tight Buffer SM	1.0 dB/km @ 1310 and 1560 Nanometers	5ZDD5	5ZDD6
62.5 µm MM	1.0 dB/km @ 1300 Nanometer	5ZDE1	—

Fiber Optic Cable

- ANSI/TIA/EIA 568B.3
- UL and C-UL Listed
- RoHS Compliant
- Operating temp.: -20° to 70°C
- 1000-ft. rolls



Type OFNP, CSA FT-6 cables feature black plenum-rated FEP jackets. Tight buffered fibers are easy to handle and strip for connection; sub-units are numbered for identification. Designed for intrabuilding and interbuilding high speed voice or data communications backbone.



Fiber Optic Cable Testing Instruments

Description	Mr. Model	Item No.
IDEAL		
Fiber Optic Test Kit, Power Measurement In dBm and W, Loss Display In dB, Four Wavelength MM/SM Light Source	33-931	6KJU4
Fiber Fault Finder, Finds Breaks, Faulty Splices and Crimps Poor Components or Connections for Fiber Cable, Visually Identifies and Locates Faults in Fiber Optic Cabling, 2.5mm Universal Adaptor for All ST, SC and FC Connectors, Useful Over a Distance of 5km (3 miles), Up to 80 hours of Operation, Ruggedised Aluminium Body	VFF5	6LFY3
Hubbell Premise Wiring		
Fiber Visual Fault Locator Kit, Fiber Terminations and Breaks, 1.25MM and 2.5MM Ferrule Adapters	OFVFLKT1	22LV15
Fluke Networks		
Fiber Optic Cleaning Supplies, Fiber Optic Cleaning, Solvent, Swabs and Cube	NFC-KIT-BOX	12N847
Fiber Optic Cleaning Supplies, Fiber Optic Cleaning, Solvent, Swabs, Cube and Case	NFC-KIT-CASE	12N848
Visual Fiber Optic Fault Locator, Visible Light Source That Helps Trace Optical Fibers, Check Fiber Continuity, And Find Faults Such as Breaks, Bad Splices, and Tight Bends In Fiber Optic Cable	VisiFault	2EHV6
Basic Fiber Verification Kit (MM), Verify Optical Loss and Power Levels	FTK1000	4AZZ3
Fiber Optic Tester, Fiber Optic Video Inspection, Allow Tier 2 Certification, Detects (850/1300nm) Multimode and (1310/1550nm) Single Mode Wavelengths, Locate Connections and Faults, Measure Loss and Reflectance	OFF-Q-ADD	54DV48
Fiber Optic Tester, Fiber Optic Video Inspection, Extended Single Mode Distance Range to 130km, Fiber Optic Loss, OTDR Testing and Fiber End Face Inspection, Versiv(TM) Modular Design Supports Copper Certification	CFP-Q-ADD	54DV49
Fiber Optic Fault Locator, Fiber Troubleshooting, Works On Multimode Fiber, 9/125micron m and 62.5/125 micron m, Locate Severe Bends, High-Loss Splices, Breaks and Dirty Connectors In Single Mode Fiber, Change The Index of Refraction (IOR) to Improve Fiber Length Accuracy	FQM-100-M	54DV52
Fiber Optic Fault Locator, Fiber Troubleshooting, Works On Multimode Fiber, 9/125micron m and 62.5/125 micron m, Locate Severe Bends, High-Loss Splices, Breaks and Dirty Connectors In Single Mode Fiber, Change The Index of Refraction (IOR) to Improve Fiber Length Accuracy	FQM-100-M-VFL	54DV53
Fiber Optic Fault Locator, Fiber Troubleshooting, Fills The Gap Between a VFL and An OTDR, VFL Simplicity, Identify Live Fiber, Provide Distance and Power Information On High Losses, Breaks At The End Of The Fiber	FQM-M	54DV54
Fiber Optic Fault Locator, Fiber Troubleshooting, Fills The Gap Between a VFL and An OTDR, VFL Simplicity, Identify Live Fiber, Provide Distance and Power Information On High Losses, Breaks At The End Of The Fiber	FQM-SFP-M	54DV55