Twistable Drop-Over Cable Ramps

ABS material

Twistable drop-over cable ramps articulate from side to side, allowing them to turn corners and adapt to an area's layout while maintaining a flat profile. They have an interlocking design which allows for reconfigurations, repairs, or replacements without moving cable or hose.

	Max. Cable Dia.	Length	W	Н	Load Capacity	YELLOW Item No.	BLACK Item No.
I	1 Number of	Channels					
Ì		13 1/8 in	3 in	3/4 in	32,000 lb/Axle	14N917	
	⅓ in	24 % ft	3 in	3/4 in	32,000 lb/Axle	23Z433	_
		39 ½ in	3 in	3/4 in	32,000 lb/Axle	14N916	14N918
	3/4 in	14 1/8 in	9 ¾ in	1 3/8 in	13,500 lb/Axle	30KD73	30KD75
		33 in	9 ¾ in	1 % in	13,500 lb/Axle	30KD72	30KD74
	1 ½ in	14 1/8 in	13 % in	2 1/8 in	13,500 lb/Axle	30KD77	30KD79
		34 in	13 % in	2 1/8 in	13,500 lb/Axle	30KD76	30KD78






LINEBACKER, GUARDDQG

Drop-Over Modular Cable Ramps

Polyurethane material

Drop-over modular cable ramps are placed over cable and hose lines that run along the ground. They have an interlocking design, which allows for reconfigurations, repairs, or replacements without moving cable or hose. These cable ramps prevent damage due to foot and vehicle traffic.



Vertil

BLACK/

Connection Style	Max. Cable Dia.	Length	w	Н	Load Capacity	Brand	BLACK Item No.	ORANGE Item No.	YELLOW Item No.
1-Channel Drop-Over Cable Ramps	Max. Cable Dia. Length W H Load Capacity Brand Item No. Item No. Item No. ps ½ in 36 ¾ in 5 ¾ in ¾ in 2,100 lb/Axle Fastlane 22F232 3KUP5 — 1 in 38 ½ in 10 ¾ in 1½ in 2,100 lb/Axle Fastlane 22F233 — — 1 in 38 ½ in 10 ¾ in 1½ in 2,100 lb/Axle Fastlane — 3KUP7 — 1 ¼ in 38 ¼ in 11 ½ in 1 ¾ in 17,000 lb/Axle Linebacker — 3KUT9 — 2 ¼ in 38 ½ in 14 ¼ in 3 in 23,400 lb/Axle Linebacker — 5MKH3 — ps 1 in 38 ½ in 10 ¾ in 1 ½ in 2,100 lb/Axle Eastlane — 5MKH3 —								
	1/2 in	36 ¾ in	5 ¾ in	3/4 in	2,100 lb/Axle	Fastlane	22F232	3KUP5	_
L Shaped	1 in	38 ½ in	10 % in	1 ½ in	2,100 lb/Axle	Fastlane	22F233	_	_
	1 in	38 ½ in	10 ¾ in	1 ½ in	2,100 lb/Axle	Fastlane	_	3KUP7	_
T Shaped	1 1/4 in	38 ¼ in	11 ½ in	1 5/8 in	17,000 lb/Axle	Linebacker	_	3KUT9	_
i Silapeu	2 1/4 in	38 ½ in	14 ¼ in	3 in	23,400 lb/Axle	Linebacker	_	5MKH3	_
2-Channel Drop-Over Cable Ramps									
L Shaped	1 in	38 ½ in	10 ¾ in	1 ½ in	2,100 lb/Axle	Fastlane	22F235	22F234	_
3-Channel Drop-Over Cable Ramps									
Dog Bone	1 5/16 in	18 in	19 ¾ in	1 1/8 in	21,000 lb/Axle	Guard Dog	32RX22	32RX21	32RX23

Lightweight Drop-Over Cable Ramps

■ Polyurethane material

Lightweight drop-over cable ramps are placed over cable and hose lines that run along the ground and have a lightweight construction that helps facilitate setup. These cable ramps protect the lines from damage due to foot and vehicle traffic.

Max. Cable Dia.	Length	w	Н	Channel Width	Channel Height	Load Capacity	Color	Brand	Item No.
1 Number of	Channels								
	2 ft	15 ¾ in	2 1/4 in	7∕8 in	7∕8 in	500 lb	Gray	Guardian Floor Protection	61HY42
7∕8 in	3 ft	15 ¾ in	2 1/4 in	7∕8 in	7∕8 in	500 lb	Gray	Guardian Floor Protection	61HY43
	4 ft	15 ¾ in	2 1/4 in	7∕8 in	7∕8 in	500 lb	Gray	Guardian Floor Protection	61HY44
2 Number of	Channels								
3/4 in	72 in	10 in	2 in	1 1/4 in	7⁄8 in	20,000 lb/Axle	Yellow	_	2GTG6
9/4 III	108 in	10 in	2 in	1 1/4 in	7⁄8 in	20,000 lb/Axle	Yellow	_	2GTG7



Aluminum Drop-Over Cable Ramps

Aluminum material

Cable ramps drop over power cords, electrical cable, and hydraulic hose to protect them from damage and prevent tripping hazards. They support heavy loads from forklifts, carts, vehicles, and personnel.

Channel Width	Channel Height	Length	w	н	Load Capacity	Color	No. of Channels	Brand	Item No.
Aluminum Ca	able & Hose R								
2 5/8 in	3/4 in	48 in	7 1/8 in	1 1/8 in	10,000 lb/Axle	Silver	1	_	1F141
2 % 111	3/4 in	36 in	7 1/8 in	1 1/8 in	10,000 lb/Axle	Silver	1	_	1TFT9
	1 1/4 in	36 in	9 1/8 in	11/2"	21,000 lb/Axle	Silver	1	_	2GWL7
2 ½ in	1 1/4 in	4 ft	9 1/8 in	11/2"	21,000 lb/Axle	Silver	1	_	2GWL8
	1 1/4 in	6 ft	9 1/8 in	11/2"	21,000 lb/Axle	Silver	1	_	2GWL9
Vide-Span A	luminum Cab	le & Hose Rai	nps						
	3 in	48 in	36 in	3 % in	2,100 lb/Axle	Silver	1	Vestil	32Y880
4 in	3 in	36 in	24 in	3 % in	2,100 lb/Axle	Silver	1	Vestil	32Y930
4 111	4 in	48 in	36 in	4 3/8 in	2,100 lb/Axle	Silver	1	Vestil	32Y883
	4 in	36 in	24 in	4 3/8 in	2,100 lb/Axle	Silver	1	Vestil	32Y931
	3 in	48 in	40 in	3 % in	2,100 lb/Axle	Silver	1	Vestil	32Y871
8 in	3 in	40 in	24 in	3 ¾ in	2,100 lb/Axle	Silver	1	Vestil	32Y928
O III	4 in	48 in	40 in	4 % in	2,100 lb/Axle	Silver	1	Vestil	32Y872
	4 in	40 in	24 in	4 3/8 in	2,100 lb/Axle	Silver	1	Vestil	32Y929
	3 in	48 in	44 in	3 ¾ in	2,100 lb/Axle	Silver	1	Vestil	32Y866
12 in	3 in	44 in	24 in	3 % in	2,100 lb/Axle	Silver	1	Vestil	32Y925
12 111	4 in	48 in	44 in	4 3/8 in	2,100 lb/Axle	Silver	1	Vestil	32Y867
	4 in	44 in	24 in	4 % in	2,100 lb/Axle	Silver	1	Vestil	32Y926
	3 in	48 in	48 in	3 % in	2,100 lb/Axle	Silver	1	Vestil	32Y856
16 in	3 in	48 in	24 in	3 ¾ in	2,100 lb/Axle	Silver	1	Vestil	32Y921
	4 in	48 in	24 in	4 3/2 in	2 100 lh/Ayle	Silver	1	Vestil	32VQ22

