



Power Distribution Carts and Power Stations

Stainless steel construction with heavy-duty frames. Clear breaker panel window. Automatic GFCI reset. NEMA 3R enclosure. UL 1640 Listed. 14N245 and 14N246 are C-UL Listed.



3GUL4

KVA Rating	Amps	Phase	Input Voltage	Input Protection	Output Voltage	Output Connection	Item No.
Portable Power Stations							
15	50 A	Three	480V AC	30A Fused Disconnect	120 to 208V AC	(2) L6-30R 250V Non-GFCI and (10) 5-20R 125V GFCI Receptacles	3GUL2
30	100 A	Three	480V AC	60A Fused Disconnect	120 to 208V AC	(4) 50A 125/250V Non-GFCI and (2) 20A 125V GFCI Receptacles	3GUL4
30	100 A	Three	480V AC	60A Fused Disconnect	120 to 208V AC	(2) L6-30R 250V Non-GFCI and (10) 5-20R 125V GFCI Receptacles	3GUL3

Features	Voltage Rating	Amps	No. of Poles	No. of Wires	Cord Length	Inlet	Outlet	Item No.
Power Distribution Carts								
Main Circuit Breaker	120/208V AC	100 A	4	5	20 ft	Direct Wired	(2) 20A @ 125V 5-20R GFCI, (4) 20A @ 120/208V L21-20R Non-GFCI	14N245
	120/208V AC	200 A	4	5	—	Cam Locks	(2) 20A @ 125V 5-20R GFCI, (8) 20A @ 120/208V L21-20R Non-GFCI	14N246
3-Phase	120/208V AC	100 A	4	5	20 ft	Direct Wired	(1) 20A @ 125V GFCI, (2) 30A @ 250V Non-GFCI	3GUK7
	120/208V AC	100 A	4	5	20 ft	Direct Wired	(2) 20A @ 125V GFCI, (4) 50A @ 125/250V Non-GFCI	3GUK8
	120/208V AC	200 A	4	5	—	Cam Locks	(2) 20A @ 125V GFCI 5-20R, (2) 30A @ 250V Non-GFCI, (6) 50A @ 125/250V	3GUK9



3GUJ2



4D577



Power Distribution Box

See pages 326 and 327 for NEMA plug configurations.

CEP—1-phase GFCI. Boxes are UL and C-UL Listed. Boxes with Automatic Reset include 6 individually protected GFCI circuits.

■ Open ground and open neutral protection

Hubbell Wiring Device-Kellems—Meets NEC requirements and is listed at the latest UL 1640 standard. Provide temporary power access for 20A and 30A straight-blade or Twist-Lock devices in a metal NEMA 3R raintight enclosure. UL Listed; 1DNU8 is also CSA Certified.

50A-input models are for use with Twist-Lock connector 3D322; see page 330.

Power First—GFCI distribution boxes feature outlets with circuit breaker protection. Raintight NEMA 3R construction. UL, C-UL, and ETL Listed.

No. of Poles	No. of Wires	Outlet	Amps	Voltage Rating	Color	Material of Constr.	Item No.
CEP							
1-Phase, Automatic GFCI with Frame							
3	4	(1) L6-30R, (6) 5-20R GFCI	50 A	120/240V AC	Yellow	Heavy-Duty Steel	3GUJ1
1-Phase, Automatic GFCI With Legs							
3	4	(1) L6-30R Single, (6) 5-20R GFCI Single	50 A	120/240V AC	Yellow	Heavy-Duty Steel	3GUJ3
3	4	(1) L6-30R, (6) 5-20R GFCI	50 A	120/240V AC	Silver	Stainless Steel	3GUJ7
3	4	(1) L6-30R, (6) L5-20R GFCI	50 A	120/240V AC	Yellow	Heavy-Duty Steel	3GUJ2
3	4	(1) L6-30R, (6) L5-20R GFCI	50 A	120/240V AC	Silver	Stainless Steel	3GUJ6
3	4	(4) 5-20R GFCI	30 A	120/240V AC	Yellow	Heavy-Duty Steel	4MXZ6
3	4	(4) 5-20R GFCI	50 A	120/240V AC	Yellow	Heavy-Duty Steel	4MXZ8
3	4	(4) 5-20R GFCI	30 A	120/240V AC	Yellow	Heavy-Duty Steel	4MXZ5
3	4	(4) 5-20R GFCI	50 A	120/240V AC	Yellow	Heavy-Duty Steel	4MXZ7
1-Phase, Automatic Reset GFCI with Frame							
3	4	(1) L6-30R, (6) 5-20R GFCI	50 A	120/240V AC	Silver	Stainless Steel	3GUJ5
3	4	(1) L6-30R, (6) L5-20R GFCI	50 A	120/240V AC	Yellow	Heavy-Duty Steel	3GUH9
3	4	(1) L6-30R, (6) L5-20R GFCI	50 A	120/240V AC	Silver	Stainless Steel	3GUJ4
1-Phase with Frame							
3	4	(4) 30A @ 125/250V L14-30R Non-GFCI	50 A	120/240V AC	Yellow	Heavy-Duty Steel	53PC82
3	4	(6) 30A @ 125/250V L14-30R Non-GFCI	50 A	120/240V AC	Yellow	Heavy-Duty Steel	53PC83
3-Phase With Frame							
4	5	(4) 20A @ 120/208V L21-20R Non-GFCI	200 A	120/208V AC	Silver/Black	Stainless Steel	53PC86
4	5	(6) 50A @ 125/250V Non-GFCI	200 A	120/208V AC	Silver/Black	Stainless Steel	53PC85
Hubbell Wiring Device-Kellems Manual Reset GFCI							
3	4	(1) 50A Twist Lock, (7) 5-20R	50 A	120/240V AC	Yellow	Painted Galvanized Steel	4D577
3	4	(1) 50A Twist Lock, (7) L5-20R	50 A	120/240V AC	Yellow	Painted Galvanized Steel	4D572
3	4	(1) L6-30, (6) 5-20R	50 A	120/240V AC	Yellow	Painted Steel	1DNV1
3	4	(1) L6-30, (6) L5-20R	50 A	120/240V AC	Yellow	Painted Steel	1DNU9
4	5	(1) 60A Class L, (6) 5-20R GFCI	60 A	120/208V AC	Green	Painted Galvanized Steel	5LY80 †
4	5	(1) 60A Pin and Sleeve, (6) 5-20R GFCI	60 A	120/208V AC	Yellow	Painted Galvanized Steel	1DNU8
Power First Automatic Reset GFCI							
3	4	(1) L6-30R Locking Non GFCI Protected Receptacle, (6) 5-20R GFCI Protected Receptacles	50 A	120/240V AC	Yellow	Steel	4HDX2

† Military Class L inlet and feed through and NATO 383 green color.



13M206

4NAF7



Temporary Power Cords

Cord Length	Wire Size	Max. Amps	Voltage	Plug Configuration	Receptacle Configuration	No. of Outlets	Color	Item No.
KH Industries								
Dead End Power Stringer								
30 ft	12 AWG	20.0 A	125V AC	NEMA 5-20P	NEMA 5-20R	6	Black	14A287
30 ft	12 AWG	20.0 A	125/250V AC	NEMA L14-20P	NEMA 5-20R	4	Black	14A289
30 ft	10 AWG	20.0 A	120/208V AC	NEMA L21-20P	NEMA 5-20R	6	Black	14A293
60 ft	12 AWG	20.0 A	125/250V AC	NEMA L14-20P	NEMA 5-20R	8	Black	14A290
60 ft	10 AWG	20.0 A	120/208V AC	NEMA L21-20P	NEMA 5-20R	12	Black	14A294
Feed Through Power Stringer								
30 ft	12 AWG	20.0 A	125V AC	NEMA 5-20P	NEMA 5-20R	6	Black	14A288
30 ft	12 AWG	20.0 A	125/250V AC	NEMA L14-20P	NEMA 5-20R	4	Black	14A291
30 ft	10 AWG	20.0 A	120/208V AC	NEMA L21-20P	NEMA 5-20R	6	Black	14A295
60 ft	12 AWG	20.0 A	125/250V AC	NEMA L14-20P	NEMA 5-20R	8	Black	14A292
60 ft	10 AWG	20.0 A	120/208V AC	NEMA L21-20P	NEMA 5-20R	12	Black	14A296
Pendant Drop Outlet Box								
25 ft	12 AWG	15.0 A	125V AC	NEMA 5-15P	NEMA 5-15R	4	Yellow	13M204
25 ft	12 AWG	20.0 A	125V AC	NEMA 5-20P	NEMA 5-20R	4	Yellow	13M206
25 ft	12 AWG	20.0 A	125/250V AC	NEMA L14-20P	NEMA 5-20R	4	Yellow	13M208
50 ft	12 AWG	15.0 A	125V AC	NEMA 5-15P	NEMA 5-15R	4	Yellow	13M205
50 ft	12 AWG	20.0 A	125V AC	NEMA 5-20P	NEMA 5-20R	4	Yellow	13M207
50 ft	12 AWG	20.0 A	125/250V AC	NEMA L14-20P	NEMA 5-20R	4	Yellow	13M209
Hubbell Wiring Device-Kellems								
Prewired Receptacle								
—	6 AWG	50 A	125/250V AC	Bare Wire	CS6369	—	Yellow	4D583
Temporary Power Cord								
50 ft	6/3, 8/1	50 A	125/250V AC	CS6369	CS6364C	—	Yellow	4D562
50 ft	6/3, 8/1	50 A	125/250V AC	CS6365L	CS6364L	—	Black	12R421
100 ft	6/3, 8/1	50 A	125/250V AC	CS6365L	CS6364L	—	Black	12R422
CEP								
Cam Lock Temporary Power Cord								
6 ft	2/0	200 A	600V AC	CL20MBK	CL20FBK	1	Black	4NAE5

Cord Length	Wire Size	Max. Amps	Voltage	Plug Configuration	Receptacle Configuration	No. of Outlets	Color	Item No.
6 ft	2/0	200 A	600V AC	CL20MBU	CL20FBU	1	Black	4NAE6
6 ft	2/0	200 A	600V AC	Bare Wire	CL20FG	1	Black	4NAE7
6 ft	2/0	200 A	600V AC	Bare Wire	CL20FR	1	Black	4NAE8
6 ft	2/0	200 A	600V AC	CL20MW	CL20FW	1	Black	4NAE9
10 ft	4/0	400 A	600V AC	CL40MBK	CL40FBK	1	Black	4NAG3
10 ft	4/0	400 A	600V AC	CL40MBU	CL40FBU	1	Black	4NAG4
10 ft	4/0	400 A	600V AC	CL40MG	CL40FG	1	Black	4NAG5
10 ft	4/0	400 A	600V AC	CL40MR	CL40FR	1	Black	4NAG6
10 ft	4/0	400 A	600V AC	CL40MW	CL40FW	1	Black	4NAG7
25 ft	4/0	400 A	600V AC	CL4MBK	CL40FBK	1	Black	4NAF2
25 ft	4/0	400 A	600V AC	CL4MBU	CL40FBU	1	Black	4NAF3
25 ft	4/0	400 A	600V AC	CL4MG	CL40FG	1	Black	4NAF4
25 ft	4/0	400 A	600V AC	CL4MR	CL40FR	1	Black	4NAF5
25 ft	4/0	400 A	600V AC	CL4MW	CL40FW	1	Black	4NAF6
25 ft	2/0	200 A	600V AC	CL20MBK	CL20FBK	1	Black	4NAF7
25 ft	2/0	200 A	600V AC	CL20MBU	CL20FBU	1	Black	4NAF8
25 ft	2/0	200 A	600V AC	CL20MG	CL20FG	1	Black	4NAF9
25 ft	2/0	200 A	600V AC	CL20MR	CL20FR	1	Black	4NAG1
25 ft	2/0	200 A	600V AC	CL20MW	CL20FW	1	Black	4NAG2
Extension Cord								
50 ft	10 AWG	30.0 A	125/250V AC	NEMA L14-30P	NEMA L14-30R	1	Black	14N229
50 ft	10 AWG	20.0 A	125/250V AC	NEMA L14-20P	NEMA L14-20R	1	Black	14N231
50 ft	12 AWG	20.0 A	120/208V AC	NEMA L21-20P	NEMA L21-20R	1	Black	14N240
50 ft	10 AWG	30.0 A	120/208V AC	NEMA L21-30P	NEMA L21-30R	1	Black	14N242
100 ft	10 AWG	30.0 A	125/250V AC	NEMA L14-30P	NEMA L14-30R	1	Black	14N228
100 ft	10 AWG	20.0 A	125/250V AC	NEMA L14-20P	NEMA L14-20R	1	Black	14N230
100 ft	12 AWG	20.0 A	120/208V AC	NEMA L21-20P	NEMA L21-20R	1	Black	14N241
100 ft	10 AWG	30.0 A	120/208V AC	NEMA L21-30P	NEMA L21-30R	1	Black	14N243
Generator Cord with Pendant Box								
4 ft	12 AWG	20.0 A	120/240V AC	NEMA L14-20P	NEMA 5-20R	4	Black	14N232
25 ft	12 AWG	20.0 A	120/240V AC	NEMA L14-20P	NEMA 5-20R	4	Black	14N233
50 ft	12 AWG	20.0 A	120/240V AC	NEMA L14-20P	NEMA 5-20R	4	Black	14N234
100 ft	12 AWG	20.0 A	120/240V AC	NEMA L14-20P	NEMA 5-20R	4	Black	14N235
Prewired Receptacle								
—	10 AWG	30 A	125/250V AC	Bare Wire	L14-30R	—	Black	3GUK5
—	6 AWG	50 A	125/250V AC	Bare Wire	CS6369	—	Black	3GUK6
Temporary Power Cord								
6 ft	2/0	100 A	120/208V AC	Bare Wire	5100C9W	1	Black	4NAF1