

1-800-GRAINGER (472-4643)

Corrugated Split-Loom Tubing

Provides flexibility and chemical resistance to solvents. Impact-resistant at low temperatures. Designed for electrical, machinery, and building harness wiring. For use in various industrial, medical, and electrical applications.

Nom. Size	Tubing Length	POLYETHYLENE	
		Item No.	Item No.
Black			
	1/4 in	25 ft	16Y250
	100 ft	16Y245	16Y261
3/16 in	25 ft	16Y251	16Y256
	100 ft	16Y246	16Y257
1/2 in	25 ft	16Y252	16Y263
	100 ft	16Y247	16Y258

* 1/4" size are 50 ft.

Connection Type/Size			Item No.
Tee Fittings, Black Nylon, Pkg. of 10			
½ in x ¼ in (Without Thread)			19A641
Industrial, Medical and Electrical Applications, Provide Flexibility			
½ in x ⅜ in (Without Thread)			19D609
Industrial, Medical and Electrical Applications, Provide Flexibility			
Nom. Size	Tubing Length	POLYETHYLENE Item No.	NYLON Item No.
½ in	25 ft	16Y253	16Y264
	100 ft	16Y248	16Y259
¾ in	25 ft	16Y254	16Y265
	100 ft	16Y249	16Y260
1 ¼ in	50 ft	16Y255	16Y266



Corrugated Tubing and Fittings

Connect or disconnect these quick-release fittings with no tools required. Designed for use in any electrical installations that require a watertight seal and quick connection. UL Listed and CSA Certified.



Description	1/4 in Item No.	3/16 in Item No.	1/2 in Item No.	3/4 in Item No.	1 in Item No.	1 1/4 in Item No.	1 1/2 in Item No.	2 in Item No.
Nylon Fittings								
90° Elbow	25D318	25D319	25D320	25D321	25D322	25D323	25D324	25D325
Locknut, Qty. 10; (5 on 1 1/4")	25D342	25D344	—	—	25D345	25D346	25D347	25D348
Straight Connector	25D310	25D311	25D312	25D313	25D314	25D315	25D316	25D317
Support, Qty. 10	25D326	25D327	25D328	25D329	25D330	25D331	25D332	25D333
Support Top, Qty. 10	25D335	—	25D336	25D337	25D338	25D339	25D340	25D341
Polyamide 6 Tubing, Unslit								
10 ft	25D285	25D288	25D291	25D294	25D297	25D301	25D304	25D307
25 ft	25D286	25D289	25D292	25D295	25D298	25D302	25D305	25D308
45 ft	25D287	25D290	25D293	25D296	25D299	25D303	25D306	25D309



Corrugated Split-Loom Tubing

Provides protection and organization to wires, cables, and hoses. Corrugated for flexibility and easy installation. Abrasion-, fluid-, and weather-resistant.

Description/ Special Features	Item No.
Split Loom Installation Tools	
Loom Tool for 1/4 in to 1/2 in Conduit	25D279
Loom Tool for 1/2 in to 3/4 in Conduit	25D280
Loom Tool for 3/4 in to 1 in Conduit	25D281
Loom Tool for 1 in to 1 1/4 in Conduit	25D282
Loom Tool for 1 1/4 in to 2 in Conduit	25D283

Nom. Size	Tubing Length	POLYETHYLENE Item No.	NYLON Item No.
Tubing			
1/4 in	3,200 ft	25D255	25D266
1/4 in	100 ft	—	25D274
3/8 in	1,900 ft	25D256	25D267
3/8 in	100 ft	—	25D275
1/2 in	1,100 ft	25D257	25D268
1/2 in	100 ft	—	25D276
5/8 in	800 ft	25D258	25D269
3/4 in	100 ft	—	25D277
3/4 in	50 ft	25D259	25D270
1 in	50 ft	—	25D278
1 1/2 in	150 ft	25D262	25D273
1 1/4 in	250 ft	25D261	25D272
1 in	300 ft	25D260	25D271
2 in	100 ft	25D263	—
2 1/2 in	500 ft	25D264	—
3 1/2 in	300 ft	25D265	—



Spiral Wrap
1LEZ3



Pan-Wrap™
1LEY8

PANDUIT®

Wire Protection Wrap

SPIRAL WRAP

- Natural color
- Temp. range: -40° to 122°F

Allows breakouts of single/multiple wires. Great for harnessing multiple cables into a single manageable bundle. Each roll includes installation tool. UL Recognized.

PAN-WRAP™

- Black color
- Temp. range: -40° to 122°F


Slot pattern provides improved flexibility and abrasion protection in any application. Wall design facilitates cable breakouts. UL Recognized.

Pan-Wrap™ Installation Tools

- Black color
- Temp. range: -40° to 122°F

180° opening allows easy loading of max. bundle diameters to considerably speed Pan-Wrap™ installation.

W	Spiral Wrap Length	Spiral Wrap Dia. Range	Mfr. Model	Item No.
Spiral Wrap, Polyethylene				
1/4 in	100 ft	0.1875 in to 2 in	T25F-C	1LEZ3
1/2 in	100 ft	0.3125 in to 3 in	T38F-C	1LEZ4
3/4 in	100 ft	0.3750 in to 4 in	T50F-C	1LEZ5
1 in	100 ft	0.6250 in to 5 in	T75F-C	1LEZ6
1 1/4 in	100 ft	0.8750 in to 6 in	T100F-C	1LEZ7
Pan-Wrap™, Polyethylene				
1/2 in	200 ft	0.430 in to 0.550 in	PW50F-T20	1LEY8
3/4 in	100 ft	0.550 in to 0.810 in	PW75F-C20	1LEY9
1 in	100 ft	0.810 in to 1.130 in	PW100F-C20	1LEZ1
1 1/2 in	50 ft	1.130 in to 1.630 in	PW150F-L	1LEZ2
For Use With				Item No.
Pan-Wrap™ Installation Tools				
Mfr. No. PW50F-T20	PWT50	1LEL5		
Mfr. No. PW75F-C20	PWT75	1LEL6		
Mfr. No. PW100F-C20	PWT100	1LEY6		
Mfr. No. PW150F-L20	PWT150	1LEY7		



1LLJ6

PANDUIT®

Braided Expandable Sleeving

- Black color
- 100-ft. lengths

Provides continuous abrasion protection for wires, cables, hoses, and tubing. Highly flexible open weave will not trap heat or humidity, and allows irregular shapes. Lightweight and durable protection. UL Recognized.

Material of Construc.	Inside Dia.	Mfr. Model	Item No.
PET	1/2 in	SE50P-CRO	1LLJ6
PET	1/2 in	SE50PFR-CRO	1LLJ7

Sign in to **Grainger.com®** to see **YOUR Pricing** and **MORE**