



CONTINUED

PHILIPS Current®

Light Efficient Design

SYLVANIA

KEYSTONE
LIGHT MADE EASY



E26 Medium Screw-Base HID & LED HID-Replacement Light Bulbs

Light Technology	Watts	Color Temp.	Lumens	Rated Life	Bulb Shape	Bulb UL Type	Voltage	Overall Length	ANSI Code	Brand	Item No.
Metal Halide	150 W	2100K	15,800 lm	24,000 hr	E17	—	—	2 3/8 in	—	Sylvania	56GJ79
	150 W	2900K	12,900 lm	10,000 hr	ED17P	No UL Type	—	1 in	M142/M102/O	Philips	492Y76
	150 W	3500K	12,500 lm	15,000 hr	ED17	No UL Type	—	5 1/2 in	C102/M102	Current	6XT93
	150 W	4000K	12,900 lm	12,000 hr	ED17	—	—	2 3/8 in	—	Sylvania	56GK07
	150 W	4300K	14,000 lm	15,000 hr	BD17	No UL Type	—	5 1/2 in	M102	Current	1E690
175W MH/175W HPS Wattage Equivalency											
LED	35 W	4000K	5,290 lm	50,000 hr	Cylindrical	Type B	120 to 277 V AC	7 1/4 in	—	Light Efficient Design	60TD91
	35 W	5000K	5,360 lm	50,000 hr	Cylindrical	Type B	120 to 277 V AC	7 1/4 in	—	Light Efficient Design	60TD92
	35 W, 45 W, 60 W	3000K, 4000K, 5000K	5,290 lm, 6,510 lm, 8,790 lm	50,000 hr	Cylindrical	Type B	120 to 277 V AC	7 1/4 in	—	Light Efficient Design	60TD81
LED	45 W	3000K, 4000K, 5000K	3,645 lm, 3,780 lm, 3,915 lm, 4,860 lm, 5,040 lm, 5,220 lm, 6,075 lm, 6,300 lm, 6,525 lm	50,000 hr	HID	No UL Type	120 to 277 V AC	9 1/8 in	—	Keystone Technologies	61DA09
	45 W	4000K	6,300 lm	50,000 hr	HID	No UL Type	120 to 277 V AC	9 1/4 in	—	Keystone Technologies	61CZ94
LED	45 W	5000K	6,400 lm	50,000 hr	HID	No UL Type	120 to 277 V AC	9 1/4 in	—	Keystone Technologies	61CZ95
	50 W	3000K, 4000K, 5000K	6400 lm, 6900 lm, 7200 lm	50,000 hr	Cylindrical	—	120 to 277 V AC	7 7/8 in	—	Light Efficient Design	792VA5
Metal Halide	60 W	4000K	6,684 lm	50,000 hr	High/Low Bay	Type B	120 to 277 V AC	6 1/8 in	—	Light Efficient Design	55VR23
	60 W	5700K	7,062 lm	50,000 hr	High/Low Bay	Type B	120 to 277 V AC	6 1/8 in	—	Light Efficient Design	55VR24
	80 W	4000K	12,000 lm	50,000 hr	ED37	Type B	120 to 277 V AC	7 3/4 in	—	Current	429U44
	175 W	4000K	14,000 lm	10,000 hr	BD17	No UL Type	—	5 1/2 in	M57/E	Philips	492Y67
	175 W	4000K	14,400 lm	7,500 hr	E17	—	—	2 3/8 in	—	Sylvania	56GK66
Metal Halide	175 W	4000K	13,600 lm	10,000 hr	BD17	No UL Type	—	5 3/4 in	M57	Current	6V751
	175 W	4000K	8,380 lm	10,000 hr	BD17	—	—	5 219/500 in	M57/E	Philips	796NT6
Hazardous Location LED HID-Replacement Light Bulbs											
50W MH/50W HPS Wattage Equivalency											
LED	21 W	3000K	3000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM18
	21 W	4000K	3000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM19
	21 W	5000K	3000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM20
70W MH/70W HPS Wattage Equivalency											
LED	35 W	3000K	5000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM21
	35 W	4000K	5000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM22
	35 W	5000K	5000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM23
100W MH/100W HPS Wattage Equivalency											
LED	45 W	3000K	6000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM24
	45 W	4000K	6000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM25
	45 W	5000K	6000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/8 in	—	Current	61JM26
150W MH/150W HPS Wattage Equivalency											
LED	45 W	5000K	6,620 lm	50,000 hr	Cylindrical	Type B	120/277 V	7 3/4 in	—	Light Efficient Design	797A46
	45 W	5000K	6,620 lm	50,000 hr	Cylindrical	Type B	120/277 V; 208 V; 240 V	7 3/4 in	—	Light Efficient Design	797A47
	80 W	4000K	12,000 lm	50,000 hr	ED23.5	Type B	120 to 277 V AC	7 3/8 in	—	Current	797RA0
	80 W	5000K	12,000 lm	50,000 hr	ED23.5	Type B	120 to 277 V AC	7 3/8 in	—	Current	797RA1
Shatter-Resistant HID Light Bulbs											
50W MH/50W HPS Wattage Equivalency											
LED	18 W	4000K	2,400 lm	50,000 hr	Cylindrical	Type B	—	5 3/4 in	—	Philips	60EE86
70W MH/70W HPS Wattage Equivalency											
LED	18 W	3000K	2,300 lm	50,000 hr	Corn Cob	—	100 to 277 V AC	5 3/4 in	—	Philips	56LX06
	20 W	3000K	2,800 lm	50,000 hr	Corn Cob	Type B	100 to 277 V AC	5 3/8 in	—	Philips	56LX15
	20 W	5000K	3,000 lm	50,000 hr	Cylindrical	Type B	—	5 3/8 in	—	Philips	60EE89
	27 W	4000K	3,700 lm	50,000 hr	Cylindrical	Type B	—	6 1/8 in	—	Philips	60EE70
	27 W	5000K	3,800 lm	50,000 hr	Cylindrical	Type B	—	6 1/8 in	—	Philips	60EE90
100W MH/100W HPS Wattage Equivalency											
LED	27 W	3000K	3,500 lm	50,000 hr	Corn Cob	Type B	100 to 277 V AC	6 3/4 in	—	Philips	56LX08
	36 W	3000K	5,000 lm	50,000 hr	Corn Cob	Type B	100 to 277 V AC	8 in	—	Philips	56LX10
150W MH/150W HPS Wattage Equivalency											
LED	36 W	4000K	5,200 lm	50,000 hr	Cylindrical	Type B	—	8 in	—	Philips	60EE71
	36 W	5000K	5,400 lm	50,000 hr	Cylindrical	Type B	—	8 in	—	Philips	60EE92

2-Pin Base HID Light Bulbs PHILIPS Current® SYLVANIA



Light Technology	Watts	Color Temp.	Lumens	Rated Life	Bulb Shape	Overall Length	ANSI Code	Brand	Item No.
612 2-Pin Base HID Light Bulbs									
35W MH Wattage Equivalency									
Metal Halide	35 W	3000K	3,300 lm	12,000 hr	T6	1 in	C130/E	Philips	492Y41
39W MH Wattage Equivalency									
Metal Halide	39 W	3000K	3,400 lm	15,000 hr	T4-1/2	3 1/2 in	M130	Current	5HB79
Metal Halide	39 W	3000K	3,400 lm	15,000 hr	T6	1 21/2 in	—	Sylvania	56GJ80
70W MH/70W HPS Wattage Equivalency									
Compact Fluorescent	70W	3000K	7400 lm	15,000 hr	T6	1 21/2 in	—	Sylvania	56GJ93
70W MH Wattage Equivalency									
Metal Halide	70 W	3000K	6,200 lm	15,000 hr	T6	3 1/2 in	M139/M85/M98	Current	5HB80
Metal Halide	70 W	3000K	6,600 lm	12,000 hr	T6	3 1/2 in	C139/E	Philips	492Y43
150W MH Wattage Equivalency									
Metal Halide	150 W	3000K	13,000 lm	12,000 hr	T6	1 in	C142/E	Philips	492Y42
G8.5 2-Pin Base HID Light Bulbs									
20W MH Wattage Equivalency									
Ceramic Metal Halide	20 W	3000K	1,650 lm	12,000 hr	T4-1/2	3 3/8 in	M156	Current	1RD93
Ceramic Metal Halide	20 W	3000K	1,620 lm	12,000 hr	T14	85 mm	—	Philips	796NR8
35W MH Wattage Equivalency									
Metal Halide	35 W	3000K	3,300 lm	12,000 hr	T4	1 in	C130/E	Philips	492Y40
39W MH Wattage Equivalency									
Metal Halide	39 W	3000K	3,400 lm	16,500 hr	T4-1/2	3 3/8 in	M130	Current	4DA27
70W MH Wattage Equivalency									
Metal Halide	70 W	3000K	6,200 lm	15,000 hr	T4-1/2	3 3/8 in	M139	Current	2DZX8
Ceramic Metal Halide	73 W	3000K	6,300 lm	12,000 hr	T14	85 mm	C139/E	Philips	796NR9
G06.5 2-Pin Base HID Light Bulbs									
20W MH Wattage Equivalency									
Ceramic Metal Halide	20 W	3000K	1,615 lm	12,000 hr	T4	2 1/2 in	C156/M156	Current	1TJR6
Metal Halide	20 W	3000K	1,800 lm	20,000 hr	T4	2 1/2 in	C156/E	Philips	492Y39
Metal Halide	20 W	3000K	1,700 lm	15,000 hr	T4	1 21/2 in	—	Sylvania	56GJ92
39W MH Wattage Equivalency									
Metal Halide	39 W	3000K	3,400 lm	10,000 hr	T4	2 1/2 in	C130/M130	Current	3DXR7
Ceramic Metal Halide	39 W	3000K	3,600 lm	12,000 hr	T13.3	56 7/16 mm	C130/E	Philips	796NT2