



PAR Light Bulbs



Parabolic aluminized reflector (PAR) light bulbs are used for indoor and outdoor accent lighting, such as highlighting flagpoles or building facades, interior track lighting, illuminating walls, security lighting, stage lighting, and sign lighting.

Medium Screw
(E26) BaseScrew Terminals
BaseMogul End
Prong
(GX16d)
Base

Light Technology	Wattage Equivalency	Watts	Color Temp.	Lumens	Bulb Beam Angle	Dimmable	Rated Life	Overall Length	Brand	Item No.	Pkg. Qty.
PAR16 Bulb Shape; 2-Pin (GU10) Bulb Base Type											
LED	50W HAL	5 W	2700K	380 lm	35°	Yes	25,000 hr	2 ½ in	Philips	45HE82	1
PAR16 Bulb Shape; Medium Screw (E26) Bulb Base Type											
LED	45W INC	4.1 W	3000K	375 lm	40°	Yes	25,000 hr	3 in	Feit Electric	56JH46	1
	45W INC	4.1 W	5000K	375 lm	40°	Yes	25,000 hr	3 in	Feit Electric	56JH47	1
	50W HAL	7 W	2700K	500 lm	35°	Yes	25,000 hr	3 ½ in	Current	45CM40	1
PAR20 Bulb Shape; Medium Screw (E26) Bulb Base Type											
LED	50W HAL	7 W	2700K	500 lm	20°	Yes	25,000 hr	3 ½ in	Current	45NY24	1
	50W HAL	7 W	3000K	520 lm	20°	Yes	25,000 hr	3 ½ in	Current	45AU69	1
	50W HAL	7 W	3000K	520 lm	20°	Yes	25,000 hr	3 ½ in	Current	45NY25	1
	50W HAL	7 W	3000K	520 lm	20°	Yes	25,000 hr	3 ½ in	Current	45NY26	1
	50W INC	5 W	3000K	450 lm	40°	Yes	25,000 hr	3 ¼ in	Feit Electric	56JH73	1
	50W INC	5 W	5000K	450 lm	40°	Yes	25,000 hr	3 ¼ in	Feit Electric	56JH74	1
	50W INC	7 W	2700K	500 lm	35°	Yes	15,000 hr	3 ½ in	Current	482P42	1
	50W PAR20 HAL	5.5 W	2700K	500 lm	25°	Yes	25,000 hr	3 ¼ in	Philips	784N84	1
	50W PAR20 HAL	5.5 W	2700K	500 lm	40°	Yes	25,000 hr	3 ¼ in	Philips	784N85	1
	50W PAR20 HAL	5.5 W	3000K	500 lm	25°	Yes	25,000 hr	3 ¼ in	Philips	784N86	1
	50W PAR20 HAL	5.5 W	3000K	500 lm	40°	Yes	25,000 hr	3 ¼ in	Philips	784N87	1
PAR30 Bulb Shape; Medium Screw (E26) Bulb Base Type											
LED	75W HAL	12 W	2700K	1,000 lm	25°	Yes	25,000 hr	3 ¾ in	Current	45NY16	1
	75W HAL	12 W	2700K	1,000 lm	40°	Yes	25,000 hr	3 ¾ in	Current	45NY17	1
	75W HAL	12 W	3000K	1,050 lm	25°	Yes	25,000 hr	3 ¾ in	Current	45NY18	1
	75W HAL	12 W	3000K	1,050 lm	40°	Yes	25,000 hr	3 ¾ in	Current	45NY19	1
	75W INC	8.3 W	3000K	750 lm	38°	Yes	25,000 hr	4 ¾ in	Feit Electric	56JH75	1
	75W INC	8.3 W	3000K	750 lm	25°	Yes	25,000 hr	4 ¾ in	Feit Electric	56JH77	1
	75W INC	8.3 W	3000K	750 lm	40°	Yes	25,000 hr	3 ½ in	Feit Electric	56JH79	1
	75W INC	8.3 W	5000K	750 lm	40°	Yes	25,000 hr	4 ¾ in	Feit Electric	56JH76	1
	75W INC	8.3 W	5000K	750 lm	25°	Yes	25,000 hr	4 ¾ in	Feit Electric	56JH78	1
	75W INC	8.3 W	5000K	750 lm	40°	Yes	25,000 hr	3 ½ in	Feit Electric	56JH80	1
	75W INC	12 W	2700K	850 lm	40°	Yes	25,000 hr	3 ¾ in	Current	246M70	1
	75W INC	12 W	3000K	900 lm	40°	Yes	25,000 hr	9 in	Current	246M68	1
PAR30L Bulb Shape; Medium Screw (E26) Bulb Base Type											
LED	75W HAL	12 W	2700K	1,000 lm	40°	Yes	25,000 hr	4 ¾ in	Current	45NY21	1
	75W HAL	12 W	3000K	1,050 lm	25°	Yes	25,000 hr	4 ¾ in	Current	45NY22	1
	75W HAL	12 W	3000K	1,050 lm	40°	Yes	25,000 hr	4 ¾ in	Current	45NY23	1
	75W INC	9 W	3000K	850 lm	40°	Yes	25,000 hr	3 ¾ in	Philips	60FV14	1
	75W INC	12 W	2700K	850 lm	40°	Yes	25,000 hr	8 ½ in	Current	246M73	1
	75W INC	12 W	2700K	1,050 lm	25°	Yes	25,000 hr	4 ¾ in	Current	55XC93	1
	75W INC	12 W	3000K	900 lm	40°	Yes	25,000 hr	9 in	Current	246M72	1
	75W INC	12 W	3000K	900 lm	25°	Yes	25,000 hr	4 ¾ in	Current	55XC92	1
	75W PAR30 HAL Long Neck	8.5 W	2700K	800 lm	25°	Yes	25,000 hr	4 ¾ in	Philips	784N74	1
	75W PAR30 HAL Long Neck	8.5 W	2700K	800 lm	40°	Yes	25,000 hr	4 ¾ in	Philips	784N76	1
	75W PAR30 HAL Long Neck	8.5 W	3000K	850 lm	25°	Yes	25,000 hr	4 ¾ in	Philips	784N75	1
	75W PAR30 HAL Long Neck	8.5 W	3000K	850 lm	40°	Yes	25,000 hr	4 ¾ in	Philips	784N77	1
PAR30S Bulb Shape; Medium Screw (E26) Bulb Base Type											
LED	75W INC	9 W	3000K	850 lm	40°	Yes	25,000 hr	3 ¾ in	Philips	60FV13	1
	75W PAR30 HAL Short Neck	8.5 W	2700K	800 lm	25°	Yes	25,000 hr	3 ½ in	Philips	784N70	1
	75W PAR30 HAL Short Neck	8.5 W	2700K	800 lm	40°	Yes	25,000 hr	3 ½ in	Philips	784N72	1
	75W PAR30 HAL Short Neck	8.5 W	3000K	850 lm	25°	Yes	25,000 hr	3 ½ in	Philips	784N71	1
	75W PAR30 HAL Short Neck	8.5 W	3000K	850 lm	40°	Yes	25,000 hr	3 ½ in	Philips	784N73	1
	75W PAR30 HAL Short Neck	8.5 W	3000K	850 lm	40°	Yes	25,000 hr	3 ½ in	Philips	784N73	1
PAR36 Bulb Shape; Screw Terminals Bulb Base Type											
Halogen	35W INC	35 W	3000K	250 lm	30°	Yes	4,000 hr	3 ¾ in	Current	4V091	1
Incandescent	100W INC	100W	3000K	8750 lm	40°	Yes	25 hr	2 ¾ in	Current	6VK26	1
PAR38 Bulb Shape; Medium Screw (E26) Bulb Base Type											
LED	90W INC	11.1 W	3000K	1000 lm	38°	Yes	25,000 hr	5 in	Feit Electric	56JH83	1
	90W INC	11.1 W	5000K	1000 lm	38°	Yes	25,000 hr	5 in	Feit Electric	56JH84	1
	90W PAR38 HAL	10 W	2700K	900 lm	40°	Yes	25,000 hr	5 ½ in	Philips	784N68	1
	90W PAR38 HAL	10 W	2700K	900 lm	25°	Yes	25,000 hr	5 ½ in	Philips	784N65	1
	90W PAR38 HAL	10 W	3000K	900 lm	25°	Yes	25,000 hr	5 ½ in	Philips	784N66	1
	90W PAR38 HAL	10 W	3000K	900 lm	40°	Yes	25,000 hr	5 ½ in	Philips	784N69	1
	90W PAR38 HAL	10 W	3500K	900 lm	40°	Yes	25,000 hr	5 ½ in	Philips	784NC4	1
	90W PAR38 HAL	10 W	4000K	900 lm	25°	Yes	25,000 hr	5 ½ in	Philips	784N67	1
	120W HAL	14 W	2700K	1,300 lm	25°	Yes	25,000 hr	5 ¼ in	Philips	55YD37	1
	120W HAL	18 W	2700K	1,250 lm	40°	Yes	25,000 hr	5 ½ in	Current	246M80	1
	120W HAL	18 W	2700K	1,550 lm	25°	Yes	25,000 hr	5 ½ in	Current	45NY11	1
	120W HAL	18 W	2700K	1,550 lm	40°	Yes	25,000 hr	5 ½ in	Current	45NY12	1
	120W HAL	18 W	3000K	1,350 lm	40°	Yes	25,000 hr	5 ½ in	Current	246M84	1
	120W HAL	18 W	3000K	1,550 lm	25°	Yes	25,000 hr	5 ½ in	Current	45NY09	1
	120W HAL	18 W	4000K	1,700 lm	25°	Yes	25,000 hr	5 ½ in	Current	45NY13	1
	120W INC	15.5 W	3000K	1400 lm	40°	Yes	25,000 hr	5 in	Feit Electric	56JH81	1
	120W INC	15.5 W	5000K	1400 lm	40°	Yes	25,000 hr	5 in	Feit Electric	56JH82	1
	120W INC	18 W	4000K	1,700 lm	40°	Yes	25,000 hr	5 ½ in	Current	45NY14	1
	120W PAR38 HAL	13 W	2700K	1,200 lm	25°	Yes	25,000 hr	5 ½ in	Philips	784N78	1
	120W PAR38 HAL	13 W	2700K	1,200 lm	40°	Yes	25,000 hr	5 ½ in	Philips	784N82	1
	120W PAR38 HAL	13 W	3000K	1,200 lm	25°	Yes	25,000 hr	5 ½ in	Philips	784N79	1
	120W PAR38 HAL	13 W	3000K	1,200 lm	40°	Yes	25,000 hr	5 ½ in	Philips	784N83	1
	120W PAR38 HAL	13 W	3500K	1,200 lm	40°	Yes	25,000 hr	5 ½ in	Philips	784NC6	1
	120W PAR38 HAL	13 W	4000K	1,200 lm	25°	Yes	25,000 hr	5 ½ in	Philips	784N80	1
	120W PAR38 HAL	13 W	5000K	1,200 lm	25°	Yes	25,000 hr	5 ½ in	Philips	784N81	1
	150W HAL	18 W	3000K	1,550 lm	40°	Yes	25,000 hr	5 ½ in	Current	45NY10	1
	250W PAR38 HAL	27 W	3000K	2,800 lm	15°	Yes	25,000 hr	5 ½ in	Philips	784NC1	1
	250W PAR38 HAL	27 W	3000K	2,800 lm	25°	Yes	25,000 hr	5 ½ in	Philips	784NC2	1
PAR56 Bulb Shape; Mogul End Prong (GX16d) Bulb Base Type											
Incandescent	300W INC	300W	2750K	3840 lm	60°	Yes	2,000 hr	5 in	Current	4V499	1
PAR56 Bulb Shape; Screw Terminals Bulb Base Type											
Incandescent	200W INC	200W	3000K	3700 lm	15°	Yes	350 hr	4 ½ in	Current	5V123	1
	350W INC	350W	3000K	6200 lm	15°	Yes	500 hr	4 ½ in	Current	1K441	1
PL Vertical Bulb Shape; 2-Pin (G24d) Bulb Base Type											
LED	75W INC/18 to 20W CFL	10.5 W	3500K	1,050 lm	120°	No	50,000 hr	6 ½ in	Current	54EL44	1
	75W INC/18 to 20W CFL	10.5 W	4000K	1,050 lm	120°	No	50,000 hr	6 ½ in	Current	54EL45	1

PAR16
45HE82PAR20
45NY24PAR30
246M68PAR30L
784N76PAR30S
60FV13PAR38
45NY09PAR56
1K441PL Vertical
54EL45