

1-800-GRAINGER (472-4643)

CONTINUED



Current © **PHILIPS SYLVANIA**
EX39 Mogul Screw-Base HID & LED HID-Replacement Light Bulbs

Light Technology	Watts	Color Temp.	Lumens	Rated Life	Bulb Shape	Bulb Power Source	Overall Length	ANSI Code	Brand	Item No.
250W MH/250W HPS Wattage Equivalency										
LED	45 W	4000K	6,525 lm	50,000 hr	Cylindrical	Direct Wired	11 1/2 in	---	Light Efficient Design	508G12
	75 W	3000K	9,750 lm	50,000 hr	High/Low Bay	Direct Wired	8 3/4 in	---	Light Efficient Design	508G05
	75 W	4000K	10,500 lm	50,000 hr	High/Low Bay	Direct Wired	8 3/4 in	---	Light Efficient Design	508G06
	75 W	5000K	10,875 lm	50,000 hr	High/Low Bay	Direct Wired	8 3/4 in	---	Light Efficient Design	508G07
	80 W	5000K	10,850 lm	50,000 hr	Cylindrical	Direct Wired	8 3/4 in	---	Light Efficient Design	493U98
	80 W	5000K	7,635 lm	50,000 hr	Cylindrical	Plug and Play	11 1/2 in	---	Light Efficient Design	53PX15
	90 W	4000K	11,825 lm	50,000 hr	High/Low Bay	Direct Wired	9 3/4 in	---	Light Efficient Design	54XJ70
	90 W	5000K	11,825 lm	50,000 hr	High/Low Bay	Direct Wired	9 3/4 in	---	Light Efficient Design	54XJ71
	95 W	4000K	12,900 lm	50,000 hr	High/Low Bay	Direct Wired	9 3/4 in	---	Light Efficient Design	45PC36
	95 W	5000K	12,900 lm	50,000 hr	High/Low Bay	Direct Wired	9 3/4 in	---	Light Efficient Design	45PC12
	100 W	4000K	11,046 lm	50,000 hr	High/Low Bay	Plug and Play	8 in	---	Light Efficient Design	53PX10
	100 W	5700K	10,096 lm	50,000 hr	High/Low Bay	Plug and Play	8 in	---	Light Efficient Design	53PX11
	115 W	4000K	18,000 lm	50,000 hr	ED37	Direct Wired	8 3/4 in	---	Current	429U49
	115 W	5000K	18,000 lm	50,000 hr	ED37	Direct Wired	8 3/4 in	---	Current	429U50
320W MH/320W HPS Wattage Equivalency										
LED	100 W, 110 W, 80 W	3000K, 4000K, 5000K	11,290 lm, 14,270 lm, 15,690 lm	50,000 hr	Cylindrical	Direct Wired	9 3/4 in	---	Light Efficient Design	60TD87
Metal Halide	320 W	3700K	30,600 lm	20,000 hr	ED28	---	8 1/4 in	M132	Current	2TJ27
Metal Halide	320 W	4000K	32,000 lm	20,000 hr	ED37	---	11 1/2 in	M132/M154	Current	6XV27
400W MH/400W HPS Wattage Equivalency										
LED	120 W	5000K	10,810 lm	50,000 hr	Cylindrical	Plug and Play	11 1/2 in	---	Light Efficient Design	53PX17
	135 W	4000K	17,055 lm	50,000 hr	High/Low Bay	Direct Wired	10 in	---	Light Efficient Design	54XJ68
	135 W	5000K	17,095 lm	50,000 hr	High/Low Bay	Direct Wired	10 in	---	Light Efficient Design	54XJ69
	140 W	4000K	19,200 lm	50,000 hr	High/Low Bay	Direct Wired	10 1/2 in	---	Light Efficient Design	45PC35
	140 W	4000K	18,619 lm	50,000 hr	High/Low Bay	Plug and Play	9 3/4 in	---	Light Efficient Design	53PX04
	140 W	5000K	19,500 lm	50,000 hr	High/Low Bay	Direct Wired	10 1/2 in	---	Light Efficient Design	45PC11
	140 W	5700K	17,047 lm	50,000 hr	High/Low Bay	Plug and Play	9 3/4 in	---	Light Efficient Design	53PX05
	150 W	4000K	23,500 lm	50,000 hr	ED37	Direct Wired	8 3/4 in	---	Current	429U51
	150 W	4000K	19,285 lm	50,000 hr	High/Low Bay	Direct Wired	10 in	---	Light Efficient Design	54XJ66
	150 W	5000K	23,500 lm	50,000 hr	ED37	Direct Wired	8 3/4 in	---	Current	429U52
	150 W	5000K	19,375 lm	50,000 hr	High/Low Bay	Direct Wired	10 in	---	Light Efficient Design	54XJ67
	165 W	4000K	20,000 lm	50,000 hr	High/Low Bay	Plug and Play	9 3/4 in	---	Philips	53XF99
	400 W	3500K	40,000 lm	20,000 hr	ED37	---	1 in	M135/O	Philips	492V61
	400 W	4000K	40,000 lm	20,000 hr	ED37	---	11 1/2 in	M59/O	Philips	492Y83
400 W	4000K	42,000 lm	20,000 hr	ED37	---	11 1/2 in	M135/M155	Current	6XV25	
1000W MH/1000W HPS Wattage Equivalency										
LED	270 W	4000K	40,000 lm	50,000 hr	BT56	Direct Wired	12 1/4 in	---	Current	493V22
	270 W	4000K	34,415 lm	50,000 hr	High/Low Bay	---	12 1/2 in	---	Light Efficient Design	55VR34
	270 W	5000K	40,000 lm	50,000 hr	BT56	Direct Wired	12 1/4 in	---	Current	493V23
	450 W	4000K	65,000 lm	50,000 hr	BT56	Direct Wired	12 1/4 in	---	Current	493V24
	450 W	5000K	65,000 lm	50,000 hr	BT56	Direct Wired	12 1/4 in	---	Current	493V25
	1000 W	3500K	107,000 lm	12,000 hr	BT56	---	15 1/8 in	M47/O	Philips	492Y72
Metal Halide	1000 W	3500K	110,000 lm	12,000 hr	BT56	---	15 1/8 in	M47	Current	5XP29
	1000 W	3800K	108,000 lm	15,000 hr	BT56	---	7 3/4 in	---	Sylvania	56GJ84
Shatter-Resistant HID Light Bulbs										
LED	35 W	3000K, 4000K, 5000K	4,800 lm, 5,000 lm	50,000 hr	Corn Cob	Direct Wired	8 1/2 in	---	Philips	784N99
	40 W	4000K	5,800 lm	50,000 hr	WP	Direct Wired	8 1/2 in	---	Philips	784N33
	40 W	5000K	6,000 lm	50,000 hr	WP	Direct Wired	8 1/2 in	---	Philips	784N34
	45 W	3000K	6,200 lm	50,000 hr	Corn Cob	Direct Wired	9 3/4 in	---	Philips	784N26
	45 W	3000K, 4000K, 5000K	5,800 lm, 6,200 lm	50,000 hr	Corn Cob	Direct Wired	9 3/4 in	---	Philips	784NA0
	45 W	3000K, 4000K, 5000K	7,500 lm, 7000 lm	50,000 hr	Corn Cob	Direct Wired	9 3/4 in	---	Philips	784NA1
	45 W	4000K	6,500 lm	50,000 hr	Corn Cob	Direct Wired	9 3/4 in	---	Philips	784N27
	45 W	5000K	6,700 lm	50,000 hr	Corn Cob	Direct Wired	9 3/4 in	---	Philips	784N28
	54 W	4000K	7,800 lm	50,000 hr	Corn Cob	Direct Wired	9 3/4 in	---	Philips	784N29
	54 W	5000K	8,000 lm	50,000 hr	Corn Cob	Direct Wired	9 3/4 in	---	Philips	784N30
	60 W	4000K	8,700 lm	50,000 hr	WP	Direct Wired	10 3/4 in	---	Philips	784N35
	60 W	5000K	9,000 lm	50,000 hr	WP	Direct Wired	10 3/4 in	---	Philips	784N36
	63 W	3000K, 4000K, 5000K	7,800 lm, 8,500 lm	50,000 hr	Corn Cob	Direct Wired	10 1/4 in	---	Philips	784NA2
	63 W	4000K	9,000 lm	50,000 hr	Corn Cob	Direct Wired	10 1/4 in	---	Philips	784N31
	63 W	5000K	9,200 lm	50,000 hr	Corn Cob	Direct Wired	10 1/4 in	---	Philips	784N32
	80 W	4000K	12,000 lm	50,000 hr	Corn Cob	Direct Wired	7 3/4 in	---	Philips	784N37
	80 W	5000K	12,000 lm	50,000 hr	Corn Cob	Direct Wired	7 3/4 in	---	Philips	784N38
	145 W	4000K	20,000 lm	50,000 hr	HB	Direct Wired	11 1/4 in	---	Philips	784N43
	145 W	4000K	20,000 lm	50,000 hr	HB	Direct Wired	11 3/4 in	---	Philips	784N44
	145 W	5000K	20,000 lm	50,000 hr	HB	Direct Wired	11 1/4 in	---	Philips	784N45
	145 W	5000K	20,000 lm	50,000 hr	HB	Direct Wired	11 3/4 in	---	Philips	784N46
	150 W	4000K	24,000 lm	50,000 hr	Corn Cob	Direct Wired	8 1/4 in	---	Philips	784N41
	150 W	5000K	24,000 lm	50,000 hr	Corn Cob	Direct Wired	8 1/4 in	---	Philips	784N42
	165 W	4000K	25,000 lm	50,000 hr	HB	Direct Wired	11 1/4 in	---	Philips	784N47
	165 W	4000K	25,000 lm	50,000 hr	HB	Direct Wired	11 3/4 in	---	Philips	784N48
	165 W	5000K	25,000 lm	50,000 hr	HB	Direct Wired	11 1/4 in	---	Philips	784N49
	165 W	5000K	25,000 lm	50,000 hr	HB	Direct Wired	11 3/4 in	---	Philips	784N50
	450 W	5000K	65,000 lm	50,000 hr	Corn Cob	Direct Wired	12 1/2 in	---	Philips	784NA4

GRAINGER CATALOGS
Are Digital Too!

- Choose From Our Library of Industry-Specific Catalogs
- Browse, Download or Share Pages
- Add Items to Your Cart and Check Out When Ready
- Browse now at grainger.com/catalogonline



Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**