



CONTINUED



**PHILIPS** Current **SYLVANIA**

**E26 Medium Screw-Base HID & LED HID-Replacement Light Bulbs**

Light Technology	Watts	Color Temp.	Lumens	Rated Life	Bulb Shape	Bulb UL Type	Voltage	Overall Length	ANSI Code	Brand	Item No.
High Pressure Sodium	150 W	2000K	16,000 lm	24,000 hr	ED17	No UL Type	—	5 3/4 in	S55	Current	2V713
	150 W	2100K	16,000 lm	24,000 hr	BD17	No UL Type	—	5 1/4 in	S55	Philips	492Y45
	150 W	2100K	15,800 lm	24,000 hr	E17	—	—	2 3/8 in	—	Sylvania	56GJ79
Metal Halide	150 W	2900K	12,900 lm	10,000 hr	ED17P	No UL Type	—	1 in	M142/M102/O	Philips	492Y76
	150 W	3400K	13,300 lm	15,000 hr	BD17	No UL Type	—	5 1/2 in	M102	Current	16G90
	150 W	3500K	12,500 lm	15,000 hr	ED17	No UL Type	—	5 1/2 in	C102/M102	Current	6XT93
	150 W	4000K	13,000 lm	20,000 hr	ED17	No UL Type	—	5 1/2 in	M142/M102/E	Philips	492Y66
	150 W	4000K	12,900 lm	12,000 hr	ED17	—	—	2 3/8 in	—	Sylvania	56GK07
	150 W	4300K	14,000 lm	15,000 hr	BD17	No UL Type	—	5 1/2 in	M102	Current	1E690
	150 W	4300K	14,000 lm	15,000 hr	BD17	No UL Type	—	5 1/2 in	M102	Current	1E690
<b>175W MH/175W HPS Wattage Equivalency</b>											
	35 W	4000K	5,290 lm	50,000 hr	Cylindrical	Type B	120 to 277 V AC	7 1/4 in	—	Light Efficient Design	60TD91
	35 W	5000K	5,360 lm	50,000 hr	Cylindrical	Type B	120 to 277 V AC	7 1/4 in	—	Light Efficient Design	60TD92
	35 W, 45 W, 60 W	3000K, 4000K, 5000K	5,290 lm, 6,510 lm, 8,790 lm	50,000 hr	Cylindrical	Type B	120 to 277 V AC	7 1/4 in	—	Light Efficient Design	60TD81
LED	45 W	3000K, 4000K, 5000K	3,645 lm, 3,780 lm, 3,915 lm, 4,860 lm, 5,040 lm, 5,220 lm, 6,075 lm, 6,300 lm, 6,525 lm	50,000 hr	HID	No UL Type	120 to 277 V AC	9 1/8 in	—	Keystone Technologies	61DA09
	45 W	4000K	5,334 lm	50,000 hr	High/Low Bay	Type B	120 to 277 V AC	5 3/4 in	—	Light Efficient Design	60RF17
	45 W	4000K	6,300 lm	50,000 hr	HID	No UL Type	120 to 277 V AC	9 1/4 in	—	Keystone Technologies	61CZ94
	45 W	5000K	6,400 lm	50,000 hr	HID	No UL Type	120 to 277 V AC	9 1/4 in	—	Keystone Technologies	61CZ95
	50 W	3000K, 4000K, 5000K	6400 lm, 6900 lm, 7200 lm	50,000 hr	Cylindrical	—	120 to 277 V AC	7 7/8 in	—	Light Efficient Design	79ZVA5
	60 W	4000K	6,684 lm	50,000 hr	High/Low Bay	Type B	120 to 277 V AC	6 1/8 in	—	Light Efficient Design	55VR23
	60 W	5700K	7,062 lm	50,000 hr	High/Low Bay	Type B	120 to 277 V AC	6 1/8 in	—	Light Efficient Design	55VR24
Metal Halide	80 W	4000K	12,000 lm	50,000 hr	ED37	Type B	120 to 277 V AC	7 3/4 in	—	Current	429U44
	175 W	4000K	14,000 lm	10,000 hr	BD17	No UL Type	—	5 1/2 in	M57/E	Philips	492Y67
	175 W	4000K	14,400 lm	7,500 hr	E17	—	—	2 3/8 in	—	Sylvania	56GK66
175 W	4000K	13,600 lm	10,000 hr	BD17	No UL Type	—	5 3/4 in	M57	Current	6V751	
<b>Hazardous Location LED HID-Replacement Light Bulbs</b>											
<b>50W MH/50W HPS Wattage Equivalency</b>											
LED	21 W	3000K	3000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/4 in	—	Current	61JM18
LED	21 W	4000K	3000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/4 in	—	Current	61JM19
<b>70W MH/70W HPS Wattage Equivalency</b>											
LED	35 W	3000K	5000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/4 in	—	Current	61JM21
LED	35 W	4000K	5000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/4 in	—	Current	61JM22
LED	35 W	5000K	5000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/4 in	—	Current	61JM23
<b>100W MH/100W HPS Wattage Equivalency</b>											
LED	45 W	3000K	6000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/4 in	—	Current	61JM24
LED	45 W	4000K	6000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/4 in	—	Current	61JM25
LED	45 W	5000K	6000 lm	50,000 hr	ED17	Type B	120 to 277 V AC	5 3/4 in	—	Current	61JM26
<b>Shatter-Resistant HID Light Bulbs</b>											
<b>50W MH/50W HPS Wattage Equivalency</b>											
LED	18 W	4000K	2,400 lm	50,000 hr	Cylindrical	Type B	—	5 3/4 in	—	Philips	60EE86
LED	18 W	5000K	2,500 lm	50,000 hr	Cylindrical	Type B	—	5 3/4 in	—	Philips	60EE87
<b>70W MH/70W HPS Wattage Equivalency</b>											
LED	18 W	3000K	2,300 lm	50,000 hr	Corn Cob	—	100 to 277 V AC	5 3/4 in	—	Philips	56LX06
	20 W	2900K	2,900 lm	50,000 hr	Cylindrical	Type B	—	5 3/8 in	—	Philips	60EE88
	20 W	3000K	2,800 lm	50,000 hr	Corn Cob	Type B	100 to 277 V AC	5 3/8 in	—	Philips	56LX15
	20 W	3000K	3,000 lm	50,000 hr	Cylindrical	Type B	—	5 3/8 in	—	Philips	60EE89
	27 W	4000K	3,700 lm	50,000 hr	Cylindrical	Type B	—	6 1/8 in	—	Philips	60EE70
	27 W	5000K	3,800 lm	50,000 hr	Cylindrical	Type B	—	6 1/8 in	—	Philips	60EE90
	100W MH/100W HPS Wattage Equivalency	27 W	3000K	3,500 lm	50,000 hr	Corn Cob	Type B	100 to 277 V AC	6 3/4 in	—	Philips
LED	36 W	3000K	5,000 lm	50,000 hr	Corn Cob	Type B	100 to 277 V AC	8 in	—	Philips	56LX10
<b>150W MH/150W HPS Wattage Equivalency</b>											
LED	36 W	4000K	5,200 lm	50,000 hr	Cylindrical	Type B	—	8 in	—	Philips	60EE71
LED	36 W	5000K	5,400 lm	50,000 hr	Cylindrical	Type B	—	8 in	—	Philips	60EE92




**B22d Bayonet-Base LED HID-Replacement Light Bulbs**

The B22d bayonet base on these light bulbs is a 22mm-dia. base with two contacts on the bottom and lugs on either side that lock the bulb in place when the base is pushed into a compatible socket and twisted. These LED bulbs replace low-pressure sodium (LPS or SOX) HID bulbs in outdoor light fixtures.



55VR26



Bayonet Base (B22d) Base

Light Technology	Watts	Color Temp.	Lumens	Rated Life	Bulb Shape	Base Type	Overall Length	Item No.
<b>B22d Bayonet-Base HID &amp; LED HID-Replacement Light Bulbs</b>								
<b>35W LPS SOX Wattage Equivalency</b>								
LED	20 W	2200K	2,030 lm	50,000 hr	T17	Bayonet Base (B22d)	12 1/2 in	55VR26
LED	20 W	4000K	3,022 lm	50,000 hr	T17	Bayonet Base (B22d)	12 1/4 in	55VR27
<b>55W LPS SOX Wattage Equivalency</b>								
LED	35 W	2200K	3,232 lm	50,000 hr	T17	Bayonet Base (B22d)	16 3/4 in	55VR28
LED	35 W	4000K	5,156 lm	50,000 hr	T17	Bayonet Base (B22d)	16 3/4 in	55VR29
<b>90W LPS SOX Wattage Equivalency</b>								
LED	60 W	2200K	5,769 lm	50,000 hr	T17	Bayonet Base (B22d)	20 1/2 in	55VR30
LED	60 W	4000K	8,198 lm	50,000 hr	T17	Bayonet Base (B22d)	20 1/2 in	55VR31
<b>180W LPS SOX Wattage Equivalency</b>								
LED	100 W	2200K	11,576 lm	50,000 hr	T17	Bayonet Base (B22d)	43 1/2 in	55VR32
LED	100 W	4000K	15,472 lm	50,000 hr	T17	Bayonet Base (B22d)	43 1/2 in	55VR33