CONTINUED

LED Strip Lights

Max. Fixture Wattage	Color Temp.	Lumens	Lumens Per Watt	Color Index	Emergency Battery Backup	Dimmable	Linkable	Lighting Certification	Series	Brand	Item No.
Tube-Style Lens											
25 W	4000K	3,565 lm	120 lm/W	80	No	Yes	No	DLC 5.0	ZL1N	Lithonia Lighting	**36UX13**
30 W	3500K	3,966 lm	132.2 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D77**
	4000K	4,028 lm	134.2 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D78**
	5000K	4,176 lm	139.2 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D79**
34 W	4000K	4,964 lm	110 lm/W	80	No	Yes	No	DLC 5.0	ZL1N	Lithonia Lighting	**36UX12**
	4000K	3,600 lm	106 lm/W	80	No	No	No	DLC	ST	ETI	**335C32**
38 W	4000K	4,900 lm	131.5 lm/W	80	No	Yes	Yes	DLC 5.0	ALC6	Albeo	**48TL79**
	5000K	4,900 lm	131.5 lm/W	70	No	Yes	Yes	DLC 5.0	ALC6	Albeo	**48TL80**
41 W	3500K	5,456 lm	133.1 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D80**
	4000K	5,541 lm	135.1 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D81**
	5000K	5,745 lm	140.1 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D82**
59 W	3500K	7,480 lm	126.7 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D83**
	4000K	7,596 lm	128.7 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D84**
	5000K	7,876 lm	133.5 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D85**
111 W	5000K	7,800 lm	72 lm/W	70	No	Yes	Yes	DLC 5.0	ALC6	Albeo	**48TL82**
8 ft. LED Strip Lights											
Curved Lens											
38 W	4000K	9,800 lm	263.1 lm/W	80	No	Yes	No	DLC 5.0	ALV2	Albeo	**49EN90**
	5000K	9,800 lm	263.1 lm/W	80	No	Yes	No	DLC 5.0	ALV2	Albeo	**49EN91**
40 W	5000K	5,400 lm	142 lm/W	80	No	Yes	Yes	DLC 5.0 Premium	MPS	Columbia Lighting	**53VU09**
54 W	3500K	7,100 lm	131.5 lm/W	82	Yes	Yes	No	DLC Listed	Micro Strip	Keystone Technologies	**61HR06**
76 W	5000K	9,500 lm	124 lm/W	80	No	Yes	No	DLC 5.0	MPS	Columbia Lighting	**53VU10**
80 W	4000K	9,231 lm	115 lm/W	80	No	Yes	Yes	DLC 5.0	MPS	Columbia Lighting	**656N93**
99 W	4000K	11,667 lm	118 lm/W	80	No	Yes	No	DLC 5.0	MPS	Columbia Lighting	**53VU08**
	5000K	12,000 lm	128 lm/W	80	No	Yes	No	DLC 5.0	MPS	Columbia Lighting	**53VU12**
111 W	4000K	15,600 lm	144.1 lm/W	80	No	Yes	No	DLC 5.0	ALV2	Albeo	**49EN92**
	5000K	15,600 lm	144.1 lm/W	80	No	Yes	No	DLC 5.0	ALV2	Albeo	**49EN93**
Flat Lens											
38.2 W	4000K	5,535 lm	145.8 lm/W	80	No	Yes	No	DLC 5.0	CLX	Lithonia Lighting	**454X24**
	5000K	5,667 lm	148 lm/W	80	No	Yes	No	DLC 5.0	CLX	Lithonia Lighting	**454X25**
40 W	4000K	5,213 lm	130 lm/W	80	No	Yes	No	DLC 5.0 Premium	MPS	Columbia Lighting	**53VU05**
66.5 W	4000K	9,137 lm	137 lm/W	80	No	Yes	No	DLC 5.0	CLX	Lithonia Lighting	**454X26**
	5000K	9,354 lm	140.1 lm/W	80	No	Yes	No	DLC 5.0	CLX	Lithonia Lighting	**454X27**
72 W	3500K	8,000 lm	119.3 lm/W	80	No	Yes	No	DLC Qualified	CSS	Lithonia Lighting	**793JZ1**
	4000K	8,000 lm	119.3 lm/W	80	No	Yes	No	DLC Qualified	CSS	Lithonia Lighting	**793JZ2**
	5000K	8,000 lm	119.3 lm/W	80	No	Yes	No	DLC Qualified	CSS	Lithonia Lighting	**793JZ3**
80.2 W	3500K	9,111 lm	114 lm/W	80	No	Yes	No	DLC 5.0 Premium	MPS	Columbia Lighting	**53VU03**
Lensless											
80.2 W	4000K	9,587 lm	136 lm/W	80	No	Yes	No	DLC 5.0 Premium	MPS	Columbia Lighting	**53VU19**
104 W	4000K	14,001 lm	134 lm/W	80	No	Yes	No	DLC 5.0	ZL1N	Lithonia Lighting	**38GT87**
Round Lens											
38.2 W	4000K	5,697 lm	149.2 lm/W	80	No	Yes	No	DLC 5.0	CLX	Lithonia Lighting	**454X32**
	5000K	5,832 lm	150.3 lm/W	80	No	Yes	No	DLC 5.0	CLX	Lithonia Lighting	**454X33**
66.5 W	4000K	9,404 lm	141.2 lm/W	80	No	Yes	No	DLC 5.0	CLX	Lithonia Lighting	**454X34**
	5000K	9,627 lm	143.1 lm/W	80	No	Yes	No	DLC 5.0	CLX	Lithonia Lighting	**454X35**
Tube-Style Lens											
60 W	4000K	8,386 lm	139.7 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D92**
81 W	4000K	11,442 lm	141.2 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D94**
111 W	4000K	15,600 lm	144.1 lm/W	70	No	Yes	Yes	DLC 5.0	ALC6	Albeo	**48TL87**
	5000K	15,600 lm	144.1 lm/W	70	No	Yes	Yes	DLC 5.0	ALC6	Albeo	**48TL88**
121 W	4000K	15,986 lm	132.1 lm/W	80	No	Yes	No	DLC 5.0	ZL1D	Lithonia Lighting	**405D93**

Linear LED Task Lighting

RemPhos

- 120/277V AC
- Dimmable

Light bars are easily installed with included magnetic clips for under cabinet, work area, display, or task lighting. Offer 3 wattages and 3 color temperatures in a single unit, except base model 61HP81. Suitable for dry or damp locations.

ACCESSORIES

Connectors and cables make it easy to connect power and control wires from one light bar to another. Multiple bars can be connected on one incoming power cable. DIM units link all connections. NODIM units link only AC power. **Emergency battery backup** allows for continuous lighting for a minimum of 90 min. during power outage or emergency situation. **Occupancy sensor** is a high frequency motion/daylight sensor that plugs directly into light bar. **Space connector** can be used when retrofitting fixtures, to bring the length of the LED bar to a standard dimension. **End caps** prevent tampering and create a finished look.

Max. Fixture Wattage	Color Index	Dimmable	Emergency Battery Backup	Lighting Certification	Nom. Size	Overall Width	Overall Height	2700K, 3000K, 3500K Lumens	2700K, 3000K, 3500K Item No.	3500K, 4000K, 5000K Lumens	3500K, 4000K, 5000K Item No.	4000K Lumens	4000K Item No.
LED Light Bar Kit													
6 W, 9 W, 12 W	80	Yes	No	DLC Premium	2 ft	1 ¼ in	1 ¼ in	700 lm	**61HP78**	770 lm	**61HP75**	—	—
10 W, 12 W, 15 W	80	Yes	No	DLC Premium	3 ft	1 ¼ in	1 ¼ in	1,268 lm	**61HP79**	1,434 lm	**61HP76**	—	—
10 W, 15 W, 25 W	80	Yes	No	DLC Premium	4 ft	1 ¼ in	1 ¼ in	1,265 lm	**61HP80**	2,130 lm	**61HP77**	—	—
15 W	80	Yes	No	DLC Premium	4 ft	1 ¼ in	1 ¼ in	—	—	—	—	1,996 lm	**61HP81**

Item	Kit Contents	Mfr. Model	Item No.
Cords & Wiring			
LED Light Bar Dimming Connector	(10) Seamless Connectors-DIM	RP-LBI-SSC-DIM-10P	**61HP83**
LED Light Bar Emergency Battery Backup	—	RP-LBI-EMG1-25W	**61HP92**
LED Light Bar No-Dimming Connector	(10) Seamless Connectors-NODIM	RP-LBI-SSC-NODIM-10P	**61HP84**
LED Light Bar Occupancy Sensor	(1) 12 in Linking Cable-DIM, (1) OC2 Sensor, (1) Surface Mount Magnetic Clip, (2) Seamless Connectors-DIM	RP-LBI-OC2-A	**61HP91**
LED Light Bar Power Cable	(10) 3 ft Incoming Power Cables (bar input side), (10) Abrasion protection grommets, (10) Service Disconnects	RP-LBI-G1-IP-3F-DIM-10P	**61HP82**
LED Light Bar Space Connector	(2) Seamless Connectors-DIM	RP-LBI-SRC-4.7IN	**61HP85**
Clips, Chains & Hangers			
LED Light Bar T-Bar Bracket	(10) T-Bar Clips	RP-LBI-T1516-10P	**61HP86**
Cords & Wiring			
LED Light Bar Troffer Linking Cable	(10) 6 in Linking Cables-DIM	RP-LBI-LC-6IN-DIM-10P	**61HP87**
	(10) 12 in Linking Cables-DIM	RP-LBI-LC-12IN-DIM-10P	**61HP88**
	(10) 18 in Linking Cables-DIM	RP-LBI-LC-18IN-DIM-10P	**61HP89**
	(10) 24 in Linking Cables-DIM	RP-LBI-LC-24IN-DIM-10P	**61HP90**
Clips, Chains & Hangers			
Surface Mount Fixture End Cap	—	RPT-P-LIVC-G2-ENDCAP-SECURITY1	**61HP93**
	—	RPT-P-LIVC-G2-ENDCAP-MODERN1	**61HP94**
	—	RPT-P-LIVC-G2-ENDCAP-MODERN2	**61HP95**