



Clamp Meters

CAT III 600V safety rating unless otherwise noted. Select models are VAR clamps, which measure volts, amps, and resistance (continuity). Each includes carrying case. All except 38RX02 and 2ATU8 include test leads, and all include batteries.

ANALOG

Instrument works in cold temperatures where digital clamp LCD screens tend to freeze, and measures amps and volts without needing batteries. Cat IV 600V safety rating.

AC Amps	DC Amps	Max. AC Volts	Resist. (Ohms)	Jaw Cap.	Temp. Range	Temperature IR	Frequency Counter	Peak Hold	Mfr. Model	Item No.	
1,000	—	600 V	1,000	1.9 in (48 mm)	•	—	—	—	RS-1007 PRO	4FFJ8	
300 Amps Electrical											
300	300	—	—	1.0 in (25 mm)	—	—	—	—	AMP-25	38RX02	
400 Amps Electrical											
400	—	600 V	40 megohm	1.2 in (30 mm)	•	•	—	—	ACD-23SW	6NZF3	
600 Amps Electrical											
600	—	600 V	40 megohm	1.0 in (25 mm)	•	•	•	—	ACD-10 PLUS	2ATU9	
600	—	600 V	40 megohm	1.0 in (25 mm)	•	•	•	—	ACD-14 PLUS	3DNV9	
600	—	600 V	40 megohm	1.3 in (33 mm)	•	•	•	—	ACD-14 TRMS-PLUS	3DNZ1	
600	2,000 uA	600 V	6,000	1.1 in (28 mm)	•	•	•	•	ACD-14-PRO	52JJ18	
800 Amps Electrical											
800	1,000	600 V	40 megohm	2.0 in (51 mm)	•	—	—	—	ACDC-100	2AUZ8	
800	1,000	600 V	40 megohm	2.0 in (51 mm)	•	—	—	—	ACDC-100 TRMS	2AUZ9	
1000 Amps Industrial											
1,000	—	600 V	40 megohm	1.8 in (46 mm)	•	—	—	—	ACD-6 PRO	2ATU8	
1,000	1,000	750 V	66 megohm	2.0 in (51 mm)	•	—	•	•	ACDC-3400 IND	4FFK1	
1,000	1,000	1,000 V	60,000	2.0 in (51 mm)	—	—	—	—	AMP-330	34NK45	
Max. AC Voltage	Max. Input Current	Max. Output Current	Features							Mfr. Model	Item No.
3-Wire AC Line Separator											
120	15 A	15.0 A	10X for Increased Sensitivity of Low Current Measurements, 1X for Direct Readings to 15 Amperes, Voltage Measurement Ports							ELS2A	2ATB3

AMPROBE

400 AMPS ELECTRICAL

A 180° rotating head measures AC current and helps take other readings in tight places.

600 AMPS ELECTRICAL

2ATU9 has extra-thin jaws for frequency measurement and is overload protected.

3DNV9 and 3DNZ1 show voltage and current on dual displays for voltage drop tests.

800 AMPS ELECTRICAL

VAR clamps for electrical and HVAC applications include relative readings; 2AUZ9 features true RMS.

1000 AMPS INDUSTRIAL AND HIGH CURRENT

2ATU8 provides a wide range of measurements. 4FFK1 is designed for high-current industrial applications, supporting a broad range of measuring functions with true RMS sensing. Large backlit display. 4FFK1 has CAT IV 600V safety rating.



Clamp Meters

WESTWARD

Autoranging instruments feature audible continuity, diode test, data hold, and auto-off. LCD shows test results. 22XX24 provides true RMS AC response. ETL Listed for U.S. and Canada. IEC 61010 Compliant.

UEI TEST INSTRUMENTS

Meters have true RMS accuracy, backlit dual display, and noncontact voltage tester. Measure temperature, capacitance, and frequency/duty cycle. Noncontact voltage in tip.



Includes	Volts	Max. AC Amps	Volts	Max. DC Amps	Max. Ohms	AC Current Accuracy	Counts	Jaw Cap.	Safety Rating	Item No.
Clamp Meter Westward										
Batteries, Soft Carrying Case and Instructions, Temperature Probe, Test Leads	600 V	400	600 V	—	20 megaohm	±1.5% + 5 Digits	2,000	1.1 in (28 mm)	CAT II 600V, CAT III 300V	22XX22
Batteries, Soft Carrying Case and Instructions, Test Leads	600 V	400	600 V	400	40 megaohm	±2.5% + 5 Digits	4,000	1.1 in (28 mm)	CAT II 600V, CAT III 300V	22XX23
Batteries, Hard Case and Instructions, Test Leads	600 V	600	600 V	—	20 megaohm	±1.5% + 5 Digits	2,000	1.1 in (28 mm)	CAT II 600V, CAT III 300V	22XX26
Batteries, Hard Case and Instructions, Test Leads	—	1,000	—	1,000	40 megaohm	±2.0% + 2 Digits	4,000	2.1 in (53 mm)	CAT II 600V, CAT III 300V	22XX24
Batteries, Hard Case and Instructions, Test Leads	600 V	1,000	600 V	1,000	40 megaohm	±2.0% + 2 Digits	4,000	2.1 in (53 mm)	CAT II 600V, CAT III 300V	22XX25
UEI Test Instruments										
(2) Batteries, K-Type Temperature Probe, Pouch, Test Leads	750 V	400	400 V	400	40 megaohm	+/-1.2% + 3 Digits	4,000	1.2 in (30 mm)	CAT II 1000V, CAT III 600V	55CH55
Alligator Clips, Batteries, K-Type Thermocouple ATT29A, Pouch, Test Leads	750 V	600	600 V	2,000 uA	60 megaohm	±2.0% + 8 Digits	6,000	1.3 in (33 mm)	CAT IV 600V	52KA90
Digital Multimeter, Clamp On Kit Westward										
Battery, Digital Electrical Multimeter, Clamp On Ammeter, Test Leads, Magnetic Strap, Deluxe Carrying Case										22XX28
Battery, Temperature Probe, Magnetic Strap, Deluxe Carrying Case, Clamp On Ammeter, Test Leads, Digital Electrical Multimeter										22XX29



Clamp/Fork Meters

Rugged, heavy-duty instruments feature true RMS measurement for greater accuracy. High-contrast, white-on-black, backlit display is easy to read. LED task light. Each includes test leads and AA batteries. 4NYX6 and 4NYX7 are CAT IV 600V. 4NYX6 features Lo-Z measurement to eliminate ghost voltage. 4NYX7 provides 600uA DC readings for flame rectification and has a dual banana thermocouple input for contact temperature measurement. 5MLK3 is CAT III 600V.

Amps (AC)	Voltage (AC/DC)	Jaw Cap.	Capacitance	Temp. Range	Non-Contact Voltage Detector	Data Hold	Calibration Certificate	Mfr. Model	Item No.
200	1,000 V	0.6 in (15 mm)	40 nF	—	Yes	Yes	No	2205-20	4NYX6
1	1,000 V	0.6 in (15 mm)	1,000 uF	-40° to 752°F	Yes	Yes	No	2206-20	4NYX7
600	600 V	1.4 in (36 mm)	40 nF	—	Yes	Yes	NIST	2237-20NIST	5MLK3

