

AMPROBE



Observation Depth	Shaft Length	Shaft Dia.	Monitor Size	Camera Size	Power Source	Brand	Item No.
Inspection Cameras							
1.2 in to 2.4 in	30 in	0.32 in	4.3 in	8 mm	(4) AA Batteries	Extech	55RV89
5.9 to 9.8 in	36 in	0.35 in	3.5 in	9 mm	(4) AA Batteries	Extech	5CVT1
3 ft	36 in	0.49 in	3.5 in	12 mm	Rechargeable Li-Ion Battery	Milwaukee	40KJ35
3 ft	36 in	0.49 in	3.5 in	12 mm	Rechargeable Li-Ion Battery	Milwaukee	40KJ38
Accessories							
9mm Waterproof Camera H	lead					Extech	5WYV1
Replacement Camera Cable	, 3 ft., For Use With	40KJ35 and	I 40KJ38			Milwaukee	40KJ36
Replacement Camera Cable						Milwaukee	40KJ39

EXTECH Milwaukee

Inspection Cameras

Extech 55RV89-Lightweight video borescope features detachable color TFT LCD for clear imaging. IP67 waterproof. Includes LED lamps. Complete with 21/2-ft. flexible gooseneck cable, extension tools, batteries, and a soft carrying case.

Extech 5CVT1—Detachable, wireless color 3.5" LCD monitor. Borescope can also transmit date-stamped video and still images up to 32 ft. to any monitor with a video jack. 2 LED lamps. IP67 waterproof. Includes flexible cable, extension tools, micro SD card with adapter. USB and video interconnect cables, AC adapter, and case

Milwaukee 40KJ35 and 40KJ38—

Recordable inspection cameras can send high-quality 640 x 480 images and video to the 3.5" wireless LCD monitor from up to 30 ft. away, and save them on included 8GB SD card for later review. Use the 3-ft. cable option for complete control of the camera head and faster positioning. 40KJ38 has a 270° pivoting camera head for better visiblity.





Carbon Monoxide Meters

AMPROBE

4FKR1—Displays CO level; adjustable alarm for alerts at 25 to 200 ppm.

EXTECH INSTRUMENTS

Carhon

4FB71—Has stabilized electromechanical gas-specific sensor.

404K03—Displays CO level; adjustable alarm for alerts at 25 to 200 ppm.

Item	Monoxide Measurement Range (ppm)				Low Battery Indicator	Display	Includes	Power Source	Mfr. Model	Item No.
Amprobe										
Carbon Monoxide Meter	0 to 999	_	_	Yes	Yes	Backlit LCD	Batteries, Carrying Case and Instructions	(3) AAA Batteries	CM100	4FKR1
Extech										
Carbon Monoxide Detector	0 to 1000	_	Yes	Yes	Yes	Back Lighted LCD	Battery, Carbon Monoxide Sensor, Carrying Case and Instructions, Holster	9V Battery	CO10	4FB71
Portable Carbon Monoxide Meter	0 to 999	_	No	Yes	Yes	Dual LCD	(3) AAA Batteries, Carrying Pouch, Wrist Strap	(3) AAA Batteries	CO15	404K03
UEI Test Inst	truments									
Carbon Monoxide Detector	0 to 999	_	No	No	No	Backlit LCD	(3) AAA Battery	(3) AAA Batteries	COA2-N	55UX46



ALNOR

Air Volume Balancing Meters and Accessories

Capture hoods channel air flow volume from supply or exhaust diffusers and grilles for fast, repeatable measurements.

CFM Range		Includes	Н	Base Dia.	Battery Life	Mfr. Model	Item No.				
Air Flow Capture Hood											
10 to 500	Digital	2 x 2 Hood, and Case, Base, Handles	34 ½ in	13.3 in	10 Hours	6200D	4KF78				
25 to 2500	Digital Multi Line LCD	Certification, Pitot Probe, Tubing		18 in	10 Hours	EBT731	3ATR7				
25 to 2500	Backlit	(2) Static Pressure Probes, (4) AA Rechargeable NiMH Batteries, 16 ft. Tubing, 18* Pilot Probe, Detachable Micromanometer, Multi Country AC Adaptor, Stand, Tablet, USB Cable, Wheeled Luggage Style Carrying Case		18 in	10 Hours	EBT731- STA	53XX16				
30 to 1000	Analog Meter	2 x 2 Hood, and Batteries, Base, Case, Meter	42 in	18 in	12 Hours	ABT701	3ATR8				