



Inspection Cameras

Extech 55RV89—Lightweight video bore-scope features detachable color TFT LCD for clear imaging. IP67 waterproof. Includes LED lamps. Complete with 2½-ft. flexible gooseneck cable, extension tools, batteries, and a soft carrying case.

Extech 5CVT1—Detachable, wireless color 3.5" LCD monitor. Bore-scope can also transmit date-stamped video and still images up to 32 ft. to any monitor with a video jack. 2 LED lamps. IP67 waterproof. Includes flexible cable, extension tools, micro SD card with adapter, USB and video interconnect cables, AC adapter, and case.

Milwaukee 40KJ35 and 40KJ38—Recordable inspection cameras can send high-quality 640 x 480 images and video to the 3.5" wireless LCD monitor from up to 30 ft. away, and save them on included 8GB SD card for later review. Use the 3-ft. cable option for complete control of the camera head and faster positioning. 40KJ38 has a 270° pivoting camera head for better visibility.



Observation Depth	Shaft Length	Shaft Dia.	Monitor Size	Camera Size	Power Source	Brand	Item No.
Inspection Cameras							
1.2 in to 2.4 in	30 in	0.32 in	4.3 in	8.0 mm	(4) AA Batteries	Extech	55RV89
5.9 to 9.8 in	36 in	0.35 in	3.5 in	9.0 mm	(4) AA Batteries	Extech	5CVT1
3 ft	36 in	0.49 in	3.5 in	12.0 mm	Rechargeable Li-Ion Battery	Milwaukee	40KJ35
3 ft	36 in	0.49 in	3.5 in	12.0 mm	Rechargeable Li-Ion Battery	Milwaukee	40KJ38
Accessories							
Stream Live Video to PC or Over VOIP (Voice Over Internet Protocol) Connection						Extech	6DWX1
9mm Waterproof Camera Head						Extech	5WVY1
Replacement Camera Cable, 3 ft., For Use With 40KJ35 and 40KJ38						Milwaukee	40KJ36
Replacement Camera Cable, For Use With 40KJ35 and 40KJ38						Milwaukee	40KJ39



Carbon Monoxide Meters

AMPROBE

4FKR1—Displays CO level; adjustable alarm for alerts at 25 to 200 ppm.

BACHARACH

31LA88 and Kit 31LA89—Monoxor Plus continuous sampling monitor measures ambient or flue gas CO between 0 and 2000 ppm in 1 ppm increments. Trend graph shows real-time readings.

EXTECH INSTRUMENTS

4FB71—Has stabilized electromechanical gas-specific sensor.

404K03—Displays CO level; adjustable alarm for alerts at 25 to 200 ppm.

UEI TEST INSTRUMENTS

8EWU2—3-color warning light and audible alarm. Backlit LCD, Max. Hold, and low-battery indicator.



Item	Carbon Monoxide Measurement Range (ppm)	Temp. Range	Data Hold	Auto Power Off	Low Battery Indicator	Display	Includes	Power Source	Mfr. Model	Item No.
Amprobe										
Carbon Monoxide Meter	0 to 999	—	—	Yes	Yes	Backlit LCD	Batteries, Carrying Case and Instructions	(3) AAA Batteries	CM100	4FKR1
Bacharach										
Carbon Monoxide Analyzer	0 to 2000	-4° to 1202°F	Yes	Yes	Yes	Monochrome Backlit LCD	(4) AA Batteries and Hard-Carry Case, 6 ft. Probe/Hose, Water Trap	(4) AA Batteries	0019-8117	31LA88
	0 to 2000	-4° to 1202°F	Yes	Yes	Yes	Monochrome Backlit LCD	(8) AA Batteries and Hard-Carry Case, 6 ft. Probe/Hose, PC Software, USB Cable, Water Trap, Wireless IrDA Magnetic Printer	(4) AA Batteries	0019-8118	31LA89
Extech										
Carbon Monoxide Detector	0 to 1000	—	Yes	Yes	Yes	Back Lighted LCD	Battery, Carbon Monoxide Sensor, Carrying Case and Instructions, Holster	9V Battery	C010	4FB71
Portable Carbon Monoxide Meter	0 to 999	—	No	Yes	Yes	Dual LCD	(3) AAA Batteries, Carrying Pouch, Wrist Strap	(3) AAA Batteries	C015	404K03
UEI Test Instruments										
Carbon Monoxide Detector	0 to 999	—	No	No	No	Backlit LCD	Holster with Belt Clip, Battery	—	C071A	8EWU2
	0 to 999	—	No	No	No	Backlit LCD	(3) AAA Battery	(3) AAA Batteries	COA2-N	55UX46
	0 to 999	32° to 104°F	No	No	Yes	Backlit LCD	9V Battery, Holster	9V Battery	CO71A-N	49CK94