



**DeWalt**  
**24WY33**



**Dremel**  
**780U17**



**Fein**  
**346EX0**



**Panasonic**  
**22EC14**

## Cordless Screwdrivers



Tools accept interchangeable screwdriver bits, and they can rotate screws without overdriving them, snapping them, or stripping the screwhead. Models run on brand-specific batteries and don't require a corded power source.

Drive Size	Max. Torque	Free Speed	Cordless Tool Kit Contents	Includes	Battery Capacity	Clutch Type	Built-In Light	Series	Item No.
<b>DeWalt</b>									
<b>8V DC, Pivot, General Purpose Screwdriver</b>									
¼ in Hex	23 in-lb	430 RPM	(1) Bare Tool, (1) Battery, (1) Charger	Kit Bag	(1) 1.0 Ah	Adjustable Clutch Collar	Yes	8V MAX	<b>24WY32</b>
¼ in Hex	23 in-lb	430 RPM	(1) Bare Tool, (2) Batteries, (1) Charger	(2) 8V MAX Compact Batteries, Hour Charger, Kit Bag, Screwdriver	(2) 1 Ah	Adjustable Clutch Collar	Yes	8V MAX	<b>24WY33</b>
¼ in Hex	23 in-lb	430 RPM	(1) Bare Tool, (2) Batteries, (1) Charger	Kit Bag	(2) 1 Ah	Direct Drive	Yes	8V MAX	<b>30RV67</b>
<b>Dremel</b>									
<b>3.6V DC, Straight, USB Rechargeable Electric Screwdriver</b>									
¼ in Hex	5 in-lb	360 RPM	(1) Battery; (1) Charger	—	3.6Ah	—	—	HSES	<b>780U17</b>
<b>Fein</b>									
<b>18V DC, Pistol Grip, General Purpose Screwdriver</b>									
¼ in Hex	266 in-lb	1,700 RPM	(1) Bare Tool	(1) Depth Stop, (1) Insert for Hexagon Bolts SW 8, (1) Plastic Carrying Case, (1) Rapid Charger ALG 50, (1) Scaffold Hook, (2) Rechargeable Batteries	—	Shut-off	—	—	<b>346EX0</b>
<b>Panasonic</b>									
<b>2.4V DC, Pivot, General Purpose Screwdriver</b>									
—	35 in-lb	400 RPM	(1) Bare Tool, (1) Battery	Battery Pack	(1) 2.8 Ah	Adjustable	Yes	Standard	<b>22EC17</b>
<b>3.6V DC, Pivot, General Purpose Screwdriver</b>									
—	39 in-lb	600 RPM	(1) Bare Tool, (2) Batteries, (1) Charger	(2) Battery Packs, Carrying Case, Charger	(2) 1.5 Ah	Adjustable	Yes	Standard	<b>22EC14</b>
<b>Proto</b>									
<b>4V, Straight, General Purpose Screwdriver</b>									
¼ in	8 in-lb	300 RPM	(1) Bare Tool; (1) Charger	Storage Box, USB-C Charging Cable, (3) Bit Extenders, (48) 1 in Premium S2 Bits	2.0 Ah	—	Yes	N	<b>787D09</b>



**Inline**  
**40TP95**



**Inline**  
**3Y475**



**Inline**  
**3Y472**



**Pistol Grip**  
**3Y477**

## Corded Production Screwdrivers



- ¼" drive size
- Reversible
- Variable speed

Tools accept interchangeable screwdriver bits to install/remove screws more quickly than manual screwdrivers. **Inline** models align the bit-holding chuck with the tool body for use in tight spaces. **Pistol-grip** models keep the tool steady and control the pressure applied to the bit during driving.

Torque Range	Free Speed	Throttle Type	Clutch Type	Includes	Brand	Item No.
<b>Inline</b>						
<b>20/30V DC</b>						
0.9 in-lb to 4.9 in-lb	1,000 RPM	Lever	Adjustable Torque	4 mm Round Bits	Asg	<b>40TP87</b>
1.8 in-lb to 10.6 in-lb	900 RPM	Lever	Shut-Off	(3) Bits, Hex Wrench, Power Cable	Asg	<b>40TP94</b>
1.8 in-lb to 15 in-lb	700 RPM	Lever	Shut-Off	(2) Bits, (2) Torque Springs, Power Cable, Replacement Brushes	Asg	<b>40TP88</b>
2.2 in-lb to 11.5 in-lb	900 RPM	Lever	Shut-Off	(3) Bits, Power Cable, Replacement Brushes	Asg	<b>40TP91</b>
2.7 in-lb to 14.2 in-lb	900 RPM	Lever	Adjustable Torque	(2) Torque Springs, (3) Bits, Power Cable, Replacement Brushes	Asg	<b>40TP89</b>
2.7 in-lb to 14.2 in-lb	900 RPM	Push to Start	Adjustable Torque	(2) Torque Springs, (3) Bits, Power Cable, Replacement Brushes	Asg	<b>40TP93</b>
2.7 in-lb to 22.1 in-lb	90 RPM	Lever	Adjustable Torque	(2) Torque Springs, (3) Bits, Power Cable, Replacement Brushes	Asg	<b>40TP92</b>
6.2 in-lb to 31 in-lb	700 RPM	Lever	Shut-Off	(3) Bits, Hex Wrench, Power Cable	Asg	<b>40TP95</b>
<b>24V DC</b>						
0.4 in-lb to 9.0 in-lb	650 RPM	Lever	Shut-Off	1.5 m Cable, Hanger Bail, Two Bits	Ingersoll Rand	<b>3Y475</b>
<b>115V AC</b>						
4.4 in-lb to 16 in-lb	2,000 RPM	Inline-Push	Shut-Off	(2) Bits, (2) Brushes, Hanger Bail	Ingersoll Rand	<b>3Y472</b>
4.4 in-lb to 17 in-lb	1,000 RPM	Inline-Push	Shut-Off	(2) Bits, (2) Brushes, Hanger Bail	Ingersoll Rand	<b>3Y474</b>
10 in-lb to 26 in-lb	700 RPM	Inline-Push	Shut-Off	(2) Bits, (2) Brushes, Hanger Bail	Ingersoll Rand	<b>3Y473</b>
<b>Pistol Grip</b>						
<b>115V AC</b>						
15 in-lb to 40 in-lb	400 RPM	Inline-Push	Shut-Off	(2) Bits, (2) Brushes, Hanger Bail	Ingersoll Rand	<b>3Y477</b>



**Drywall**  
**4LF91**



**Drywall**  
**6KX33**



**Metal Fastening**  
**4LF87**

## Corded Screw Guns



- ¼" drive size
- Variable speed
- Reversible
- 120V AC

An adjustable nose sets the drive to fasten screws to a consistent depth. Their clutch automatically disengages the drive at the set depth to prevent overdriving. **Drywall screw guns** set screw heads flush with the drywall paper surface. **Metal-fastening screw guns** drive sheet metal screws and other metal-to-metal or metal-to-wood fasteners. They provide more torque than drywall screw guns.

Free Speed	Torque Range	Current	Clutch Type	Includes	Brand	Item No.
<b>Drywall Screw Gun</b>						
2,500 RPM	132 in-lb	6.2 A	Auto Adjustable	#2 Bit Tip And Holder, Set and Forget Nose Piece, Soft Grip	DeWalt	<b>4LF80</b>
2,500 RPM	132 in-lb	6.5 A	Positive	2-Finger Trigger Switch, Helical Cut Steel, Heat-Treated Gears	DeWalt	<b>4LF91</b>
2,500 RPM	132 in-lb	6.5 A	Standard	#2 Bit Tip And Holder, Metal Gear Housing Set, Set and Forget Nosepiece, Soft Grip	DeWalt	<b>4LF90</b>
4,000 RPM	60 in-lb	6 A	Standard	#2 Bit Tip And Holder, Set and Forget Nose Piece, Soft Grip	DeWalt	<b>4JB76</b>
4,000 RPM	81 in-lb	6.3 A	Standard	Metal Gear Housing Set, Set-and-Forget Nosepiece, Soft Grip Handle	DeWalt	<b>4NZ46</b>
4,000 RPM	Not Specified	6.5 A	Adjustable Positive	(1) Belt Clip	Milwaukee	<b>6KX33</b>
5,300 RPM	60 in-lb	6 A	Positive	#2 Bit Tip And Holder, Set and Forget Nose Piece, Soft Grip	DeWalt	<b>6GD99</b>
<b>Metal Fastening Screw Gun</b>						
1,000 RPM	344 in-lb	6.5 A	Auto Adjustable	¼ in Depth Adj., Clutch Override, Mag Bit Holder, Soft Grip Handle	DeWalt	<b>4LF87</b>
2,000 RPM	132 in-lb	6.5 A	Auto Adjustable	¼ in Depth Adj., Clutch Override, Mag Bit Holder, Soft Grip Handle	DeWalt	<b>4LF84</b>
2,500 RPM	132 in-lb	6.5 A	Auto Adjustable	Clutch Override, Mag Bit Holder, Soft Grip Handle	DeWalt	<b>4LF85</b>