	JED	GERENLEE PROTOC MEGAPRO DEWALT WELL LEAT	HERMAN"	RWIN
Scre	wdriv	rer Bit Sets Wing Wing Manager 11 Manager 12	KLEIN	₩ Wer
No. of Pcs. Si	Hex hank Size	Includes	Brand	Item No.
land Scre 35	wdriver Bit S 1/4 in	1 in PH1. (4) 1 in PH2. 1 in SL8. 1 in O1. (2) 1 in O2. (2) 2 in PH1. (4) 2 in PH2. 2 in PH3. 2 in SL8. 2 in SL10. (2) 2 in O2. 2 in T20. 2 in T25. 3.5	DeWalt	55KH39
42	1/4 in	in PH2, ½ in Spade, ¾ in Spade, ¼ in Nutsetter, ¾ in Nutsetter, (2) ¼ in, ½ in, ½ in, ½ in, ½ in, ½ in, ocompact Magnetic Drive, 3 in Holder Square Drive #1 x #2, Torx 115 x Hex ½ in, Torx #6 x #6, Torx #10 x #15, Torx #10 x #25, Torx #20 x #30, Eyeglasses Screwdriver, Pozi #2 x #1 Hex 1 5 mm x 2 0 mm Hex 2 5 mm x 3 0 mm Hex 4 0 mm x 5 0 mm Hex 6 mm and 14 in Hex ½ in x ¾ in x ¾ in x ½ in x 2 in x	Leatherman	19LY98
		x #1, Hex 1.5mm x 2.0mm, Hex 2.5mm x 3.0mm, Hex 4.0mm x 5.0mm, Hex 6mm and 1/2 in, Hex ½e in x ¾e in, Hex ½e in x ¼e in Xe in		
65	1/4 in	1/4 Socket, 1/4 in Netter, 7 in in Hall, 7 in	DeWalt	55KH40
00	1/. in	(6) 1 in PH2, (5) 1 in Q2, (5) 1 in T20, (5) 1 in T25, (2) 2 in Q2, 2' SL8, (2) 2 in PH2, 2 in T20, 2 in T25, 3.5 in SL8, 3.5 in SQ2, 3.5 in PH2, 3.5 in PH1, Magentic Compact Drive, ¼ Nutsetter, ¾ Nutsetter, ¾ Nutsetter, ¼ Adapter Socket, ¾ Adapter Socket, (2) ¼6	DoWolt	EEVIIA4
80	1⁄4 in	in PH2, 3.5 in PH1, Magentic Compact Drive, ¼ Nutsetter, ¾ Nutsetter, ¾ Adapter Socket, ¾ Adapter Socket, (2) ¼ in, (3) in SL10, (2) 1 in PH1, (3) 1 in PH3, (3) 1 in SL10, (2) 1 in SL10, (2) 1 in O1, (2) 1 in O3, 1 in T10, 1 in T130, 1 in T30, 1 in T40, Bit Holder	DeWalt	55KH41
npact Sc isert Bit	rewdriver Bi Set			
6	1/4 in 1/4 in	Phillips, Slotted, Square, Torx	IRWIN IRWIN	55KG85 55KH92
19	1/4 in 1/4 in	1/6 in Bit, 1/6 in Bit, 1/2 in Bit, 1/2 in Bit, 1/2 in Bit, 1/2 in Bit, 1/4 in Bit, 1/4 in Bit	IRWIN IRWIN	787P71 55KJ13
32 crewdriv	½ in er Bit Set	Tool Case	IRWIN	55KJ08
19	1⁄4 in	Phillips #2 x 1 in (8), Square #1 x 1 in, Square #2 x 1 in (2), Square #3 x 1 in, Phillips #2 x 2 in (2), Phillips #3 x 2 in, Square #2 x 2 in, Mag Bit Holder, ¼ in Mag Nutsetter, 5/6 in Mag Nutsetter	Vega Ind., Inc.	45AW5
orx Bit Se	1/4 in	T15, T20, T25	DeWalt	787P70
ower Scr all End H	rewdriver Bit Iex Bit Set	Sets		
9 10	½ in ¼ in	362, 764, 1⁄6, %4, 1⁄62, 3⁄16, 1⁄62, 1⁄4 in Bits, Storage Rail Holder 3⁄2, 1⁄44, 1⁄4, 9⁄44, 9⁄42, 3⁄46, 1⁄42, 1⁄4 in, 1⁄4 in Bits, Magnetic Bit Holder, Molded Storage Box	Wiha Wiha	5HYL2 5HYL3
it Set 4		Socket Adaptor, Bit Holder, Bit Ratchet, Rapid Adaptor Bit Holder, Phillips (2) #1, (3) #2, #3, Square #1, (3) #2, #3, Torx T10, T15, T20, T25,	Milwaukee	13G26
	Oriver Bit Set		Willwaukee	13020
12	1⁄4 in	Drill Drive Holder: Drill Drive Connector; #6, #8, and #10 Drill Bits with Countersinks; (2) #6, #8, and #10 Replacement Bits; (3) Screwdriver Bit Tips, Heavy-Duty Container (1) ¾ in Black Oxide Drill Bit, (1) ¾ in Black Oxide Drill Bit, (1) ¼ in Black	DeWalt	6XG79
		(1) ¾ in Black Oxide Drill Bit, (1) ¾ in Black Oxide Drill Bit, (1) ¼ in Black Oxide Drill Bit, (1) ¼ in Thunderbolt Black Oxide Drill Bit, (1) ¼ in Thund		
05	1/ :	Oxide Drill Bit, (2) Hex Bit 1 in 1/16 in, (2) Hex Bit 1 in 1/4 in, (2) Hex Bit 1 in 3/6 in, (1) Hex Bit 1 in 5/6 in, (1) Hex Bit 1 in 5/6 in, (1) Hex Bit 1 in 5/6 in, (2)	Milwaukee	OCEVC
95	1/4 in	in PR2 , (1) Phillips Bit 2 in P2, (1) Pozidrive Bit 1 in PZ2, (1) Pozidrive Bit 1 in PZ3, (2) Slotted Bit #4, (2) Slotted Bit #6, (2) Slotted Bit #8, (2) Slotted Bit #10, (1) Slotted Bit #6, (2) Slotted Bit 2 in SO2.	wiiiwaukee	36FX6
		Thunderbolt Black Oxide Drill Bit, (1) \\(\frac{4}{2}\) in Black Oxide Drill Bit, (1) \\(\frac{4}{2}\) in Black Oxide Drill Bit, (1) \\(\frac{4}{2}\) in Thunderbolt Black Oxide Drill Bit, (1) \\(\frac{4}{2}\) in Thunderbolt Black Oxide Drill Bit, (1) \\(\frac{4}{2}\) in Thunderbolt Black Oxide Drill Bit, (1) \\(\frac{4}{2}\) in Thunderbolt Black Oxide Drill Bit, (2) Hex Bit 1 in \\(\frac{4}{2}\) in, (2) Hex Bit 1 in \\(\frac{4}{2}\) in \\(4		
ive Guid 14	le Set 1/4 in	(2) Magnetic Drive Guides, (6) #2 Phillips, (2) #8 and #10 Slotted, (3) #2 Square Recess Bits, Case	DeWalt	2KLK3
ex Bit So	crewdriver S	et 1/4 in Magnetic Quick Disconnect for Impact/Power Bits, Phillips #0, #1, #2, #4-5, Slotted #8-10, Star T15, Square		
26 ex Wren	1/4 in i ch Socket S e	Recess R1, R2 , Sockets ¾6, ¼, ½2, ¾6,11/32, ¾, ¼6, 1½ and ½ in, Flexible Extension 10½ in	Eazypower	5UXU7
19	3/8 in	11 in Length % in Hex Flex A Bit Plus Extension, Phillips #1, #2, Slotted #6-8, #8-10, Tee Star T15, T20, Square Recess R1, R2, Sockets %6, ¼, %6, %, %, ½, %6, % in, ¼ in Hex Female Socket Adapter, Socket Adapter	Eazypower	5UFZ4
ex/Torx B	To	mper Resistant Torx TR7, TR8, TR10, TR15, TR20, TR25, TR27, TR30, TR40, SAE Tamper Resistant Hex 1/32, 1/44, 1/4, 1/44, 1/4, 1/44, 1/4, 1/44, 1/4, 1/		
32 sert Bit	74 111	Hex 2, 2.5, 3, 4, 5, Spanner #4, #6, #8, #10, Tri-Wing(R) #1, #2, #3 #4, TORQ-SET(R) #6, #8, #10, ¼ in Square to ¼ in Hex Adaptor, ¼ in Drive Sockets	Klein Tools	3MJA9
30	1⁄4 in	Phillips #1, (3) #2, #3, Hex 2½, 3, 4, 5, 5½ in, Pozi Drive (2) PZ1, (3) PZ2, PZ3, Torx (2) T10, (2) T15, (3) T20, (3) T25, (2) T30, T40, ¼ in Hex Quick Release Rapidaptor Bit Holder	Wera	3EJY5
	Drive Guide	Set #1, (6) #2, and #3 Square Recess, #6, (2) #8, and #10 Slotted, Bit Tips: #1, (10) #2, and #3 Phillips, Compact Magnetic Drive Guide,	D-14/-14	4347844
7 apid Loa	¼ in d Holder and	Double-End Power Bits: P#1/S#6, (3) P#2/S#8, (3) P#2/P#2, and P#3/S#10, Magnetic Nut Setters: ¼ in and ¾6 in, Power Bits: Bit Set	DeWalt	4WM4
20	1/4 in	(2) 1 in Philips Bits: (2) PH2, 1 in Square Bits: SQ2, (3) 2 in Phillips Bits: PH1. (2) PH2, 1 in Torx Bits: T25, 2 in Torx Bit: T25, 2 in Torx Bit: T25, 2 in Square Bits: SQ1, SQ2, (3) Titanium Hex Shank Drill Bits: 1/2 in, 5/2 in, 1/4 in, 1/3	DeWalt	25CC5
crewdriv	er Bit Set		DeWalt	5TE33
15 20	1/4 in	7 Piece - 6-in-1 Flip and Switch Driver System 2 in PH#2, 2 in SQ#2, (2) 1 in SL#8, (3) 1 in PH#2, 1 in PH#3, SQ#1, SQ#2, T25, ¼, ¾6, % Nutsetter, 3 in Magnetic Holder Compact Screw Guide, (19) 1 in Insert Bits: P1, (7) P2, P3, S01, (3) SQ2, S03, T15, T20, T25, SL6-8, SL8-10 2 in Magnetic Bit Tip Holder; Bit Tips: #1, (6)#2, and #3 Phillips; #6, #8, and #10 Slotted; #1 and (3)#2 Square	DeWalt Milwaukee	5XFA5 45L15
21	1/4 in	2 in Magnetic Bit Tip Holder; Bit Tips: #1, (6)#2, and #3 Phillips; #6, #8, and #10 Slotted; #1 and (3)#2 Square Recess; Magnetic Nut Setters: ¼ in and 5½ in ; Power Bits: 2 in #2; 2 in #2 Square Recess	DeWalt	4WM4
29	1/4 in		DeWalt	4WM4
31	1/4 in	(4) Security Hex - Metric 2mm, 2.5mm, 3mm, 4mm, (4) Spanner Bits 4, 6, 8, 10, (4) Tri-W in g 1, 2, 3, 4, (6) Security Hex Rito 56c in 36c in 76c in 16 in 36c in 16 in 16 in 36c i	DeWalt	34D64
37	1/4 in	(20) 1 in Phillips Bits: PH1, (18) PH2, PH3, (8) 1 in Square Bits: PH1, (6) PH2, PH3, (4) 1 in Slotted Bits: SL6, (2) SL8,	DeWalt	25CC4
		(1) Hex Bit 1 in 1/4 in, (1) Hex Bit 1 in 1/4 in in, (1) Phillips Bit 1 in P1, (6) Phillips Bit 1 in in (1) P1, (2) Phillips Bit 1 in P3, (2) Phillips Bit 1 in P3, (2) Phillips Bit 1 in P3, (3) Phillips Bit 1 in P3, (4) Phillips Bit 2 in P3, (4) Phillips Bit 3 in P3, (4) Phillips Bit 4 in P3, (5) Phillips Bit 4 in P3, (6) Phillips Bit 4 in P3, (7) Philli		
42	1/4 in	(1) Slotted 2 in Bit #8, (1) Slotted 2 in Bit #10, (2) Square Bit 1 in SQ1, (6) Square Bit 1 in SQ2, (1) Square Bit 1 in SQ3, (1) Square Bit 1 in	Milwaukee	36FX65
		Bit 1 in T25, (1) Torx Bit 1 in T30, (1) Torx Bit 2 in T31, (1) Torx Bit 2 in T20, (1) Torx Bit 1 in T30, (1) Torx Bit 2 in T30, (1) Torx Bit 3 in T30, (1) Torx Bit 3 in T30, (1) Torx Bit 4 in T30, (1) Torx Bit 4 in T30, (1) Torx Bit 5 in T30, (1) Torx Bit 5 in T30, (1) Torx Bit 1 in T30, (1) Torx Bit 2 in T30, (1) Torx		
45	1/4 in	Magnetic Drive Guide; Bit Tips; #1, (10)#2, and #3 Phillips; #6, (2)#8, and #10 Slotted; #1, (6)#2, and #3 Square Recess; Magnetic Nut Setters: ¼ in and % in ; Power Bits: 2 in #2 Phillips; 2 in #2 Square Recess (4) Security Hex - Metric 2mm, 2.5mm, 3mm, 4mm, (4) Spanner Bits 4, 6, 8, 10, (4) Tri-W in g 1, 2, 3, 4, (6) Security Hex Bits %i in, ½2 in, ¼4 in, ¼6 in, ½6 in, 9) Security Star Bits T8, T10, T15, T20, T25, T27, T30, T35, T40 (20) 1 in Phillips Bits: PH1, (18) PH2, PH3, (8) 1 in Square Bits: PH1, (6) PH2, PH3, (4) 1 in Slotted Bits: St. 6, (2) SL8, SL10, (2) Nut Drivers: ¼ in, ¼6 in, Magnetic Drive Guide, Compact Magnetic Drive Guide, 2 in Power Bits: PH2 (1) Hex Bit 1 in ¼ in, (1) Hex Bit 1 in ¾6 in, (1) Phillips Bit 1 in P1, (6) Phillips Bit 1 in P2, (2) Phillips Bit 1 in P3, (9) Phillips Bit 1 in P3, (1) Slotted Bit #6, (1) Slotted Bit #10, (1) Slotted 2 in Bit #10, (2) Square Bit 1 in S01, (6) Square Bit 5 so S02, (1) Square Bit 1 in S03, (1) Square Bit 2 in S03, (1) Square Bit 3.5 in S02, (1) Torx Bit 1 in T10, (1) Torx Bit 1 in T15, (1) Torx Bit 1 in T20, (1) Torx Bit 1 in T20, (1) Torx Bit 1 in T30, (1) Torx Bit 1 in T5, (1) Magnetic Drive Guide, (16) 1 in PH Bits: PH4, 3½ in Slotted Bits: SL2, (8) 2 in Double Ended Bits: (3) PH2/PH2, PH1/SL6, (3) PH2/SL8, PH3/SL10, (2)	DeWalt	25CC4
2	ower Bit Set	Slotted #5-6	Eazypower	5UXW
4	ower Bit Set	Case, Spanner #4, #6,#8, #10	Eazypower	5UXU8
6	II Hex Bit Set	Stubby Cushion Grip Driver, Hex 1/6, 1/64, 1/32, 1/4 in	Wiha	5HYL4
6	mbination Bi	Stubby Cushion Grip Driver, Slotted 4.5, 6.5mm, Phillips #1, #2, #1, Pozi #2	Wiha	5HYL5
	½ in rx Bit Set	Stubby Cushion Grip Driver, Slotted 4.5, 6.0mm, Phillips #1, #2, Square #1, #2	Wiha	5HYL8
6	1/4 in 1/4 in	Stubby Cushion Grip Driver, Security Torx T8S, T10S, T15S, T20S, T25S, T30S Stubby Cushion Grip Driver, Torx T8, T10, T15, T20, T25, T30	Wiha Wiha	5HYL
rx Bit Se 7	et ¾ in	% in Drive Bit Holder, Torx T10, T15, T20, T25, T27, T30	Proto	3R754
i ple-Y In 2	1/4 in	Triple-Y #6	Eazypower	5UXZ
2	1/4 in 1/4 in	Triple-Y #5 Triple-Y #2	Eazypower Eazypower	5UXZ 5UXY
2	1/4 in	Triple-Y #3	Eazypower	5UXY9
2	1/4 in	Triple-Y #1	Eazypower	5UXY7