



## Nutsetters and Sets

- Tool insertion size: 1/4" Hex

These nonimpact-rated tools are used with power drills and power screwdrivers to generate more force (torque) in rotating hex head fasteners than a hand-operated tool.



**Nutsetter  
36C173**



**Set  
55KG63**

Fastening Size	Overall Length	Tool Insertion Size	Finish	Nutsetter Hex Size	Brand	Item No.	Pkg. Qty.
<b>Nutsetters</b>							
<b>Magnetized Tip Yes</b>							
1/4 in	1 1/2 in	1/4 in Hex	—	—	IRWIN	787P78	3
	1 1/2 in	1/4 in Hex	Satin	8 mm	Proto	1FR32	1
	1 1/2 in	1/4 in Hex	Tool Steel	—	IRWIN	55EV91	1
	2 1/2 in	1/4 in Hex	—	—	IRWIN	787P80	3
	2 1/2 in	1/4 in Hex	Tool Steel	—	IRWIN	55EV93	1
	4 in	1/4 in Hex	—	—	IRWIN	787P82	1
5/16 in	6 in	1/4 in Hex	—	—	IRWIN	787P83	1
	1 1/2 in	1/4 in Hex	Tool Steel	—	IRWIN	55EV92	1
	1 3/4 in	5/16 in Hex	Unfinished	5/16 in	Zephyr	411A72	1
	2 1/2 in	1/4 in Hex	Satin	5/16 in	Proto	1FR61	1
	2 1/2 in	1/4 in Hex	Tool Steel	—	IRWIN	55EV94	1
	2 1/2 in	5/16 in Hex	Unfinished	5/16 in	Zephyr	411A74	1
3/8 in	6 in	1/4 in Hex	—	—	IRWIN	787P84	1
	1 1/2 in	1/4 in Hex	—	—	IRWIN	55KH69	10
	1 1/2 in	1/4 in Hex	—	—	IRWIN	787P79	3
	1 1/2 in	1/4 in Hex	Tool Steel	—	IRWIN	55EW16	1
	1 3/4 in	1/4 in Hex	Unfinished	5/16 in	Zephyr	411A71	1
	2 1/2 in	1/4 in Hex	Tool Steel	—	IRWIN	55EW17	1
7/16 in	6 in	1/4 in Hex	Tool Steel	—	IRWIN	55EW18	1
	1 1/2 in	1/4 in Hex	Sand Blasted	5/16 in	DeWalt	5T25	1
	1 1/2 in	1/4 in Hex	Satin	5/16 in	Proto	1FR47	1
	2 1/2 in	1/4 in Hex	—	—	IRWIN	787P81	10
	2 1/2 in	1/4 in Hex	Tool Steel	—	IRWIN	55KG64	1
	2 1/2 in	1/4 in Hex	Tool Steel	1/2 in	IRWIN	55KG62	5
10 mm	1 1/2 in	1/4 in Hex	Satin	10 mm	Proto	1FR31	1
	2 1/2 in	1/4 in Hex	Black Oxide	5/16 in	Sammys	36C173	1
<b>Magnetized Tip No</b>							
<b>Number of Nutsetters Included</b>							
<b>Nutsetter Sets</b>							
<b>Magnetized Tip Yes</b>							
3	1/4 in, 5/16 in, 3/8 in	1 1/2 in	Gold	Proto	41V28		
	1/4 in, 5/16 in, 3/8 in	1 1/2 in	Tool Steel	IRWIN	55KG60		
4	1/4 in, 5/16 in, 3/8 in, 7/16 in	1 1/2 in	Tool Steel	IRWIN	55KG61		
	1/4 in, 5/16 in, 3/8 in	2 1/2 in	Tool Steel	IRWIN	55KG63		



**4JB74**



**6KX41**



**1GUB3**



## Corded Impact Wrenches

- 120V AC

These wrenches combine a hammer-like impact with high rotational torque to drive and remove fasteners. The impact force is initiated when resistance with the fastener is detected, and the impact is delivered in bursts to reduce stress on the user. Wrenches use interchangeable impact-rated sockets and are for use in general maintenance, construction, and automotive applications. Tools allow long run times for repetitive tasks, maintain full power during operation, and have no batteries to recharge.

Fastening Torque	Breakaway Torque	Free Speed	Impacts per Minute	Current	Includes	Brand	Item No.
<b>1/2 in Square Drive, Friction Ring</b>							
300 ft-lb	300 ft-lb	1,800 RPM	2,600	7 A	—	Milwaukee	6KX38
345 ft-lb	345 ft-lb	2,100 RPM	2,700	7.5 A	—	DeWalt	4JB74
<b>1/2 in Square Drive, Pin Detent</b>							
258 ft-lb	258 ft-lb	2,000 RPM	2,000	3.5 A	Belt Clip, Tool Case	Makita	14F191
300 ft-lb	300 ft-lb	1,800 RPM	2,600	7 A	—	Milwaukee	6KX37
345 ft-lb	345 ft-lb	2,100 RPM	2,700	7.5 A	Kit Bag	DeWalt	4JB73
<b>3/4 in Square Drive, Friction Ring</b>							
380 ft-lb	380 ft-lb	1,800 RPM	2,600	7 A	—	Milwaukee	6KX41
433 ft-lb	433 ft-lb	1,700 RPM	1,600	9 A	Side Handle, Steel Tool Case	Makita	14G997
<b>3/4 in Square Drive, Pin Detent</b>							
345 ft-lb	345 ft-lb	2,100 RPM	2,700	7.5 A	—	DeWalt	4JB75
<b>1 in Square Drive, Friction Ring</b>							
738 ft-lb	738 ft-lb	1,400 RPM	1,500	12 A	Side Handle, Tool Case	Makita	1GUB3

## Corded Shear Wrench

- 120V AC
- 12 A

This tool is used with tension control bolts to ensure the correct tension is achieved. Wrench is nonimpact so it operates more quietly than impact tools and

transfers less vibration to reduce the risk of hand injuries and fatigue. Requires no calibration and does not require adjustment prior to use. Tool allows long run times for repetitive tasks, maintains full power during operation, and has no batteries to recharge.

For A325 Bolt Size Capacity For A490 Bolt Size Capacity

Drive Size	Fastening Torque	Item No.
3/4 in, 1 in, 1 1/4 in	593 ft-lb	4DZJ2



## Corded Hammer Drills

- 1/2" chuck
- 120V AC
- Reversible

Hammer drills spin their bits and vibrate them at high speed and low impact for drilling small-diameter holes in asphalt, brick,

cinder block, tile, and light concrete more cleanly and easily than drilling alone. Tools have a rotate-only mode to drill wood, metal, plastic, and other non-concrete materials. For use in applications that require more power than

a standard drill but don't require the large-diameter bits and heavy impact of rotary or demolition hammers. Tools allow long run times for repetitive tasks, maintain full power during operation, and have no batteries to recharge.



**5VC48**



**60NK83**

Drilling Capacity in Concrete	Drilling Capacity in Wood	Maximum Tool Speed	Maximum Blows per Minute	Tool Length	Includes	Current	Brand	Item No.
<b>1 Speed</b>								
3/8 in	1 1/4 in	2,800 RPM	47,600 bpm	10 5/8 in	360 Degree Side Handle, Chuck Key with Holder, Depth Rod	7 A	DeWalt	21RY66
3/8 in	1 1/4 in	1,150 RPM	46,000 bpm	11 1/2 in	360° Auxiliary Handle, Carrying Case, Chuck Key, Depth Gauge	8.5 A	DeWalt	5VC48
3/8 in	1 1/4 in	3,000 RPM	48,000 bpm	11 in		7 A	Bosch	2LD81
<b>2 Speed</b>								
7/16 in	1 1/2 in	1,200 RPM, 3,500 RPM	56,000 bpm	13 in	360° Locking Side Handle, Chuck Key with Holder, Kit Box, Steel Depth Rod	10 A	DeWalt	3GRF6
7/16 in	1 1/2 in	1,200 RPM, 3,500 RPM	56,000 bpm	14 in		10 A	DeWalt	3GRF5
3/4 in	1 1/2 in	1,200 RPM, 3,200 RPM	19,550 bpm, 51,000 bpm	13 1/8 in	360° Auxiliary Handle, Chuck Key, Depth Gauge	8.5 A	Bosch	39RY34
3/4 in	1 1/2 in	900 RPM, 3,000 RPM	15,300 bpm, 51,000 bpm	13 1/2 in	360° Auxiliary Handle, Carrying Case, Chuck Key, Depth Gauge	9.2 A	Bosch	5EEW4
<b>Continuous Speed</b>								
3/8 in	1 1/2 in	2,700 RPM	19,000 bpm, 46,000 bpm	13 in	360 Degree Side Handle, Chuck Key with Holder, Depth Rod, Kit Box	7.8 A	DeWalt	6HC39
3/8 in	1 1/2 in	2,700 RPM	19,000 bpm, 46,000 bpm	13 in	360 Degree Side Handle, Chuck Key, Depth Rod	7.8 A	DeWalt	4KZ90
23/32 in	1 1/2 in	3,100 RPM	58,900 bpm	—	Chuck Keys, Drilling Depth Guide, Geared Chucks, Metabo 145 L, Rubber-Coated Side Handle	7 A	Metabo	60NK83