



DEWALT WESTWARD



**Impact** Driver Bit Set 60HU17



## **Impact Screwdriver Bit Sets**

Provide a range of drilling and driving capabilities, and are precision machined for an exact fit allowing quick changeouts.





19RK07

		Fastening										
	Shank	Tool			Item							
	Size	Material	Includes	Brand	No.							
Impac	Impact Driver Bit Set											
34	1⁄4 in	Chrome Vanadium Steel	Handle, Bit Holder, Metal Storage Box, Bits, PoziDriv (1) #1, (1) #2, (1) #3, Square (1) #1, (2) #2, (1) #3, Phillips (2) #1, (2) #2, (2) #3, Hex Metrix (1) 3.0mm, (1) 4.0mm, (1) 5.0mm, (1) 6.0mm, Hex Inch (1) ½ in, Torx(R) (1) T10, (1) T10, (2) T20, (2) T25, (2) T30, (1) T40 ½ Nut Driver, ¾6 Nut Driver, Hex ½7, Hex ½7, Hex ¾67,	Wiha	440A44							
100		Alloy Steel	74" Nut Driver, 746" Nut Driver, Hex 74", Hex 746", Hex 746", Hex 752", Hex 752", Hex 752", Hex 754", Hex 754", PH1, PH2, PH3, PR2, SL #12, SL #4, SL #6, SL#10, SL#8, SQ1, SQ2, SQ3, T10, T15, T20, T25, T27, T30	Milwaukee	60HU17							
	Bit Set											
40	1/4 in	Steel	Tool Case	IRWIN	55KJ04							
Magne		e Guide Set										
7	1/4 in	Steel	3 in Magnetic Drive Guide, (2) PH2 Insert Bits, SQ2 Insert Bit, T20 Insert Bit, (2) T25 Insert Bits	Milwaukee	419J71							
Pivot I	Pivot Holder and Bit Set											
11	1/4 in	Steel	(1) Phillips Bit 1 in P1, (1) Phillips Bit 1 in P2, (1) Phillips Bit 1 in P3, (1) Slotted Bit 1 in SL ¼ in, (1) Slotted Bit 1 in SL ½ in, (1) Slotted Bit 1 in SL ½ in, (1) Slotted Bit 1 in SL ½ in, (1) Square Bit 1 in SQ, (1) Square Bit 1 in SQ2, (1) Bit 1 in T25, (1) Shockwave 30 Degree Knuckle Pivoting Bit Holder	Milwaukee	10Z808							
Screw	driver Bi	t Set										
22	1 in	High Speed Steel	(5) TORX(R) Bit 1 in T25, (3) Phillips Bit 1 in P2, (3) TORX(R) Bit 1 in T20, (3) Square Bit 1 in S02, (2) Phillips Bit 1 in P3, (1) SHOCKWAVE(R) Compact Magnetic Bit Holder, (1) Phillips Bit 1 in P1, (1) Square Bit 1 in S01, (1) Square Bit 1 in S03, (1) TORX(R) Bit 1 in T10, (1) TORX(R) Bit 1 in T30, (1) Slotted Bit 1 in S1. 1/4 in S1. 1	Milwaukee	423P08							
26	1⁄4 in	Steel	(1) Phillips Bit 1 in P1, (1) Phillips Bit 1 in P2, (3) Phillips Bit 1 in P3, (1) Square Bit 1 in SQ1, (2) Square Bit 1 in SQ2, (1) Square Bit 1 in SQ3, (2) TORX(R) Bit 1 in T20, (2) TORX(R) Bit 1 in T20, (2) TORX(R) Bit 1 in T25, (1) TORX(R) Bit 1 in T30, (1) ½ in Hex to ¾ in Square Adapter, (1) ½ in Magnetic Nut Driver, (1) Phillips Bit 2 in P2, (1) Square Bit 2 in SQ2, (1) TORX(R) Bit 2 in T20, (1) Slotted Bit 1 in SL ¾ in (1) ¾ in Drive; ½ in Socket, (1) ¾ in Drive № in Socket, (1) ¾ in Magnetic Nut Driver, (1) ¾ in Magnetic Nut Driver, (1) ¾ in Magnetic Nut Driver, (1) % in Magnetic Nut Driver, (1) ¾ in Magnetic Nut Driver, (1) ¾ in Magnetic Nut Driver, (1) % in Magnetic Nut Driver,	Milwaukee	19RK07							
35	1/4 in	Steel	Impact Ready Socket Adapters ¾ in, ¼ in, ¼ in, ¼ in, ⅓ in, Impact Ready ¼ in Hex Shank Adapter, Impact Ready Nutsetters ¾ in, ¾ in, ¼ in, 3 in Impact Ready Bits: SQ1, (4) SQ2, SQ3, 1 in Philips	DeWalt	20UH15							
40	1/4 in	Steel	¼ in Nutsetter, ¾s in Nutsetter, Impact Ready Sleeve, 3 in Impact Ready Screw Lock Holder, 6-2 in PH2 Impact Ready Bit, 2 in SQ2 Impact Ready Bit, 2 in T25 Impact Ready Bit, 2 in SL8 Impact Ready Bit, (4) 1 in PH2 Bit, (2) 1 in SL8 Impact Ready Bit, 1 in	DeWalt	20UH16							
50	1⁄4 in	Steel	(1) Compact Bit Holder, (1) ¼ in Magnetic Nut Driver, (1) ¾ in Magnetic Nut Driver, (1) ¾ in Socket Adapter, (1) ½ in Socket Adapter, (1) Insert PH1 Bits, (2) Insert PH3 Bits, (1) Insert SU   Insert SU   Bits, (3) Insert SU   Bits, (1) Insert SU   Bits, (2) Insert SU   Bits, (3) Inser	Milwaukee	48ZJ62							
60	1⁄4 in	Steel	Compact Bit Holder, 6 in Bit Holder, Magnetic Nut Drivers ¼ in, ¾6 in, Socket Adapter ¾ in, Hex Drill Bits ⅙6 in, ¾6 in, ¾6 in, ¾6 in, ¼6 in, ¾6 in, ¼6 in, ¾6 in, ¼6 in, ¾6 in, ¼6 in, ¼6 in, ¾6 in,	Milwaukee	415H78							
65	½ in	Steel	Compact Magnetic Bit Holder, ¼ in Magnetic Nut Driver, ¾s in Magnetic Bit Holder, ¼ in Socket Adapter, 1 in PH1, 1 in PH2, 1 in PH3, 1 in PH3, 1 in SOL, 2 in SOL, 1 in SOL, 2	Milwaukee	415H87							
175	1/4 in	Steel	Phillips Ribbed, Slotted , Phillips, Pozi Phillips, Hex, Torx(R), Spline, Roberts, Security Bits, Tri Wing, Clutch Bits, Quick Change Chuck, 1 and 2 in Drive Socket Adapter, 4 to 11/16 in Screw Guide Driver, Storage Case	Westward	1VXP2							









## **Impact Screwdriver Bits**

■ Hex shank size: 1/4" For use with impact drivers and suitable for applications requiring a high level of torque.

Fastening Tool Tip Size	Overall Bit Length	Shank Style	Fastening Tool Material	Brand	Item No.	Pkg. Qty.
Headlok(R)	Dit Long	Onami Otyro	1001	D. u.i.u		w.,,.
Headlok	2 in	Hex	Alloy Steel	Milwaukee	60HU41	1
Hex						
T10, T15, T20, T25, T27, T30	1 in	Hex	Alloy Steel	Milwaukee	415H77	1
Phillips						
	1 in	Hex	S2 Steel	Milwaukee	10Z765	5
#1	2 in	Hex	S2 Steel	Milwaukee	10Z771	1
	6 in	Hex Power Drive	S2 Steel	DeWalt	20GY06	50
	1 in	Hex	S2 Steel	Eazypower	52JL90	10
	1 in	Hex	S2 Steel	Eazypower	36JF78	500
	1 in	Hex	S2 Steel	Milwaukee	5EAX1	2 5
	1 in	Hex	S2 Steel	Milwaukee	5EAX2	5
	1 in	Hex	Steel	IRWIN	55KJ11	20
	2 in	Hex	S2 Steel	Eazypower	36JF70	250
	2 in	Hex	S2 Steel	Milwaukee	5EAX6	1
	2 in	Hex	S2 Steel	Milwaukee	10Z772	15
#2	2 in	Hex	S2 Steel	Milwaukee	33GM81	25
	3 ½ in	Hex	S2 Steel	IRWIN	783HT9	10
	3 ½ in	Hex	S2 Steel	Milwaukee	5EAX9	1
	3 ½ in	Hex	S2 Steel	Milwaukee	10Z780	5
	3 ½ in	Hex	S2 Steel	Milwaukee	33GN01	25
	6 in	Hex	S2 Steel	Milwaukee	10Z781	1
	6 in	Hex	S2 Steel	Milwaukee	33GN11	10
	6 in	Hex Power Drive	S2 Steel	DeWalt	20GY07	50
	6 in	Hex Power Drive	S2 Steel	Westward	38RV95	1
	1 in	Hex	S2 Steel	Milwaukee	10Z766	5
#3	2 in	Hex	S2 Steel	Milwaukee	5EAX8	1
#3	2 in	Hex	S2 Steel	Milwaukee	33GM87	25
	3 ½ in	Hex	S2 Steel	Milwaukee	10Z778	1

