Round-Shank

## **Rotary Drill and Hammer Drill Bits for Concrete and Masonry**

BITZ			crete	e and		SOI		$\sim$		СНИ	( <del>ISIN</del> /AL	RD'	4KZ		1		Mason 6PTC		
	Maximun							Maximum							1 1 1	12			
Drill	Drilling		Shank		ltem	Pkg.	Drill	Drilling	Overal			Item	Pkg.	3-Flat	881	1			
Bit Size	Depth		Diameter		No.	Qty.	Bit Size	Depth		Diameter	Brand	No.	Qty.	Shank	1 5	11		Shank	
				tion Bits &			<u>1/4 in</u>	4 in	6 in	1/4 in	Bosch	26KR30			6 9	18	Hoy.	Shank	C. C. C.
5/32 in	3 in	41/2 in	25/64 in	Tapcon	4AL07	1	1/4 in	4 in	6 in		DeWalt	45HF07		Set	6	281	. Her	JIIAIIK	-
3/16 in	3 in	4½ in	25/64 in	Tapcon	4AL10	<u></u>	5/16 in	4 in	6 in	5/16 in	Bosch	46U336		4PC22				t-Rated	
3/16 in	31/8 in	5½ in	<sup>25</sup> ⁄64 in	Tapcon	4AL11	1	3/8 in	4 in	6 in	5⁄16 in	Bosch	46U339					46	J358	
			Bits for Ro		41/700		1⁄2 in	4 in	6 in	5/16 in	Bosch	46U343	1	Number of					Item
1/8 in	2 in	<u>3 in</u>	1/8 in	DeWalt	4KZ93						Masonry D			Drill Bits		t Sizes Inc	luded	Brand	No.
5/32 in	4 in	6 in	1/4 in	DeWalt	4PC23	1	1/8 in	3 in	41/2 in		DeWalt	34D629		3-Flat Shar			04.1	D 14/ 11	40000
3/16 in	2 in	3 in	3/16 in	DeWalt	4KZ94	1	3/16 in	3 in	41/2 in		DeWalt	34D631		4		¼ in, 5⁄16 in		DeWalt	4PC22
3/16 in	4 in	<u>6 in</u>	<sup>3</sup> /16 in	DeWalt	4KZ95	1	1/4 in	3 in	43/4 in		DeWalt	34D633			3/16 IN, 1/4 I	n, 5⁄16 in, 3⁄8	i in, ½ in	DeWalt	4KZ92
3/16 in	4 in	6 in	3/16 in	DeWalt	1ELE3	25	1/4 in	4 in	6 in	1/4 in	Bosch	48XX32	. 1	Hex-Shank				D 14/ 11	4511500
1/4 in	2 in	4 in	1/4 in	DeWalt	4KZ96	1		hank Mase						3		n, ¾16 in, ¼		DeWalt	45HF08
1/4 in	4 in	6 in	1⁄4 in	DeWalt	4KZ97	1	5/32 in	3 in	6 in	<sup>25</sup> ⁄64 in	Bosch	53DM27		5		n, ¼ in, %e		Bosch	46U355
5/16 in	4 in	6 in	5/16 in	DeWalt	4KZ99	1	3/16 in	4 in	6 in	3/16 in	Bosch	53DM28	81	5		in, ¼ in, ¾		Bosch	46U356
3⁄8 in	4 in	6 in	3⁄8 in	DeWalt	4LC02	1	3∕16 in	23/4 in	4 in	3⁄16 in	Westward	6PTC8	1			n, ¾16 in, ¼		Bosch	46U358
1/2 in	4 in	6 in	1/2 in	DeWalt	4LC05	_1	1/4 in	23/4 in	4 in	1/4 in	Westward	6PTE3	1	Multi-Mate					
5⁄8 in	4 in	6 in	1/2 in	DeWalt	4LC07	1	1/4 in	41/2 in	6 in	1/4 in	Westward	6PTD5	1	5		n, ¼ in, %e		DeWalt	34D628
3⁄4 in	4 in	6 in	1⁄2 in	DeWalt	4LC09		1/4 in	11½ in	13 in	3∕16 in	Westward	6PTF5		5		in, ¼ in, ¾		Bosch	48XX36
				Masonry Dr			5∕16 in	41/2 in	6 in	5∕16 in	Westward	6PTD9	1	Round-Sha					
3⁄16 in	4 in	6 in	1⁄4 in	Bosch	46U360		3⁄8 in	41⁄2 in	6 in	3% in	Westward	6PTD8	1	7	<sup>3</sup> ⁄16 in, 1⁄4 i	n, 5⁄16 in, ¾	in, ½ in	Westward	6PTC5
3∕16 in	4 in	6 in	3∕16 in	Bosch	46U331		3⁄8 in	16¼ in	18 in	3⁄8 in	Westward	6PTE5	1	10	1/8 in, 5/32 ir 9/32 in, 5/16	1, ¾16 in, ¾	2 in, 1⁄4 in,	Westward	20UR67
³∕16 in	4 in	6 in	1⁄4 in	Bosch	46U363		1⁄2 in	4½ in	6 in	3% in	Westward	6PTD7		10	%32 in, 5⁄16	in, ¾ in, 7⁄1	6 in, ½ in	wostwaru	2001107
1⁄4 in	4 in	6 in	1⁄4 in	Bosch	46U333		1⁄2 in	11½ in	13 in	<sup>13</sup> /32 in	Westward	6PTD2	1	14	1⁄8 in,	5⁄32 in, 3⁄16 i	n, ¼	Bosch	44H427
1⁄4 in	4 in	6 in	1⁄4 in	Bosch	46U362	5	1/2 in	16¼ in	18 in	<sup>13</sup> /32 in	Westward	6PTE0	1	14	in, 5⁄1	6 in, ¾ in, 1	∕₂ in	DUSCII	4411427
Wesn	WARD	Milu	uukee	<b>A</b> PI	EX.	IR\	WIN.	Fasteni Size Nutsett	ers (Con	verall ength t.)	Finish		Brand	ltem No.	Pkg. Qty.		_		
_	_		-					Magnet		Yes (Cont.)						-	(Section of the	Constraints	and a second second
Tnak	ita 🕒	EV/A	🚺 🛄 G	EARWI	RENCH	B				7/8 in	Black Phos	phate	Milwauk			Contraction of the local division of the loc		A State of the	
			-							7/8 in	Black Phos		Milwauk					1	
mnant_Dated									1	1 7⁄8 in	Black Phos	ohate	Milwauk	ee 33GN2	<b>0</b> 10				

Tapcon Dewalt

**3-Flat Shank** 

Masonry

## Impact-Rated **Nutsetters and Sets**

Tool insertion size: 1/4" Hex

Milwaukee

Fastening Size	Overall Length	Finish	Brand	ltem No.	Pkg. Qty.	
Nutsetters						
Magnetized						
	1 7/8 in	Black Electrophoresis	Westward	38RV63	3	
	1 7⁄8 in	Black Phosphate	Milwaukee	33GN18	10	
	1 1 1/8 in	Black Phosphate	Milwaukee	5ECC1	1	
	1 ¾ in	Unfinished	Apex	5UFG8	1	
1⁄4 in	2 %16 in	Black Phosphate	Milwaukee	5ECD0	1	
74 111	2 %16 in	Black Phosphate	Milwaukee	33GN22	10	
	2 1⁄2 in	Sand Blasted	Westward	1VXN2	3	
	4 in	Black Oxide	IRWIN	55EW52	1	
	6 in	Black Oxide	IRWIN	55EW55	1	
	6 in	Unfinished	Apex	5UFG4	1	
	1 7⁄8 in	Black Electrophoresis	Westward	38RV64	3	
	1 1 1/8 in	Black Phosphate	Milwaukee	33GN19	10	
	1 7⁄8 in	Black Phosphate	Milwaukee	5ECC2	1	
	1 ½ in	Black Phosphate	Milwaukee	36GG55	3	
5⁄16 in	1 ¾ in	Unfinished	Apex	5UFG9	1	
710 111	2 in	Black Oxide	DeWalt	55HE77	1	
	2 %16 in	Black Phosphate	Milwaukee	5ECD1	1	
	2 %16 in	Black Phosphate	Milwaukee	33GN23	10	
	4 in	Black Oxide	IRWIN	55EW54	1	
	6 in	Unfinished	Apex	5UFG6	1	

		3 in <sup>13</sup> / <sub>32</sub> 8 in <sup>13</sup> / <sub>32</sub>			14	1⁄8 i	n, 5⁄32 in, 3⁄16 in, 1⁄4 5⁄16 in, 3⁄8 in, 1⁄2 in	Bosch	44H427		
	Fastening Size Nutsetters		Finish	Brand	ltem No.	Pkg. Qty.					
	Magnetized	i Tip Yes (Co	nt.)				C Aller	and a second	2020		
		1 1/8 in	Black Phosphate	Milwaukee	5ECC8	3	and the second second	STREET, STREET, ST			
		1 7⁄8 in	Black Phosphate	Milwaukee	5ECC3	1		Contract of the	and in case of the local division of the loc		
		1 1 1/8 in	Black Phosphate	Milwaukee	33GN20	10		Nutsetter			
	3⁄8 in	1 ¾ in	Unfinished	Apex	5UFH0	1					
		2 %16 in	Black Phosphate	Milwaukee	5ECD2	1		5UFG8	FG8		
		2 %16 in	Black Phosphate	Milwaukee	33GN24	10					
		6 in	Black Oxide	IRWIN	55EW56	1		100			
	7∕16 in	2 %16 in	Black Phosphate	Milwaukee	5ECD3	_1_		8 .			
		2 %16 in	Black Phosphate	Milwaukee	33GN25	10		1 4			
	1/2 in	2 %16 in	Black Phosphate	Milwaukee	10Z764	1		/ # #	-		
1	7mm	2 %16 in	Black Phosphate	Milwaukee	33GN30	10		1 1	8 0		
	10mm	2 %16 in	Black Phosphate	Milwaukee	33GN27	10			1 1 2		
-	13mm	2 %16 in	Black Phosphate	Milwaukee	33GN29	10	-		1 4		
-	Magnetized						Set	TO A	ð //		
-	9⁄16 in	3 in	Corrosion Resistant	Makita	40KG34	1	785HR4	V 6			
-		12 in	Corrosion Resistant	Makita	40KG39	1	7051114				
-	3⁄4 in	12 in	Corrosion Resistant	Makita	40KG36						
	Numbe Nutsetters	Included	Fastening Siz	ze	Overall Length		Finish	Brand	ltem No.		
	Nutsetter S										
	Magnetized	l Tip Yes									
	3		1⁄4 in, 5⁄16 in, 3⁄8		1 7/8 in		Black Oxide	IRWIN	55EW47		
	J		1/4 in, 5/16 in, 3/8		1 ½ in		ack Phosphate	Milwaukee	4RRP3		
_			1/4 in, 5/16 in, 3/8 in,		1 ½ in		Black Oxide	IRWIN	55EW49		
	4		1/4 in, 5/16 in, 3/8 in,	7/16 in	1 7/8 in		ack Phosphate	Milwaukee	5ECC5		
			1/4 in, 5/16 in, 3/8 in,	7/16 in	3 ½ in		ack Phosphate	DeWalt	4WLT1		
_	5		1/4 in, 5/16 in, 3/8 in, 7/1		1 1 1/8 in		Black Oxide	DeWalt	4WLR5		
_			1⁄4 in, 5⁄16 in, 3⁄8 in, 7⁄1	6 in, ½ in	2 in		Black Oxide	DeWalt	55HE73		
_	Magnetized	I TIP No	4/1 5/1 0/								
_	3		1/4 in, 5/16 in, 3/8		2 ½ in		Sand Blasted	Westward	1VXN5		
-	8		in, 7 mm, 5⁄16 in, 8 mm, 11 mm, 7⁄16 in, 12 mm,		<sup>1,</sup> 2 %16 in		Black Oxide	Gearwrench	785HR4		

## DAWALL IRWIN. STEELMAN PRO Impact Socket Adapters, **Extensions. and Accessories**

WESTWARD PROTO APEX

EACOILO	iono, a					29AR0	
	Drive Gender	Overall Length	Finish	Locking	Brand	ltem No.	Pkg. Qty.
<sup>1</sup> / <sub>4</sub> " Input Drive	Flex Socket Ada	pters					
Male Input Driv							
1/4 in Square	Female	1 7⁄16 in	Black Phosphate	No	Milwaukee	61DN61	1
Female Input D							
1/4 in Square	Male	1 ½ in	Black Oxide	No	Westward	4PRE5	1
	Male	1 3⁄8 in	Black Oxide	Yes	Proto	4UHR1	1
3/8" Input Drive	Flex Socket Ada	pters					
Male Input Driv	/e Gender						
3/8 in Square	Female	2 in	Black Phosphate	No	Milwaukee	61DN64	1
Female Input D	rive Gender		•				
34 in Causes	Male	2 1/16 in	Black Oxide	Yes	Proto	4UHT7	1
3/8 in Square	Male	2 1/2 in	Black Oxide	Yes	Westward	4LYV7	1
1/2" Input Drive	Flex Socket Ada	pters					
Male Input Driv	/e Gender						
1/2 in Square	Female	2 1/2 in	Black Phosphate	No	Milwaukee	61DN67	1
Female Input D	rive Gender		•				
	Male	2 11/16 in	Black Oxide	No	Apex	6UGG1	1
1/2 in Square	Male	2 1/2 in	Black Oxide	Yes	Westward	4LZD4	1
	Male	2 5 in	Black Oxide	Yes	Proto	4HVA7	1
	Flex Socket Ada	pters					
Male Input Driv	/e Gender						
3/4 in Square	Female	3 5 in	Black Phosphate	No	Milwaukee	61DN70	1
Female Input D	rive Gender						
	Male	3 1/2 in	Black Oxide	No	Westward	4PRC8	1
3/4 in Square	Male	3 1/2 in	Black Oxide	No	Wright Too	29AK67	1
	Male	3 1/2 in	Black Oxide	No	Proto	1AX64	1

				-								
Flex S	ocket	Adapte	r Socke	t					. As ROand		Retain Ring &	
	29AK6	37	Adapte	er	Sock	et Adap	ter Set	Ex	tensio	m	19C65	51
			61 DN6		5000	45KG8			2AY73			
	Item			-			<i>'</i>	5	2A1/3	•		
Brand	No.	Qty.	Output Driv		Dutput	Overall						Pkg.
			Size & Shap	e_Driv	e Gender	Length	Fi	nish l	ocking	Brand	i No.	Qty.
			1" Input Driv	e Flex S	ocket Adap	ters						
Milwaukee	61DN61	1.	Male Input D			10/1						
A/= = +	40055		1 in Square		emale	4 ¾ in	Black F	hosphate	No	Milwaul	kee 61DN7	31
Westward Proto	4PRE5 4UHR1		Female Input		Male	4 5% in	Diag	k Oxide	No	Droto	1ACR9	1 1
Proto	40HK1		1 in Square 1½" Input Dr				Blac	k Oxide	NO	Proto	TACKS	<u>,                                     </u>
			Female Input			apters						
Milwaukee	61DN6/	1	1 ½ in Squa		Male	6 5⁄16 in	Blac	k Oxide	No	Proto	19ZA6	1 1
viiiwaukee	010104	<u> </u>				0 916 111	Didu	K UXIUE	NU	FIUL	I I I I I I	
Proto	4UHT7	1	Output Drive Size	Output Drive							Item	Dka
Westward		1	& Shape	Gende			Finish	Locking	Br	and	No.	Pkg. Qty.
riootinala			#5 Spline Inp				i iiiiəli	LUCKING	DIG	anu	NU.	uly.
			Female Input			ah1012						
Milwaukee	61DN67	1	1 in Square	Male		n Bla	ck Oxide	No	Pr	oto	1AKF7	1
			1/4" Input Driv					110		010	1743317	
Apex	6UGG1		Male Input D									
Westward			3% in Square			1 Black	Phosphate	No	Milw	aukee	61DN60	1
Proto	4HVA7	1	1/4" Hex Input									
			Male Input D									
				Male	1 7/s ii		ck Oxide	No		aukee	5ECA8	1
Milwaukee	61DN70	11	1/4 in Square—	Male	2 in		ck Oxide	Yes		Nalt	4WM51	1
	488.000		74 III Square	Male	2 <sup>35</sup> /64		ck Oxide	Yes		Nalt	2KLR4	1
Westward				Male	6 in	1	Vatural	Yes	West	tward	4PRJ1	1

## Sign in to Grainger.com® to see YOUR Pricing and MORE

CONTINUED