

## Corded Core Drill Rigs and Motors

Core drill rigs have a core drill motor and a matching stand to create deep, large-diameter holes in concrete and masonry to run plumbing lines, HVAC ducts, electrical wires, and telecom cables. They grind out material around the edge of a hole and leave the core intact for removal.

Compatible with Grainger Part Number	Column Height	Base Length	Base Width	Item No.
<b>Milwaukee Core Drill Stand Mount Type Leveling Screws</b>				
1Y044	47 in	10 1/2 in	13 in	38D750
<b>Husqvarna Core Drill Stand Mount Type Vacuum</b>				
2LEA5, 3RDN7, 40ZU86	31 1/2 in	25 in	10 1/2 in	2ETR3
3RDN8, 40ZU86, 6PEV2	39 in	16 in	10 1/2 in	18G515

Milwaukee

Husqvarna



Handheld Core Drill 6PEV2

Horsepower in Concrete	Coring Capacity	Current	Column Height	Angle-to-Surface	Tool Weight	Maximum Spindle Speed	Includes	Brand	Mfr. Model	Item No.
<b>Handheld Core Drill</b>										
2.5 hp	6 in	13 A	—	90°	15.4 lb	2,900 RPM	—	Husqvarna	DM220	6PEV2
2.5 hp	6 in	15 A	—	90°	15.4 lb	2,900 RPM	Side Handle, Water Kit, 5/8"-11 to 1 1/4"-7 Adapter	Husqvarna	DM230	2LEA5
<b>Core Drill Rig</b>										
<b>120/240V AC</b>										
2.3 hp	6 in	15 A	31 in	60°	51 lb	800 RPM	Vacuum Plate	Husqvarna	DMS180	3RDN8
<b>120V AC</b>										
2.9 hp	10 in	10 A	39 in	60°	51 lb	890 RPM	Vacuum Plate	Husqvarna	DMS240	3RDN7
4.8 hp	10 in	20 A	43 1/2 in	90°	137.8 lb	900 RPM	4096 Diamond Coring Rig Motor, Large Base Stand, Meter Box, Vac-U-Rig Kit	Milwaukee	4120-22	38D748
4.8 hp	10 in	20 A	43 1/2 in	90°	111.5 lb	900 RPM	4096 Diamond Coring Rig Motor, Meter Box, Small Base Stand, Vac-U-Rig Kit	Milwaukee	4115-22	38D746
<b>Core Drill Motors</b>										
<b>120V AC</b>										
4 1/4 hp	7 in	20 A	—	—	24 lb	1,200 RPM	Open End Wrench, Water Control Valve, Water Hose Adapter	Milwaukee	4005	38D739
4 1/4 hp	10 in	20 A	—	—	24 lb	900 RPM	Open End Wrench	Milwaukee	4096	1Y044
4 1/4 hp	10 in	20 A	—	—	24 lb	900 RPM	(6) Shear Pins, Open End Wrench, Water Control Valve, Water Hose Adapter	Milwaukee	4094	38D742
4 1/4 hp	14 in	20 A	—	—	24 lb	600 RPM	Open End Wrench, Water Control Valve, Water Hose Adapter	Milwaukee	4004-20	3F859



## Tile Saws

Water lubricates the blade and tile during cutting to reduce airborne dust and particles.



QEP 48Z886



DeWalt 4YY94

Blade Dia.	Max. Cutting Depth	Max. Cut Length	Arbor Size	Blade Speed	Voltage	Current	Includes	Brand	Item No.
7 in	1 1/4 in	—	5/8 in	3,600 RPM	120V AC	4.8 A	Blade, Manual, Miter Guide, Rip Guide	QEP	48Z886
7 in	2 in	—	—	—	120	7.4 A	Rip Guide, Water Pump	MK Diamond Products	55EC68
10 in	3 in	20 in	5/8 in	3,450	120	12.6 A	Rip Guide, Water Pump	MK Diamond Products	55EC69
10 in	3 1/2 in	28 in	5/8 in	4,200 RPM	120V AC	15 A	Removable Thermoplastic Water Reservoir, 10 in Diamond Blade, Water Pump Assembly, 45° and 90° Rip Guides	DeWalt	4YY94
10 in	3 1/2 in	24 in	—	—	120	15 A	Protractor, Rip Guide, Submersible Water Pump	MK Diamond Products	55EC70



## Masonry Saws

Masonry saws use a diamond saw blade to wet or dry cut stone, brick, cinder block, and concrete. Wet cutting reduces airborne contaminants and keeps the blade cooler, extending blade life. Dry cutting requires a dust collection system to keep dust to a minimum.

Handheld 6FKG8



Benchtop 45RM23



Blade Dia.	Cutting Type	Max. Cutting Depth	Miter Angle Range	Arbor Size	Voltage	Current	Horsepower	Includes	Brand	Item No.
<b>Handheld</b>										
4 3/8 in	Dry	1 3/8 in	—	3/4 in	120V AC	15 A	—	Socket Wrench, Spanner Wrench, (2) 4 in Diamond Blade Turbo	Makita	45PC96
4 3/8 in	Wet/Dry	3 1/8 in	—	20 mm	120V AC	10.8 A	—	12 ft Water Line and Regulator, Diamond Blade, (2) Wrenches for Blade Change, Instruction Manual	DeWalt	6FKG8
5 in	Wet	1 1/2 in	—	7/8 in	120V AC	12 A	—	Side Handle	Flex North America	53GK18
14 in	Dry	9 3/4 in	—	1 in	120V AC	15 A	—	Wrench	Makita	14G991
14 in	Dry	9 3/4 in	—	1 in	120V AC	15 A	—	14 in Diamond Blade Sgmt Gen/Purp	Makita	45PC97
<b>Benchtop</b>										
14 in	Wet	5 in	45°	1 in	115/230V AC	14.0 A	1.5	Blade	Husqvarna	45RM23
14 in	Wet	5 in	45°	1 in	115/230V AC	14.0 A	2	Blade	Husqvarna	45RM24
14 in	Wet	5 in	45°	1 in	115V AC	14.0 A	1.5	Blade	Husqvarna	45RM22
14 in	Wet	5 in	45°	1 in	230V AC	14.0 A	3	Blade	Husqvarna	45RM25



## Flooring Saw

- 120VAC, 7A
- 1 HP
- 11,000 RPM

Circular saw blades to make straight, rip, and angled cuts in wood and laminate flooring. Adjustable stops to cut miters.



Blade Dia.	Cutting Type	Max. Cutting Depth	Miter Angle Range	Arbor Size	Item No.
4 3/8 in	Dry	3/4 in	0°-22.5°-45°	3/4 in	19M485



## Cordless Handheld Concrete Saws

- Wet/Dry
- 9" Blade Dia.
- 3 1/4" Max. cutting depth
- 7/8" Arbor

Cordless handheld concrete saws are battery-operated tools used to cut masonry, stone, and reinforced concrete. They can be used vertically, making them a good choice for demolition and cutting through walls and automobile and infrastructure wreckage.



Bare Tool 453U31

Battery Series	Cordless Tool Kit Contents	Item No.
60V MAX FLEXVOLT	(1) Bare Tool	453U31
	(1) Bare Tool, (1) Charger, (2) Batteries	453U30