





Voltage	Speed Setting	Collet Size	Brushless Motor	Cordless Tool Kit Contents	Mfr. Model	Item No.						
Cordless Tool Kits												
4V DC	Variable Speed	1 ¾ in	No	(1) Bare Tool, (1) Universal Micro-USB cord, (1) USB Wall Plug Power Supply	7760- N/10	784J43						
12V DC	Variable Speed	1/32 in, 1/16 in, 3/32 in, 1/8 in	2 No	Bare Tool, Battery, Charger, (5) Accessories	8240-5	794A70						
Replacement Battery												
	1:	R814-01	784.152									

3W843

Bit &

Set 5EEV1



**DREMEL** 

■ 35,000 RPM max. speed









## **Rotary Tool Bits & Attachments**

Shape	Head	Width	Item No.	Pkg. Qty.	
Abrasive Po		wiutii	140.	uty.	
Aluminum O					
		in	3W850	1	
Cylinder			1UH81	i	
Round Disk			41HR09	1	
			3W849	1	
Tapered			41HR12	1	
Silicon Carb					
Round Disk		ie in	3CY76	1	
Tapered	1/2	in 4	41HR03	1	
Shape	Head Width	Head Length	Item No.	Pkg. Qtv.	
Carving Bit	with	Lungtii	140.	uty.	
High Speed	Steel				
Arrow	½ in	3/8 in	21CJ07	2	
Culindor	1/8 in	1/4 in	21CJ09	2 2 2 1	
Cylinder –	5/16 in	3% in	21CJ05	2	
Disc	3⁄8 in	3/8 in	3W845	1	
Pear	3∕16 in	3∕16 in	21CJ08	2	
Tapered	1/4 in	7∕₁6 in	21CJ06	2	
Tungsten Ca					
Ball —	1/8 in	1/8 in	41HR14	1	
Duil	5/16 in	1/8 in	1UH87	1	
—	1/8 in	9/16 in	6X194	1	
Cylinder _	1/8 in	½ in	41HR13	1	
	5∕16 in	½ in	1UH86	1	
Small Taper	1⁄4 in	¾ in	1UH85	1	
Engraving B	it				
Alloy Steel					
Ball —	1/32 in	1/16 in	21CJ13	2	
	3∕32 in	1/8 in	21CJ04	2	
Diamond					
Point	3∕32 in	1/4 in	1UH84	1	
Tungsten Ca			4111100		
Point	¹∕₃₂ in		1UH83	1	
No. of Pieces					

**Bit and Attachment Set** 

70

75

160

Dia. Thickness		Material			iax. Deed	No.	Qty.
Cutting \	Wheels		,,				
Mounted							
1½ in	1⁄32 in	Reinforced Fiberglass	EZ Lock	35,00	00 RPM	1PKX3	1
31/2 in	1/32 in	Diamond		20,00	00 RPM	38EY50	1
Unmount							
7∕8 in	1/32 in	Diamond	Standard	20,00	00 RPM	1UH72	1
15/16 in	1/32 in	Emery	Screw on	35,00	00 RPM	3W841	36
1¼ in	1/32 in	Reinforced Fiberglass	Screw on	30,00	00 RPM	44J150	20
	1/32 in	Diamond	EZ Lock	35,00	00 RPM	3DRN4	1
	1/16 in	Carbide	EZ Lock	35,00	00 RPM	3DRN6	1
1½ in	1/8 in	Aluminum Oxide	EZ Lock	35,00	00 RPM	38EY44	2
	1/8 in	Reinforced Fiberglass	EZ Lock	35,00	00 RPM	1PKX6	12
Flap Who	eel						
Mounted							
3∕16 in	3/16 in	Emery	_		00 RPM	1UH70	1
11/8 in	3⁄8 in	Emery	_		00 RPM	1UH69	1
1½ in	2 in	Emery	Screw on	35,00	00 RPM	41HR02	. 1
Drum Dia	ameter	Grit	Mandrel	Type	Item No.		Pkg. Qty.
Sanding	Band, Alur	ninum Oxide					
1/4 ii		120	Slide or		41HP9		6
1/2 ji	n	60	Slide or	ı Fit	1UH5		6
72 II		120	Slide or	ı Fit	1UH6	5	6
Sanding	Drum, Aluı	ninum Oxide					
1/2 ii	n	60	_		1UH5	8	1
1 ½	in	50,-80,- 120180	Round S	hank	29UH9	19	1

		6	X194		1PK	X6	THE REAL PROPERTY.	MANAGE.			10	JH62					
M	ΕĽ	•	X134					ng Band H59				Brush Diameter Bru	sh Type B	ristle Type	Max. Speed	Item No.	Pkg. Qty.
	Too	ı n		A44.	lb			H59				Wire Brushes		M	-11		
ıry	100	I R	ાઇ હ	Atta	achm	ients						Abrasive Impre	gnated Ki Vheel	Straight	15.000 RPM	5EEV8	- 1
												Brass. Mounte		Juaiyiii	13,000 111 101	JLLVO	
			Item	Pkg.	Wheel	Wheel	Abrasive	Mandrel	Max.	Item	Pkg.		traight	Straight	15.000 RPM	45AF64	2
е	Head Wi	dth	No.	Qty.	Dia.	Thickness	Material	Туре	Speed	No.	Qty.	½ in	Cup	Crimped	15,000 RPM	45AF57	
Point					Cutting \							Carbon Steel, I			,		
m Oxid			NUOFO.	1	Mounted		Dainfarand						traight	Straight	15,000 RPM	45AF65	2
er -	3/8 in 5/8 in		3W850 1UH81	+	1½ in	1/32 in	Reinforced Fiberalass	EZ Lock	35,000 RPM	1PKX3	1		Cup	Straight	15,000 RPM	45AF67	2
Disk	1 in		1HR09	+	3½ in	1/32 in	Diamond		20,000 RPM	38FY50	1		Vheel	Straight	15,000 RPM	45AF58	2
	3/8 in		3W849	1	Unmount		Diamona		20,000 111 101	002100		Nylon, Mounte		Ctroight	15 000 DDM	AEAFEC	0
ed –	5/8 in		1HR12	<del>-i</del>	7/8 in	1/32 in	Diamond	Standard	20,000 RPM	1UH72	1		traight Vheel	Straight Straight	15,000 RPM 15,000 RPM	45AF56 45AF61	2
Carbide					15/16 in	1/32 in	Emery		35,000 RPM		36		Vheel	Straight	20.000 RPM	45AF63	2
Disk	13/ <sub>16</sub> in	- ;	3CY76	1	11/4 in	1/32 in	Reinforced	Screw on	30,000 RPM	44 1150	20	Stainless Steel			20,000 111 101	70A1 00	
ed	1/2 in	4	1HR03	1	1 74 111		Fiberglass						traight	Straight	15.000 RPM	45AF62	2
He	ead	Head	Item	Pkg.		1/32 in	Diamond		35,000 RPM		1		Vheel	Straight	15,000 RPM	45AF60	2
	idth L	ength	No.	Qty.		1/16 in	Carbide		35,000 RPM		1			Head		Item	Pka.
Bit					1½ in	⅓ in	Aluminum Oxide	EZ Lock	35,000 RPM	38EY44	2	Material	Shape	Diameter	r Mandrel Type	e No.	Qtý.
ed Ste		97.	040107				Reinforced					Abrasive Buff					
		3⁄8 in	21CJ07	2		⅓ in	Fiberglass	EZ Lock	35,000 RPM	1PKX6	12	Unmounted					
		1/4 in 3/8 in	21CJ09 21CJ05	2	Flap Whe	eel	r iborgiaco					Abrasive	Disc	15/16 in	EZ Lock	1PKY1	2
		⅓8 IN 3⁄8 in	3W845	1	Mounted							Coated Steel	Disc	15/16 in	EZ Lock	1PKY2	2
		98 III 3∕16 in	21CJ08	2	3∕16 in	3∕16 in	Emery	_	35,000 RPM		1	Polishing Point	IS .				
		7/16 in	21CJ06	2	11/8 in	3/8 in	Emery		35,000 RPM		1	Unmounted Felt	Tapered	3/8 in	Threaded Poir	nt 111UG2	- 1
n Carbi		/ 10 111	110000		1½ in	2 in	Emery	Screw on	35,000 RPM			Polishing When		78 111	Tilleaueu Full	IL TUNUZ	
		⅓ in	41HR14	1					Item		Pkg.	Mounted	<b>,</b> 1				
5/1	6 in	1/8 in	1UH87	1	Drum Dia		Grit	Mandrel	Type No.		Qty.	Silicon Carbide	0.4:4	1/ :		AFAFFF	2
		9∕16 in	6X194	1			ninum Oxide		n Fit <b>41HP</b> 9	10	c	Impregnated Fel		½ in	_	45AF55	2
		½ in	41HR13	1	1/4 ir	П	120	Slide or			6	Unmounted					
5/1	6 in	½ in	1UH86	1	½ ir	n —	120	Slide or Slide or			6	Felt	Disc	½ in	Threaded Poir		6
1/	4 in	3∕4 in	1UH85	1	Candina	Drum Alun	ninum Oxide		II FIL IUNU	J	U	1 610	Disc	1 in	EZ Lock	1PKX9	1
	* 111	74 111	101100		1/2 it		60		1UH5	8	1		Overal		hank Iter		kg.
ig Bit eel							50,-80,-					Mandrel Type	Length	Dia	meter No	. 0	ty.
	ı2 in	1/16 in	21CJ13	2	1 ½	III	120,-180	Round S	Shank <b>29UH</b>	99	1	Chuck	4.1/ :	4	/ i #1111	co	
		1/8 in	21CJ04	2								Keyless Mandrel	1 ½ in	- 7	% in 1UH	DØ	1
93 1	111	/0 111	210004									EZ Lock	3 in	1/	% in 1PK	YS	1
	ı2 in	1/4 in	1UH84	1								Cutting Wheel	2 3/4 in		8 in 3W8		1
n Carbi												EZ Drum	2 ½ in		6 in 34E3		i
1/3	ı2 in	_	1UH83	1								Threaded Point	1 ½ in		6 in 1UH		1
														Shank	Max.	Item	Pkg.
							Include	S						Diameter	Speed	No.	Qty.
Attach	ment Set																
	447	:- O- '	.: 0	- \\//'			Bits-and-1-S			. Diest'	0+ 0# 14	(hl (A) d d (C		⅓ in	35,000 RPM	1UH73	1
	11/2	ın-Uari Motal (	Diae-Cutting	g-wneel,-	· 1 - 1/2 IN-DIA	amona-Cutt	ing-wneel,-L	OCK-Mand	rei,-(2)-1-1/2	Crit (20)	-UUT-UTT-W	/heel,-(4)-1-1/2					
	IN-I	vietai-U	วนเ-UII-WN	661,- 1-1/4	nding-Rand	anding-ivlar -/6)-1-1/4	iuiel,-(b)-1-1 in-Sandina F	/ 14 III-San	iuiiig-DISC-60-	urit,-(20)	)- 1/2 IN-60 k-Thin-Cut	-Grit-Sanding- -Wheel,-Lock-		1/8 in	35,000 RPM	39FV52	1
	Dal	ıu,=(20 Fini	y-1/2 111-12 china=Δhra	o-um-ba		,-(0)=1=1/4 t) =l ock=Ein	iii-Sanuniy-L iehina-Ahrac	1136-240-G 11/0-Ruff-/9	320-Grit),-(3)-	II-EZ-LUU Lock-Poli	ching_Clot	-vviiddi,=LUUK= h_Whool					
(-20)	)-HD-And-	-Fihera	lass-Cut-O	ff-Wheels	-(6)-1/2-an	d-(4)-1 in-F	elt-Polishing	-Wheel-/4	1)-1/2-Sanding	-Band-(1	2)-Coarse-	Sanding-Discs-(12)	\-Fine-				
Sar	ndina-Disc	s-1-Ea	-Polishina	-Compou	nd3/4-Cark	bon-Steel-B	rush1-1/4-	Cut-Off-Wh	heel-3/8-And-	5/8-Alumi	num-Oxide	Stone,-25/32-Silic	one-	⅓ in	35.000 RPM	3DRN3	1
(	Carbide-St	tone,-6	0-Grit-San	ding-Drur	n-&-Mandre	el,-1/2-Fine-	Sanding-Bar	nd,-HSS-Ci	utter,-1/8-Drill	-Bit,-402-	Mandrel-A	ind-(2)-401-Mandre	els		-,		

35,000 RPM 5EEV1

Carbide-Stone,-60-Grit-Sanding-Drum-&-Mandrel,-1/2-Fine-Sanding-Band,-HSS-Cutter,-1/8-Drill-Bit,-402-Mandrel-And-(2)-401-Mandrels
Everything-You-Need-To-Cut,-Grind,-Sand,-Polish,-Sharpen-And-Clean