







## metabo

Item

## **Corded Pistol-Grip Drills**

Tool

Cord

- 120V AC
- Variable speed reversing trigger switch

These corded drills provide ergonomic handling for a range of positions on vertical and horizontal surfaces. Pistol-grip positioning keeps the tool steady and controls pressure during drilling and driving.

Free Speed	Current	Wt.	Length	Train	Includes	Brand	No.
3/8 in Keyless							
1.250 RPM	6.7 A	3.3 lb	8 ft	Double	_	DeWalt	4LF69
2,500 RPM	6.5 A	3.2 lb	6 ft	Triple	_	Porter Cable	34G828
2.500 RPM	8.0 A	4.1 lb	8 ft	Single	Belt Hook, Heavy-Duty Kit Bag	DeWalt	2EKR7
2.500 RPM	8.0 A	4.1 lb	8 ft	Single	Heavy-Duty Kit Box	DeWalt	2EKR8
2,500 RPM	8.0 A	4.1 lb	8 ft	Single	Belt Hook, Soft Grip Handle	DeWalt	2VDJ8
2.600 RPM	6.3 A	3.4 lb	8 ft	Single		Bosch	44K694
2.800 RPM	8.0 A	4.2 lb	8 ft	Double	_	Milwaukee	4VYZ3
1/2 in Keyless	Chuck						
600 RPM	7.8 A	4.4 lb	8 ft	Triple	Soft Grip Side Handle	DeWalt	4LF77
1,250 RPM	10.0 A	5.2 lb	8 ft	Double	360° Side Handle with Soft Grip	DeWalt	3GRF2
5/8 in Keyless	Chuck				·		
1,600 RPM	13.0 A	7.3 lb	13 ft	Double	Case, Centering Pin, Quick Clamping Chuck, Side Handle	Slugger By Fein	54FH36
1/4 in Keyed C	huck						
4,000 RPM	6.7 A	3.2 lb	8 ft	Single	Chuck Key	DeWalt	4LF67
3/8 in Keyed C							
1,200 RPM	7.0 A	4.2 lb	8 ft	Double	(1) Chuck Key With Holder	Milwaukee	6KW92
1,250 RPM	7.0 A	3.6 lb	8 ft	Double	Chuck Key	DeWalt	4LF70
2,800 RPM	7.0 A	3.6 lb	8 ft	Single	Chuck Key	DeWalt	53DR71
1/2 in Keyed C	huck						
600 RPM	7.8 A	4.4 lb	8 ft	Triple	Side Handle	DeWalt	4LF76
850 RPM	8.0 A	5.4 lb	8 ft	Double	(1) Chuck Key With Holder, (1) Side Handle	Milwaukee	6KW95
850 RPM	8.0 A	5.6 lb	8 ft	Double	(1) Side Handle	Milwaukee	6MR87
950 RPM	5.5 A	4.8 lb	8 ft	Double	Side Handle	Milwaukee	4Z371
1,000 RPM	8.5 A	4.2 lb	8 ft	Double	Side Handle	DeWalt	4LF73
1,200 RPM	10.0 A	4.9 lb	8 ft	Double	Holder	DeWalt	5YAW9
1,250 RPM	10.0 A	4.9 lb	8 ft	Double	360° Side Handle with Soft Grip	DeWalt	3GRF1
	6.7 A	6.7 lb	9 ft	Double	Side Handle	Metabo	36H096
850 RPM	8.0 A	5.4 lb	8 ft	Double	(1) Chuck Key With Holder, (1) Side Handle	Milwaukee	3DU39



**Keyless Chuck** ½" Keyless Chuck 34G828 3GRF2







## **Corded Right-Angle Drills**

- Reversing
- Keyed chuck
- Variable speed
- Continuous speed
- 3/8" drill capacity in steel
- 120V AC
- Paddle switch

Free Speed 1,300 RPM 2,400 RPM	3.5 A 4.0 A	Type Lever Paddle	Wt. 3.9 lb 3.5 lb	Brand Milwaukee Makita	No 1XH	Н9			
Item		ize	Max. Speed	Brand	Item No.	Pkg. Qty.			
Accessories Surface Prep Wheel, For Slow Speed Right Angle Drills									
3M(TM) SR Cutter No.3	¾ in D	ia x 1 in	1,500 RPM	3M	787C25	50			
3M(TM) SR Cutter No.8	13/16 in [	Dia x 1 in	1,500 RPM	3M	787C26	50			



- 1/2" chuck
- 2 speed settings
- ½" drilling capacity in steel
- 120V AC

Milwaukee


These two-handled, high-torque drills drive wide drill bits and hole-saw attachments to make large holes for running duct, pipe, and wiring through framing and flooring. Users hold them at waist level and lean into them to increase drilling force. The chuck

is oriented 90° to the tool body, so they have a slim profile for accessing corners or narrow spaces.

Current	Free Speed	Drilling Capacity in Wood	Switch Type	Reversible	Brand	Item No.
Keyless						
7.0 A	750 RPM	4 % in	Trigger	Yes	Milwaukee	6Z338
Keyed						
7.0 A	900 RPM	2 %16 in	Trigger	Yes	Milwaukee	2Z728
11.0 A	1,300 RPM	1 ½ in	Trigger	Yes	DeWalt	36TN85
13 A	1,750 RPM	1 ½ in	Paddle	No	Milwaukee	3TY44
IJ A	1,7 30 111 101	1 72 111	i auuit	INU	IVIIIWaukee	31144

## **Corded Spade-Grip Drills**





Chuck Size	Drill Chuck Type	Free Speed	Current	Variable Speed	Drilling Capacity in Steel	Drilling Capacity in Wood	Gear Train	Brand	Item No.
Straight Handle									
½ in -	Keyed	1,200 RPM	7.5 A	Yes	3/4 in	1 ½ in	Triple	Milwaukee	6Z041
	Keyed	1,200 RPM	7.5 A	Yes	½ in	4 % in	Triple	Milwaukee	2Z965
Spade Handle									
	Keyed	450 RPM	7.0 A	Yes	½ in	1 ½ in	Triple	Milwaukee	2Z727
1/2 in	Keyed	550 RPM	9.0 A	Yes	_	_	Triple	DeWalt	4YY99
	Keyed	650 RPM	7.0 A	Yes	½ in	1 ½ in	Double	Milwaukee	6Z042
3/4 in	Keyed	350 RPM	10.0 A	No	3/4 in	1 ½ in	Triple	Milwaukee	6Z330
1 1/4 in	Keyless	250 RPM	10.0 A	No	3/4 in	1 ½ in	Triple	Milwaukee	1Y033
Angle Drive 33 Degrees Kit									
Includes 33° 30" Angle Extension Tube, Side Handle, Drive Shaft with Hex Sockets on Both Ends, and 2 Clamping Collars; For Use with Nos. 2Z726 and 6Z324								Milwaukee	4AC31

A bit-holding chuck oriented 90°

profile for accessing corners and

to the tool body creates a slim

reaching into tight spaces.

