**Screwdriver Bit Sets** 

CONTINUED





















o. Hex of Shank ss. Size Hand Screwdr	iver Bit Sets (Cont.)	Brand	Item No.
	it Set (Cont.)  Square Drive #1 x #2, Torx T15 x Hex 1/64 in, Torx #6 x #8, Torx #10 x #15, Torx #20 x #25, Torx #27 x #30, Eyeglasses Screwdriver, Pozi #2 x	Leatherman	191 Y98
	#1, Hex 1.5mm x 2.0mm, Hex 2.5mm x 3.0mm, Hex 4.0mm x 5.0mm, Hex 6mm and ½ in, Hex ½ in x ¾ in, Hex ½ in x in Nutsetter, ¼ in Adaptor, Compact Magnetic Drive, 6 in ½ Spade, 6 in ¾ in Spade, 6 in ¼ Spade, 8 Socket, ½ Socket, ½ Socket, ½ in, (2) ½ in, (2) ½ in, (2) ½ in, (2) ½ in, ¾ in, Small Stoarge, (2) 1	DeWalt	55KH40
0 1/4 in Dr 1/4	# 1, HeX 1.5min X 2.0min, HeX 2.5min X 3.0min, HeX 4.0min X 5.0min, HeX 6min and w in, HeX 92: In X 94: In X 94	DeWalt	55KH4 <sup>-</sup>
sert Bit Set	Phillips, Slotted, Square, Torx	IRWIN	55KG8
1/4 in 1/4 in 1/4 in	% in Bit, %6 in Bit, ½2 in Bit, ½2 in Bit, ½4 in Bit, ¼4 in Bit, ‰4 in Bit	IRWIN	55KH9 787P7
1/4 in 1/4 in	Tool Case	IRWIN IRWIN	55KJ1 55KJ0
1/4 in 1/4 in	T15/T20, T20/T25, T25/T30, T25/T25 2% in Bits Plus Magnetic Screw-Hold Attachment (3) #2PH/#2PH, #2SO/#2SO 2% in Bits Plus Magnetic Screw-Hold Attachment	IRWIN IRWIN	30TH7 30TH7
rewdriver Bi	t Set  Phillips #2 x 1 in (8), Square #1 x 1 in, Square #2 x 1 in (2), Square #3 x 1 in, Phillips #2 x 2 in (2), Phillips	Vega Ind.,	45AW5
x Bit Set	#3 x 2 in, Square #2 x 2 in, Mag Bit Holder, ¼ in Mag Nutsetter, ¾ in Mag Nutsetter	Inc.	
1/4 in wer Screwd	T15, T20, T25	DeWalt	787P7
III End Hex B 1/4 in 1/4 in	3/s2, 764, 1/s, 9/s4, 5/s2, 3/16, 1/s2, 1/4 in Bits, Storage Rail Holder	Wiha Tools Wiha Tools	5HYL2
Set	Socket Adaptor, Bit Holder, Bit Ratchet, Rapid Adaptor Bit Holder, Phillips (2) #1, (3) #2, #3, Square #1, (3) #2, #3, Torx T10, T15, T20, T25, T30, T40, Security Torx T10s, T15s, T20s, T25s, T30s, Slotted 5.5mm, Hex Plus %2, 1/s, 1/s2, 1/s, 1/s, 1/s, 1/s, 1/s, 1/s, 1/s, 1/s	Milwaukee	
II and Drive			
(1) 9 Bit, 1/4 in 5 1/4 in Bit 1 Bit T	The Hoter of Drive Connector; #6, #8, and #10 Drill Bits with Countersinks; (2) #6, #8, and #10 Replacement Bits; (3) Screwdriver Bit Tips, Heavy-Duty Container is in Drive Holder; Drill Drive Container is lack Oxide Drill Bit, (1) 10 in Black Oxide Drill Bit, (1) 10 in Thunderbolt Black Ox	Milwaukee	36FX6
½ in	(2) Magnetic Drive Guides, (6) #2 Phillips, (2) #8 and #10 Slotted, (3) #2 Square Recess Bits, Case	DeWalt	2KLK3
x Bit Screw 1/4 in	driver Set  1/4 in Magnetic Quick Disconnect for Impact/Power Bits, Phillips #0, #1, #2, #4-5, Slotted #8-10, Star T15, Square Recess R1, R2 , Sockets 9/6, 1/4, 9/42, 9/6, 1/1/32, 9/6, 9/6, 9/6, 9/6, 9/6, 9/6, 9/6, 9/6	Eazypower	5UXU
x Wrench S	necess h1, h2, 30ckets 916, 74, 922, 916, 11/32, 98, 916, 1932 all of 2 in, riexhble Extension 1072 in  cket Set  11 in Length % in Hex Flex A Bit Plus Extension, Phillips #1, #2, Slotted #6-8, #8-10, Tee Star T15, T20, Square Recess	-	
: ¾ in • <b>x/Torx Bit S</b> o : ¼ in	R1, R2, Sockets ¾6, ¼, ¾6, ¾, ¾6, ½, ¾6, ¾ in, ¼ in Hex Female Socket Adapter, Socket Adapter	Eazypower Klein Tools	
sert Bit Set	Phillips #1, (3) #2, #3, Hex 2½, 3, 4, 5, 5½ in, Pozi Drive (2) PZ1, (3) PZ2, PZ3, Torx (2) T10, (2) T15,	Wera	3EJY!
gnetic Driv	(3) T20, (3) T25, (2) T30, T40, ¼ in Hex Quick Release Rapidaptor Bit Holder <b>Stude Set</b> #1 (6) #2 and #3 Square Recess #6 (2) #8 and #10 Slotted Bit Tins: #1 (10) #2 and #3 Phillins Compact Mannetic Drive Guide Double-		
¼ in pid Load Ho	#1, (6) #2, and #3 Square Recess, #6, (2) #8, and #10 Slotted, Bit Tips: #1, (10) #2, and #3 Phillips, Compact Magnetic Drive Guide, Double- End Power Bits: P#1/S#6, (3) P#2/S#8, (3) P#2/P#2, and P#3/S#10, Magnetic Nut Setters: ¼ in and %s in, Power Bits: Ider and Bit Set	DeWalt	4WM4
1⁄4 in	(2) 1 in Phillips Bits: (2) PH2, 1 in Square Bits: SQ2, (3) 2 in Phillips Bits: PH1. (2) PH2, 1 in Torx Bits: T25, 2 in Torx Bit: T25, 2 in Slotted Bits: SL8, 3½ in Slotted Bit: SL8, 2-2 in Square Bits: SQ1, SQ2, (3) Titanium Hex Shank Drill Bits: ½ in, ½ in, ¼ in, (3	DeWalt	25CC5
rewdriver Bi 1/4 in —	7 Piece - 6-in-1 Flip and Switch Driver System 2 in PH#2, 2 in SO#2, (2) 1 in SL#8, (3) 1 in PH#2, 1 in PH#3, SO#1, SO#2, T25, ¼, ¾6, ¾ Nutsetter, 3 in Magnetic Holder Compact Screw Guide, (19) 1 in Insert Bits: P1, (7) P2, P3, SO1, (3) SO2, SO3, T15, T20, T25, SL6-8, SL8-10 2 in Magnetic Bit Tip Holder: Bit Tips: #1, (6)#2, and #3 Phillips; #6, 8, and #10 Slotted; #1 and (3)#2 Square Recess; Magnetic Nut Setters: ¼ in and ¾s in ; Power Bits: 2 in #2; 2 in #2 Square Recess Magnetic Drive Guide; Bit Tips: #1, (10)#2, and #3 Phillips; #6, (2)#8, and #10 Slotted; #1, (6)#2, and #3 Square Recess; Magnetic Nut Setters: ¼ in and ¾s in ; Power Bits: 2 in #2 Phillips; 2 in #2 Square Recess (4) Security Hex - Metric 2mm, 2.5mm, 3mm, 4mm, (4) Spanner Bits 4, 6, 8, 10, (4) Tri-W in g 1, 2, 3, 4, (6) Security Hex	DeWalt DeWalt	5TE3
1/4 in	Compact Screw Guide, (19) 1 in Insert Bits: P1, (7) P2, P3, S01, (3) S02, S03, T15, T20, T25, S16-8, S18-10 2 in Magnetic Bit Tip Holder: Bit Tips: #1, (6)#2, and #3 Phillips: #6, #8, and #10 Slotted: #1 and (3)#2 Square	Milwaukee	45L15
½ in 1¼ in	Recess; Magnetic Nut Setters: ¼ in and ¾6 in ; Power Bits: 2 in #2; 2 in #2 Square Recess  Magnetic Drive Guide; Bit Tips: #1, (10)#2, and #3 Phillips; #6, (2)#8, and #10 Slotted; #1, (6)#2, and #3 Square	DeWalt	4WM4
1/4 in 1/4 in	Recess; Magnetic Nut Setters: ½ in and ¾s in ; Power Bits: 2 in #2 Phillips; 2 in #2 Square Recess  (4) Security Hex - Metric 2mm, 2.5mm, 3mm, 4mm, (4) Spanner Bits 4, 6, 8, 10, (4) Tri-W in g 1, 2, 3, 4, (6) Security Hex	DeWalt DeWalt	4WM4
	Bits 1/6 in, 1/2 in, 1/6 in, 1/6 in, 1/6 in, 1/8 in, 1/8 in, 1/9 Security Star Bits 18, 110, 115, 120, 125, 127, 130, 135, 140  (20) 1 in Phillips Bits: PH1, (18) PH2, PH3, (8) 1 in Square Bits: PH1, (6) PH2, PH3, (4) 1 in Slotted Bits: SL6, (2) SL8, SL10,	DeWalt	25CC4
′ 1⁄4 in ( ! 1⁄4 in i	(2) Nut Drivers: ¼ in, ¾6 in,	Milwaukee	
1/4 in	1 in 115, (1) 107X Bit 1 in 120, (1) 107X Bit 1 in 125, (1) 107X Bit 1 in 130, (1) 107X Bit 2 in 120, (1) 107X Bit 2 in 125, (1) Magnetic Drive Guide (16) 1 in PH Bits: PH1, (14) PH2, PH3, (4) 1 in SL Bits: SL6, (2) SL8, SL10, 98) 1 in SQ Bits: SQ1, (6)SQ2, SQ3, Magnetic Drive Guide, 3½ in Phillips Rits: PH2, 3½ in Slotted Rits: SL2, (8) 2 in Phillips Finded Rits: (3) PH2/PH2, PH1/SL6, (3) PH2/SL8, PH3/SL10, (2)	DeWalt	25CC4
1/4 in	Slotted #5-6	Eazypower	5UXW
anner Powe ¼ in	Case, Spanner #4, #6,#8, #10	Eazypower	5UXU
ubby Ball He	Stubby Cushion Grip Driver, Hex 1/8, 1/84, 1/82, 1/4 in	Wiha Tools	5HYL4
ubby Combir 1/4 in 1/4 in	ation Bit Set  Stubby Cushion Grip Driver, Slotted 4.5, 6.5mm, Phillips #1, #2, #1, Pozi #2  Stubby Cushion Grip Driver, Slotted 4.5, 6.0mm, Phillips #1, #2, Square #1, #2	Wiha Tools Wiha Tools	
ubby Torx Bi 1/4 in	Stubby Cushion Grip Driver, Security Torx T8S, T10S, T15S, T20S, T25S, T30S	Wiha Tools	5HYL7
1/4 in orx Bit Set	Stubby Cushion Grip Driver, Torx T8, T10, T15, T20, T25, T30	Wiha Tools	5HYL6
3% in iple-Y Insert		Proto	3R754
. ½ IN	Triple-Y #6 Triple-Y #5	Eazypower Eazypower	5UXZ1
2 1/4 IN		Eazypower	DUXIO
2 ½ in 2 ¼ in 2 ¼ in 2 ¼ in	Triple-Y #2 Triple-Y #3 Triple-Y #1	Eazypower Eazypower	5UXYS