



## Impact Screwdriver Bit Sets

Provide a range of drilling and driving capabilities, and are precision machined for an exact fit allowing quick changeouts.



**Impact Driver Bit Set 60HU17**



**Pivot Holder Bit Set 10Z808**



**Power Bit Set 30TH76**

No. of Pieces	Hex Shank Size	Fastening Tool Material	Includes	Brand	Item No.
<b>Impact Driver Bit Set</b>					
34	1/4 in	Chrome Vanadium Steel	Handle, Bit Holder, Metal Storage Box, Bits, Pozidriv (1) #1, (1) #2, (1) #3, Square (1) #1, (2) #2, (1) #3, Phillips (2) #1, (2) #2, (2) #3, Hex Metrix (1) 3.0mm, (1) 4.0mm, (1) 5.0mm, (1) 6.0mm, Hex Inch (1) 1/8 in, (1) 3/16 in, (1) 1/4 in, (1) 5/16 in, (1) 3/8 in, (1) 1/2 in, Torx(R) (1) T10, (1) T15, (2) T20, (2) T25, (2) T30, (1) T40 3/8 in, (1) 1/2 in, (1) 5/8 in, (1) 3/4 in, (1) 7/8 in, (1) 1 in, Torx(R) Bit 1 in T15, (1) TORX(R) Bit 1 in T27, (1) TORX(R) Bit 1 in T30, (1) Slotted Bit 1 in SL 1/4 in, (1) Slotted Bit 1 in SL 3/8 in, (1) Slotted Bit 1 in SL 1/2 in, (1) Slotted Bit 1 in SL 3/4 in, (1) Slotted Bit 1 in SL 5/8 in, (1) Slotted Bit 1 in SL 3/4 in, (1) Slotted Bit 1 in SL 1/2 in, (1) Slotted Bit 1 in SL 3/8 in, (1) Slotted Bit 1 in SL 1/4 in	Wiha Tools	440A44
100	1/4 in	Alloy Steel	1/4" Nut Driver, 3/16" Nut Driver, Hex 1/4", Hex 1/8", Hex 3/16", Hex 3/32", Hex 1/4", Hex 5/64", PH1, PH2, PH3, PR2, SL #12, SL #4, SL #6, SL #10, SL #8, SQ1, SQ2, SQ3, T10, T15, T20, T25, T27, T30	Milwaukee	60HU17
<b>Magnetic Drive Guide Set</b>					
7	1/4 in	Steel	3 in Magnetic Drive Guide, (2) PH2 Insert Bits, SQ2 Insert Bit, T20 Insert Bit, (2) T25 Insert Bits	Milwaukee	419J71
<b>Pivot Holder and Bit Set</b>					
11	1/4 in	Steel	(1) Phillips Bit 1 in P1, (1) Phillips Bit 1 in P2, (1) Phillips Bit 1 in P3, (1) Slotted Bit 1 in SL 1/4 in, (1) Slotted Bit 1 in SL 1/8 in, (1) Slotted Bit 1 in SL 3/16 in, (1) Slotted Bit 1 in SL 1/8 in, (1) Square Bit 1 in SQ, (1) Square Bit 1 in SQ2, (1) Bit 1 in T25, (1) Shockwave 30 Degree Knuckle Pivoting Bit Holder	Milwaukee	10Z808
<b>Power Bit Set</b>					
7	1/4 in	Steel	(3) #2PH/#2PH, #2SQ/#2SQ 2 3/8 in Bits Plus Magnetic Screw-Hold Attachment	IRWIN	30TH76
<b>Screwdriver Bit Set</b>					
22	1 in	High Speed Steel	(5) TORX(R) Bit 1 in T25, (3) Phillips Bit 1 in P2, (3) TORX(R) Bit 1 in T20, (3) Square Bit 1 in SQ2, (2) Phillips Bit 1 in P3, (1) SHOCKWAVE(R) Compact Magnetic Bit Holder, (1) Phillips Bit 1 in P1, (1) Square Bit 1 in SQ1, (1) Square Bit 1 in SQ3, (1) TORX(R) Bit 1 in T10, (1) TORX(R) Bit 1 in T15, (1) TORX(R) Bit 1 in T27, (1) TORX(R) Bit 1 in T30, (1) Slotted Bit 1 in SL 1/4 in, (1) Slotted Bit 1 in SL 3/8 in, (1) Slotted Bit 1 in SL 1/2 in, (1) Slotted Bit 1 in SL 3/4 in, (1) Slotted Bit 1 in SL 1/4 in	Milwaukee	423P08
26	1/4 in	Steel	(1) Phillips Bit 1 in P1, (1) Phillips Bit 1 in P2, (3) Phillips Bit 1 in P3, (1) Square Bit 1 in SQ1, (2) Square Bit 1 in SQ2, (2) TORX(R) Bit 1 in T20, (2) TORX(R) Bit 1 in T25, (1) TORX(R) Bit 1 in T30, (1) 1/4 in Hex to 3/8 in Square Adapter, (1) 1/4 in Magnetic Nut Driver, (1) Phillips Bit 2 in P2, (1) Square Bit 2 in SQ2, (1) TORX(R) Bit 2 in T20, (1) TORX(R) Bit 2 in T25, (1) Slotted Bit 1 in Hex Bit, (1) Insert 1/4 in Hex Socket, (1) 3/8 in Drive 3/16 in Socket, (1) 3/8 in Magnetic Nut Driver, (1) 3/8 in Magnetic Nut Driver, (1) SHOCKWAVE(TM) Compact Magnetic Bit Holder	Milwaukee	19RK07
35	1/4 in	Steel	Impact Ready Socket Adapters 3/8 in, 1/2 in, 5/8 in, 3/4 in, 1 in, Impact Ready 1/4 in Hex Shank Adapter, Impact Ready Nutsetters 3/16 in, 1/8 in, 1/4 in, 3 in Impact Ready Screw Lock Holder, 2 in PH2 Impact Ready Bits, 1 in Square Impact Ready Bits: SQ1, (4) SQ2, SQ3, 1 in Phillips	DeWalt	20UH15
40	1/4 in	Steel	1/4 in Nutsetter, 3/8 in Nutsetter, Impact Ready Sleeve, 3 in Impact Ready Screw Lock Holder, 6-2 in PH2 Impact Ready Bit, 2 in SQ2 Impact Ready Bit, 2 in T25 Impact Ready Bit, 2 in SL8 Impact Ready Bit, (4) 1 in PH2 Bit, (2) 1 in SL8 Impact Ready Bit, 1 in	DeWalt	20UH16
50	1/4 in	Steel	(1) Compact Bit Holder, (1) 1/4 in Magnetic Nut Driver, (1) 3/16 in Magnetic Nut Driver, (1) 3/8 in Socket Adapter, (1) Insert PH1 Bit, (4) Insert PH2 Bits, (2) Insert Phillips Recessed Bits, (2) Insert PH3 Bits, (1) Insert SQ1 Bit, (4) Insert SQ2 Bits, (3) Insert SQ3 Bits, (1) Insert T15 Bit, (2) Insert T20 Bits, (5) Insert T25 Bits, (1) Insert T30 Bit, (1) Insert SL#6 Bit, (1) Insert SL#10 Bit, (1) Insert 3/8 in Hex Bit, (1) Insert 1/4 in Hex Bit, (2) 2 in PH2 Bits, (2) 2 in PH3 Bits, (2) 2 in SQ2 Bits, (1) 2 in SQ3 Bit, (1) 2 in T20 Bit, (1) 2 in T25 Bit, (1) 1/4 in Titanium Red Helix Bit, (1) 3/8 in Titanium Red Helix Bit, (2) 1/2 in Titanium Red Helix Bit, (1) 3/8 in Titanium Red Helix Bit, (1) 1/2 in Titanium Red Helix Bit	Milwaukee	48ZJ62
60	1/4 in	Steel	Compact Bit Holder, 6 in Bit Holder, Magnetic Nut Drivers 1/4 in, 3/8 in, Socket Adapter 3/8 in, Hex Drill Bits 1/8 in, 3/32 in, 1/8 in, 3/16 in, 1/4 in, 1/2 in, Double Ended Power Bits PH2/SQ2, PH2/T25, PH2/SL#10, T20/T25, Insert Driver Bits PH1, (6) PH2, PR2, (2) PH3, SQ1, (3) SQ2, SQ3, T10, T15, (2) T20, (3) T25, T30, SL#6, SL#10, Hex 3/8 in, Hex 1/4 in, 2 in Power Bits PH1, (4) PH2, (2) PH3, SQ1, (3) SQ2, SQ3, (2) T20, (2) T25, T30, SL#10	Milwaukee	415H78
65	1/4 in	Steel	Compact Magnetic Bit Holder, 1/4 in Magnetic Nut Driver, 3/8 in Magnetic Bit Holder, 1/4 in Socket Adapter, 1 in PH2, 1 in PH3, 1 in PR2, 1 in SQ1, 1 in SQ2, 1 in SQ3, 1 in T10, 1 in T15, 1 in T20, 1 in T25, 1 in T27, 1 in T30, 1 in T40, 1 in Slotted #8, 1 in Slotted #10, 1 in 3/8 in Hex, 1 in 1/4 in Hex, 1 in Torx Security T7, 1 in Torx Security T8, 1 in Torx Security T9, 1 in Torx Security T10, 1 in Torx Security T15, 1 in Torx Security T20, 1 in Torx Security T25, 1 in Torx Security T27, 1 in Torx Security T30, 1 in Torx Security T40, 1 in 3/8 in Hex Security, 1 in 1/2 in Hex Security, 1 in 1/4 in Hex Security, 1 in 1/8 in Hex Security, 1 in 3/16 in Hex Security, 1 in 1/4 in Hex Security, 1 in 3/8 in Hex Security, 1 in 1/2 in Hex Security, 1 in 3/4 in Hex Security, 1 in 1 in Hex Security, 1 in 1 1/4 in Hex Security, 1 in Spanner #6, 1 in Spanner #8, 1 in Spanner #10, 1 in Spanner #12, 1 in 1/8 in Clutch, 1 in 3/16 in Clutch, 1 in 1/4 in Clutch, 1 in PZ1, 1 in PZ2, 1 in PZ3, 1 in TRI-WING #1, 1 in TRI-WING #2, 1 in TRI-WING #3, 1 in TRI-WING #4, 1 in TRI-WING #5, 1 in TORQ-SET #4, 1 in TORQ-SET #6, 1 in TORQ-SET #8, 1 in TORQ-SET #10, 1 in Spline #4, 1 in Spline #5, 1 in Spline #6, 1 in Spline #8, 1 in Spline #10, 1 in Insert Bit HEADLOK Screw	Milwaukee	415H87
175	1/4 in	Steel	Phillips Ribbed, Slotted, Phillips, Pozidriv, Phillips, Hex, Torx(R), Spline, Roberts, Security Bits, Tri Wing, Clutch Bits, Quick Change Chuck, 1 and 2 in Drive Socket Adapter, 4 to 1 1/8 in Screw Guide Driver, Storage Case	Westward	1VXP2



## Impact Screwdriver Bits

Hex shank size: 1/4" For use with impact drivers and suitable for applications requiring a high level of torque.

Fastening Tool Tip Size	Overall Bit Length	Shank Style	Fastening Tool Material	Brand	Item No.	Pkg. Qty.
<b>Headlok(R)</b>						
Headlok	2 in	Hex	Alloy Steel	Milwaukee	60HU41	1
<b>Hex</b>						
T10, T15, T20, T25, T27, T30	1 in	Hex	Alloy Steel	Milwaukee	415H77	1
<b>Phillips</b>						
#1	1 in	Hex	S2 Steel	Milwaukee	10Z765	5
	2 in	Hex	S2 Steel	Milwaukee	10Z771	1
	6 in	Hex Power Drive	S2 Steel	DeWalt	20GY06	50
	1 in	Hex	S2 Steel	Eazypower	52JL90	10
	1 in	Hex	S2 Steel	Eazypower	36JF78	500
	1 in	Hex	S2 Steel	Milwaukee	5EAX1	2
	1 in	Hex	S2 Steel	Milwaukee	5EAX2	5
	1 in	Hex	Steel	IRWIN	55KJ11	20
	2 in	Hex	S2 Steel	Eazypower	36JF70	250
	2 in	Hex	S2 Steel	Milwaukee	5EAX6	1
	2 in	Hex	S2 Steel	Milwaukee	10Z772	15
	2 in	Hex	S2 Steel	Milwaukee	33GM81	25
	3 1/2 in	Hex	S2 Steel	IRWIN	783HT9	10
	3 1/2 in	Hex	S2 Steel	Milwaukee	5EAX9	1
	3 1/2 in	Hex	S2 Steel	Milwaukee	10Z780	5
	3 1/2 in	Hex	S2 Steel	Milwaukee	33GN01	25
	6 in	Hex	S2 Steel	Milwaukee	10Z781	1
	6 in	Hex	S2 Steel	Milwaukee	33GN11	10
	6 in	Hex Power Drive	S2 Steel	DeWalt	20GY07	50
	6 in	Hex Power Drive	S2 Steel	Westward	38RV95	1
	1 in	Hex	S2 Steel	Milwaukee	10Z766	5
	2 in	Hex	S2 Steel	Milwaukee	5EAX8	1
	2 in	Hex	S2 Steel	Milwaukee	33GM87	25
	3 1/2 in	Hex	S2 Steel	Milwaukee	10Z778	1



**Phillips Double Ended 55KG89**



**Slotted 787P76**



**Torx 5EAZO**

Fastening Tool Tip Size	Overall Bit Length	Shank Style	Fastening Tool Material	Brand	Item No.	Pkg. Qty.
PH2	2 in	Hex	S2 Steel	IRWIN	55EW81	10
	3 1/2 in	Hex	S2 Steel	IRWIN	55EW41	1
<b>Phillips Double-Ended</b>						
PH2	2 1/2 in	Hex	Steel	IRWIN	55KG89	3
	4 in	Hex	Steel	IRWIN	55KH24	2
<b>Slotted</b>						
6F-8R	1 in	Hex	S2 Steel	Milwaukee	19RK11	2
SL 10-12	2 in	Hex	S2 Steel	IRWIN	787P76	10
<b>Square Recess</b>						
#1	2 in	Hex	S2 Steel	Milwaukee	5EAY5	1
	1 in	Hex	S2 Steel	Milwaukee	5EAY3	10
	2 in	Hex	S2 Steel	Eazypower	36JF71	250
	2 in	Hex	S2 Steel	Milwaukee	5EAY7	5
	2 in	Hex	S2 Steel	Milwaukee	33GM82	25
	3 1/2 in	Hex	S2 Steel	Milwaukee	5EAY9	1
	6 in	Hex	S2 Steel	Milwaukee	33GN13	10
	6 in	Hex Power Drive	S2 Steel	Westward	38RV96	1
	2 in	Hex	S2 Steel	Milwaukee	33GM94	25
<b>Torx(R)</b>						
T15	2 in	Hex	S2 Steel	Milwaukee	5EAZO	1
	1 in	Hex	S2 Steel	IRWIN	33GM76	25
	6 in	Hex	Steel	IRWIN	55KH35	1
	2 in	Hex	S2 Steel	Milwaukee	33GM84	25
	3 1/2 in	Hex	Alloy Steel	Milwaukee	60HU31	1
T30	1 in	Hex	S2 Steel	IRWIN	34E573	25
T40	2 in	Hex	S2 Steel	Milwaukee	33GM97	25