



39RV99



Corded SDS Plus® Rotary Hammer Drills

Solid Bit Capacity	Core Bit Capacity	No Load RPM	Blows per Minute	Amps	Features	Tool Length	Tool Weight	Brand	Mr. Model	Item No.
Pistol Grip Rotary Hammer Drills										
3/4 in	1 1/2 in	0-1000	0-4,400 bpm	6.1 A	Dual Mode Selector, Integral Clutch Helps Minimize Torque Reaction	13 3/4 in	5.4 lb	Bosch	11250VSR	35KG01
1 in	2 1/2 in	0-1500	0-5,500 bpm	8.0 A	High Performance Motor, Integral Clutch, Pistol Grip Handle, Rotating Brush Ring	13 1/4 in	5.7 lb	DeWalt	D25133K	39RW17
D-Handle Rotary Hammer Drills										
1 1/2 in	2 1/2 in	0-1450	0-5,350 bpm	8.5 A	High Performance Motor, Integral Clutch, Rotating Brush Ring, Vibration Control	17 1/2 in	6.8 lb	DeWalt	D25263k	39RV99
1 in	2 1/2 in	0-1500	0-5,500 bpm	8.0 A	High Performance Motor, Integral Clutch, Rotating Brush Ring, Vibration Control	17 1/4 in	6.6 lb	DeWalt	D25262K	39RW23
1 in	2 1/2 in	0-1300	0-5,800 bpm	7.5 A	Aux Handle with Built-In Quick Release Depth Gauge, D-Handle	17 1/4 in	6.7 lb	Bosch	11255VSR	2LDB3
1 1/2 in	2 1/2 in	0-1300	0-5,100 bpm	8.5 A	Counter Balanced Vibration Control, Hammer Hook, Kickback Control, Multifunction Selector, Vario-Lock(TM)	17 3/4 in	6.9 lb	Bosch	GBH2-28L	54EF82
Corded Side Handle Drills										
1 1/2 in	—	0-820	0-4,700 bpm	9.0 A	Active Vibration Control, Anti-Rotational Technology, Grounded Plug, Three Modes of Operation, Variable Speed Trigger	14 3/4 in	9.2 lb	DeWalt	D25416K	30RV74
1 1/2 in	2 1/2 in	0-1000	0-5,200 bpm	8.5 A	3.5 J, Constant Speed, Low Vibration Side Handle, Shocks Active Vibration Control(R) System	14 in	8.2 lb	DeWalt	D25333K	54JJ36
L-Shape Rotary Hammer Drills										
1/2 in	2 1/2 in	0-1000	0-5,200 bpm	—	3.5 J, Constant Speed, Durable Clear High Capacity Dust Box, Easily Adjusted Depth Stop, Low Vibration Side Handle, Quick Release, Shocks Active Vibration Control(R) System	14 in	8.2 lb	DeWalt	D25333KDH	54JJ37
1 1/2 in	2 1/2 in	0-1150	0-5,200 bpm	4.0 A	Compact, Lightweight, Mechanical Clutch	14 in	8.2 lb	DeWalt	D25333K-QS	437K02
1 1/2 in	3 1/2 in	0-900	0-4,000 bpm	8.0 A	Active Vibration Control, Rotary or Hammer Only and Rotation	13 3/4 in	7.9 lb	Bosch	RH328VC	5EEW2
1 1/4 in	3 1/2 in	0-760	0-3,600 bpm	8.5 A	Active Vibration Control	15 3/4 in	10.3 lb	Bosch	RH432VCQ	5EEW3
1 1/2 in	3 1/2 in	0-900	0-4,000 bpm	8.0 A	360° Auxiliary Handle, Integral Clutch, Multi-function Selector, Variable Speed 3 Finger Trigger, Active Vibration Control(TM)	12 1/2 in	7.7 lb	Bosch	RH328VC	49AX82

Accessories

Description	Mr. Model	Item No.
Bosch		
Chuck Adapter w/Key and SDS Plus Arbor Adapter	1618571014	1UL64
Dust Extraction Surface Attachment, For Use with 1 3/4 in Vacuum Hoses	HDC250	35GN78
Dust Extraction Surface Attachment, For Use with 1 3/4 in Vacuum Hoses	HDC200	35GN79
Dust Extraction Tool Attachment, For Use with 11255VSR, 11536-C, 11536VSR, Mr. No. 11253VSR, RH228VC, RH328VC, RH328VCQ, RHH181-01	HDC100	423N84
Right-Angle Attachment, 4 1/2" L	RHA-50	35KF98
SDS Right Angle Attachment, 5 1/2" L	1618580000	2LDB4
DeWalt		
Dust Extractor - Hole Cleaning; Includes 3/16 and 1/8" Hole Cleaning Tubes, 1 1/2 and 2" Hole Drilling Head Attachments, Dust Extractor Body	DWH050K	19M477
On-Tool Dust Extractor, Dust Box, Corded Adapter and Dust Nozzle	DWH304DH	54JJ53

SDS-Plus Concrete and Masonry Drill Bits

■ Shank size: 25/64" dia.

Carbide-Head bits have a cutting head of solid carbide construction for long life compared to standard bits that only have a carbide tip. All bits have an

SDS-Plus shank that prevents them from slipping in high-torque drilling applications and are compatible with SDS-Plus chucks that allow one-handed drill bit changeouts.

Drill Bit Size	Maximum Drilling Depth	Overall Length	Brand	Item No.	Pkg. Qty.
Carbide-Head SDS-Plus Concrete & Masonry Drill Bits					
2 Cutters					
5/32"	4"	6"	Bosch	48XX38	1
3/16"	4"	6 1/2"	Bosch	36H184	1
	4"	6"	Bosch	36H188	1
1/4"	6"	8 1/2"	Bosch	36H189	1
	8"	10"	Bosch	48XX44	1
	10"	12"	Bosch	36H190	1
	4"	6"	Bosch	36H193	1
3/8"	10"	12"	Bosch	36H194	1
	16"	18"	Bosch	36H195	1
	4"	6"	Bosch	36H210	1
1/2"	10"	12"	Bosch	36H212	1
	16"	18"	Bosch	36H214	1
	6"	8"	Bosch	36H215	1
5/8"	10"	12"	Bosch	36H181	1
	16"	18"	Bosch	36H182	1
4 Cutters					
1/4"	6"	8 1/2"	DeWalt	2PRF9	25
	8"	10"	DeWalt	2PRG7	1
3/8"	10"	12"	DeWalt	38A908	1
	16"	18"	DeWalt	2PRG8	1
	6"	8"	Bosch	48XX52	1
3/4"	8"	10"	Bosch	36H216	1
	16"	18"	Bosch	36H217	1

Drill Bit Size	Maximum Drilling Depth	Overall Length	Brand	Item No.	Pkg. Qty.
1/2"	10"	12"	Bosch	48XX53	1
	8"	10"	Bosch	36H220	1
1"	16"	18"	Bosch	36H221	1
	1 1/2"	16"	Bosch	36H223	1
SDS-Plus Concrete & Masonry Drill Bits					
2 Cutters					
3/16"	4"	6"	Bosch	19L458	1
	2"	4"	DeWalt	4TG17	1
	6"	6"	DeWalt	1ELF1	25
1/4"	6"	8 1/2"	DeWalt	4TG21	1
	10"	12"	DeWalt	4TG23	1
	16"	18"	Bosch	44H210	1
	4"	6"	DeWalt	4TG28	1
	6"	8"	Bosch	44H218	1
3/8"	8"	10"	DeWalt	4TG30	1
	10"	12"	Milwaukee	23V528	1
	22"	24"	DeWalt	4TG33	1
	37"	39"	Bosch	44H221	1
	4"	6"	DeWalt	4TG36	1
	6"	8"	Bosch	44H226	1
1/2"	10"	12"	Bosch	19L457	1
	16"	18"	DeWalt	4TG40	1
	22"	24"	DeWalt	4TG41	1
	37"	39"	Bosch	44H229	1



Drill Bit Size	Maximum Drilling Depth	Overall Length	Brand	Item No.	Pkg. Qty.
5/8"	6"	8"	DeWalt	4TG45	1
	6"	8"	Bosch	19L460	1
	10"	12"	Bosch	19L465	1
	16"	18"	DeWalt	4TG48	1
	37"	39"	Bosch	44H233	1
3/4"	6"	8"	DeWalt	4TG51	1
	6"	8"	Bosch	19L466	1
	16"	18"	DeWalt	4TG53	1
	22"	24"	DeWalt	4TG54	1
	37"	39"	Bosch	44H234	1
7/8"	6"	8"	DeWalt	4TG55	1
	10"	12"	DeWalt	4TG56	1
1"	8"	10"	DeWalt	4TG58	1
	16"	18"	Bosch	19L463	1
1 1/8"	16"	18"	DeWalt	4DV51	1
4 Cutters					
3/8"	10"	12"	Milwaukee	23V504	1
5/8"	8"	10"	DeWalt	2KLJ1	1
	10"	12"	Milwaukee	23V564	1
1 1/4"	16"	18"	Milwaukee	45KP07	1
Number of Drill Bits					
SDS-Plus Concrete & Masonry Drill Bit Sets					
2 Cutters					
5	3/16 in, 1/4 in, 3/8 in, 1/2 in	DeWalt	4TG60		
7	3/16 in, 1/4 in, 3/8 in, 1/2 in	Bosch	48XX67		
10	3/32 in, 1/16 in, 3/16 in	DeWalt	1GEF8		
4 Cutters					
5	3/16 in, 1/4 in, 3/8 in, 1/2 in	Bosch	44H334		
6	3/16 in, 1/4 in, 3/8 in, 1/2 in, 3/8 in	Milwaukee	45KP09		



SDS-Plus Rebar Cutting Drill Bits

■ Max. drill depth: 10"
■ Overall length: 12"

Used after standard concrete and masonry drill bits have drilled through the concrete surrounding the embedded rebar or wire mesh.

Drill Bit Size	Shank Diameter	Brand	Item No.
1 1/4"	3/8 in	Bosch	2PPZ9
1 1/8"	3/8 in	Bosch	2PPZ8
1/2"	3/8 in	Bosch	2PPZ2
	1/2 in	DeWalt	56DL81
	3/8 in	Bosch	2PPZ5
3/4"	3/4 in	DeWalt	56DL83
	3/8 in	Bosch	2PPZ1
5/8"	3/8 in	Bosch	2PPZ4
	5/8 in	DeWalt	56DL82
	3/8 in	Bosch	2PPZ6
7/8"	7/8 in	DeWalt	56DL84
	3/8 in	Bosch	2PPZ3
9/16"	3/8 in	Bosch	2PPZ7
1"	3/8 in	Bosch	2PPZ7
	1 in	DeWalt	56DL85

SDS-Plus Dust-Extraction Hollow Core Bits

Have a hollow shaft and dust-extraction holes at their tip that allow dust removal with a dust extractor during drilling.

Drill Bit Size	Maximum Drilling Depth	Overall Length	Shank Diameter	Brand	Item No.
2 Cutters					
1/2"	9 3/4"	14 1/2"	25/64"	DeWalt	54FH75
4 Cutters					
3/16"	4"	9"	45/64"	Bosch	55JD97
1/16"	7 1/2"	13"	45/64"	Bosch	55JE08
1/2"	7 1/2"	13"	25/64"	Bosch	48UR89
	7 1/2"	13"	45/64"	Bosch	55JE09
5/8"	10"	15"	25/64"	Bosch	48UR91
1 1/16"	12 1/2"	18"	25/64"	Bosch	48UR92
3/4"	12 1/2"	18"	25/64"	Bosch	48UR93

