

Bandfiles

Quickly grind and deburr ends of metal stock. Also blend, clean, polish, surface, and condition.



| Belt Size | Features | Amps @ 120V | Tool Length | Tool Weight | Includes | Brand | Mfr. Model | Item No. |
|-------------------------|---|-------------|-------------|-------------|---|-----------|------------|----------|
| ¼"-to-3/4" x 18"-to-24" | | 7 A | 19 | | | Dynabrade | 40610 | 11X738 |
| ½" x 18" | 1½ in x 18 in Arm Capacity, ⅝ to 11 in Spindle Thread | 5.5 A | 18 in | 6 lb | 3 Position Side Handle, Double Insulated, On/Off Paddle Switch | Milwaukee | 6101-6 | 3LJ30 |
| ½"-to-3/4" x 18" | Sanding Head Pivots 360° | 6 A | 19 in | — | 40610 Electric Dynaflex II with 11203 Contact Arm and 11202 and 11204 Contact Arms, (8) Abrasive Belts, Platen Pads | Dynabrade | 40611 | 25H831 |
| 1½" x 21" | 1½ in Dust Collection Port, Exposed Front Pulley | 5 A | 15 in | 4.6 lb | Multi Position Side Handle, 2 Ea 40, 60, 80, 100 And 120 Grit Abrasive Belts | Makita | 9031 | 1GUB9 |



Belt Sander

Feature gear and belt drive, and flush sand capability.



| Belt Size | No-Load SFPM* | Amps | Features | Tool Length | Tool Wt. | Mfr. Model | Item No. |
|--------------|---------------|-------|--|-------------|----------|------------|----------|
| 3 in x 18 in | 1050 | 6.0 A | Auto Track Belt Alignment, Built-in Vacuum Port, Clear View Dust Canister, Micro-filtration, Pressure Control Technology, Single Lever Belt Changes, Soft Grip | 12 ¼ in | 6.4 lb | 7510-01 | 19M482 |

*Surface feet per minute.



Drywall Sander



- 9" Pad
- 16.5" Power Cord

| No Load RPM | Type of Sandpaper | Speed Type | Tool Length | Mfr. Model | Item No. |
|-------------|-------------------|------------|-------------|------------|----------|
| 2400 | Hook-and-Loop | Variable | 63 in | DWE7800 | 60NP22 |

Random Orbit Sanders



| Pad Size | Orbits per Min. | Amps | Type of Sandpaper | Features | Tool Length | Tool Weight | Brand | Mfr. Model | Item No. |
|---------------------------------|-----------------|-------|-------------------|---|-------------|-------------|--------------|------------|----------|
| Corded Sanders | | | | | | | | | |
| 4 ½ in x 4 in | 12,000 | 2.0 A | ¼ Sheet | Microfilter Dust Canister with Screw-Off Cap, Precision-Machined Aluminum Sanding Plate | 10 in | 2.7 lb | Bosch | GSS20-40 | 48XY73 |
| 4 ¼ in x 4 ½ in | 12,000 | 2.4 A | ¼ Sheet | Improved Paper Clamp, Locking Dust Port System, Low Vibration, Rubber Overmold Texture | 10 ½ in | 2.7 lb | DeWalt | DWE6411K | 39RW05 |
| 4 ¼ in x 4 ½ in | 13,500 | 2.0 A | ¼ Sheet | Counter-Balanced Low-Vibration Design, Dual-Plane | 9 in | 2.3 lb | Porter Cable | 380 | 6XZU1 |
| 4 ¼ in x 4 ½ in | 14,000 | 2.3 A | ¼ Sheet | Improved Paper Clamp, Locking Dust Port System, Low Vibration, Rubber Overmold Texture | 10 ½ in | 2.8 lb | DeWalt | DWE6411 | 39RW26 |
| 5 in | 12,000 | 1.9 A | Hook-and-Loop | Controlled Finishing System Maintains Pad Speed, Dual-Plane Counter-Balanced Fan | 11 in | 3.0 lb | Porter Cable | 382 | 6XZU2 |
| 5 in | 12,000 | 3.0 A | Hook-and-Loop | Dust Sealed Switch, Improved Dust Collection, Low Vibration, Rubber Overmold | 11 in | 2.9 lb | DeWalt | DWE6421K | 39RW24 |
| 5 in | 12,000 | 3.0 A | Hook-and-Loop | Dust Sealed Switch, Improved Dust Collection, Low Vibration, Rubber Overmold, Variable Speed | 11 in | 2.9 lb | DeWalt | DWE6423K | 39RW15 |
| 5 in | 8000 to 12,000 | 3.0 A | Hook-and-Loop | Dust Sealed Switch, Improved Dust Collection, Low Vibration Design, Rubber Overmold, Variable Speed | 11 in | 2.9 lb | DeWalt | DWE6421K | 39RW24 |
| 5 in | 0 to 3700 | 6.0 A | Hook-and-Loop | Adjustable Dust Shroud, Variable Speed Trigger Dial | 9 ¼ in | 4.0 lb | DeWalt | DWE6401DS | 24T879 |
| 6 in | 4000 to 10,000 | 2.7 A | Hook-and-Loop | Lock On Button, Speed Control | 12 ½ in | 5.2 lb | Makita | B06030 | 14F072 |
| 6 in | 2500 to 6800 | 4.5 A | PSA | Compact Lightweight Design, Two Position Removable Side Handle | 11 ½ in | 7 lb | Porter Cable | 7346SP | 53DR79 |
| 7 in | 2500 to 4700 | 7.9 A | PSA | Lock On Button, Side Handle | 8 ¼ in | 4.6 lb | Makita | GV7000C | 6RA91 |
| Sander Accessories | | | | | | | | | |
| 5" Diameter Plastic Back Up Pad | | | | Grinder And Polishers With ⅝-11 Thread Mount, Sander | | | Makita | 743025-8 | 6RA94 |
| 7" Diameter Rubber Back Up Pad | | | | Grinder And Polishers With ⅝-11 Thread Mount, Sander | | | Makita | 192978-2 | 6RA95 |

Handheld Planers



| W (in.) | Depth of Cut (in.) | No Load RPM | Amps @ 120V | Tool Length (in) | Includes | Tool Weight (lb.) | Mfr. Model | Item No. |
|--|--------------------|-------------|-------------|------------------|---|-------------------|------------|----------|
| Handheld Planers | | | | | | | | |
| Bosch | | | | | | | | |
| 3 ¼ in | ¼ in | 16,500 RPM | 6.5 | 11 ½ in | Blade Wrench, Dual-Mount Guide Fence, Overshoe for Fence, Reversible Woodrazor(TM) Blade, Shavings Bag | 6.3 | PL1632 | 36WH96 |
| 3 ¼ in | ⅝ in | 16,500 RPM | 6.5 | 11 ½ in | Blade Wrench, Carrying Case, Shavings Bag, Straight Plastic Overshoe for Fence | 6.3 | PL2632K | 39RY32 |
| DeWalt | | | | | | | | |
| 3 ¼ in | ¼ in | 17,000 RPM | 5.5 | 11 ½ in | 2 High-Speed Steel Blades, Blade Depth Setting Gauge, Blade Resharpener Tool, Rabbing Fence, Socket Wrench | 6 | D26676 | 5NAK0 |
| 3 ¼ in | ¼ in | 17,000 RPM | 5.5 | 11 ½ in | 2 Reversible Carbide Blades, Blade Depth Setting Gauge, Dust Adaptor, Kit Box, Rabbing Fence, Socket Wrench | 6 | D26677K | 5NAK1 |
| 3 ¼ in | ⅝ in | 15,000 RPM | 7.0 | 12 ½ in | 2 Carbide Blades, Carry Case, Rabbing Fence | 6.6 | DW680K | 5VC66 |
| Makita | | | | | | | | |
| 3 ¼ in | ⅝ in | 17,000 RPM | 6.5 | 11 ¼ in | Blade Gauge Set, Blade Set, Case, Wrench | 5.7 | KP0800K | 14F142 |
| 3 ¼ in | ⅝ in | 16,000 RPM | 7.5 | 11 ¾ in | (1) 3/4 in Planer Blade, 2/pk.(1) Blade Gauge, (1) Socket Wrench, (1) Guide Rule | 7.3 | KP0810 | 14F143 |
| 4 ¾ in | ¼ in | 16,000 RPM | 7.5 | 14 in | Blade Gauge Set, Blade Set., Wrench | 9.3 | 1912B | 14U128 |
| 4 ¾ in | ⅜ in | 15,000 RPM | 9.6 | 13 ½ in | Blade Gauge Set, Blade Set., Wrench | 11.4 | 1002BA | 14H007 |
| 6 ¾ in | ¼ in | 15,000 RPM | 10.9 | 20 ¾ in | Blade Gauge Set, Blade Set., Wrench | 19.8 | 1806B | 14U127 |
| DeWalt Accessories | | | | | | | | |
| Carbide Replacement Blades, Pk. of 2, For Use with No. 5VC66 | | | | | | | DW6654 | 4TG61 |
| HSS Replacement Blades, Pk. of 2, For Use with No. 5VC66 | | | | | | | DW6655 | 1PX40 |