

HAND TOOLS

Torque Wrenches

Scan. Order. Done.
Details on page A1.



Kit 33NT63



Interchangeable Head Torque Wrenches

Attach to multiple torque wrench heads. **Preset** torque wrenches are set with a range of torque values that can be changed with a separate tool. **Electronic** torque wrenches can be programmed and have audible and visual cues to indicate when the desired torque setting is near.



Interchangeable Torque Wrench Heads

Multiple heads attach to a compatible torque wrench.

Size	Overall Length	Maximum Torque	Head Offset Angle	Brand	Item No.
12-Point Box End Torque Wrench Heads					
1 3/16 in Drive Size					
9/16 in	1 3/4 in	350 in-lb	0 °	Sturtevant Richmond	53KJ04
3/4 in	1 13/16 in	450 in-lb	0 °	Sturtevant Richmond	53KJ05
1/2 in	1 13/16 in	850 in-lb	0 °	Sturtevant Richmond	53KJ07
9/16 in	1 15/16 in	1,050 in-lb	0 °	Sturtevant Richmond	53KJ08
1 in Drive Size					
9/16 in	1 3/4 in	2,097 in-lb	0 °	Sturtevant Richmond	53KJ27
3/4 in	2 1/8 in	1,800 in-lb	0 °	Sturtevant Richmond	53KJ11
1 1/8 in Drive Size					
1 1/16 in	2 1/4 in	2,700 in-lb	0 °	Sturtevant Richmond	53KJ13
1 in	2 1/4 in	3,000 in-lb	0 °	Sturtevant Richmond	53KJ14
1 1/16 in	2 1/4 in	3,150 in-lb	0 °	Sturtevant Richmond	53KJ15
1 1/8 in	2 1/4 in	3,300 in-lb	0 °	Sturtevant Richmond	53KJ16
H4 Drive Size					
9/16 in	3 3/16 in	900 in-lb	7.5 °	Proto	4NAN8
H5 Drive Size					
9/16 in	3 13/16 in	1,340 in-lb	7.5 °	Proto	4NAT7
3/4 in	3 7/8 in	2,050 in-lb	7.5 °	Proto	4NAU4
3/4 in	3 15/16 in	2,400 in-lb	7.5 °	Proto	4NAV7
7/8 in	4 in	2,400 in-lb	7.5 °	Proto	4NAW2
14 mm	3 13/16 in	1,340 in-lb	7.5 °	Proto	4NAR5
H7 Drive Size					
9/16 in	5 5/8 in	1,340 in-lb	7.5 °	Proto	4NAX5
3/4 in	5 1/2 in	2,050 in-lb	7.5 °	Proto	4NAY3
3/4 in	5 1/2 in	2,630 in-lb	7.5 °	Proto	4NAZ6
7/8 in	5 5/8 in	3,600 in-lb	7.5 °	Proto	4RUD5
1 1/16 in	5 5/8 in	3,600 in-lb	7.5 °	Proto	4RUE2
1 in	5 11/16 in	3,600 in-lb	7.5 °	Proto	4RUE8
1 1/16 in	5 3/4 in	3,600 in-lb	7.5 °	Proto	4RUF5
1 1/8 in	5 3/4 in	3,600 in-lb	7.5 °	Proto	4RUF9
1 1/16 in	5 13/16 in	3,600 in-lb	7.5 °	Proto	4RUG2
1 1/4 in	5 7/8 in	3,600 in-lb	7.5 °	Proto	4RUG4
15 mm	5 3/8 in	1,770 in-lb	7.5 °	Proto	4NAW8
24 mm	5 5/8 in	3,600 in-lb	7.5 °	Proto	4NAZ8
30 mm	5 13/16 in	3,600 in-lb	7.5 °	Proto	4RUE4



Key-Adjustable 36WD66



Preset Torque Wrenches

Set to specific torque settings for tightening fasteners. **Electrical Connector** wrenches feature a small profile for use inside electrical boxes and other tight spaces. **Key-Adjustable** wrenches feature torque values that can be changed by the end user with a separate tool.

766 **GRAINGER**

Find even **MORE** on **Grainger.com**

1-800-GRAINGER (472-4643)

Drive Size	Torque Range	Overall Length	Calibration Certificate Included	Brand	Item No.
Interchangeable Head Torque Wrenches					
Foot-Pound					
3/8 in	20 ft-lb to 100 ft-lb	16 3/4 in	No	Insize	55VP40
1/2 in	30 ft-lb to 150 ft-lb	19 1/8 in	No	Insize	55VP41
1/2 in	50 ft-lb to 250 ft-lb	20 1/16 in	No	Insize	55VP44
3/4 in	100 ft-lb to 600 ft-lb	41 3/4 in	No	Insize	55VP45
H5	16 ft-lb to 80 in-lb	15 in	No	Proto	4NAW4
H7	50 ft-lb to 250 in-lb	25 1/4 in	No	Proto	4NAW5
Preset Interchangeable Head Torque Wrenches					
Foot-Pound, Newton Meter					
2 1/64 in	15 ft-lb to 75 ft-lb, 20 N-m to 102 N-m	11 in	Yes	Cdi	38A305
Inch-Pound, Newton Meter					
2 1/64 in	250 in-lb to 50 in-lb, 6 N-m to 28 N-m	10 in	Yes	Cdi	38A303
1/2 in x 3/4 in	60 in-lb to 300 in-lb, 7 N-m to 34 N-m	8 3/4 in	Yes	Sturtevant Richmond	36WD74
9mm x 12mm	0.4 N-m to 2 N-m, 2 in-lb to 18 in-lb	4 in	Yes	Gedore	49AD75
Electronic Interchangeable Head Torque Wrenches					
Inch-Pound, Centimeter-Kilogram					
3/8 in	5 ft-lb to 99.5 ft-lb	16 3/8 in	Yes, NIST, TAF	Westward	6PAF7
1/2 in	12.5 ft-lb to 250.7 ft-lb, 250.7 ft-lb to 12.5 ft-lb	25 3/8 in	Yes, NIST, TAF	Westward	6PAG0
Interchangeable Head Torque Wrench Kits					
Foot-Pound, Newton-Meter					
16 mm, 17 mm, 21 mm, 22 mm, 24 mm, 26 mm, 27 mm, 29 mm	10 N-m to 80 N-m, 7 ft-lb to 59 ft-lb	16 in	Yes	Yellow Jacket	33NT63
17 mm, 22 mm, 24 mm, 26 mm, 27 mm, 29 mm	10 N-m to 80 N-m, 7 ft-lb to 59 ft-lb	16 in	Yes	Yellow Jacket	33NT62

Size	Overall Length	Maximum Torque	Head Offset Angle	Brand	Item No.
Adjustable Torque Wrench Heads					
1/2 in Drive Size					
9/16 in	6 1/2 in	752 in-lb	0 °	Yellow Jacket	423N90
9mm x 12mm Drive Size					
1 1/16 in	4 in	147 ft-lb	0 °	Westward	19ZC61
14mm x 18mm Drive Size					
1 1/2 in	5 1/2 in	147 ft-lb	0 °	Westward	19ZC62
Hex Drive Torque Wrench Heads					
Dovetail Drive Size					
3/2 in	1 3/4 in	30 in-lb	15 °	Sturtevant Richmond	60GV74
3/2 in	1 3/4 in	135 in-lb	15 °	Sturtevant Richmond	60GV75
3/2 in	1 3/4 in	235 in-lb	15 °	Sturtevant Richmond	60GV76
5/8 in	1 13/16 in	850 in-lb	15 °	Sturtevant Richmond	60GV78
Open End Torque Wrench Heads					
1 3/16 in Drive Size					
9/16 in	1 15/16 in	400 in-lb	15 °	Sturtevant Richmond	53KH74
2 9/32 in Drive Size					
1 1/8 in	1 15/16 in	800 in-lb	15 °	Sturtevant Richmond	53KH76
1 1/2 in Drive Size					
1 in	2 1/4 in	2,000 in-lb	15 °	Sturtevant Richmond	53KH81
1 1/8 in	2 3/4 in	2,500 in-lb	15 °	Sturtevant Richmond	53KH83
9mm x 12mm Drive Size					
7 mm	1 1/2 in	22 ft-lb	0 °	Westward	19ZC63
H5 Drive Size					
9/16 in	3 13/16 in	695 in-lb	15 °	Proto	4NAT6
3/4 in	3 7/8 in	835 in-lb	15 °	Proto	4NAU3
1 1/16 in	3 7/8 in	1,185 in-lb	15 °	Proto	4NAU9
3/4 in	3 15/16 in	1,500 in-lb	15 °	Proto	4NAV6
7/8 in	4 in	2,310 in-lb	15 °	Proto	4NAW1
17 mm	3 3/4 in	1,235 in-lb	15 °	Proto	4NAT4
22 mm	4 in	2,400 in-lb	15 °	Proto	4NAV2
H7 Drive Size					
7/8 in	5 5/8 in	2,470 in-lb	15 °	Proto	4RUD4
1 1/16 in	5 5/8 in	2,970 in-lb	15 °	Proto	4RUE1
1 in	5 11/16 in	3,575 in-lb	15 °	Proto	4RUE7
1 1/16 in	5 5/8 in	3,600 in-lb	15 °	Proto	4RUF4
1 1/8 in	5 13/16 in	3,600 in-lb	15 °	Proto	4RUF8
1 1/16 in	5 7/8 in	3,600 in-lb	15 °	Proto	4RUG1
1 1/4 in	5 7/8 in	3,600 in-lb	15 °	Proto	4RUG3
1 3/8 in	5 7/8 in	3,600 in-lb	15 °	Proto	4RUG7
Square Ratcheting Torque Wrench Heads					
1/4 in Drive Size					
3/4 in	2 3/8 in	250 in-lb	0 °	Sturtevant Richmond	36WD52
3/8 in Drive Size					
3/4 in	2 9/16 in	1,250 in-lb	0 °	Sturtevant Richmond	36WD53
1/2 in Drive Size					
1 1/2 in	2 1/2 in	2,500 in-lb	0 °	Sturtevant Richmond	36WD54
9mm x 12mm Drive Size					
3/4 in	2 in	99 ft-lb	0 °	Westward	19ZC57
1 1/2 in	2 in	99 ft-lb	0 °	Westward	19ZC58
H4 Drive Size					
3/4 in	3 1/4 in	250 in-lb	15 °	Proto	4NAN3
H7 Drive Size					
1 1/2 in	5 1/2 in	3,000 in-lb	0 °	Proto	4NAW6

Drive Size	Torque Range	Overall Length	Calibration Certificate Included	Ratcheting	Head Type	Brand	Item No.
Electrical Connector Preset Torque Wrenches							
Inch-Pound							
7/16 in	0 in-lb to 20 in-lb	6 1/2 in	No	No	Standard	Jonard Tools	4AVJ9
1/2 in	0 in-lb to 30 in-lb	6 1/2 in	No	No	Standard	Jonard Tools	4AVJ7
9/16 in	0 in-lb to 30 in-lb	6 1/2 in	No	No	Standard	Jonard Tools	34RR16
Factory Preset Ratcheting Torque Wrenches							
Newton-Meter							
1/4 in	1 N-m to 5 N-m	7 1/4 in	Yes	Yes	Standard	Gedore	49AD68
3/8 in	10 ft-lb to 40 ft-lb	12 3/4 in	Yes	Yes	Standard	Gedore	49AD73
1/2 in	40 N-m to 125 N-m	18 1/4 in	Yes	Yes	Standard	Gedore	49AD74
Key-Adjustable Preset Ratcheting Torque Wrenches							
Inch-Pound							
1/4 in	10 in-lb to 50 in-lb	7 1/4 in	Yes	Yes	Standard	Sturtevant Richmond	36WD69
3/8 in	30 in-lb to 150 in-lb	7 1/4 in	Yes	Yes	Standard	Sturtevant Richmond	36WD70
1/2 in	0 in-lb to 40 in-lb	7 in	No	Yes	Flexible	Jonard Tools	23Z373
3/8 in	30 in-lb to 150 in-lb	8 in	Yes	Yes	Standard	Sturtevant Richmond	36WD72
1/2 in	150 in-lb to 750 in-lb	14 3/4 in	No	Yes	Standard	Sturtevant Richmond	36WD66
1/2 in	240 in-lb to 1200 in-lb	17 1/2 in	Yes	Yes	Standard	Sturtevant Richmond	36WD71
1/2 in	600 in-lb to 3000 in-lb	23 in	No	Yes	Standard	Sturtevant Richmond	36WD68