











## **Breaker Bars**

Drive Size	Overall Length	Grip Style	Finish	Brand	Item No.
lex-Head Breal		any ony o		2.4	
1/ :-	5½ in	Knurled	Chrome	SK Tools	12D245
1/4 in	5¾ in	Knurled	Chrome	Proto	426G25
3/s in	8½ in	Knurled	Black Oxide	Proto	1AH70
	8½ in	Knurled	Chrome	Proto	426G26
	10 in	Knurled	Chrome	SK Tools	12D266
98 III	10 in	Smooth	Chrome	Westward	33M360
	12 in	Knurled	Chrome	Proto	1FX33
	15 in	Smooth	Chrome	Westward	5TZD9
	10½ in	Knurled	Chrome	Proto	426G2
	15 in	Smooth	Chrome	Westward	440G0
	151/4 in	Knurled	Chrome	Proto	426G2
	16 in	Knurled	Chrome	SK Tools	12D28
1/2 in	18 in	Smooth	Chrome	Westward	5TZE0
72 111	181/4 in	Knurled	Black Oxide	Proto	1AM36
	181/4 in	Knurled	Chrome	Proto	426G2
	24 in	Knurled	Chrome	Proto	449N2
	24 in	Knurled	Chrome	SK Tools	12D28
	24 in	Smooth	Chrome	Westward	5TZE1
3⁄4 in	18 in	Knurled	Chrome	SK Tools	12D28
	20 in	Knurled	Black Oxide	Proto	1AP31
	20 in	Knurled	Chrome	Proto	426G3
	40 in	Smooth	Chrome	Westward	440G0
1 in	26 in	Knurled	Chrome	Westward	45J26
	271/4 in	Knurled	Chrome	Proto	426G3
isulated Break					
3⁄8 in	81⁄2 in	Soft Grip	Chrome	Wiha Tools	53KD7
½ in	10½ in	Soft Grip	Chrome	Wiha Tools	53KD6
-Style Breaker					
3/4 in	16 in	Knurled	Satin	Proto	1AP33
	x-Head Breaker				
3/8 in	8½ in	Smooth	Natural	Ampco	49UL6
½ in	12 in	Non-slip	Natural	Ampco	46C00
3/4 in	18 in	Non-slip	Natural	Ampco	46C02
	ding T-Style Brea				
1/4 in	4½ in	Smooth	Natural	Ampco	49UL5
3% in	8 in	Smooth	Natural	Ampco	49UL5
½ in	12 in	Smooth	Natural	Ampco	49UL5
9/16 in	11 in	Smooth	Natural	Ampco	46C010
	16 in	Smooth	Natural	Ampco	21XU9
3/4 in	18 in	Smooth	Natural	Ampco	49UL5
13/16 in	18 in	Smooth	Natural	Ampco	46C03
	25 in	Smooth	Natural	Ampco	21XU9
1 in	22 in	Smooth	Natural	Ampco	49UL5
liding T-Style E					
1/4 in	4½ in	Smooth	Chrome	Proto	1AF44









483J81

Drive	e Size	Overall Length	Grip Sty	le	Finish	Brand		Item No.
¾ in —		8 in	Knurle	d	Chrome	SK Tool:	S	46C164
		8 in	Smoot	h	Chrome	Proto		1AH71
½ in —		10¾ in	Knurle	d	Chrome	SK Tool:	S	20K385
		12 in	Smoot	h	Chrome	Westwar	ď	437V03
		12¾ in	Smoot	h	Chrome	Proto		1AM37
		18 in	Knurle	d	Chrome	SK Tool:	S	12A487
3/4	in	18 in	Smoot	h	Chrome	Westwar	ď	5MZ16
		20 in	Smoot	h	Chrome	Proto		1AP32
	in —	22 in	Smoot	h	Chrome	Westwar	ď	45J263
- 1	in —	28½ in	Knurle	d	Chrome	Proto		1AR23
Sluggin	g Breaker E	Bars						
3/4	in	11½ in	Smoot	h	Black Oxide	Wright To	ol	29AT68
1	in	11½ in	Smoot	h	Black Oxide	Wright To	ool	29AT69
Head Shape	Reversing	Overall Length	Minimum Arc Swing	Ratchet Type		cludes	Brand	Item No.
Ratche	t & Breaker	Bar Sets						
Pear	Yes	1½",-7",-13"	4-°	Spinner, Standar		F x ½ in M e Adapter	Proto	483J8
	Yes	5",-9"	4-°	Standar	d Exten	Drive 2 in sion, ¼ in in Extension, in Drive	Proto	483J7
	Yes	11",-18"	4-°	Standar		Drive 2 ½ xtension	Proto	483J8











## **Socket Drivers & Speeder Handles**

Connect to sockets to tighten or loosen fasteners.

**Speeder handles** have a large bend in the shaft for rapid rotation. Nonsparking speeder handles won't spark and can install fasteners where flammable vapors or liquids are present. Socket drivers tighten small nuts and bolts that only require hand tightening. Flexible **shaft socket drivers** bend around obstructions to reach fasteners. T-handle insulated socket drivers protect against electrical shock from live circuits and are suitable for use near electrical components. Hand impact socket drivers turn and loosen rusted, frozen, and overtightened bolts and screws. They are struck with a hammer to rotate the socket and loosen the fastener.

Drive Size	Overall Length	Grip Style	Finish	Brand	Item No.
Speeder Handles	-				
½ in -	14 ½ in	Knurled	Chrome	SK Tools	20K387
94 III -	15 ½ in	Plain	Chrome	Proto	55EN65
3/8 in -	16 ¾ in	Knurled	Chrome	SK Tools	20K388
98 III -	17 ½ in	Plain	Chrome	Proto	55EN64
½ in -	18 in	Knurled	Chrome	SK Tools	20K386
72 III -	18 1/4 in	Plain	Chrome	Proto	55EN66
<b>Nonsparking Spe</b>	eder Handles				
½ in. ¾ in	16 in	Plain	Natural	Ampco	21XX15







Flexible Shaft Socket Driver 1AF55





**Hand Impact Socket** 1AT29

Drive Size	Overall Length	Grip Style	Finish	Brand	ltem No.
Socket Drivers					
	6 ¾ in	Cushion	Chrome	Westward	437V02
1/4 in	6 in	Molded	Chrome	SK Tools	20K842
_	7 in	Hardened Plastic	Chrome	Proto	426J24
Flexible Shaft So	cket Drivers				
1/4 in	6 ¾ in	Hardened Plastic	Chrome	Proto	1AF55
3/8 in	9 in	Hardened Plastic	Chrome	Proto	1AH86
T-Handle Insulate	ed Socket Driv	ers			
1/4 in	6 1/4 in	Double Insulated	Chrome	Wiha Tools	53KF25
3% in	7 ¾ in	Double Insulated	Chrome	Wiha Tools	53KF26
½ in	7 ¾ in	Double Insulated	Chrome	Wiha Tools	53KF27
<b>Hand Impact Soc</b>	ket Drivers				
3/8 in	5 ½ in	Knurled	Black Oxide	Proto	1AT29