Box End Wrenches



For more information on Wrenches, see page 780.

WESTWARD 2:(0)(0)® (Wiha)



Box End Wrench Sets

- Standard wrench length
- Straight
- 12-point box end
- Alloy steel material

Feature an enclosed head end that fits around the entire head of the fastener for a secure grip. A 15° head offset provides knuckle clearance while turning, and a 40° head offset clears obstructions and reaches nuts and bolts in tight spaces.



Double Ended. Insulated 40JD22

	• .							
No. of	Range of		Container		Item			
Tools	Head Sizes	ıd Sizes Head Type		Brand	No.			
Double I	nd							
Black 0:	cide Finish							
8	5/16 in to 1 1/4 in	15 ° Offset	Pouch	Proto	1AKP6			
Chrome								
7	5/16 in to 1 1/8 in	15 ° Offset	Pouch	Proto	1AKP7			
Double I	ind, Insulated							
Chrome	Chrome Finish							
11	6 mm to 32 mm	15 ° Offset	Pouch	Proto	40JD22			
11	6 mm to 32 mm	15 ° Offset	Pouch	Proto	4LT81			
Satin Fir								
13	1/4 in to 1 in, 6 mm to 19 mm	40 ° Offset	Canvas Pouch	Westward	54DG06			
13	1/4 in to 1 in, 6 mm to 19 mm	40 ° Offset	Canvas Pouch	Westward	54DG06			
14	¼ in to ⅓ in, 6 to 19mm	15 ° Offset	Canvas Pouch	Westward	4YR23			
14	1/4 in to 1/8 in, 6 to 19mm	15 ° Offset	Canvas Pouch	Westward	4YR23			
Single End								
Chrome Finish								
- 8	5/16 in to 3/4 in	15 ° Offset	Wrench Roll	Wiha Tools	26X334			
Single End, Insulated								
Chrome Finish								
- 8	10 mm to 19 mm	15 ° Offset	Wrench Roll	Wiha Tools	26X337			

ELICIO B KLEIN (Wind) WESTWARD



Ratcheting Box End Wrench Sets

- Alloy steel material
- Straight

Enclosed head with gear mechanism rotates freely without repositioning the wrench. Reversing wrenches change direction without removing the head from the fastener.



No. of Tools	Range of Head Sizes	Head	Wrench Length Style	Reversing	Container Type	Brand	Item No.			
Double End, 12-Point Box End										
Chrome Finish										
5	1/4 in to 1/8 in	0 ° Standard	Standard	No	Pouch	Proto	1AKR2			
5	1/4 in to 1/8 in	0 ° Standard	Standard	Yes	Pouch	Proto	1UK89			
5	7 mm to 17 mm	0 ° Standard	Stubby	Yes	Pouch	Proto	1UK90			
6	8 mm to 19 mm	0 ° Standard	Standard	No	Canvas Pouch	Westward	54DG35			
7	1/4 in to 1/8 in	25 ° Offset	Standard	Yes	Wrench Roll	Klein Tools	3LZP6			
Satin Fin	ish									
8	3% in to 1 in	60 ° Offset	Standard	No	Pouch	Proto	1AKP5			
Double End, 12-Point Box End, 6-Point Box End										
Chrome	Finish									
5	1/4 in to 1/8 in	0 ° Standard	Stubby	No	None	Proto	40JC82			
5	7 mm to 17 mm	0 ° Standard	Stubby	No	Pouch	Proto	4LT85			
7	7 mm to 21 mm	25 ° Offset	Standard	Yes	Pouch	Proto	4LT82			
Double End, 12-Point Box End, 6-Point Box End, Tether Ready										
Chrome	Finish									
7	5/16 in to 1 1/4 in	25 ° Offset	Standard	Yes	Pouch	Proto	40JD31			
	Double End, 6-Point Box End									
Chrome										
3	1/4 in to 9/16 in	25 ° Offset	Standard	Yes	Wrench Roll	Klein Tools	3LZR1			
	ind, Spline Box End	1								
Black Ch	rome Finish									
8	32 in to 1 1/8 in √32 in to 1 1/8 in	0 ° Standard	Standard	Yes	Pouch	Proto	1WNC4			
Single End, 12-Point Box End, Insulated										
Chrome	Finish									
6	% in to ¾ in	0 ° Standard	Standard	Yes	Molded Case	Wiha Tools	26X335			
7	8 mm to 19 mm	0 ° Standard	Standard	Yes	Molded Case	Wiha Tools	26X332			
16	1/4 in to 1 1/4 in	15 ° Offset	Standard	No	Wrench Roll	Wiha Tools	26X333			
16	8 mm to 32 mm	15 ° Offset	Standard	No	Wrench Roll	Wiha Tools	26X336			

FACOM. PROTO 8









Box End Wrenches

 Alloy steel material, Nonsparking wrenches are aluminum bronze material

Enclosed head end applies more torque and is less likely to slip off the fastener than an open-end wrench.





Head Size	Overall Length	Head	Wrench Length Style	Item No.	
Half Moon, Do	uble End	I, 12-Point	Box End		
Satin Finish					
7∕16 in, 1⁄2 in	5¾"	15° Offset	Standard	Proto	1AMP4
9/16 in, 5/8 in 5/8 in, 3/4 in	61/2"	15° Offset	Standard	Proto	1AMP5
5⁄8 in, 3∕4 in	71/4"	15° Offset	Standard	Proto	1AMP6
Straight, Doub		12-Point Bo	ox End		
Chrome Finish	61/2"	60° Offset	Standard	Droto	483J37
1/4 in, 5/16 in 1/4 in, 5/16 in	8"	15° Offset	Standard	Proto Proto	483H38
54c in 36 in	9"	15° Offset	Standard	Proto	483H39
5/16 in, 3/8 in 3/8 in, 7/16 in	73/4"	7.5° Offset	Standard	Proto	3R425
3/8 in, 7/16 in	10"	15° Offset	Standard	Proto	483H40
½ in, % in	83/4"	60° Offset	Standard	Proto	483J39
½ in, % in	111/2"	15° Offset	Standard	Proto	483H42
3/4 in. 7/8 in	111/2"	60° Offset	Standard	Proto	483J42
Satin Finish					
1/4 in, 5/16 in	61/2"	40° Offset	Standard	Westward	5MP90
3/8 in. 7/16 in	73/4"	40° Offset	Standard	Westward	5MP91
1/2 in, 9/16 in	8¾"	40° Offset	Standard	Westward	5MP93
5/8 in, 3/4 in	6"	15° Offset	Stubby	Proto	1AMN3
15/16 in, 1 in	141/8"	40° Offset	Standard	Westward	446G59
1 ¼ in, 1 ¾ in	201/4"	15° Offset	Standard	Proto	1AML1
1 1/16 in, 1 1/2 in	221/4"	15° Offset	Standard	Proto	1AML3
Straight, Doub Natural Finish	ie Ena,	12-Point Bo	IX Ena, Nons	parking	
3/4 in, 7/8 in	121/4"	15° Offset	Standard	Amnoo	4RPG1
7/8 in, 1 1/16 in	15"	15° Offset	Standard	Ampco Ampco	46C045
15/16 in, 1 1/16 in	15"	15° Offset	Standard	Ampco	4RPG3
1 7/16 in, 1 5/8 in	191/4"	15° Offset	Standard	Ampco	21XW27
1 1/8 in, 1 5/16 in	191/4"	15° Offset	Standard	Ampco	21XW26
1 1/4 in, 1 5/16 in	191/4"	15° Offset	Standard	Ampco	21XW25
Straight, Doub	le End, 1	12-Point Bo	x End, Tethe	r Ready	
Chrome Finish					
7/16 in, 1/2 in	8"	15° Offset	Standard	Proto	34GP76
13/16 in, 7/8 in	13"	15° Offset		Proto	34GP79
1 1/16 in, 1 1/8 in	171/2"	15° Offset		Proto	34GP81
Straight, Doub					01/015
1/4 in, 5/16 in	71/4"	15° Offset 15° Offset		Proto	2KGJ5
% in, 1 in Straight, Singl	171/8"		Long	Proto	483H53
Black Oxide Fi		Z-PUIIIL DU	X EIIU		
1 ½ 6 in	101/2"	60° Offset	Extra Long	Proto	22DJ60
1 7/16 in	103/4"	60° Offset	Extra Long	Proto	22DJ66
1 1/4 in	103/4"	60° Offset	Extra Long	Proto	22DJ63
1 1/8 in	103/4"	60° Offset	Extra Long	Proto	22DJ61
1 5/8 in	11"	60° Offset	Extra Long	Proto	22DJ68
1 ½ in	11"	60° Offset	Extra Long	Proto	22DJ67
1 13/16 in	131/4"	60° Offset	Extra Long	Proto	22DJ71
2 in	131/2"	60° Offset	Extra Long	Proto	22DJ74
2 ¾16 in	13¾"	60° Offset	Extra Long	Proto	22DJ76
2 3/8 in	13¾"	60° Offset	Extra Long	Proto	22DJ79
2 1/4 in	13¾"	60° Offset	Extra Long	Proto	22DJ77

	Overall Length	He	ad	Le	rench ength etvle	R	rand	Item No.
Straight, Single							Tullu	140.
Chrome Finish					,			
1/4 in	61/4"	15° 0	ffset	Sta	ndard	Wih	a Tools	53KE51
½ in	71/2"	15° 0			ndard		a Tools	53KE55
15/16 in	11"	15° 0			ndard		a Tools	53KE63
Straight, Single	e End, 1	2-Poin	t Box	End	, Nonsp	arki	ng	
Natural Finish								
19/32 in	6"	0° Sta			ndard		mpco	49UM48
1 1½16 in	13"	0° Sta	ndard	Sta	ndard		mpco	49UM68
	0				Wrei			
Head Size	Overa Lengt		Head		Leng Stv		Brand	Item No.
Half Moon, Dou						IE	Drailu	NU.
Satin Finish	INIC FIII	u, 12-r	UIIIL E	JUX E	iiu			
	61/2"	3	0° Off	fset	Stand	lard	Facom	2TLE1
11 mm, 13 mm 19 mm, 22 mm	10"		0° Off		Stand		Facom	2TLE7
Straight, Doubl	e End,							
Chrome Finish								
17 mm, 19 mm	111/4		5° Off		Stand		Proto	4HJ06
22 mm, 24 mm	13¾		.5° Of		Stand		Proto	4HJ11
27 mm, 30 mm	16"		.5° Of	tset	Stand	lard	Proto	4HJ13
Satin Finish	83/4"	- 1	0° Off	foot	Ctone	lord	Montuor	d EMD04
12 mm, 14 mm 13 mm, 15 mm	91/2"		0° Off		Stand		Westwar	
16 mm, 18 mm	10"		0° Off		Stand		Westwar	
17 mm, 19 mm	10"	- 4	0° Off		Stand			
Straight, Doubl								u omno-
Natural Finish					.,		9	
6 mm, 7 mm	4"		Stan		Stand		Ampco	
8 mm, 9 mm	6"	1	5° Off	fset	Stand		Ampco	
8 mm, 10 mm	71/8"		5° Off		Stand		Ampco	
17 mm, 19 mm	11"		5° Off		Stand		Ampco	49UN04
Straight, Doubl Chrome Finish	e Ena,	12-POI	ut Rox	K Enc	ı, letne	r Ke	ady	
16 mm, 18 mm	103/4	. 1	5° Off	feat	Stand	lard	Proto	34GP87
17 mm, 19 mm	111/4		5° Off		Stand		Proto	34GP88
22 mm, 24 mm	133/4		5° Off		Stand		Proto	34GP90
27 mm, 30 mm	16"	1	5° Off	fset	Stand		Proto	34GP91
Straight, Single	End, 1							
Satin Finish								
24 mm	7"		0° Off		Stand		Facom	36T974
30 mm	81/4"		0° Off	fset	Stand		Facom	36T975
41 mm	10½		0° Off		Stand		Facom	36T978
Straight, Single	: Ena, 1	z-Poin	I ROX	End	, Nonsp	arki	ng	
Natural Finish 23 mm	71/2"	00	Stan	dord	Stand	lord	Amnoo	49UM11
26 mm	9"	0.	Stan	dard	Stand		Ampco Ampco	
29 mm	9"		Stan		Stand		Ampco	
46 mm	153/4		Stan		Stand		Ampco	
82 mm	241/2		Stan		Stand		Ampco	49UM45
- OL			Juli		Otario	u	,poo	