

1-800-GRAINGER (472-4643)

Retaining Ring & Snap Ring Pliers



Retaining Ring and Snap Ring Pliers

▶CHOOSE: Retaining Ring Plier						▶CHOOSE: Lock Ring Plier					
Tip Dia.	Tip Angle	For Shaft Dia.	For Bore Dia.	Overall Length	Item No.	Tip Dia.	Tip Angle	For Shaft Dia.	For Bore Dia.	Overall Length	Item No.
<b>Internal</b>						<b>Internal</b>					
0.025 in	0°	—	¼ in to ¾ in	5 ¾ in	Proto 3R330	0.036 in	0°, 90°	¼ in to 2 in	¾ in to 2 in	8 in	Channellock 3WDW5
0.035 in	0°	—	¾ in to 1 ½ in	5 ½ in	Knipex H3967	0.047 in	0°	—	—	—	—
0.035 in	0°	—	8mm to 13mm	5 ½ in	Knipex 38U762	0.071 in	0°	—	—	—	—
0.036 in	45°	—	¾ in to 1 ½ in	5 ½ in	Knipex H3967	0.071 in	0°	¼ in to ¾ in	¾ in to 1 ½ in	5 ½ in	Proto 3R333
0.038 in	0°	—	¾ in to ¾ in	5 ¾ in	Proto 5C630	0.071 in	18°	¼ in to ¾ in	¾ in to 1 ½ in	6 in	Westward 33HD62
0.038 in	45°	—	¾ in to 1 in	5 ¾ in	Proto 3R332	0.071 in	45°	½ in to 2 ½ in	¾ in to 1 ½ in	5 ½ in	Proto 3R317
0.046 in 0°, 45°, 90°	—	—	½ in to 1 in	5 ½ in, 5 ¾ in	Knipex H3968	0.071 in	45°	¾ in to 4 ¾ in	¾ in to 1 ½ in	6 in	Westward 33HD72
0.046 in 90°	—	—	¾ in to 1 ½ in	5 ½ in	Knipex H3967	0.071 in	90°	—	¾ in to 1 in	6 in	Proto 4JV83
0.046 in 90°	—	—	½ in to 1 in	5 ½ in	Knipex 10T949 *	0.071 in	90°	¾ in to ¾ in	¾ in to 1 in	5 ½ in	Proto 3R318
0.047 in 90°	—	—	12mm to 25mm	5 ½ in	Knipex 38U768	0.071 in	90°	¾ in to 4 ¾ in	¾ in to 1 ½ in	6 in	Westward 33HD69
0.051 in 0°	—	—	12mm to 25mm	5 ½ in	Knipex 38U763	0.071 in	0°	1 ½ in to ¾ in	¾ in to 1 ½ in	5 ½ in	Proto 3R319
0.071 in 0°	—	—	19mm to 60mm	7 ½ in	Knipex 38U764	0.071 in	0°	1 ½ in to 6 ¾ in	½ in to 1 in	6 in	Westward 33HD66
0.071 in 90°	—	—	19mm to 60mm	6 ¾ in	Knipex 38U769	0.071 in	45°	1 ½ in to 1 in	1 in to 1 ½ in	5 ½ in	Proto 3R320
0.078 in 0°, 45°, 90°	—	—	¾ in to 2 ¾ in	7 ½ in, 6 ¾ in	Knipex H3969	0.071 in	45°	1 ½ in to 6 ¾ in	½ in to 1 in	6 in	Westward 33HD67
0.078 in 90°	—	—	¾ in to 2 ¾ in	6 ½ in	Knipex 10T950 *	0.071 in	90°	¾ in to 1 in	1 ½ in to 1 ½ in	5 ½ in	Proto 3R321
0.087 in 30°	—	0 in to 1/36 in	—	7 ½ in	Knipex 38U771	0.071 in	90°	1 ½ in to 4 ¾ in	¾ in to 1 ½ in	6 in	Westward 33HD70
0.09 in 0°	—	—	1 ½ in to 3 in	9 in	Proto 5C600	0.071 in	0°	½ in to 2 ½ in	½ in to 1 ½ in	6 ½ in	Westward 4YF50
0.091 in 0°	—	—	40mm to 100mm	8 ½ in	Knipex 38U765	0.071 in	0°	1 ½ in to 1 ½ in	1 ½ in to 1 ¾ in	7 ½ in	Proto 3R328
0.091 in 90°	—	—	40mm to 100mm	8 ½ in	Knipex 38U770	0.071 in	0°	4 ¾ in to 1 ¾ in	1 ½ in to 1 ¾ in	8 in	Westward 33HD64
0.093 in 0°, 45°, 90°	—	—	1 ½ in to 4 in	8 ½ in, 8 ½ in	Knipex H3970	0.071 in	18°	1 ½ in to 1 ½ in	1 ½ in to 1 ¾ in	7 ½ in	Proto 4JV85
0.093 in 90°	—	—	1 ½ in to 4 in	8 ½ in	Knipex 10T951 *	0.071 in	45°	1 in to 2 in	1 ½ in to 1 ¾ in	7 ½ in	Proto 3R322
0.12 in 0°	—	—	3 ½ in to 6 in	16 ½ in	Proto 3R312	0.071 in	45°	4 ¾ in to 1 ¾ in	1 ½ in to 1 ¾ in	8 in	Westward 33HD68
0.125 in 90°	—	—	3 ½ in to 5 ½ in	5 ½ in	Knipex 10T952 *	0.071 in	90°	¾ in to ¾ in	1 ½ in to 2 in	7 ½ in	Proto 3R323
0.126 in 0°	—	—	85mm to 140mm	12 ¾ in	Knipex 38U766	0.071 in	90°	4 ¾ in to 1 ¾ in	1 ½ in to 1 ¾ in	8 in	Westward 33HD65
0.177 in 90°	—	—	252mm to 400mm	23 ¾ in	Knipex 38U767	0.071 in	90°	¾ in to 2 in	1 ½ in to 2 in	7 ½ in	Proto 4JV84
<b>External</b>						<b>External</b>					
0.023 in 0°	—	—	¼ in to ¾ in	5 ¼ in	Proto 3R329	0.09 in 0°	—	1 ½ in to 3 ½ in	1 ½ in to 3 ¼ in	9 in	Westward 33HD63
0.038 in 0°	—	—	¼ in to 2 ½ in	6 ½ in	Proto 5C599	0.09 in 45°	—	1 ½ in to 1 ¾ in	1 ½ in to 3 in	9 in	Proto 3R325
0.038 in 90°	—	—	¼ in to 1 in	6 ½ in	Proto 3R331	0.09 in 45°	—	1 ½ in to 3 ¾ in	1 ½ in to 3 ¼ in	9 in	Westward 33HD71
0.046 in 0°	—	—	½ in to ¾ in	5 ½ in	Knipex 10T953 *	0.09 in 90°	—	1 ½ in to 3 in	1 ½ in to 3 in	8 ½ in	Proto 10G635
0.046 in 0°	—	—	¾ in to 1 in	5 ½ in	Knipex 10T954 *	0.09 in 90°	—	1 ½ in to 3 ¾ in	1 ½ in to 3 ¼ in	9 in	Westward 33HD73
0.046 in 90°	—	—	½ in to ¾ in	5 ½ in	Knipex 10T958 *	<b>Compact</b>					
0.046 in 90°	—	—	¾ in to 1 in	5 ½ in	Knipex 10T959 *	0.046 in 0°	—	¾ in to 1 ½ in	5 ½ in	Knipex 10N913 *	
0.047 in 0°	—	—	¾ in to 1 in	5 ½ in	Knipex 38GJ31	0.046 in 0°	—	½ in to 1 in	5 ½ in	Knipex 10N914 *	
0.07 in 0°	—	—	¾ in to 2 in	6 ¾ in	Proto 5C628	0.046 in 0°	—	¼ in to ¾ in	5 ½ in	Knipex 10N908	
0.071 in 90°	—	—	13mm to 60mm	6 ¾ in	Knipex 38U773	0.046 in 0°	—	¾ in to ¾ in	5 ½ in	Knipex 10N909	
0.078 in 0°, 45°, 90°	—	—	¾ in to 2 ¾ in	7 ½ in, 6 ¾ in	Knipex H3964	0.046 in 0°	—	½ in to ¾ in	5 ½ in	Knipex 10T963 *	
0.078 in 90°	—	—	¾ in to 2 ¾ in	7 ½ in	Knipex 10T955 *	0.046 in 90°	—	½ in to ¾ in	5 ½ in	Knipex 10T964 *	
0.078 in 90°	—	—	¾ in to 2 ¾ in	6 ½ in	Knipex 10T960 *	0.046 in 90°	—	¾ in to 1 ½ in	5 ½ in	Knipex 10T948 *	
0.091 in 90°	—	—	40mm to 100mm	7 ½ in	Knipex 38U774	0.05 in 0°	—	¾ in to 1 ½ in	5 ½ in	Knipex 10N911	
0.093 in 0°, 45°, 90°	—	—	1 ½ in to 4 in	8 ½ in, 7 ½ in	Knipex H3965	0.07 in 0°	—	¾ in to 1 ½ in	7 ½ in	Knipex 10N912	
0.093 in 90°	—	—	1 ½ in to 4 in	8 ½ in	Knipex 10T956 *	0.078 in 0°	—	¾ in to 2 ¾ in	7 ½ in	Knipex 10N915 *	
0.093 in 90°	—	—	1 ½ in to 4 in	8 ½ in	Knipex 10T961 *	0.078 in 0°	—	¾ in to 1 ½ in	5 ½ in	Knipex 10N910	
0.115 in 0°	—	—	1 ½ in to 3 ½ in	9 ½ in	Proto 5C629	0.093 in 0°	—	—	1 ½ in to 4 in	8 ½ in	Knipex 10N916 *
0.12 in 0°	—	—	3 ½ in to 6 ½ in	16 ½ in	Proto 3R313	0.125 in 0°	—	—	3 ¾ in to 5 ½ in	12 ¾ in	Knipex 10T947 *
0.125 in 0°	—	—	3 ¾ in to 5 ½ in	12 ¾ in	Knipex 10T957 *	0.14 in 0°	—	—	4 ½ in to 11 ¾ in	22 ½ in	Knipex 10N904
0.125 in 90°	—	—	3 ¾ in to 5 ½ in	5 ½ in	Knipex 10T962 *	0.14 in 0°	—	—	—	22 in	Knipex 10N906
0.177 in 90°	—	—	252mm to 400mm	22 ¾ in	Knipex 38U772	0.187 in 0°	—	—	—	22 ½ in	Knipex 10N907
<b>Convertible</b>						<b>Convertible</b>					
0.023 in	0°, 90°	—	¼ in to 1 in	6 ¼ in	Channellock 38GU16	0.187 in 0°	—	—	9 ½ in to 15 ¾ in	22 ½ in	Knipex 10N905
0.036 in	0°, 90°	—	¼ in to 1 in	6 ¼ in	Channellock 38GU16	<b>Lock Ring Plier</b>					
0.047 in	0°, 90°	—	¼ in to 1 in	6 ¼ in	Channellock 38GU16	<b>Internal</b>					
						—	0°	—	—	9 in	Proto 3R221
						—	0°	—	—	10 ¾ in	Proto 3R223

\* Inserted, nondetachable tips made from high-density spring steel for added strength and 30% more stability.

No. of Pieces	Tip Dia.	Tip Angle	For Shaft Dia.	For Bore Dia.	Overall Length	Includes	Brand	Item No.
<b>Retaining Ring Plier Sets</b>								
<b>Internal/External</b>								
2	0.047 in	0°	2 ¾ in to 6 ¾ in	1 ¼ in	5 ½ in, 5 ¾ in	—	Knipex	38U005
2	0.078 in	0°	¾ in to 2 ¾ in	1 ¼ in	8 in	—	Knipex	38U006
4	0.049 in, 0.07 in	0°	½ in to 1 in, ¾ in to 2 ¾ in	½ in to 1 in, ¾ in to 2 ¾ in	5 ¼ in, 8 in	Nylon Pouch with Locking Clip	Knipex	3JXP2
4	0.049 in	0°, 90°	¾ in to 1 in	¾ in to 1 in	5 in, 5 ¼ in, 5 ¾ in	Nylon Pouch with Locking Clip	Knipex	3JXP3
4	0.035 in, 0.07 in	0°	½ in to 2 ¾ in, ¾ in to 2 ¾ in	¾ in to 2 ¾ in, ¾ in to 1 ½ in	5 ¼ in, 8 in	Nylon Pouch with Locking Clip	Knipex	3JXP4
4	0.035 in, 0.07 in	90°	½ in to 2 ¾ in, ¾ in to 2 ¾ in	¾ in to 2 ¾ in, ¾ in to 1 ½ in	5 in, 5 ¼ in, 6 ¾ in	Nylon Pouch with Locking Clip	Knipex	3JXP5
4	0.071 in	0°, 90°	¾ in to 2 ¾ in	¾ in to 2 ¾ in	6 ¾ in, 7 ¼ in	(4) Circlip Pliers	Knipex	10N809
4	0.049 in, 0.07 in	0°	¾ in to 2 ¾ in	¾ in to 2 ¾ in	5 ½ in, 7 ¼ in	(4) Circlip Pliers	Knipex	10N810
4	0.038 in, 0.047 in, 0.07 in, 0.09 in	0°	½ in to 1 in	½ in to 2 ¾ in	5 ½ in, 7 ¼ in	(6) Circlip Pliers, Foam Tray	Knipex	38U722
4	0.049 in, 0.07 in	90°	2 ¾ in to 6 ¾ in, ¾ in to 2 ¾ in	1 ¼ in	5 ½ in, 7 in	Tool Roll	Knipex	38U007
6	0.038 in, 0.047 in, 0.07 in, 0.09 in	0°, 90°	¾ in to 2 ¾ in	¾ in to 2 in	9 ½ in	Plastic Case	Imperial	40AW29
6	0.038 in, 0.047 in, 0.07 in, 0.09 in	0°, 90°	¾ in to 2 ¾ in	1 ½ in to 2 ¾ in	5 ½ in, 6 ½ in, 7 ¼ in	(6) Circlip Pliers, Foam Tray	Knipex	38UR98
8	0.023 in, 0.036 in, 0.047 in	0°, 90°	½ in to 1 in	½ in to 2 ¾ in	5 ½ in, 5 ½ in, 6 ½ in, 7 ¼ in	(8) Circlip Pliers	Knipex	38U723
18	0.038 in, 0.047 in, 0.07 in	0°	¾ in to 2 in	¾ in to 2 in	6 ¼ in	Plastic Case	Proto	5C601
<b>Internal</b>								
4	0.049 in	45°	—	¾ in to 2 ¼ in	5 ¾ in, 8 in, 9 in	Plastic Pouch	Knipex	10U091
<b>External</b>								
4	0.07 in	45°	1 ¾ in to 3 ½ in, 1 ½ in to 2 ¾ in, 2 ¾ in to 6 ¾ in, ¾ in to 2 ¾ in	—	5 ¼ in, 7 ¼ in, 8 ¼ in	Plastic Pouch	Knipex	10U092
18	0.108 in, 0.12 in	90°	1 ½ in to 3 ¾ in	2 ½ in to 4 in	9 ½ in	Carrying Case	Proto	3R309
<b>Convertible</b>								
2	0.038 in, 0.047 in, 0.07 in	0°, 15°, 45°, 90°	¼ in to 2 in	¾ in to 2 in	6 ¼ in	(8) Pairs of Color Coded Interchangeable Tips, External Pliers, Internal Pliers, Plastic Case	Imperial	40AW31
4	0.038 in, 0.07 in	18°, 90°	¼ in to 2 in	¾ in to 2 in	6 in, 7 ¼ in	(2) Retaining Ring Convertible Pliers 6", (2) Retaining Ring Convertible Pliers 7 ¼"	Proto	4JV80
6	0.038 in, 0.047 in, 0.07 in	0°, 90°	¼ in to 2 in	¾ in to 3 in	5 ¾ in, 5 ¾ in, 7 ½ in, 7 ½ in	Carrying Case	Proto	4JV79
12	0.038 in, 0.047 in, 0.07 in, 0.09 in	0°, 45°, 90°	¼ in to 3 ½ in	¾ in to 3 in	5 ¾ in, 5 ¾ in, 7 ½ in, 7 ½ in, 7 ½ in, 8 ½ in, 9 in, 9 ¼ in	Carrying Case	Proto	5C602
<b>Snap Ring Plier Sets</b>								
<b>Internal/External</b>								
12	0.038 in, 0.047 in, 0.07 in, 0.09 in	0°, 45°, 90°	¾ in to 3 ¼ in	¾ in to 3 ¼ in	6 in, 9 in	Carrying Case	Westward	33HD61
12	0.037 in, 0.039 in, 0.047 in, 0.074 in	0°, 45°, 90°	¾ in to 1 ¾ in	¾ in to 1 ¾ in	6 ½ in	Carrying Case	Westward	33HD60
<b>Convertible</b>								
4	0.045 in, 0.06 in	45°, 90°	¾ in to 2 in	¾ in to 2 in	6 in	—	Westward	4YP48

Sign in to Grainger.com® to see YOUR Pricing and MORE