



Bending Equipment

ELECTRIC BENDERS

The 555 Series, commonly referred to as "triple nickel", are portable units bending 1/2" to 2" dia Rigid, IMC, and EMT conduit up to 180°. Built-in bend charts guide for accurate bends. Operate with a remote pendant control.

Combos include bender and shoe listed on same line.

PROGRAMMABLE BENDER

Intellibender offers conduit capacity: 3/4" rigid, 1 to 2" rigid, EMT, or IMC. Sensors automatically adjust for conduit dia. and type. LCD interface.

MECHANICAL BENDERS

Standard—Ratchet action and built-in 0° to 90° bending gauge. Capacities: 1/2", 3/4", and 1" IMC and rigid conduit. Welded frame and wheels. Handle not included. Use 5 ft. of 1" rigid conduit for handle.

Heavy-Duty—Independent ratchet mechanism simplifies both conduit bending and shoe changes. Each shoe has its own "swing-away" clamp to lock pipe in place. Conduit capacities: 3/4" to 2" EMT, 1/2" to 1 1/4" IMC, 1/2" to 1 1/2" rigid, and 1/2" to 1 1/2" aluminum. Includes frame and heavy-duty undercarriage with wheels, 5 shoes, 2 EMT follow bars, EMT follow bar roller, roller, and roller pin.

Little Kicker Offset Bender—Bends offsets for 1/2" EMT.

Description	Brand	BENDER Mfr. Model	Item No.	SHOE Mfr. Model	Item No.	COMBO Mfr. Model	Item No.
Electric Benders							
w/Standard Pendant; 1/2-2 in EMT Shoes	Greenlee	555CX	6TFG7	13934	22PE99	7J385	7J385
1/2 to 2 in., 120V, Horizontal and Vertical Operating Position	Greenlee	854DX	38GU29	—	—	—	—
w/Standard Pendant; 1/2-2 in Rigid/IMC Shoes	Greenlee	—	—	28008	22PE98	7J384	7J384
w/1/2 in, 1 1/4 in 1 1/2 in and 2 in Shoes and Support Roller Units	Gardner Bender	B2555EMT	15V885	—	—	—	—
w/1/2 in and 1 1/4 in Rigid and IMC Shoes, and Support Rollers; 1 1/2 and 2 in Rigid Shoes and Support Rollers	Gardner Bender	B2555RIG	15V886	—	—	—	—
Programmable Benders							
Cyclone w/Bending Shoe and Weather Resistant Cover	Gardner Bender	B2000	15V883	—	—	—	—
IntelliBender Electric Conduit Bender, 1/2 - 2 in Rigid/EMT/IMC	Greenlee	855GX	6TFG6	—	—	—	—
Mechanical Benders							
Standard Mechanical Bender	Greenlee	1800	1ATF2	—	—	—	—
Heavy-Duty Mechanical Bender	Greenlee	1818	1ATF3	—	—	—	—
Little Kicker Offset Bender	Greenlee	1810	4A724	—	—	—	—

Description	Brand	Mfr. Model	Item No.
PVC Heating/Bending Equipment			
Electric PVC Heater for 1/2 to 2 in PVC Pipe	Greenlee	849	5C637
PVC Heating Blanket for 1/2 to 1 1/2 in PVC Pipe	Greenlee	860-1-1/2	5C638
EMT Size	Rigid/IMC Size	Centerline Bend Radius	Brand
1/2 in	—	4 in	Klein Tools
3/4 in	1/2 in	5 in	Klein Tools
Hand Benders w/Handles - Cast Iron			
1/2 in	—	4 5/8 in	IDEAL
3/4 in	1/2 in	5 1/4 in	IDEAL
1 in	3/4 in	6 1/2 in	IDEAL
1 1/4 in	1 in	9 3/4 in	IDEAL
Hand Benders w/Handles - Ductile Iron			
1/2 in	—	4 5/8 in	IDEAL
3/4 in	1/2 in	5 1/4 in	IDEAL
1 in	3/4 in	6 1/2 in	IDEAL
1 1/4 in	1 in	9 3/4 in	IDEAL
Hand Benders w/Handles - Aluminum			
1/2 in	—	4 1 1/2 in	IDEAL
3/4 in	1/2 in	5 1 3/4 in	IDEAL
1 in	3/4 in	—	Klein Tools
1 1/4 in	—	—	Klein Tools

EMT Size	Rigid/IMC Size	Centerline Bend Radius	Brand	Mfr. Model	Item No.
Hand Benders w/out Handles - Ductile Iron					
1/2 in	—	4 1 1/2 in	IDEAL	74-001	10F487
3/4 in	1/2 in	5 1 3/4 in	IDEAL	74-002	10F488
1 in	3/4 in	6 3/4 in	IDEAL	74-003	10F489
1 1/4 in	1 in	9 3/4 in	IDEAL	74-006	10F490
Hand Benders w/out Handles - Aluminum					
1/2 in	—	4 3/4 in	Greenlee	840A	4A732
3/4 in	1/2 in	5 1/2 in	Greenlee	841A	4A733
1 in	3/4 in	6 1/2 in	Greenlee	842A	4A734
Handle Length	For Use With	Brand	Mfr. Model	Item No.	
Handles for Hand Benders					
38 in	10F496, 74-002, 74-031, Mfr. No. 74-001	IDEAL	74-019	10F491	
	6EXR5, 6EXR6	Westward	—	6EXR8	
	51608, 51609	Klein Tools	51427	4VDG3	
	4A732, 4A733	Greenlee	841H	5C635	
	10F489 Conduit Bender	IDEAL	74-020	10F492	
44 in	51610	Klein Tools	51428	4VDG4	
	4A734	Greenlee	841H	5C636	
54 in	Mfr. No. 56211	Klein Tools	51429	4VDH8	
55 in	Mfr. No. 74-006	IDEAL	74-021	10F493	



Telescoping Reel Stands and Spindles

Use with pins for rough adjustment and a screw-type final height adjustment. Stands have ball bearing rollers. 1FAH3 is a ratcheting stand, providing specific adjustments to spool height. Order spindles separately.

Description	Load Capacity	Overall Height	For Use With	Mfr. Model	Item No.
Ratcheting Reel Stand	3,750 lb	47 in	58 to 90 in Reel Dia	656	1FAH3
Screw Type Reel Stand	2,500 lb	54 in	46 to 96 in Reel Dia	683	5C649
Screw Type Reel Stand	2,500 lb	27 in	28 to 56 in Reel Dia	687	5C650
Spindle, 2 3/8 in dia. x 62 in L	6,000 lb	2 1/2 in	5C650	647	5C652
Spindle, 2 3/8 in dia. x 76 in L	5,000 lb	2 1/2 in	5C649	684	5C651
Spindle, 3 1/2 in dia. x 100 in L	7,500 lb	3 1/2 in	1FAH3 Reel Stands, 5C649, 5C650	657	1FAH4