



Gas-Powered
22P306

Power Concrete Screeds, Boards & Pipes

Power screeds level poured concrete after it's been spread and leave a flat, dense slab that's ready for troweling or finishing. Also known as strike offs, they skim their vibrating board or rotating pipe along a surface to remove excess concrete, push down aggregate, and leave cream on the surface for finishing.

| Overall Height | Tool Weight | Compatible Board Length | | Engine Type | Horsepower | No. of Mounting Holes | Mfr. Model | Item No. |
|----------------------------|-----------------------|---|--|----------------|-------------|-----------------------|------------|----------|
| Vibratory Concrete Screeds | | | | | | | | |
| Gas-Powered | | | | | | | | |
| 30 1/2 in | 33.5 lb | 4 ft, 6 ft, 8 ft, 10 ft, 12 ft, 14 ft, 16 ft | | 4 Stroke | 1 3/4 hp | 2 | SW100H | 22P306 |
| Spin Screeds | | | | | | | | |
| Corded | | | | | | | | |
| 36 in | 52 lb | 4 ft, 6 ft, 8 ft, 10 ft, 12 ft, 14 ft, 16 ft, 18 ft, 20 ft, 22 ft | | — | — | 1 | SPNRSSAD | 788FK9 |
| Blade Length | No. of Mounting Holes | Compatible with Manufacturer Part Number | | Blade Material | Blade Shape | | Item No. | |
| Concrete Screed Boards | | | | | | | | |
| 8 ft | 1 | SW100H | | Aluminum Alloy | L-Shaped | 788FK4 | | |
| 10 ft | 1 | SW100H | | Aluminum Alloy | L-Shaped | 788FK5 | | |
| 12 ft | 1 | SW100H | | Aluminum Alloy | L-Shaped | 22P307 | | |
| 16 ft | 2 | SW100H | | Aluminum Alloy | L-Shaped | 788FK8 | | |
| 16 ft | 1 | SW100H | | Aluminum Alloy | L-Shaped | 788FK7 | | |
| Spin Screed Pipes | | | | | | | | |
| 12 ft | 1 | SPNRSSA18V, SPNRSSADI | | Aluminum Alloy | Round | 788FL5 | | |
| 16 ft | 1 | SPNRSSA18V, SPNRSSADI | | Aluminum Alloy | Round | 788FL7 | | |
| 22 ft | 1 | SPNRSSA18V, SPNRSSADI | | Aluminum Alloy | Round | 788FMO | | |



Westward
10N694

Concrete Mixers

MARSHALLTOWN MIXERS

Wheelbarrow Mixer—Hand-tow mixer includes stand and has removable handles for easy storage. Tires are made of flat-free rubber.



KUSHLAN WHEELBARROW MIXERS

21-rpm electric mixers feature 8" power cords and 3/16"-thick, easy-clean polyethylene drums that resist dents, cracking, and rust. Welded steel frames. Steel mixing blades.

ACCESSORIES

Mixer Stand 6LCX9 converts mixer to a stationary unit.

| Description | Size | Drum Dia. | Drum Opening | Drum Gauge/Material | Motor | Overall Length | Overall Width | Overall Height | Axle Type | Mfr. Model | Item No. |
|---|-------------|-----------|-------------------|---------------------|------------------------|----------------|---------------|----------------|----------------|-----------------|----------|
| Westward Mixers | | | | | | | | | | | |
| Wheelbarrow Mixer | 4 3/4 cu ft | 22 1/2 in | 15 3/4 in | 19 Ga., Steel | 120V | 55 1/2 in | 28 in | 49 1/2 in | Rigid | — | 10N694 |
| Marshalltown Mixers | | | | | | | | | | | |
| Wheelbarrow Mixer | 3 cu ft | 24 in | 14 1/2 in | 20, Steel | 115V Direct Drive | 45 in | 29 in | 35 1/2 in | Hand Tow | MIX3 | 32ZU70 |
| Tow Behind | 6 cu ft | 30 in | 18 in | 10 Ga., Steel | Honda Gas | 75 in | 61 in | 51 in | Steel U Spring | MIX59289 | 18F334 |
| | 6 cu ft | 30 in | 18 in | 10 Ga., Steel | 1.5 HP Electric | 78 in | 54 in | 65 in | Rubber Torsion | MIX59292 | 18F335 |
| Mortar Plaster Mixer | 12 cu ft | 31 in | 33 3/8 in x 29 in | 11 in, Heavy Steel | Gas | 85 in | 59 in | 83 in | Rubber Torsion | 1200MP8PH | 35FV48 |
| Kushlan Mixers | | | | | | | | | | | |
| Wheelbarrow Mixer | 3 1/2 cu ft | 22 in | 17 in | 3/8 in, Poly | 115V Direct Drive | 47 in | 25 in | 44 in | Rigid | 350EPOXY | 22DA16 |
| | 3 1/2 cu ft | 22 in | 17 in | 3/8 in, Poly | 115V Direct Drive | 53 in | 25 in | 42 in | Rigid | 350DD | 22DA20 |
| | 6 cu ft | 28 in | 17 1/2 in | 3/8 in, Poly | Loncin Gas | 65 in | 29 in | 43 in | Rigid | 650GAS-L | 56LA90 |
| | 6 cu ft | 28 in | 17 1/2 in | 3/8 in, Poly | Honda Gas | 65 in | 29 in | 43 in | Rigid | 650GAS-H | 56LA89 |
| | 6 cu ft | 28 in | 18 in | 3/8 in, Poly | 115V Direct Drive | 50 in | 29 in | 46 in | Rigid | 600DD | 22DA21 |
| Pedestal Mixer | 3 1/2 cu ft | 22 in | 17 in | 3/8 in, Poly | 115V Direct Drive | 57 in | 29 in | 62 in | Rigid | 350MP | 22DA24 |
| | 4 1/2 cu ft | 22 in | 17 in | 3/8 in, Poly | 120V, Direct Drive ODP | 57 in | 36 in | 62 in | Rigid | 450DD | 20CL5 |
| | 10 cu ft | 36 in | 16 3/4 in | 3/8 in, Poly | 120V, Direct Drive ODP | 56 in | 42 in | 68 in | Rigid | 1000DD | 20CL7 |
| Kushlan Accessories | | | | | | | | | | | |
| Cement Mixer Stand, For Use With 2DCL1 | | | | | | | | | | Universal Stand | 6LCX9 |
| Cement Mixer Drum, For Use With 2DCL5 | | | | | | | | | | 450-3 | 6LCY0 |
| Cement Mixer Drum Lid, For Use With 2DCL5 | | | | | | | | | | 450-4 | 6LCY1 |

metabo

Makita



Collomix

Mud Mixer & Paddles

■ Nominal Voltage 115V AC

Mixer's motor size, rotation speed, paddle style, and number of paddles determine how much material it can mix, the type of materials it mixes, and how quickly it mixes. **Corded mixers** allow long run times for repetitive tasks, maintain full power during operation, and have no batteries to recharge. **Cordless mixers** operate in areas without access to wired power, eliminate the tripping hazard of a cord, and run on brand-specific batteries. **Paddles** connect to a mud mixer and convert rotational power into mixing power.



Single Paddle
29UK09

| | | | | | Compatible Container Capacity | Trigger Style | Number of Speed Settings | Maximum Mixing Speed | Brand | Item No. |
|---|----------------------------------|--------------------|----------------------------|-------------|--|------------------|--------------------------------|----------------------------|-----------------------|-------------|
| Single-Paddle Corded Mud Mixers | | | | | | | | | | |
| M14 Threaded Paddle Connection | | | | | | | | | | |
| Number of Speed Settings | Number of Handle Positions | Brushless Motor | Maximum Mixing Speed | Item No. | 25 gal | Lock-On | 2 | — | Bn Products Usa | 56GW27 |
| | | | | | 25 gal | Lock-On | Continuous | 800 RPM | QEP | 61HP14 |
| | | | | | Quick-Disconnect Hexafix Paddle Connection | | | | | |
| | | | | | 10 gal | Dual Safety | 1 | 650 RPM | Collomix | 29UK09 |
| | | | | | 17 gal | Dual Safety | 2 | 620 RPM | Collomix | 29UK10 |
| | | | | | 24 gal | Dual Safety | 2 | 580 RPM | Collomix | 29UK11 |
| Double-Paddle Corded Mud Mixers | | | | | | | | | | |
| Quick-Disconnect Hexafix Paddle Connection | | | | | | | | | | |
| Continuous | | | | | 1 | No | 550 RPM | 483U80 | | |
| 18V DC Makita Cordless Mud Mixers | | | | | | | | | | |
| ½ in Keyed Paddle Connection | | | | | | | | | | |
| 2 | | 2 | Yes | 1,300 RPM | 225GN4 | | | | | |
| Mixing Material Application | | | | | | | | | | |
| Double Paddles | | | | | | | | | | |
| ½ in Hex Paddle Connection | | | | | | | | | | |
| Cement, Concrete, Fibrated Aluminum Roof Coating, Grout, Gypsum Lime Plaster, Mortar, Paint | | | | | 22 gal | All | 24 in | 4 ¾ in | Bn Products Usa | 56GW41 |
| Hexafix Quick-Disconnect Paddle Connection | | | | | | | | | | |
| All Materials | | | | | 13.2 gal | Low | 22 in | 4 ¾ in | Collomix | 29UK20 |
| | | | | | 23 gal | Medium | 22 in | 5 ½ in | Collomix | 29UK21 |
| Single Paddles | | | | | | | | | | |
| Hexafix Quick-Disconnect Paddle Connection | | | | | | | | | | |
| Bitumen-Free Sealing, Cementitious Grout, Leveling Compound, Slurry | | | | | 13.2 gal | Low | 23 in | 6 in | Collomix | 29UK13 |
| Concrete, Mortar, Plaster, Quartz Filled Epoxy Mortars, Smoothing Cement, Underlayments | | | | | 10.6 gal | Low | 23 in | 5 ½ in | Collomix | 29UK18 |
| Epoxy Grouts, Fillers, Glues, Grouting Compounds, Self-Leveling Underlayments, Tile Adhesive | | | | | 15.9 gal | Low | 23 in | 6 ¼ in | Collomix | 29UK16 |
| Epoxy Resin Grout, Grout, Joint Cement, Masonry Cement, Stucco | | | | | 13.2 gal | High | 23 in | 6 ¼ in | Collomix | 448K94 |
| | | | | | 6.6 gal | Low | 23 in | 4 ¾ in | Collomix | 29UK14 |
| | | | | | 9.5 gal | Low | 23 in | 5 ½ in | Collomix | 29UK15 |
| M14 Threaded Paddle Connection | | | | | | | | | | |
| Grout, Mortar, Thinset | | | | | 25 gal | High | 24 in | 5 ½ in | QEP | 35T137 |