



Diesel Engine Oil

Lubricants are designed to maintain performance and extend the life of diesel motors.

Series	SAE Grade	Size	Item No.
Chevron			
Conventional			
Delo 400 SDE	15W-40	1 qt	52HG05
	15W-40	1 gal	52HG06
Mag 1			
Conventional			
	10W-30	1 gal	20RW86
	30W	5 gal	43Y896
	30W	1 qt	43Y902
All Fleet	40W	5 gal	43Y897
	15W-40	1 gal	43Y894
	15W-40	55 gal	43Y901
FMX	15W-40	1 qt	43Y899
Synthetic			
FMX	5W-40	1 gal	43Y898
Mobil			
Conventional			
	30W	1 gal	805Y43
	30W	1 qt	805Y44
	30W	1 gal	805Y46
	30W	5 gal	805Y47
Delvac	40W	5 gal	805Y45
	40W	1 gal	805Y48
	40W	5 gal	805Y49
	40W	1 qt	805Y50
Delvac 1230	15W-40	5 gal	805Y37
	30W	1 qt	6KXK8
Synthetic			
	5W-40	1 gal	805Y30
	5W-40	5 gal	805Y31
	10W-30	1 gal	805Y33
Delvac	10W-30	1 gal	805Y35
	15W-40	1 gal	805Y34
Delvac 1 ESP	5W-40	1 gal	5XB62
Synthetic Blend			
	10W-30	1 gal	805Y38
Delvac	15W-40	1 qt	805Y40
	15W-40	2.5 gal	805Y41
	15W-40	5 gal	805Y42
Delvac 1300 Super	15W-40	1 gal	4ZF24
	15W-40	1 qt	787M95
Rotella			
Conventional			
	30W	55 gal	33GP50
	30W	1 qt	33GP53
	30W	1 gal	56RU30
T1	40W	5 gal	33GP56
	40W	1 gal	52ND95
	10W	55 gal	33GP49
Synthetic			
T6	5W-40	1 qt	33GP72
	5W-40	1 gal	52NE06
Synthetic Blend			
	10W-30	1 gal	52ND96
T4	15W-40	1 gal	52NE01
	15W-40	5 gal	52NE02
	15W-40	55 gal	52NE03
T5	10W-30	1 gal	52NE09
	15W-40	1 gal	52NE10
Valvoline			
Conventional			
	30W	1 qt	1UBY8
	30W	5 gal	4NPT4
	40W	5 gal	4NPT6
All-Terrain	15W-40	1 qt	1UBY6
	15W-40	55 gal	2MWE1
	15W-40	5 gal	4NPT7
	15W-40	1 gal	4NPT8
	15W-40	1 gal	1UBY7
Premium Blue One Solution Gen 2	15W-40	55 gal	2MWE3
	15W-40	5 gal	4NPR8
Synthetic			
Premium Blue	5W-40	55 gal	453C31
	5W-40	1 gal	4NPT1
Synthetic Blend			
Premium Blue One Solution Gen 2	10W-30	55 gal	453A89
	10W-30	1 gal	46KK33



52HG05



43Y902



4ZF24



52NE01



1UBY7



KleenDEF

DEF Diesel Exhaust Fluid

Specially blended to help meet the EPA's near-zero emission requirements in selective catalytic reduction (SCR) diesel engines.

Size	Item No.
Peak Blue DEF	
2.5 gal	48RH22
55 gal	48RH23
330 gal	48RH24
Kleen DEF	
2.5 gal	54UD30
55 gal	54UD31



48RH22



54UD30



487A71



BlueDEF Transfer Pumps

GPM	Hose Length	Includes	Voltage	Item No.
Electric Operated Drum Pump				
7 to 9	20 ft	Bracket, Dispense Hose, Fittings, Nozzle, Pump, Suction Hose	115VAC	48RH25
8 to 10	13 ft	Discharge Hose, Drum Adapter, Polyethylene Nozzle	120VAC	487A71
8 to 10	13 ft		12VDC	487A72
Electric Operated Tote Pump				
8 to 10	20 ft	4 ft Suction, Discharge Hose, Stainless Steel Nozzle	120VAC	487A77
8 to 10	20 ft	4 ft Suction, Discharge Hose, Polyethylene Nozzle	120VAC	487A76
8 to 10	20 ft		12VDC	487A79
Hand Operated Drum Pump				
0.13	20 ft	Drum Adapter, Expandable Downtube	—	487A70



Diesel Exhaust Fluid (DEF) Filters

Filters remove contaminants to ensure proper function of your vehicle's Selective Catalytic Reduction (SCR) system.



493V07

Application	Mfr. Model	Item No.
Diesel Exhaust Fluid Filter		
Autocar, Blue Bird, DAF, Ford, Foton, Freightliner, Heuliez, Hino, International, Isuzu, Iveco, Kenworth, Mack, Peterbilt, R.V.I., Spartan, Solaris, Volvo, Western Star, and Off-Hwy Equipment using Diesel Exhaust Fluid	PE17000	493V07
Urea Diesel Exhaust Fluid Filter		
Freightliner, Mercedes-Benz, Western Star Buses, Trucks	PE5272	36VX13
Challenger, Fendt, Massey Ferguson Tractors; Volvo Trucks	PE5271	49T348