WESTWARD

LINCOL





No. of Pieces	- Includes	Brand	ltem No.
Grease Fit			
60	(8) ½-27 PTF 45°, (8) ½-27 PTF 90°, (15) ½-27 PTF Straight, (25) ½-28 SAE-LT Straight (1) Professional Hand Coupler, (1) Air Operated Equipment Coupler, (1) Right Angled Coupler, (1) Needle Nose Dispenser	Westward	2CAN7
60	(12) M8-1mm 90°, (12) M6-1mm Straight, (12) M8-1mm Straight, (20) M10-1mm Straight (1) Professional Hand Coupler, (1) Air Operated Coupler, (1) Right Angled Coupler, (1) Needle Nose Dispenser	Westward	2CAN8
100	(20) ½" NPT Straight, (40) ½"-28" Straight Short Thread, (10) ½"-28" 45°Short Thread, (10) ½" NPT 65°,(10) ½" NPT 90°,(10) ½"-28" 90°Short Thread	Lincoln	6Y864
<b>Grease Fit</b>	ting and Installation Tool Kit		
101	1/8"-27 PTF [(22) Straight, (5) 30°, (10) 45°, (10) 65°, (10) 90°], 1/4"-28 SAE-LT [(22) Straight, (10) 45°, (10) 90°], Easy Out Tool (Small), Easy out Tool (Large), Plastic Case	Westward	5NUF2
101	M6-1mm [(30) Straight, (5) 45°, (10) 90°], M8-1mm [(14) Straight, (5) 90°], M10-1mm [(20) Straight, (5) 45°, (10) 90°], Easy Out Tool (Small), Easy Out Tool (Large), Plastic Case	Westward	5NUF3
<b>Grease Fit</b>	ting and Fitting Cap Kit		
65	1/3"-27 PTF, 1/4"-28 SAE-LT, M6-1mm Straight, M8-1mm Straight, Easy Out Tools, Small, Large, Grease Fitting Caps, Professional 4 Jaw Couplers,, Grease Fitting Thread Tester	Westward	13X065
100	<ul> <li>(15) <sup>1</sup>/<sub>8</sub>-27 Straight, (10) <sup>1</sup>/<sub>8</sub>-27 45°, (10) <sup>1</sup>/<sub>8</sub>-27 90°, (15) <sup>1</sup>/<sub>8</sub>-28 Straight,</li> <li>(10) <sup>1</sup>/<sub>8</sub>-28 45°, (10) <sup>1</sup>/<sub>8</sub>-28 90°, (10) Grease Fitting Caps Red, (10) Grease Fitting Caps Yellow, (10) Grease Fitting Caps Black, Plastic Case</li> </ul>	Westward	3APF4
100	(15) M6-1mm Straight, (10) M6-1mm 90°, (15) M8-1mm Straight, (5) M8-1mm 90°, (15) M10-1mm Straight, (10) M10-1mm 90°, (10) Grease Fitting Caps Red, (10) Grease Fitting Caps Vellow, (10) Grease Fitting Caps Black,Plastic Case	Westward	3APF5
194	(36) %-27 Straight, (12) %-27 30°, (12) %-27 45°, (12) %-27 65°, (12) %-27 90°, (24) %-28 Straight, (12) %-28 45°, (12) %-28 90°, (10) Greens Grease Fitting Cap with Retaining Ring, (10) White Grease Fitting Cap with Retaining Ring, (10) White Grease Fitting Cap with Retaining Ring, (10) White Grease Fitting Cap with Retaining Ring, (10) Black Grease Fitting Cap with Retaining Ring, (10) Black Grease Fitting Cap with Retaining Ring, (2) %, % Fitting Cap with Retaining Ring, (10) Black Grease Fitting Cap with Retaining Ring, (2) %, % Fitting Cap with Retaining Ring, (2) %.	Kingfisher	4RZK9
Easy Out T			
_	Hardened Tap for Retapping ¼-28 Holes, Screw Extractor for Removing Worn and Broken Grease Fittings	Westward	15F208



52PA04

52PA07

## Grease Fittings

4RZK9



**Grease Fitting Kits** 

 Find more Grease Fitting sizes and styles on Grainger.com<sup>®</sup> Meet appropriate SAE and DIN requirements.

Fitting Thread Size	Overall Length lead Angle	Fitting Material	Grease Fitting Style	Brand	ltem No.	Pkg. Qty.
Juaight h	icau Aligic					
M10- 1.00mm	5% in	Stainless Steel	Standard	Westward	52NZ95	10
1.0011111	5∕s in	Steel	Standard	Westward	52NZ38	10
M10- 1.50mm	16 mm	Steel	Standard	Kingfisher	1XGK5	10
M6-	14 ½ mm	Steel	Thread Forming	Kingfisher	3APA8	10
1.00mm	5⁄8 in	Stainless Steel	Standard	Westward	52NZ82	10
	5⁄8 in	Steel	Standard	Westward	52NZ27	10
3/16"	1⁄2 in	Steel	Drive (Push-In)	Kingfisher	2PA93	10
9/16	<sup>33</sup> ⁄64 in	Stainless Steel	Drive (Push-In)	Westward	52NZ78	10
	<sup>17</sup> / <sub>32</sub> in	Steel	Drive (Push-In)	Westward	52NZ26	10
	<sup>49</sup> ⁄64 in	Steel	Button Head	Kingfisher	5PU34	10
1⁄8⁼-27	<sup>21</sup> / <sub>32</sub> in	Stainless Steel	Standard	Westward	52NZ85	10
	<sup>21</sup> / <sub>32</sub> in	Steel	Standard	Westward	52NZ29	10
	27/32 in	Steel	Standard	Westward	52NZ99	10

Fitting Thread Size	Overall Length	Fitting Material	Grease Fitting Style	Brand	ltem No.	Pkg. Qty.
1/8"-28	<sup>39</sup> ⁄64 in	Steel	Standard	Kingfisher	3ANZ2	10
78-20	<sup>39</sup> ⁄64 in	Stainless Steel	Standard	Kingfisher	3APA1	5
1⁄4⁼-18	<sup>53</sup> ⁄64 in	Stainless Steel	Standard	Kingfisher	2PA89	10
74 -10	<sup>53</sup> ⁄64 in	Steel	Button Head	Kingfisher	5PU35	10
	7∕8 in	Steel	Standard	Westward	52NZ34	5
1⁄4"-19	<sup>13</sup> ⁄16 in	Steel	Standard	Kingfisher	3ANZ3	10
1⁄4=-28	<sup>35</sup> ⁄64 in	Stainless Steel	Standard	Westward	52NZ73	10
	<sup>35</sup> ⁄64 in	Steel	Standard	Westward	52NZ23	10
90 ° Head	Angle					
	<sup>27</sup> / <sub>32</sub> in	Stainless Steel	Standard	Westward	52PA05	10
1⁄8"-27	<sup>49</sup> ⁄64 in	Steel	Thread Forming	Kingfisher	3APA7	10
	<sup>27</sup> / <sub>32</sub> in	Steel	Standard	Westward	52NZ59	10
	<sup>31</sup> / <sub>32</sub> in	Steel	Standard	Westward	52PA18	10
1⁄8"-28	3⁄4 in	Steel	Standard	Kingfisher	3ANZ8	10
1⁄4"-18	<sup>15</sup> ⁄16 in	Steel	Standard	Kingfisher	2PA87	10
1/4"-28	<sup>49</sup> ⁄64 in	Stainless Steel	Standard	Westward	52PA04	10
94 <b>-</b> 20	49⁄64 in	Steel	Standard	Westward	52NZ48	10
45 ° Head	Angle					
1/8"-27	55/64 in	Stainless Steel	Standard	Westward	52PA07	10
78 -Z7	55/64 in	Steel	Standard	Westward	52NZ57	10
1⁄8"-28	<sup>61</sup> /64 in	Steel	Standard	Kingfisher	3ANZ4	10
1⁄4"-18	1 1/8 in	Steel	Standard	Kingfisher	2PA86	10
1/4"-28	<sup>53</sup> ⁄64 in	Stainless Steel	Standard	Westward	52PA03	10
74 -20	<sup>53</sup> ⁄64 in	Steel	Standard	Westward	52NZ49	10

	6¥877		Control Guns & Valves		
Item	Inlet (in.)	Outlet (in.)	Max. Pressure (psi)	Mfr. Model	Item No.
Legacy					
Booster Gun	1/4 in NPT	Coupler	10,000 psi	LCG1-01	6Y641
Grease Control Gun	1/8 in (F)NPT	1/8 in (H)NPT	7,500 psi	LCG2	4ZT53
Lincoln					
High Pressure Control Handle	3% in (F)NPT	1/8 FNPT	7,500 psi	81495	6Y914
High Pressure Control Handle	1/4 in (F)NPT	1/8 FNPT	7,500 psi	740	6Y877
Westward					
Booster Valve with Z Swivel	1/4 in (F)NPT	1/8 FNPT	_	_	1ZTD2
Control Valve	1/4 in (F)NPT	1/8 FNPT	7,500 psi	_	1ZTD1
Grease Control Valve	1/4 in (F)NPT	1/8 FNPT	10.000 psi	_	2CAN6



## Grease Gun Tool Kits

ltem No.
1ZTC9
45FG56
1XGN7

868 **GRAINGER**®

Find even **MORE** on **Grainger.com**®

1-800-GRAINGER (472-4643)

WESTWARD