

# HAND TOOLS

## Pipe Threading Stands & Pipe Freeze/Thaw Units

Scan. Order. Done.  
Details on page A1.



**Tribench  
53RE87**

**V-Head Pipe  
Stand  
22XR01**



**Bench  
Chain Vise  
1VUV7**



**Threading  
Machine  
Stand  
2ZB62**



### Pipe Threading Stands and Vises

**Roller Head Pipe Stands**—Roller heads support pipe weighing up to 2500 lb. The rollers allow the pipe to be turned while work is in progress. Additional stands are recommended for longer and heavier lengths of pipe. 22XP99 and 3FE65 allow height adjustment from 32" to 55".

**Pipe Threading Machine Stands**—Wheel stands feature 16" wheels. 2ZB62 features equipment cabinet for storage and includes 2 internal shelves and a large external shelf. For use with RIDGID Pipe Threading Machines 3RY43, 3FE64, and 4CW39, sold on page 871.

**V-Head Pipe Stands**—Allow height adjustments up to 52" on select models.

Pipe Cap.	Overall Height	Load Capacity	Leg Type	Max. Leg Spread	Brand	Item No.
<b>Pipe Stand with Roller Head</b>						
½ to 16 in	27 to 50 in	2,500 lb	Rigid	22 in	Rothenberger	53RF40
<b>Portable Tribench</b>						
½ to 6 in	36 in	48 lb	Collapsible Tripod	51 ½ in	Rothenberger	53RE87
<b>Roller Head Pipe Stand</b>						
½ to 12 in	32 to 55 in	2,500 lb	Adjustable	22 in	Westward	22XP99
½ to 12 in	32 to 55 in	1,000 lb	Adjustable	—	Ridgid	3FE65
½ to 16 in	27 to 50 in	2,500 lb	Folding	22 in	Rothenberger	53RF38
2 to 36 in	34 in	2,500 lb	Adjustable	30 in	Ridgid	1VXG9
<b>V-Head Pipe Stand</b>						
½ to 12 in	28 to 52 in	2,500 lb	Adjustable	22 in	Westward	22XR01
½ to 12 in	28 to 52 in	2,500 lb	Adjustable	—	Ridgid	4CX07
½ to 16 in	27 to 50 in	2,500 lb	Rigid	22 in	Rothenberger	53RF36
½ to 16 in	27 to 50 in	2,500 lb	Folding	22 in	Rothenberger	53RF37
½ to 16 in	27 to 50 in	2,500 lb	Rigid	22 in	Rothenberger	53RF39
12 in	28 to 52 in	2,500 lb	Folding	—	Ridgid	26C170

Pipe Cap.	Type	Overall Height	Brand	Item No.	
<b>Bench Chain Vises</b>					
½ to 2½ in	Top Screw	3½ in	Ridgid	1VUV7	
	Top Screw	3½ in	Westward	22XR02	
¼ to 4 in	Top Screw	4 in	Ridgid	1VUV9	
	Top Screw	4 in	Westward	22XR03	
¼ to 6 in	Top Screw	4½ in	Ridgid	1VUW2	
	Top Screw	4½ in	Westward	22XR04	
½ to 8 in	Top Screw	5 in	Westward	22XR05	
	Top Screw	5 in	Ridgid	1VUW4	
<b>Bench Yoke Vises</b>					
½ to 2 in	—	4½ in	Ridgid	1ED98	
	—	—	Westward	22XP96	
½ to 3 in	With Pipe Jaws	12½ in	Ridgid	4CPD8	
½ to 4 in	—	5 in	Ridgid	4NV31	
	—	—	Westward	22XP97	
½ to 6 in	With Pipe Jaws	19 in	Ridgid	4CPD9	
	—	—	—	—	
<b>Portable Chain Vises</b>					
½ to 2½ in	—	37 in	Ridgid	4ZA21	
	Tri-Stand	48 in	Ridgid	13CS94	
¼ to 6 in	—	35 in	Westward	22XP94	
	Tri-Stand	48 in	Ridgid	13CS95	
<b>Portable Yoke Vises</b>					
½ to 2½ in	—	35½ in	Ridgid	1VUV5	
	—	—	Westward	22XP98	
<b>For Use With</b>					
<b>Pipe Threading Machine Stand w/Cabinet</b>		400 lb.	32 in	Ridgid	2ZB62
5A191, 3RY43, 3FE64, 4CW39 Pipe Threading Machines					
<b>Pipe Threading Machine Stand w/Trolley</b>		400 lb.	32 in	Ridgid	1EZ17
5A191, 3RY43, 3FE64 and 4CW39 Pipe Threading Machines					
<b>Bending Threading Cart</b>		2000 lb.	28 ½ in	Greenlee	449T96
Mfr. No. 555, 854DX, 855DX, 467					



**Superfreeze Pipe  
Freezing Unit  
6YJ42**



**Pipe Freezing Spray  
56MD48**



**Pipe Thawing Unit  
1XEA2**



### Pipe Freezing/Thawing Units

**Superfreeze Pipe Freezing Unit**—Make repairs without shutting down water systems. System acts as a mini-refrigeration unit that circulates refrigerant to its aluminum freeze heads. Self-contained unit uses no consumables. Pipe capacity: ½" to 2" steel, ½" to 2½" copper tube.

**Pipe Thawing Unit**—Electric current clears frozen metal pipes in minutes without digging or breaking through walls. Two 25-ft. cables clamp on to provide continuous heat for 4 ft. to 150 ft. of ½" to 1½" dia. pipes. Adjustable current output.

Description	Brand	Mfr. Model	Item No.
Superfreeze Pipe Freezing Unit	Ridgid	68967	6YJ42
Pipe Freezing Spray	Rothenberger	1500003432	56MD48
Pipe Freezing Spray Kit	Rothenberger	1500003034	56MD47
Pipe Thawing Unit	Ridgid	62747	1XEA2



**ZIRCON**

### Electronic Water Detector

Automatically sounds a loud alarm when in direct contact with water, alerting user to leaks and flooding. Features low-battery warning. Floats on surface. Splash- and water-resistant. Not waterproof. Made of molded, impact-resistant plastic. Powered by 9V battery (not included).

Description	Mfr. Model	Item No.
Water Detector	64003	1TJT7



### Pressure Test Pump

Use to test piping systems for leaks. Features 1-valve operation, automatic pressure check valves, corrosion-proof construction, and variable lever-arm design. Pressure gauge is protected from damage; dirt filter is replaceable.



Max. Pressure (psi)	Connection Size (NPT)	Hose Length (in.)	Mfr. Model	Item No.
725	½ in	30	50557	1XD23