



20C895

STEELMAN. Electronic Stethoscopes

Sensor tips can be placed directly on a housing to amplify sound while the headphones shut out surrounding noise. Nonconductive microphone will not zap computer circuitry. Flexible-shaft probe reaches into hard-to-reach areas. 20C895 EngineEAR II adds 7-level control for extra sensitivity and reduced distortion.



Description	Mfr. Model	Item No.
EngineEAR Electric Stethoscope	65001	20C897
EngineEAR II Electronic Stethoscopes	06800	20C895
ChassisEAR Electric Stethoscope	06600	20C894



3T063

4R388

OTC mityvac PROTO[®] Compression Test Equipment

Allow you to perform standard maintenance and diagnostics that can help keep your fleet on the road.

Includes	Mfr. Model	Brand	Item No.
Gasoline Engine			
Polished Chrome Gauge and all Chrome Adapters	5606	OTC	3T063
(2) 3/4 in Gauge with High Impact Lens, Rubber Boot, (4) Scales of Measure (psi, kg/cm ² , bar, kPa), 10 in Hose, Quick Release Coupler, (2) 14mm Short Thread Adapter, 6 1/2 in Hose, (3) 12 in Hose, 14mm Long Thread Adapter, 18mm Short Thread Adapter, 18mm Long Thread Adapter, 10mm Thread Small Engine Adapter, 12mm Thread Small Engine Adapter, Quick Release Air Hold Adapter, Custom Blow Molded Case, Field Service Kit	MV5530	Mityvac	45PG66
Test Gauge and Rubber Boot, 10 in High Pressure Hose, Female Quick Release Coupler, 14mm Hose Long Thread, 14mm Hose Short Thread, 18mm Hose Short Thread, 18mm, 16mm, 14mm, 12mm Long Thread Adapters, Air Hold Adapter, Field Service Kit, and Custom Molded Case	MV5532	Mityvac	1XGR3
Adapters for Regular 18mm Spark Plugs and for Regular & Long 14mm Spark Plugs	JCTR10	Proto	4R388
Diesel Engine			
Right Angle Adapter, Digital Test Gauge, Glow Plug Adapters, Injector Adapters, Molded Case	MV5535	Mityvac	3FH26



1MZU2



Mechanic's Stethoscopes

Diagnostic tools help pinpoint potential trouble spots in noisy engine compartments, blocking the distraction of surrounding sound.

Features	Brand	Mfr. Model	Item No.
Aluminum Steel Probe and Needle	Westward	1MZU2	1MZU2
Aluminum Steel Probe and Needle and Shock-Resistant Handle	Gearwrench	835D	2ZPG5
Spring Steel Diaphragm and Shock-Resistant Handle	Proto	JFP500A	6RKV0



38EG22

2TVR4

OTC Barring Socket and Tool

Socket 38EG22 helps rotate Mack E7 and Cat 3208 diesel engines. 2TVR4's load-bearing collar offers friction-free operation while rotating Cummins B and C series diesel engines and 5.9L diesels. Works with a 1/2" square drive ratchet or breaker bar.

Item	Mfr. Model	Item No.
Engine Barring Socket	6749	38EG22
Barring Tool	7471A	2TVR4



1UBG2



45JW57



Piston Ring Tension Bands

Application	Includes	Item No.
Install Pistons 3 1/2 to 7 in, 89 mm to 178 mm Dia For Trucks and Tractors	(1) Square Handle, (4) Spring Steel Tension Bands	1UBG2
Assemble and Disassemble the Piston	Clip Pliers., Metal Bands for Piston Rings 2 7/8 in to 3 1/8 in, 3 1/8 in to 3 1/2 in, 3 1/2 in to 3 3/4 in, 3 3/4 in to 4 1/8 in, 4 1/8 in to 4 1/2 in, 4 1/2 in to 4 3/4 in	45JW57



2ZPJ9

45FF52



Engine Cylinder Hone

Adjustable spring tension and spread limiter help provide positive cutting action to hone and remove glaze. The hone is complete with 240-grit medium grit stones.

For Use With	Brand	Mfr. Model	Item No.
2834D, 2835D, 2836DD Engine Cylinders	Gearwrench Westward	2833D 45FF52	2ZPJ9 45FF52