

1-800-GRAINGER (472-4643)

Concrete Mixers



WESTWARD WHEELBARROW MIXERS

Mixers feature metal blades and a gear locking system. 10N693 features a heavy-duty frame and removable handles for compact storage. 10N694 has a welded steel frame, torsion bar suspension, and easy-to-use dump mechanism.

MARSHALLTOWN MIXERS

Wheelbarrow Mixer—Hand-tow mixer includes stand and has removable handles for easy storage. Tires are made of flat-free rubber.

Tow-Behind Concrete Electric Mixers, 18F334 and 18F335—25-rpm mixers feature reinforced square tubular frame with steel channel yoke; wheel- and hand-brake tilting mechanism; and any-position frictional hand brake.

KUSHLAN WHEELBARROW MIXERS

21-rpm electric mixers feature 8" power cords and 5/16"-thick, easy-clean polyethylene drums that resist dents, cracking, and rust. Welded steel frames. Steel mixing blades.

KUSHLAN PEDESTAL-MOUNTED MIXERS

21-rpm electric mixers swivel 360° and can be discharged in any direction. Drums can be adjusted to the correct angle for particular mixes. Welded steel frames are easily broken down without tools. 8" power cords included.

22DA24—This mixer is designed with polyethylene drum, heavy-gauge steel tubing frame, and telescoping handles.

2DCL5—This mixer has a steel frame that's easy to move from place to place. Food-grade liner extracts easily from basket. 10" x 2 1/4" flat-free tires.

2DCL7—Drum holds ten 80-lb. bags of premix concrete. Driven by a 20:1 gear box with a chain sprocket drive system. Aggressive mixing blades. 16" x 4" flat-free tires.

ACCESSORIES

Mixer Stand 6LXC9 converts mixer to a stationary unit.



Description	Size	Drum Dia.	Drum Opening	Drum Gauge/Material	Motor	Overall Length	Overall Width	Overall Height	Axle Type	Mfr. Model	Item No.
Westward Mixers											
Wheelbarrow Mixer	3 1/2 cu ft	20 1/2 in	16 3/4 in	15 ga. Poly	115V	48 1/2 in	25 1/2 in	41 3/4 in	Rigid	—	10N693
	4 3/4 cu ft	22 1/2 in	15 3/4 in	19 Ga., Steel	120V	55 1/2 in	28 in	49 1/2 in	Rigid	—	10N694
Marshalltown Mixers											
Wheelbarrow Mixer	3 cu ft	24 in	14 1/2 in	20, Steel	115V Direct Drive	45 in	29 in	35 1/2 in	Hand Tow	MIX3	32ZU70
Tow Behind	6 cu ft	30 in	18 in	10 Ga., Steel	Honda Gas	75 in	61 in	51 in	Steel U Spring	MIX59289	18F334
	6 cu ft	30 in	18 in	10 Ga., Steel	1.5 HP Electric	78 in	54 in	65 in	Rubber Torsion	MIX59292	18F335
Mortar Plaster Mixer	12 cu ft	31 in	33 3/8 in x 29 in	11 in, Heavy Steel	Gas	85 in	59 in	83 in	Rubber Torsion	1200MP8HP	35FV48
Kushlan Mixers											
Wheelbarrow Mixer	3 1/2 cu ft	22 in	17 in	5/16 in, Poly	115V Direct Drive	47 in	25 in	44 in	Rigid	350EPOXY	22DA16
	3 1/2 cu ft	22 in	17 in	5/16 in, Poly	115V Direct Drive	53 in	25 in	42 in	Rigid	350DD	22DA20
	6 cu ft	28 in	17 1/2 in	5/16 in, Poly	Loncin Gas	65 in	29 in	43 in	Rigid	650GAS-L	56LA90
	6 cu ft	28 in	17 1/2 in	5/16 in, Poly	Honda Gas	65 in	29 in	43 in	Rigid	650GAS-H	56LA89
	6 cu ft	28 in	18 in	5/16 in, Poly	115V Direct Drive	50 in	29 in	46 in	Rigid	600DD	22DA21
Pedestal Mixer	3 1/2 cu ft	22 in	17 in	5/16 in, Poly	115V Direct Drive	57 in	29 in	62 in	Rigid	350MP	22DA24
	4 1/2 cu ft	22 in	17 in	5/16 in, Poly	120V, Direct Drive ODP	57 in	36 in	62 in	Rigid	450DD	2DCL5
	10 cu ft	36 in	16 3/4 in	5/16 in, Poly	120V, Direct Drive ODP	56 in	42 in	68 in	Rigid	1000DD	2DCL7
Kushlan Accessories										Universal Stand	6LXC9
Cement Mixer Stand, For Use With 2DCL1										450-3	6LCY0
Cement Mixer Drum, For Use With 2DCL5										450-4	6LCY1
Cement Mixer Drum Lid, For Use With 2DCL5											

Collomix® Handheld Concrete Mixers

HEXAFIX coupling lets you change the mixing paddle quickly without tools. Feature reduced noise and electronic speed control. Easy-to-operate with straight back and ergonomic grip handles. Double-action trigger has safety lock-off to prevent unintentional machine start-up. 29UK09 can be used with cement, plaster, and ready-mixed mortar. 29UK11 is for plaster, mortar, screed, concrete, and quartz-filled epoxy resins. Counter-rotating mixer 29UK12 has no counter-torque, making it easy to move in heavy and viscous material. Ideal for miscellaneous mortars, slightly moist mixes, plaster, screed, coverings, filler, filled and unfilled epoxy resin, cement, and bitumen mixes.



Description	HP	Rotation Speed at Load	Mixing Volume	Mfr. Model	Item No.
Handheld Mixers					
Mixer	1 1/32 hp	0 to 590 rpm	0 to 10 gal	X01R	29UK09
2-Gear Mixer	1 4/64 hp	0 to 470 rpm, 0 to 640 rpm	0 to 17 gal	X04R	29UK10
2-Gear Mixer	2 7/64 hp	0 to 410 rpm, 0 to 580 rpm	0 to 23.5 gal	X06R	29UK11
2-Paddle Mixer	1 29/32 hp	0 to 430 rpm	0 to 25 gal	X055R	29UK12
Description	For Use With	Mfr. Model	Item No.		
Mixing Paddles					
2-Blade	CX100, X01	WK120HF	29UK14		
3-Blade	CX600, X06	MK160HF	29UK19		
Bird Cage	CX100, X01	KR120HF	29UK16		
Low Viscosity	Mfr. No. X04, X06	DLX152HF	29UK13		
Dual	CX44, X055	MKD140HF	29UK21		
Concrete Stirring Paddle	Mfr. No. X04, X06	WK140HF	29UK15		

Sign in to **Grainger.com®** to see **YOUR Pricing** and **MORE**