



## Wheeled Battery Chargers

Provide battery charging and maintenance to help keep fleet vehicles powered up and ready to drive. Chargers are wheeled and have a handle to ease transport from different locations.

**Boosting**—Provides high-amperage power to start the vehicle if the battery has enough power to turn the engine over, but not sufficient to start the engine.

**Charging**—Allows a weak or dead battery to become fully charged. The procedure may take several hours to complete.

**Maintaining**—Detects when a battery drops below a certain threshold and then supplies a very low-amperage charge to the battery.



**Associated Equip**  
**55CN48**



**DSR Proseries**  
**485C83**



**Schumacher**  
**Electric**  
**444N26**



**Westward**  
**473X76**

| For Use With Battery Type              | For Battery Voltage               | Boost Current @ Voltage            | Charging Current @ Voltage                     | Maintaining Current @ Voltage     | Charge Type   | Cable Length | Power Cord Length | Includes   | Item No. |
|--|-----------------------------------|------------------------------------|--|-----------------------------------|---------------|--------------|-------------------|--|----------|
| <b>Associated Equip</b>                |                                   |                                    |  |                                   |               |              |                   |  |          |
| <b>Boosting</b>                        |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, Wet Cell                          | 12 V DC                           | 1100 A @ 12V                       | 10 A @ 12V                                     | —                                 | Manual On/Off | 8 ft         | 6 ½ ft            | Clamp Bar for Clamp Storage  | 40GL85   |
| <b>Boosting, Charging</b>              |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, EFB, Lead Acid                    | 6 V DC, 12 V DC                   | 250 A @ 12V                        | 60 A @ 12V, 70 A @ 6V                          | 60 A @ 12V, 70 A @ 6V             | Timer         | —            | —                 | Clamp Bar for Clamp Storage  | 55CN46   |
|  | 6 V DC, 12 V DC, 24 V DC          | 280 A @ 12V                        | 30 A @ 24V, 65 A @ 12V, 70 A @ 6V              | 30A @ 24V, 65A @ 15.5V, 70 A @ 6V | Timer         | —            | —                 | Clamp Bar for Clamp Storage  | 55CN44   |
| AGM, EFB, LED Acid                     | 6 V DC, 12 V DC                   | 265 A @ 12V                        | 60 A @ 12V, 70 A @ 6V                          | 60 A @ 12V, 70 A @ 6V             | Timer         | —            | —                 | Clamp Bar for Clamp Storage, Stop/Go Light for Polarity Indication   | 55CN45   |
|  | 6 V DC, 12 V DC                   | 375 A @ 12V, 375 A @ 6V            | 100 A @ 6V, 75 A @ 12V                         | —                                 | Timer         | 8 ft         | 10 ft             | Clamp Bar for Clamp Storage, Protective Gauge Cover, Stop/Go Light for Polarity Indication   | 29RV90   |
| Deep Cycle, Lead Acid                  | 6 V DC, 12 V DC, 18 V DC, 24 V DC | 400 A @ 12V                        | 100 A @ 6V, 40 A @ 24V, 50 A @ 18V, 80 A @ 12V | —                                 | Timer         | 8 ft         | 10 ft             | Clamp Bar for Clamp Storage, Protective Gauge Cover, Stop/Go Light for Polarity Indication   | 11Z379   |
| <b>Boosting, Charging, Maintaining</b> |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, Deep Cycle, EFB, Gel, Lead Acid   | 12 V DC                           | 270 A @ 12V                        | 60 A @ 12V                                     | 14.4 A @ 12V                      | Smart         | 6 ft         | 6 ft              | Clamp Bar for Clamp Storage  | 29RV97   |
|  | 12 V DC                           | 270 A @ 12V                        | 60 A @ 12V                                     | 15 A @ 12V                        | Smart         | 6 ft         | 6 ft              | 15A Memory Saver Port and OBDII Cable, Clamp Bar for Clamp Storage, Dead Battery Override Control                                      | 29RV98   |
|  | 12 V DC, 24 V DC                  | 270 A @ 12V, 270 A @ 24V           | 30 A @ 24V, 70 A @ 12V                         | 70 A @ 14.8V                      | Smart         | 6 ft         | 6 ft              | Clamp Bar for Clamp Storage, Dead Battery Override Control   | 29RW19   |
|  | 12 V DC, 24 V DC                  | 200 A @ 12V, 200 A @ 24V           | 30 A @ 24V, 70 A @ 12V                         | 70 A @ 14.8V                      | Smart         | 6 ft         | 6 ft              | Clamp Bar for Clamp Storage, Dead Battery Override Control, Quick Disconnect DC Leads Change to 13 ft Leads with NATO Plug             | 45RK19   |
| AGM, Deep Cycle, EFB, Gel, Lithium     | 12 V DC                           | 270 A @ 12V                        | 60 A @ 12V                                     | 60 A @ 15.5 V                     | Smart         | —            | 6 ft              | Adjustable Voltage Re-Flash Mode, Clamp Bar for Clamp Storage  | 55CN47   |
|  | 12 V DC                           | 270 A @ 12V                        | 60 A @ 12V                                     | 60 A @ 15.5 V                     | Smart         | —            | 6 ft              | 20 A Memory Saver Port and OBDII Cable, Adjustable Voltage Re-Flash Mode, Polarity Indicated and Polarity Protected with Audible Alarm | 55CN48   |
| Deep Cycle, Lead Acid                  | 6 V DC, 12 V DC                   | 200 A @ 12V, 200 A @ 6V            | 10 A @ 12V, 40 A @ 12V, 40 A @ 6V              | 14.4 A @ 12V                      | Timer         | 6.5 ft       | 6 ft              | Clamp Bar for Clamp Storage  | 29RV96   |
| <b>Charging</b>                        |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, Deep Cycle, EFB, Gel, Lead Acid   | 12 V DC                           | 130 A @ 12V                        | 45 A @ 12V                                     | 45 A @ 12V                        | Smart         | 6 ft         | 6 ft              | Clamp Bar for Clamp Storage, Dead Battery Override Control   | 29RV91   |
| AGM, Wet Cell                          | 12 V DC                           | 1100 A @ 12V                       | 10 A @ 12V                                     | —                                 | —             | 8 ft         | 6 ½ ft            | Clamp Bar for Clamp Storage  | 11Z387   |
| <b>DSR Proseries</b>                   |                                   |                                    |  |                                   |               |              |                   |  |          |
| <b>Boosting, Charging, Maintaining</b> |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, Deep Cycle, Gel                   | 6 V DC, 12 V DC                   | 50 A @ 12V, 50 A @ 6V              | 6 A @ 12V, 6 A @ 6V                            | 0.14 A @ 13.2V                    | Float         | 2 ft         | 6 ft              | (4) Cable Clamp Cleats   | 485C79   |
|  | 6 V DC, 12 V DC                   | 50 A @ 12V                         | 125 A @ 6V, 15 A @ 6V, 15A @ 12V, 275 A @ 12V  | 4 A @ 12V                         | Float         | 17 ft        | 9 ft              | (4) Cable Clamp Cleats, Memory Saver Cable   | 485C81   |
|  | 6 V DC, 12 V DC, 24 V DC          | 50 A @ 6V, 50 A @ 12V              | 30 A @ 24V, 15 A @ 6V, 15 A @ 12V              | 4 A @ 12V                         | Float         | 17 ft        | 9 ft              | (4) Cable Clamp Cleats, Memory Saver Cable   | 485C83   |
|  | 12 V DC                           | 50 A @ 12V                         | 20 A @ 12V                                     | 4 A @ 12V                         | Float         | 17 ft        | 9 ft              | (4) Cable Clamp Cleats   | 485C80   |
|  | 12 V DC                           | 150 A @ 24V, 250 A @ 12V           | 50 A @ 12V                                     | 4 A @ 12V                         | Float         | 17 ft        | 9 ft              | (4) Cable Clamp Cleats   | 485C82   |
|  | 12 V DC                           | 150 A @ 24V, 250 A @ 12V           | 50 A @ 12V                                     | 4 A @ 12V                         | Float         | 17 ft        | 9 ft              | (4) Cable Clamp Cleats   | 485C82   |
| <b>Charging</b>                        |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, Gel, Lead Acid                    | 6 V DC, 12 V DC                   | 25 A @ 12V, 25 A @ 6V, 50 A @ 12V  | 10 A @ 12V                                     | —                                 | Timer         | 6 ft         | 6 ft              | —  | 60JJ13   |
|  | 12 V DC, 24 V DC                  | 25 A @ 12V, 25 A @ 24V, 50 A @ 12V | 10 A @ 12V                                     | —                                 | Timer         | 6 ft         | 6 ft              | —  | 60JJ14   |
| <b>Quickcable</b>                      |                                   |                                    |  |                                   |               |              |                   |  |          |
| <b>Boosting, Charging</b>              |                                   |                                    |  |                                   |               |              |                   |  |          |
| Lead Acid                              | 12 V DC                           | Varies On Battery Installed        | 7 A @ 12V                                      | —                                 | Float         | 42 in        | —                 | —  | 49EK15   |
|  | 12 V DC                           | Varies On Battery Installed        | 7 A @ 12V                                      | —                                 | Float         | 42 in        | —                 | —  | 49EK16   |
| <b>Schumacher Electric</b>             |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, Deep Cycle, Lead Acid             | 6 V DC, 12 V DC                   | 40 A @ 12V, 40 A @ 6V              | 2 A @ 12V, 6 A @ 12V                           | 2 A @ 12V                         | Float         | 2 ft         | 7 ft              | —  | 444N26   |
| <b>Charging</b>                        |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, Deep Cycle, Gel                   | 6 V DC, 12 V DC                   | 25 A @ 12V, 25 A @ 6V, 50 A @ 12V  | 10 A @ 12V                                     | —                                 | Manual On/Off | 6 ft         | 6 ft              | —  | 60JJ11   |
|  | 6 V DC, 12 V DC                   | 20 A @ 12V, 20 A @ 6V, 40 A @ 12V  | 10 A @ 12V                                     | —                                 | Manual On/Off | 6 ft         | 6 ft              | —  | 60JJ12   |
|  | 12 V DC                           | 25 A @ 12V                         | 6 A @ 12V                                      | —                                 | Manual On/Off | 6 ft         | 6 ft              | —  | 60JJ10   |
|  | 12 V DC                           | 25 A @ 12V                         | 6 A @ 12V                                      | —                                 | Manual On/Off | 6 ft         | 6 ft              | —  | 60JJ10   |
| <b>Westward</b>                        |                                   |                                    |  |                                   |               |              |                   |  |          |
| <b>Boosting, Charging, Maintaining</b> |                                   |                                    |  |                                   |               |              |                   |  |          |
| AGM, Lead Acid                         | 6 V DC, 12 V DC                   | 130 A @ 6V, 200 A @ 12V            | 20 A @ 12V, 40 A @ 12V, 40 A @ 6V              | 40 A @ 12V, 40 A @ 6V             | Auto On/Off   | 6 ft         | 6 ft              | Alligator Clips  | 473X75   |
|  | 6 V DC, 12 V DC                   | 185 A @ 6V, 250 A @ 12V            | 60 A @ 12V, 60 A @ 6V                          | 60 A @ 12V, 60 A @ 6V             | Auto On/Off   | 6 ft         | 6 ft              | Alligator Clips  | 473X76   |
|  | 6 V DC, 12 V DC                   | 160 A @ 6V, 225 A @ 12V            | 30 A @ 24V, 60 A @ 12V, 60 A @ 6V              | 40 A @ 12V, 40 A @ 6V             | Auto On/Off   | 6 ft         | 6 ft              | Alligator Clips  | 473X77   |
|  | 6 V DC, 12 V DC, 24 V DC          | 225 A @ 12V                        | 30 A @ 24V, 60 A @ 12V, 60 A @ 6V              | 40 A @ 12V, 40 A @ 6V             | Auto On/Off   | 6 ft         | 6 ft              | Alligator Clips  | 473X77   |