



QUICKCABLE

SB Connectors and Contacts

Battery and cable connectors are used to connect batteries to a power source. These terminal connectors and battery cable connectors are commonly used at charging stations with construction equipment or for use in other machinery and vehicles.

Wire Size Wire (AWG) Amps Color Dia. (in.)
Anderson Power Products
SB Connectors




3BY20





The Sand	12
5	NEH4



Cable Well Depth

(in.)

Item

3BY22 3BY20 3BY21

WESTWARD

Battery Lugs

		Pkg. of 2	Pkg. of 25
	Stud	Item	Item
Gauge	Size	No.	No.
	1/4 in	23YY86	23YZ13
6 ga	5∕16 in	23YY87	23YZ14
	⅓ in	23YY88	23YZ15
	1/4 in	23YY90	_
4 ga	5∕16 in	23YY91	23YZ18
	⅓ in	23YY92	23YZ19
	1/4 in	23YY94	23YZ21
2 ga	5∕16 in	23YY95	23YZ22
2 ya	⅓ in	23YY96	23YZ23
	½ in	_	23YZ24
1 ga	3⁄8 in	23YY99	23YZ26



23YZ03

auge	Size	No.	No.				
	1/4 in	23YY86	23YZ13			Pkg. of 2	Pkg. of 25
ga	5/16 in	23YY87	23YZ14		Stud	Item	Item
	3/8 in	23YY88	23YZ15	Gauge	Size	No.	No.
	1/4 in	23YY90	_	1/0.00	3/8 in	23YZ02	23YZ28
ga	5∕16 in	23YY91	23YZ18	1/0 ga -	1/2 in	23YZ03	23YZ29
	3⁄8 in	23YY92	23YZ19	0/0 00	3/8 in	23YZ04	23YZ30
	1/4 in	23YY94	23YZ21	2/0 ga -	½ in	23YZ05	23YZ31
	5∕16 in	23YY95	23YZ22	2/0.00	3/8 in	23YZ06	_
ga	3/8 in	23YY96	23YZ23	3/0 ga -	1/2 in	23YZ07	_
	1/2 in	_	23YZ24	4/0.00	3/8 in	23YZ34	23YZ08
ga	3⁄8 in	23YY99	23YZ26	4/0 ga -	1/2 in	23YZ09	23YZ35













Compression Lug & Splice Crimpers

■ Compatible with Battery Lugs, Compression Lugs & Splices

Minimum Compatible Wire Size	Maximum Compatible Wire Size	Insulated	Overall Length	Brand	
8 AWG	250 kcmil	No	22½ in	Eclipse	22C703
8 AWG	4/0 AWG	No	15 in	Quickcable	5NFK4
8 AWG	1 AWG	Yes	15 in	Quickcable	2FEG1
8 AWG	1/0 AWG	No	15¾ in	Greenlee	49NV75
6 AWG	4/0 AWG	No	19½ in	Klein Tools	25D147
1 AWG	250 kcmil	No	26½ in	Greenlee	490Z05









Item





Booster Cable Connective Ends and Caps

Style	Gauge	Amps	Color	No.
Westward				
Light-Duty Connector, Plug-In Style	12 ga to 10 ga	50A	Gray	23PC31
Medium-Duty Connector,	2 ga	175A	Blue	23PC37
Plug-In Style	1/0 ga	150A	Red	23PC34
Heavy-Duty Connector,	2/0 ga	350A	Red	23PC35
Plug-In Style	2/0 ga	350A	Gray	23PC32
Grote				
	_	50 A	Black	2FGC3
Plug-In Cap	_	175 A	Black	2FFR7
	_	350 A	Black	2FGC4
Associated Equip				
Plug-In Style	_	175A	Gray	45RK29



Battery Cables

 Resist water, grease, sunlight, and abrasion

PVC jacket

	Wire		Item
Item	Size	L	No.
Grote			
	1 ga	10 in	2FFU9
Switch to	4 ga	10 in	2FFF5
Starter Cable	4 ga	15 in	2FFF6
	4 ga	18 in	2FFF7
Quickcable			
Dattanii Cabla	2/0 ga	10 in	2FFT4
Battery Cable Heavy Duty	2/0 ga	15 in	2FFT5
neavy Duty	2/0 ga	20 in	2FFT6
Southwire			
Battery Cable with Lugs	4 ga	19 in	1YPG9









Battery Disconnect Switches

Use to quickly disconnect batteries to prevent battery drain, theft, tampering, and unauthorized use; help improve the safety of stored vehicles







Max. Voltage	Connec. Material	Includes	Mfr. Model	Item No.
Battery Do	ctor			
In-Line Kni				
12V	Copper	_	20304	4NGU2
12V	Brass/Copper	_	20188	4NGU1
12V	Brass/Copper		20218	6TXD4
In-Line Pus	sh Button			
12V	Copper	Waterproof Cover	20302	4NGV4
In-Line Rot				
12/24/24V	Copper	_	20387	6TXD8
12/24/24V	Copper	_	20393	6TXD9
12/24V	Copper	2 Keys and Cover	20314	4NGU6
12/24V	Silver Plated Copper	Lockout / Mounting Bracket	20247-7	34RD22
12/24V	Silver Plated Copper	Key, Mounting Bracket	20243-7	34RD23
12/24V	Copper	_	20256	6TXE0
12/24V	Silver Plated Copper	_	20257	6TXE1
12V	Copper	Weather-Resistant Cover, Key	20259	4NGV3
Side Post I	Knife Blade			
12V	Brass/Copper	_	20128	4NGT7
Side Post I	Rotary			
12V	Zinc	Bypass Fuse	20310	4NGU5
Top Post K	nife Blade			
12V	Brass/Copper	_	20138	4NGT8
12V	Brass/Copper	Wing Nut	20148	4NGT9
12V	Brass/Copper	_	20208	6TXD3
Top Post R				
12V	Zinc	_	20308	4NGU3
12V	Zinc	Bypass Fuse	20309	4NGU4
Flaming Ri		-,,		
	with Lock Out			
12-24V	Silver Plated	Aluminum Mounting Bracket and Zinc Mounting Hardware, Lock-Out Bracket	FR1044	5LPK5
Removable	. Kev	2001. Gat Bradnot		
12-24V	Silver Plated	Aluminum Mounting Bracket and Zinc Mounting Hardware, Removable Key	FR1009	5LPK6

090104 **21DH99**