## FLEET & VEHICLE MAINTENANCE Vehicle Lighting

GOLIGHT



Horizontal axis rotation: 370°

Vertical axis rotation: 135°

Powerful lights are designed to provide intense illumination for automotive, first responder, work truck, marine, military, and outdoor applications. They are UV- and saltwater-resistant. Remote control and mounting options include wireless handheld (H/H) or dash-mount, hardwired dash-mount, and handheld portable wired remote. Mounted searchlights are available with permanent mounting or portable magnetic-mount.

Amps	Watts	Candle Power	Includes	Body Color	н	W	D	Mfr. Model	ltem No.		
LED Wireless Ha		and Oranta I									
			Stainless Steel Mounting Plate, Black Rubber Gasket,								
3.5 A	40 W	410,000	Mounting Plate Screws, Wireless Handheld Remote	White	7.5 in	7.25 in	6 1/10 in	20004GT	55AV63		
3.5 A	40 W	410.000	15 ft Power Cord with Cigarette Plug, Magnetic Mount Shoe, Wireless Handheld Remote	White	8 in	7.25 in	8 ½ in	79014GT	55AV67		
3.5 A	40 W	410,000	15 ft Power Cord with Cigarette Plug, Magnetic Mount Shoe, Wireless Handheld Remote	Black	8 in	7.25 in	8 1/2 in	79514GT	55AV68		
3.5 A	40 W	410,000	Stainless Steel Mounting Plate, Mounting Plate Screws, Wireless Handheld Remote	White	<u>7 in</u>	7.25 in	7 ½ in	30004ST	55AV70		
3.5 A	40 W	410,000	Stainless Steel Mounting Plate, Mounting Plate Screws, Wireless Handheld Remote	Black	7 in	7.25 in	7 ½ in	30514ST	55AV71		
Hardwired - Remote Controlled											
3.5 A	40 W	410,000	20 ft Wiring Harness, Black Rubber Gasket, Hardwired Dash Mount Remote, Mounting Plate Screws, Stainless Steel Mounting Plate	White	7.5 in	7.25 in	6 1⁄10 in	20204GT	55AV65		
3.5 A	40 W	410,000	20 ft Wiring Harness, Black Rubber Gasket, Hardwired Dash Mount Remote, Mounting Plate Screws, Stainless Steel Mounting Plate	Black	7.5 in	7.25 in	6 1/10 in	20214GT	55AV66		
Dual Wireles	ss - Remote	Controlled									
3.5 A	40 W	410,000	Stainless Steel Mounting Plate, Black Rubber Gasket, Mounting Plate Screws, Wireless Handheld Remote, Wireless Dash Mount Remote	White	7.5 in	7.25 in	6 1/10 in	20074GT	55AV64		
Halogen											
Wireless - R	emote Conti	rolled									
5.5 A	65 W	225,000	Rockguard, Stainless Steel Mounting Plate, Black Rubber Mounting Gasket, Mounting Plate Screws, Wireless Handheld Remote	White	7.5 in	7.25 in	6 1/10 in	2000GT	55AV56		
5.5 A	65 W	225,000	15 ft Power Cord with Cigarette Plug, Permanent Mount Shoe, Rockguard, Wireless Handheld Remote	White	8 in	7.25 in	8 ½ in	7900GT	55AV60		
Wireless Ha	ndheld - Rer	note Control									
5.5 A	65 W	225,000	15 ft Power Cord with Cigarette Plug, Magnetic Mount Shoe, Rockguard, Wireless Handheld Remote	White	8 in	7.25 in	8 ½ in	7901GT	55AV61		
5.5 A	65 W	225,000	15 ft Power Cord with Cigarette Plug, Magnetic Mount Shoe, Rockguard, Wireless Handheld Remote	Black	8 in	7.25 in	8 ½ in	7951GT	55AV62		
5.5 A	65 W	225,000	Rockguard, Stainless Steel Mounting Plate, Mounting Plate Screws, Wireless Handheld Remote	White	7 in	7.25 in	7 ½ in	3000ST	55AV69		
Hardwired -	Remote Con	trolled									
5.5 A	65 W	225,000	20 ft Wiring Harness, Black Rubber Gasket, Hardwired Dash Mount Remote, Mounting Plate Screws, Rockguard, Stainless Steel Mounting Plate	White	7.5 in	7.25 in	6 %10 in	2020GT	55AV58		
5.5 A	65 W	225,000	20 ft Wiring Harness, Black Rubber Gasket, Hardwired Dash Mount Remote, Mounting Plate Screws, Rockguard, Stainless Steel Mounting Plate	Black	7.5 in	7.25 in	6 1/10 in	2021GT	55AV59		
<b>Dual Wireles</b>	s - Remote	Controlled	meaning rate colored, neergaald, olamoo oloor mounting rate								
5.5 A	65 W	225,000	Rockguard, Stainless Steel Mounting Plate, Black Rubber Gasket, Mounting Plate Screws, Wireless Handheld Remote, Wireless Dash Mount Remote	White	7.5 in	7.25 in	6 1/10 in	2007GT	55AV57		
Accessories											
Wireless Ha		ote						30100	52WT49		
LED Retrofit	Insert							15444	36E687		



		Current	wiring					<b>B</b> <sup>1</sup> .	INITY.	item
Lens Shape	Volt Bulb	Rating	Connection	Lens Color	Includes	Length	Width	Diameter	Model	No.
LED										
Grote										
Round	12	0.6A	Pigtail	Clear, White	With Shock-Absorbing and Weatherproof Housing	—	3⁄4 in	4 <sup>2</sup> 1⁄64 in	61E41	13W958
Rectangular	14 to 30	_	Hardwired	Clear, White	_	5 ¾ in	3⁄4 in	_	61991	5UVX2
Rectangular	12	0.6A	Hardwired	White	Switch	18 in	3⁄4 in	_	61F01	13W963
Rectangular	12	1.2A	Hardwired	Clear, White		18 ¼ in	1 in	_	61881	2CWL9
J.W. Speaker										
Rectangular	12 to 24	0.14A	Molex Connector	White	_	6 ½ in	1 in	_	410	45RJ47
Maxxima										
Round	10 to 30	1.4 to 6A	Hardwired	Clear	_	_	1 ¼ in	5 29/32 in	M84435-A	49XE37
Round	_	12V	Hardwired	Red, White	On/Off Switch	-	1 in	5 29/32 in	M84434RW	22JC93
Round	10 to 30	1.5A	Hardwired	Clear	_	—	1 ¼ in	5 29/32 in	M84434-A	49XE38
Round	12.8	0.36A	Pigtail	White	(2) 13 in Wires	—	3/4 in	5 ½ in	M84405-C	52YP18
Round	12.8	0.56A	Pigtail	White	(2) 13 in Wires	—	3⁄4 in	5 ½ in	M84406-C	52YP19
Round	12 to 24	110mA, 160mA	Hardwired	White	Thin Low Profile Design	—	1 ¼ in	5 29/32 in	M84435RW	54DE35
Incandescent										
Grote										
Round	12	1.04A	Hardwired	Clear, White	With On/Off Switch	_	1 ½ in	5 1/8 in	61161	2VPE1
Rectangular	12		Hardwired	Clear, White	3-Way Switch	7 in	1 ¾ in		61301	2VPE3

Sign in to Grainger.com<sup>®</sup> to see YOUR Pricing and MORE