



STEELMAN.
Electronic Stethoscopes



Sensor tips can be placed directly on a housing to amplify sound while the headphones shut out surrounding noise. Nonconductive microphone will not zap computer circuitry. Flexible-shaft probe reaches into hard-to-reach areas. 20C895 EngineEAR II adds 7-level control for extra sensitivity and reduced distortion.

Description	Mfr. Model	Item No.
EngineEAR Electric Stethoscope	65001	20C897
EngineEAR® II Electronic Stethoscopes	06800	20C895



3T063



45PG66

Compression Test Equipment

Allow you to perform standard maintenance and diagnostics that can help keep your fleet on the road.

Gasoline Engine	Includes	Mfr. Model	Brand	Item No.
Compression Tester Gauge with 12 in Rubber Hose, 14mm Thread Spark Plug Adapter, 18mm Thread Spark Plug Adapter		1MZU3	Westward	1MZU3
Polished Chrome Gauge and all Chrome Adapters		5606	OTC	3T063
(2) 3/4 in Gauge with High Impact Lens, Rubber Boot, (4) Scales of Measure (psi, kg/cm2, bar, kPa), 10 in Hose, Quick Release Coupler, (2) 14mm Short Thread Adapter, 6 1/2 in Hose, (3) 12 in Hose, 14mm Long Thread Adapter, 18mm Short Thread Adapter, 18mm Long Thread Adapter, 10mm Thread Small Engine Adapter, 12mm Thread Small Engine Adapter, Quick Release Air Hold Adapter, Custom Blow Molded Case, Field Service Kit		MV5530	Mityvac	45PG66



1MZU2



Mechanic's Stethoscopes

Diagnostic tools help pinpoint potential trouble spots in noisy engine compartments, blocking the distraction of surrounding sound.

Features	Brand	Mfr. Model	Item No.
Aluminum Steel Probe and Needle	Westward	1MZU2	1MZU2
Aluminum Steel Probe and Needle and Shock-Resistant Handle	Gearwrench	835D	2ZPG5
Spring Steel Diaphragm and Shock-Resistant Handle	Proto	JFP500A	6RKV0

OTC Barring Socket and Tool

Socket 38EG22 helps rotate Mack E7 and Cat 3208 diesel engines. 2TVR4's load-bearing collar offers friction-free operation while rotating Cummins B and C series diesel engines and 5.9L diesels. Works with a 1/2" square drive ratchet or breaker bar.



38EG22



2TVR4

Item	Mfr. Model	Item No.
Engine Barring Socket	6749	38EG22
Barring tool	7471A	2TVR4



1UBG2



45JW57

WESTWARD
Piston Ring Tension Bands

Application	Includes	Item No.
Install Pistons 3 1/2 to 7 in, 89 mm to 178 mm Dia For Trucks and Tractors	(1) Square Handle, (4) Spring Steel Tension Bands	1UBG2
Assemble and Disassemble the Piston	Clip Pliers., Metal Bands for Piston Rings 2 7/8 in to 3 1/8 in, 3 1/8 in to 3 3/8 in, 3 3/8 in to 3 7/8 in, 3 7/8 in to 4 1/8 in, 4 1/8 in to 4 3/8 in	45JW57



2ZPJ9

45FF52

GEARWRENCH WESTWARD
Engine Cylinder Hone

Adjustable spring tension and spread limiter help provide positive cutting action to hone and remove glaze. The hone is complete with 240-grit medium grit stones.

For Use With	Brand	Mfr. Model	Item No.
2834D, 2835D, 2836DD	Gearwrench	2833D	2ZPJ9
Engine Cylinders	Westward	45FF52	45FF52