



## Safety Whips

High-visibility warning whips alert other vehicles to your presence, to help prevent accidents. Whips are constructed of premium fiberglass resin and include mounting base and Day Bright™ fluorescent orange nylon mesh flag, with or without 3M® Scotchlite® Reflective X.

Note: Replacement flags are available on Grainger.com®.

Description	Overall Height	Flag Height	Flag Width	Mfr. Model	Item No.
<b>Whip with Threaded Hex Base</b>					
<b>Light Duty</b>					
Without (X)	7 ft	7 ¼ in	11 ½ in	FSRR70-HB	5YMH7
<b>General Duty</b>					
Without (X)	3 ft	11 in	12 in	FS3-O	5UYJ9
With Reflective (X)	3 ft	11 in	12 in	FS3X-O	5UYK0
Without (X)	5 ft	11 in	12 in	FS5-O	5UYK3
With Reflective (X)	5 ft	11 in	12 in	FS5X-O	5UYK4
Without (X)	8 ft	11 in	12 in	FS8-O	5UYK7
With Reflective (X)	8 ft	11 in	12 in	FS8X-O	5UYK8
Without (X)	10 ft	11 in	12 in	FS10X-O	5UYL2
With Reflective (X)	12 ft	11 in	12 in	FS12X-O	5UYL6
<b>Whip with Quick-Disconnect Base</b>					
<b>General Duty</b>					
With Reflective (X)	5 ft	11 in	12 in	FS5X-QD-O	16D793
With Reflective (X)	6 ft	11 in	12 in	FS6X-QD-O	16D797
Without (X)	6 ft	11 in	12 in	FS6-QD-O	16D795
With Reflective (X)	8 ft	11 in	12 in	FS8X-QD-O	16D808
With Reflective (X)	10 ft	11 in	12 in	FS10X-QD-O	16D776
<b>Whip Split Pole with Quick-Disconnect Base</b>					
<b>General Duty</b>					
With Reflective (X)	8 ft	11 in	12 in	FS8X-SPQD-O	16D809
With Reflective (X)	10 ft	11 in	12 in	FS10X-SPQD-O	16D777
<b>Lighted Whip Split Pole with Quick-Disconnect Base</b>					
With Reflective (X)	8 ft	11 in	12 in	FS8XL-SPQD-O	16D807
<b>Lighted Whip Split Pole with Threaded Hex Base</b>					
With Reflective (X)	8 ft	11 in	12 in	FS8XL-O	5UYL0
<b>Replacement Flag</b>					
<b>Heavy Duty</b>					
Without (X)	—	11 in	12 in	FS9024-O	16D818
<b>General Duty</b>					
With Reflective (X)	—	11 in	12 in	FS9025-O	16D830
<b>Orange Warning Whip Replacement Flags</b>					
<b>7 ¼ inH x 11 ½ inW</b>					
Light-Duty Replacement Flag, Plain	—	7 ¼ in	11 ½ in	FS3007	5YMJ1

Description	Mfr. Model	Item No.
<b>Warning Whip Accessories</b>		
Heavy-Duty Spring Mount For Whips Up to 8 ft.	FS7006	5UYR2
Ultra Heavy Duty Spring Mount for 10' and 12' Lighted Whips	FS7006U	5UYR3
Magnetic Mount Base for Non-Lighted Whips	FS7009	5UYR6
Female Quick-Disconnect Base Mount with Debris Cap	FSQDB-DUD	16D835
Female Quick-Disconnect Base Mount with Hot Plug and Debris Cap	FSQDB-B	16D834
Quick-Disconnect Base Mount Kit for Non-Lighted Whips	FSQDKIT-DUD	16D840
Female Quick-Disconnect Base Mount with 6" Pigtail and Debris Cap	FSQD-BPT	16D837
Lighted Quick-Disconnect Base Mount Kit	FSQD-KIT	16D839



## Black Rubber Mud Flaps

■ Sold as a Pair


W	L	Thickness	Item No.
12 in	18 in	¼ in	3VUH3
20 in	18 in	¼ in	3VUH4
24 in	12 in	¼ in	3VUH7
24 in	14 in	¾ in	3VUH8
24 in	18 in	¼ in	3VUH5
24 in	20 in	¼ in	3VUH6
24 in	24 in	½ in	400K18
24 in	30 in	¼ in	400K16
24 in	30 in	½ in	400K19
24 in	36 in	¼ in	400K17
24 in	36 in	½ in	400K20

## Cribbing Blocks

- Black plastic
- Rope handles



Load Capacity Vertical	Overall Length	Overall Width	Overall Thickness	Item No.	Pkg. Qty.
<b>AME</b>					
40 ton	18 in	4 in	2 in	153V72	1
	18 in	4 in	4 in	153V76	1
	24 in	7 in	6 in	153V78	1
60 ton	24 in	7 in	6 in	153V91	12
	24 in	7 in	6 in	153W34	42



## Truck Hood Latches

Latch Style	L (in.)	Item No.
<b>Catch Latches</b>		
Rubber Hood	4 ½ in	3VUN5
U-Shaped Ball Cup	4 ¾ in	3VUN6
U-Shaped Ball Cup	6 in	3VUN3
U-Shaped Ball Cup	7 ½ in	3VUN4
<b>Spring Latches</b>		
Spring Latch	4 ½ in	3ZULU5
Spring Latch	4 11/16 in	3ZULU7
Spring Latch	6 19/64 in	3ZULU6



## Measuring Sticks

Lightweight fiberglass measuring stick has a folding 48" cross arm and folds down to 66". Marked to take measurements in standard units. 55MN04 collapses to 51" for storage and is orange in color. Fiberglass material.

Description	Item No.
B/A Products Co. 70" to 180"	3VTG6
J.J. Keller 6 ft. to 25 ft.	55MN04



## Bolt-On Truck Steps



No. of Rungs	Step Width	Step Depth	Material	Color	Item No.
<b>Flexible Truck Steps</b>					
1	12 in	4 ¾ in	Steel	Black	30PD55
<b>Foldable Truck Steps</b>					
1	4 ¾ in	2 ½ in	Stainless Steel	Silver	3VRY7
1	6 ¾ in	7 ¼ in	Aluminum	Silver	3VTD6
1	4 ¾ in	2 ½ in	Steel	Black	30PD97
1	4 ¾ in	2 ½ in	Steel	Silver	30PD95
<b>Permanent Truck Steps</b>					
1	12 in	1 ¾ in	Steel	Black	30PD60
1	12 in	1 ¾ in	Steel	Black	30PD59
<b>Retractable Truck Steps</b>					
2	14 ¼ in	2 ¼ in	Steel	Black	19A787
2	14 ¼ in	2 ¼ in	Steel	Yellow	30PD58
3	14 ¼ in	2 ¼ in	Steel	Black	19A788
3	14 ¼ in	2 ¼ in	Steel	Yellow	30PD56
3	16 ¾ in	1 ¼ in	Steel	Black	19A785



## Outrigger Pads

Load Capacity Vertical	Overall Length	Overall Width	Overall Thickness	Material	Handle Type	Item No.
<b>AME</b>						
100 ton	24 in	24 in	2 in	Polymer	Rope Style	153V39
<b>Buyers Products</b>						
—	24 in	24 in	1 in	HDPE	Rope Style	30PD57
—	18 in	18 in	2 in	Rubber	Molded In	3MH08
—	18 in	18 in	1 in	HDPE	Rope Style	30PD61
—	18 in	18 in	2 in	Wood	U-Bolt Style	30PD66
<b>Safety Tech Outrigger Pad</b>						
22.5 ton	15 in	15 in	¾ in	Thermoplastic	Rope Style	45TX96
27.5 ton	18 in	18 in	1 in	Thermoplastic	Rope Style	45TX97
30 ton	24 in	24 in	1 in	Thermoplastic	Rope Style	45TX98
31 ton	24 in	24 in	2 in	Thermoplastic	Rope Style	45TX99
<b>Titan</b>						
50 ton	12 in	12 in	1 in	Polymer	Rope Style	33W475
	18 in	18 in	1 in	Polymer	Rope Style	33W480
	12 in	12 in	1 ½ in	Polymer	Rope Style	33W476
100 ton	24 in	24 in	2 in	Polymer	Rope Style	33W478
	18 in	18 in	2 in	Polymer	Rope Style	33W479
	18 in	18 in	1 ½ in	Polymer	Rope Style	33W481
150 ton	36 in	36 in	2 ½ in	Polymer	Rope Style	33W473
	36 in	36 in	3 in	Polymer	Rope Style	33W474
200 ton	18 in	12 in	3 in	Polymer	Rope Style	33W477