

1-800-GRAINGER (472-4643)

ARO[®] WESTWARD[®] Legacy
Heavy-Duty High Flow (Oil, ATF) Pumps

ARO Thunder Pumps—Stall-free, ice-free air motor design. 85dB. Include 2" bung adapter. 1/4" FNPT air inlet.

Westward Pumps—Oil pumps come complete with bung nut. 3APF2 features all-metal, industrial-quality construction. With spigot and piping connectors. 3APE7 composite construction allows the pump to operate without using a lubricator unit in the air supply.

Pump Packages—4ZT12 and 5TCU6 include pump, control handle, meter (pts.), drum cover, and 6-ft. hose. 4ZT12 also has a band dolly.

45CT51's 3:1 pump transfers oils up to SAE 130 up to 30m; with 3.5m hose. 45CT52's 5:1 pump dispenses oils up to SAE 240 up to 50m; with hose reel. Both include steel trolley, air-operated oil pump, digital oil control gun, and miniature filter-regulator/lubricator combo with gauge.



Pump Ratio	Air Motor Size (in.)	Container Size	Working Flow Max. (gpm)	Max. Air Inlet PSI	Outlet Pressure Max. (psi)	Fluid Inlet Thread (in.)	Fluid Outlet Thread (in.)	Brand	Item No.
3:1	2	Stub	6	150	450	3/4 FNPT	1/2 FNPT	Aro	4KK55
	2	55 gal.	6	150	450	3/4 FNPT	1/2 FNPT	Aro	4KK57
	2 1/2 in	Stub	3.7 gpm	115 psi	345 psi	1 FNPT	1/2 FNPT	Westward	3APF2
	2 1/2	—	7.5	115	345	—	3/4 MNPT	Westward	5TC18
	2 1/2	55 gal.	7.5	115	345	—	1/2 MNPT	Westward	5TCU0
	2 1/2	275 gal.	7.5	115	345	—	1/2 MNPT	Westward	5TCU1
5:1	3	Stub	6	150	750	1 1/2 FNPT	1/2 FNPT	Aro	4KK59
	3	16 gal.	6	150	750	1 1/2 FNPT	1/2 FNPT	Aro	4KK60
	3	55 gal.	6	150	750	1 1/2 FNPT	1/2 FNPT	Aro	4KK61
	3	275 gal.	6	150	750	1 1/2 FNPT	1/2 FNPT	Aro	4KK62
	—	Stub	4 gpm	145 psi	725 psi	1 FNPT	1/2 in FNPT	Westward	3APE7
	2 1/2	2.8 gal.	6.6	115	580	—	3/4 MNPT	Westward	5TCU2
2 1/2	55 gal.	6.6	115	580	—	3/4 MNPT	Westward	5TCU4	
2 1/2	275 gal.	6.6	115	580	—	3/4 MNPT	Westward	5TCU5	
Pump Packages									
3:1	2	16 gal.	6	150	450	—	—	Aro	4ZT12
	2 1/2 in	16 gal.	7.9 gpm	115 psi	345 psi	—	3/4 MNPT	Legacy	5TCU6
	2 1/2 in	55 gal.	3.7 gpm	145 psi	435 psi	—	1/2	Westward	45CT51
5:1	2 1/2 in	56 gal.	4.7 gpm	145 psi	725 psi	—	1/2	Westward	45CT52

LINCOLN
Fluid Transfer Pumps

Transfer oil, diesel, kerosene, coolants, petroleum-based fluids, hydraulic oils, and automatic transmission fluid. Fit 16- and 55-gal. containers with 2" bung opening. 14U106 is FM Certified for gasoline transfer.

Includes	Max. Output	Mfr. Model	Item No.
Drum Pump 6 Ft Hose	4 gpm	1335	6WB29
Rotary Pump 8 ft Hose, Aluminum Nozzle and Hanger	10 gpm	1385-H	14U105
8 Ft Hose, Flame Arrestor And Vacuumbreaker, Non-sparking Dispensenozzle And Hose Holder	10 gpm	1387	14U106



WESTWARD[®] Legacy LubriMatic[®]
Fluid Transfer Pumps

Lever-Action—5NUD4 is for dispensing oils and antifreeze from 15- to 55-gal. drums.

5NUD5 is for dispensing heavy oils from 5-gal. pails. Handle has 3 settings for use with oils of different viscosities.

Rotary—Westward pumps come complete with 2" cast-iron bung nut and 3-pc. threaded suction tube for use on 15- to 55-gal. drums. 5NUD6 works in both directions, to empty and refill drums.

41AA65 transfers light- to medium-viscosity noncorrosive petroleum-based fluids from 55-gal. containers. 1 gal. per 18 revolutions. Spout O.D. 1 1/16".

Includes	Type	Output	Brand	Item No.
Lever Action Barrel Pump				
1 1/2" and 2" Drum Bung, Steel Discharge Spout, and Telescopic Suction Tube	Lever Action	10 oz. per Stroke	Westward	5NUD4
Adjustable and Telescoping Pipe	Oil	10 oz./Stroke	Legacy	4ZT137
Lever Action Bucket Pump				
18" Pump with 12" Drum Cover, and 4-ft PVC Hose with Steel Discharge Spout	Oil	Up to 4 oz per Stroke	Westward	5NUD5
Rotary Transfer Pump				
Cast Iron Pump and Handle with Steel Discharge Spout	Oil	8.5 oz. Per Rotation	Westward	5NUD6
Aluminum Die Cast Pump and Handle with Security Locking Latch and Steel Discharge Spout	Oil and Fuel	7 oz. Per Rotation	Westward	5NUD7
Aluminum Die Cast Pump and Handle with Security Locking Latch and Steel Discharge with 8-ft. Discharge Hose	Oil and Fuel	1 Pint Per Rotation	Westward	5NUD8
Cast Iron 2 Vane Pump, 42" Steel Suction Pipe, 7oz. Per Stroke	Single Direction	—	Lubrimatic	41AA65



WESTWARD[®]
Downstroke Flow Pump

For use with 5-gal. containers with plastic pull out (Rieke[®] spout) or 2" external threads. Choice of 7 adapters for use with most metal and plastic containers.

Hose Length	Output	Item No.
48"	Up to 1.9 oz./stroke	21EM38



WESTWARD[®] LINCOLN
Suction and Transfer Guns

Evacuates and dispenses fluids. 3APG2 is a dual-direction transfer gun that draws in and pumps out liquid in a single stroke.

Hose Length	Cap.	Brand	Item No.
Transfer Gun			
4 ft	12 oz	Westward	3APG2
Suction Gun			
12 in	16 oz	Westward	1ZTC6
12 in	16 oz	—	44C503
12 in	18 oz	Lincoln	6WB11

Sign in to **Grainger.com[®]** to see **YOUR Pricing** and **MORE**