



Tire Mounting & Demounting Tools

Tire mounting and demounting tools break the bond between the tire and rim.

Product Type	Overall Length	Brand	Item No.
Bead Breakers			
Bead Breaker	48 in	Haltec	33W455
Bead Breaker	11 in	Ame	33W454
Bead Breaker	16 7/8 in	Omegalift	54HH33
Bead Breaker Leverage Bar	33 in	Ken-Tool	2WFJ6
Bead Breaker Leverage Bar	30 in	Ken-Tool	2WFJ4
Bead Breaking Wedge	32 in	Ken-Tool	2WFE7
Bead Breaking Wedge	18 in	Ken-Tool	2WFE6
Bead Breaking Wedge	30 in	Ken-Tool	2WFE5
Bead Breaking Wedge	17 in	Ken-Tool	2WFE4
Bead Holder	4 1/2 in	Ken-Tool	2WFH7
Impact Bead Breaker	46 in	Ken-Tool	2WFE2
Impact Bead Breaker	50 in	Ken-Tool	2WFE3
Bead Seater Tools			
Bead Expander	22 in	Ken-Tool	36P412
Bead Holder	—	Ken-Tool	36P429
Bead Seater	—	Ken-Tool	36P426
Bead Seater	17 1/2 in	Ken-Tool	55JE70
Bead Seating Stand	27 in	Ken-Tool	5JKL5
Tire Bead Seater	24 1/2 in	Ken-Tool	2WFL6
Tire Bead Seater	17 1/2 in	Ken-Tool	2WFL4
Tire Bead Seater	19 1/2 in	Ken-Tool	2WFL5
Lock Ring Tools			
Combination Rim and Ring Tool	23 1/2 in	Ken-Tool	2WFD5
Lock Ring Tool	30 in	Ken-Tool	2WFD4
Lock Ring Tool	24 in	Ken-Tool	2WFD3
Lock Ring Tool	18 in	Ken-Tool	2WFD7
Lock Ring Tool	37 in	Ken-Tool	2WFD9
Tire Hammers			
Tire Hammer	18 in	Ken-Tool	36P418
Tire Irons			
Motorcycle/Small Tire Tools	16 1/2 in	Ken-Tool	36P413
Motorcycle/Small Tire Tools	16 in	Ken-Tool	8D753
Mount Tool	38 in	Ken-Tool	2WFH3
Straight Mount/Demount Tool	36 in	Ken-Tool	2WFG1
Straight Mount/Demount Tool	52 in	Ken-Tool	2WFG5
Tire Iron Set	—	Ken-Tool	2WFF9
Tire Mount/Demount Tool	37 in	Ken-Tool	2WFF7
Tire Mount/Demount Tool	41 in	Ken-Tool	2WFF8
Tire Mount/Demount Tool	54 in	Ken-Tool	6ZCF1
Tire Mount/Demount Tool	37 in	Ken-Tool	20KT04
Tire Mount/Demount Tool	38 in	Ken-Tool	6ZCF0
Tubeless Tire Iron	37 in	Ken-Tool	2WFF6
Tire Mounting & Demounting Tool Sets			
Tire Changing Set	39 in	Ken-Tool	2WFH4
Tire Mount/Demount Set	38 in	Ken-Tool	6ZCE8
Truck Tire Service Set	—	Ken-Tool	36P436
Tire Service Charts			
Tire Charts	40 in	Ken-Tool	36P440
Tire Spoons			
Curved Tire Mount/Demount Spoons	30 in	Ken-Tool	2WFJ1
Tire Mount/Demount Spoons	30 in	Ken-Tool	2WFH9
Tire Mount/Demount Spoons	18 in	Ken-Tool	36P415
Tire Mount/Demount Spoons	24 in	Ken-Tool	8D044
Tire Mount/Demount Spoons	24 in	Ken-Tool	8D043
Wheel Lifting Bar	58 in	Ken-Tool	5JKL4
Vehicle Rim O-Rings			
Standard 1/4 in O-Ring	25 in	Haltec	48WC46
Standard 3/8 in O-Ring	25 in	Haltec	48WC47
Wheel Hub Cap Cover Pullers & Removers			
Wheel Cover Puller and Replacer	14 in	Ken-Tool	2WFP8



33W455



36P426



2WFF7



2HLA8



4-Way Lug Nut Wrenches

Socket Size	Overall Length	Leverage Bar Hole	Brand	Item No.
Bus, Tractors, Trucks				
1 1/8 in, 1 1/4 in, 1 1/2 in, 1 3/4 in	27 1/2 in	Yes	Ken-Tool	2WEY3
1 1/8 in, 1 1/4 in, 1 1/2 in, 1 3/4 in	27 1/2 in	No	Ken-Tool	2WEY4
1 1/4, 1 1/2, 3/4 in Service Arm, 1 3/8 in Square	27 1/2 in	Yes	Ken-Tool	2WEY5
1 1/2 in, 1 3/8 in Square, 30 mm, 33 mm	27 1/2 in	Yes	Ken-Tool	2WEY2
24 mm, 27 mm, 30 mm, 33 mm	27 1/2 in	Yes	Ken-Tool	2WEY6
Cars, RVs, SUVs, Trucks, Vans				
1 1/8 in, 3/4 in, 1 3/8 in, 1/2 in	14 in	No	Westward	2HLA8
1 1/8 in, 3/4 in, 1 3/8 in, 1/2 in	20 in	No	Westward	2HLA9
1 3/8 in, 1 1/2 in, 3/4 in, 1/2 in	22 in	No	Ken-Tool	8UMX4
3/4 in, 1 3/8 in, 1/2 in, 1 1/4 in	23 in	No	Ken-Tool	36P419
3/8 in Deepwell, 1 3/8 in, 1 in, 1 1/4 in	25 in	No	Ken-Tool	36P420
1/2 in, 1 3/8 in, 1 in, and 1 1/4 in	25 in	No	Westward	2HLB2
17 mm, 3/4 in, 1 3/8 in, 1/2 in	18 in	No	Ken-Tool	46UA54
17 mm, 3/4 in, 1 3/8 in, 1/2 in	20 in	No	Ken-Tool	46UA55
17 mm, 19 mm, 21 mm, 22 mm	14 in	No	Ken-Tool	46UA53
17 mm, 19 mm, 21 mm, 22 mm	20 in	No	Ken-Tool	46UA51
17 mm, 19 mm, 21 mm, 23 mm	20 in	No	Westward	2HLB1



4VCT9



4VCU2



2WFP1

Tire Changing Systems



Machines mount and dismount tires from the wheel assembly.

Description	Maximum Rim Dia.	Width	Features	Item No.
Powered Tire Changing Machines				
John Bean				
Tilt Tower Tire Changer, System II-E	24 in	12 in	Adjustable Clamping Jaws, Column-Integrated Air Tank, Pedal-Operated Bead Breaker, Tabletop Bead Seater	4VCT9
Tilt Tower Tire Changer, System IV-E	24 in	12 in	Adjustable Clamping Jaws, Tabletop Bead Seater, Tilt-Tower	4VCU1
Tilt Tower Tire Changer, System V	26 in	26 in	Adjustable Clamping Jaws, Tabletop Bead Seater, Tilt-Tower	4VCU2
Manual Tire Changing Machines				
Ken-Tool				
Manual Tire Changer, Floor Mount	15 in	24 in	Adjustable Bead Breaker for Rims up to 15 in Diameter and 24 in Width without Disassembly	2WFP1
Manual Tire Changer, Bench Mount	12 in	12 in	Square Base Prevents Turning in the Changer During Use	2WFN9

Container Type	Product Form	Container Size	Color	Item No.	
Bead Sealer					
Tru-Flate	Can	Liquid	1 qt	Clear	1EKX3
Xtra Seal					
Can	Liquid	32 oz	Black		33K060
Tire Installation Lubricants					
Ken-Tool					
Bottle	Liquid	1 gal	Red		2WFN7
Bucket	Paste	8 lb	White		6ZCF7
Bucket	Paste	8 lb	Blue		6ZCF0
Pail	Paste	25 lb	Amber		6ZCF8
Pail	Liquid	25 lb	Black, Gray		6ZCF9
Mohawk					
Bottle	Liquid	1 gal	Blue		33K125
Bucket	Liquid	5 gal	White		33K126
Pail	Paste	8 lb	White		33K120
Pail	Liquid	8 lb	White		33K103
Pail	Paste	22 lb	White		33K119
Pail	Liquid	40 lb	White		33K102
Tru-Flate					
Bottle	Liquid	1 gal	Clear		1EKX8
Pail	Paste	8 lb	Amber		1EKX6
Zep					
Bottle	Liquid	1 gal	Yellow		453D52

Product Type	Overall Length	Item No.
Tire Lubrication Tools		
Ken-Tool		
Bead Lubricant Swab	12 in	2WFN2
Euro Style Lube Brush	11 in	36P425
Mohawk		
Tire Swab	15 in	33K141
Tire Swab	18 in	33K142
Tru-Flate		
Applicator Swab	4 3/8 in	1ELD3

Tire Bead Sealers & Tire Lubricants

Bead sealers and lubricants help support tire replacement and maintenance by easing tire mounting, ensuring a tight bead seal.



6ZCF7



36P425

Size	Working Torque	Overall Length	Color	Item No.
1/2 in Drive				
1/2 in	80 ft-lb	8 3/8 in	Blue	55RZ84
1 1/8 in	100 ft-lb	8 3/8 in	Brown	20C909
1 1/2 in	120 ft-lb	8 3/8 in	White	20C913
1 3/4 in	140 ft-lb	8 3/8 in	Blue	20C914
17 mm	110 ft-lb	8 3/8 in	Purple	20C917
19 mm	100 ft-lb	8 3/8 in	Gray	20C912
3/4 in Drive				
3/4 in	175 ft-lb	10 in	Orange	55RZ64
3/4 in	250 ft-lb	10 in	Red	55RZ63
3/4 in	350 ft-lb	10 in	Purple	55RZ65
3/4 in	475 ft-lb	10 in	Yellow	55RZ62
1 in Drive				
1 in	350 ft-lb	10 in	Purple	55RZ68
1 in	475 ft-lb	10 in	Yellow	55RZ69
1 in	550 ft-lb	11 in	Black	55RZ70

STEELMAN Torque Sockets

Sockets have the ability to set the torque value to the proper setting to ensure lug nuts are not over tightened.



55RZ62