



Tire Inflator and Inflator Repair Kits

12V tire inflators plug into a vehicle's accessory power outlet to inflate tires that lose pressure or go flat on the road.



Item	Hose Length	Features	Item No.
12V Tire Inflators			
Airman			
Tire Inflator	5 in	Digital Pressure Gauge with LCD Display, Handheld, Rechargeable	54XM29
Bell			
Programmable Tire Inflator	2 ft	Dial Pressure Gauge with Auto-Stop Feature, Carrying Handle	352892
5000 Tire Inflator	2 ft	Digital Pressure Gauge with Auto-Stop Feature, Lighted Safety Triangle and Raft Pump	352894
4000 Tire Inflator	2 ft	Dial Pressure Gauge with Auto-Stop Feature, Flashing Warning Light and Safety Triangle	352893
12V Tire Inflator	4 in	Carrying Handle, Dial Pressure Gauge	352890
12V Tire Inflator	14 in	Built-In Storage, Fills Standard Tire in 5 min, Large Dial Pressure Gauge	352891
Slime			
12-Volt Digital Tire Inflator	1 1/2 ft	Bright LED, Digital Display, Rubberized Feet for Stability, Tire Sensor Safe, Automatically Shut Off When Desired Pressure is Reached	33M157
12-Volt Tire Inflator	2 ft	8 min to Inflate Standard Tire, Bright LED Light, Built in Dial Gauge, Grab Handle, On/Off Button, Tire Sensor Safe	33M153
12-Volt Tire Inflator	2 ft	Bright LED, Built in Dial Gauge, Compact, On/Off Button, Tire Sensor Safe	33M152
Heavy-Duty 12-Volt Tire Inflator	15 ft	Bright LED Light, Canvas Carrying Bag, Coil Air Hose with Twist Disconnect, In-Line Dial Gauge, Power Cord AC Head Plugs in the Handle of the Inflator for Clean Cord Storage, Tire Sensor Safe	33M154
12V Tire Inflators For Use with Sealants			
Airman			
Tire Repair Air Compressor Kit	2 ft	All-in-One Solution for Passenger Vehicles	41P298
Tire Repair Air Compressor Kit	2 ft	Sealant for Larger Vehicles	41P301
Tire Repair Air Compressor Kit	2 ft	Sealant for Passenger Vehicles	41P297
Slime			
12-Volt Tire Inflator	2 ft	All-in-One Solution, Dial Display Gauge Integrated into the Kit, Tire Sensor Safe	443P45
Manual Operation			
Maxair			
Hand Air Pump	—	—	1NUV7
Slime			
Hand Floor Bicycle Pump	—	Ridged Foot Petal For Improved Grip. Metal Barrel. Flexible Air Hose.	33M150
Single Cylinder Foot Pump	—	Improves Vehicle Handling, Maintaining Proper Tire Pressure Maximizes Tread Life	33M151



Vehicle & Trailer Wheel Boot Locks

- Yellow steel
 - Includes 2 keys
- Wheel boot locks clamp onto tires to prevent theft or movement of a vehicle.

Lock Type	Fits Width Range	Fits Wheel Diameter	Adjustable	Item No.
Trailer Wheel Boot Locks				
Type B	14 in to 15 in	9 in	Yes	39C426
Type C	16 in	10 1/2 in	Yes	39C427
Vehicle Wheel Boot Locks				
7 Pin Integrated Lock	12 in to 13 in	5 1/2 in	No	39C432
Push Lock	Fits All Tire Sizes	—	Yes	39C431



Tire Inflation Cages

Cages hold tires during inflation and reduce flying debris in the event of a tire burst.

Overall Width	Overall Length	Overall Height	Base Width	Brand	Item No.
3-Bar					
16 in	22 in	30 in	21 1/2 in	Ken-Tool	2WFK1
20 1/2 in	26 in	43 1/2 in	22 in	Ken-Tool	2WFK4
4-Bar					
20 1/2 in	31 1/2 in	43 1/2 in	26 in	Ken-Tool	2WFK9
26 in	32 in	57 in	26 in	Ame	33W470
5-Bar					
20 1/2 in	41 in	43 1/2 in	26 in	Ken-Tool	2WFK3
24 1/2 in	48 in	41 1/2 in	30 in	Ken-Tool	20KR95
24 in	48 in	41 1/2 in	30 in	Ken-Tool	20KR96
39 1/2 in	41 in	68 in	26 in	Ame	33W471



Truck Wheel Dollies

They limit the need to lift and move heavy tires by hand.

Dolly Type	Maximum Weight Capacity	Maximum Lift Height	Tilt Range	Brand	Item No.
Single-Wheel Dollies					
Easy Lever	300 lb	5 in	—	OTC	48XV62
High Lift	300 lb	42 in	45°	Omegalift	54HH35
Truck Wheel	300 lb	4 in	45°	Ame	33W456
Truck Wheel	400 lb	6 in	45°	Ame	33W457
Dual-Wheel Dollies					
Easy Roller	1,500 lb	9 in	+/-3°	Hein-Werner	14N884
High Lift	1,100 lb	42 in	-8° to 15°	OTC	38EG39
Hydraulic	1,500 lb	5 in	4°	OTC	48XV57
Hydraulic	1,500 lb	8 in	-0.4°	Gray	11N138



Vehicle Tire Inflators

- Digital display
- Inflators connect to compatible hose and a compressed air supply in service centers, car rental agencies, and other fleet maintenance applications.

Minimum Operating Air Pressure	Maximum Operating Air Pressure	Features	Thread Size	Item No.
5 psi	145 psi	Automatically Inflates or Deflates to target psi when attached to Tire Position	1/4"-18	32HE93

Loose Wheel Nut Indicators

Use these convenient indicators to improve the safety by providing a visual indication of nut movement where it is critical, such as on commercial vehicle wheels. Can also help to identify if a wheel is overheating.



Hex Size	Overall Length	Max. Temp.	Brand	Item No.
Black				
Universal	4 in	257 °F	Ken-Tool	55JE71
Green				
Universal	4 in	257 °F	Ken-Tool	55JE72
Orange				
30 mm	2 1/4 in	329 °F	Checkpoint	38XK67
31 mm	2 1/4 in	329 °F	Checkpoint	38XK68
32 mm	2 1/4 in	329 °F	Checkpoint	38XK69
33 mm	2 1/2 in	329 °F	Checkpoint	38XK66
38 mm	2 1/4 in	329 °F	Checkpoint	38XK70
44 mm	2 1/4 in	329 °F	Checkpoint	38XK71
Red				
32 mm	2 1/4 in	257 °F	Checkpoint	38XK99
33 mm	2 1/2 in	257 °F	Checkpoint	38XK97
38 mm	3 1/2 in	257 °F	Checkpoint	38XK98
Universal	4 in	257 °F	Ken-Tool	55JE73
Yellow				
17 mm	2 1/4 in	257 °F	Checkpoint	38XK72
18 mm	2 1/4 in	257 °F	Checkpoint	38XK73
19 mm	2 1/4 in	257 °F	Checkpoint	38XK74
20 mm	2 1/4 in	257 °F	Checkpoint	38XK75
21 mm	2 1/4 in	257 °F	Checkpoint	38XK76
22 mm	2 1/4 in	257 °F	Checkpoint	38XK77
23 mm	2 1/4 in	257 °F	Checkpoint	38XK78
24 mm	2 1/4 in	257 °F	Checkpoint	38XK79
25 mm	2 1/4 in	257 °F	Checkpoint	38XK80
26 mm	2 1/4 in	257 °F	Checkpoint	38XK81
27 mm	2 1/4 in	257 °F	Checkpoint	38XK82
28 mm	2 1/2 in	257 °F	Checkpoint	38XK83
29 mm	2 1/4 in	257 °F	Checkpoint	38XK84
30 mm	2 1/2 in	257 °F	Checkpoint	38XK85
31 mm	2 1/2 in	257 °F	Checkpoint	38XK86
32 mm	2 1/2 in	257 °F	Checkpoint	38XK87
33 mm	2 1/2 in	257 °F	Checkpoint	38XK88
34 mm	2 1/4 in	257 °F	Checkpoint	38XK89
35 mm	2 1/4 in	257 °F	Checkpoint	38XK90
36 mm	3 1/2 in	257 °F	Checkpoint	38XK91
38 mm	3 1/2 in	257 °F	Checkpoint	38XK92
40 mm	3 1/2 in	257 °F	Checkpoint	38XK93
41 mm	3 1/2 in	257 °F	Checkpoint	38XK94
44 mm	2 1/4 in	257 °F	Checkpoint	38XK95
46 mm	2 1/4 in	257 °F	Checkpoint	38XK96

