



	Lifting Cap.	Size	Mfr. Model	Item No.	Pkg. Qty.
Standard Duty					
1500 lbs per Dolly (6000 lbs. set of four)		8W x 16L x 4 in H	M998001	3MHC4	4
1500 lbs per Dolly (6000 lbs. set of four)		12W x 16L x 4 in H	M998002	3MHC5	4
1500 lbs per Dolly (6000 lbs. set of four)		16W x 16L x 4 in H	M998027	3MHC6	4
Heavy-Duty					
2500 lbs per Dolly (5000 lbs. pair)		16W x 16L x 4 in H	M998105	11N216	2
2500 lbs per Dolly (10,000 lbs. set of four)		12 in W x 16 in L x 4 1/2 in H	M998035	3MHC7	4
Wall Mount					
Car Dolly Dock		4 in W x 16 in L x 8 in H	M998071	52WP43	1



Truck Wheel Step

Load Capacity	W	L	H	Item No.
Westward				
300 lb	4 3/4 in	22 3/4 in	15 3/4 in	1MZL5
OTC				
300 lb	23 1/2 in	23 1/2 in	17 in	53GK13



Hydraulic Dual-Wheel Dolly

- Holds up to 52"-dia. tires and wheels
- Load levelers help with alignment
- Carriage arm rollers with self-lubricating bearings

Handles both dual wheels and large single wheels. Includes built-in tool/parts tray and 2 swivel ball bearing casters for easy positioning. Wide frame and lifting carriage.



Lift Range (lb.)	Lift Arms x Width (in.)	Lift Height (in.)	Tilt Range Deg.	Overall Dim. (in.)	Item No.
1,500 lb	26 1/2 in	4 to 9	+/-3°	32 in H 39 in L 39 1/2 in W	14N884



Air-Actuated Pump

Internal check valve, eliminates pulsing and provides a consistent pressure. Used to operate and control hydraulic presses.

Cap. (psi)	Oil Cap. (cu. in.)	Air Inlet NPT (in.)	Fluid Port NPT (in.)	Item No.
10,000	91.5	1/4	3/8	5ML66



Truck Ramps

- Sold in pairs

Load Capacity	W	L	H	Item No.
Westward				
20 ton	13 1/2 in	45 3/4 in	9 1/2 in	1AVP9
20 ton	18 1/4 in	45 3/4 in	9 1/2 in	1MZK3
Gray				
20 ton	15 in	51 in	9 in	11N143
Black Widow				
10,000 lb	12 in	35 1/2 in	8 1/2 in	60AG56



Truck Wheel Dollies

Allow easy removal and installation of tire/rim assemblies and help reduce back injuries.

Description	Lift Range (lb.)	Lift Height (in.)	Lift Arms x Width (in.)	Tilt Range (Deg.)	Mfr. Model	Item No.
Single Truck Wheel Dolly						
For 19.5 to 24.5" tires	300 lb	4	28 3/4 in	45°	71300	33W456
For 22.5 to 24.5" tires	400 lb	6	29 in	45°	71320	33W457



48XV57



Wheel Dollies

AIR-OPERATED HYDRAULIC DUAL-WHEEL DOLLY

Effortless lift system with 6" lateral adjustment for a variety of applications. 4 swivel casters, 2 locking, for enhanced mobility.

HYDRAULIC WHEEL DOLLIES

Efficient method of moving a disabled vehicle. 19XY27 has an easy-to-use foot pedal that activates hydraulic lift mechanism. Fits tread widths up to 12". 4 easy rolling swivel casters. The hydraulic jack on 48XV57 provides almost 5" of lift and tilts wheel assembly 4° to prevent damage to wheel seal. 6-ft. chain holds load in place. Swivel casters for maneuverability.

Lift Cap.	Lift Arms x Width (in.)	Lift Height (in.)	Tilt Range Deg.	Overall Dim. (in.)	Mfr. Model	Item No.
Air-Operated Hydraulic Dual Wheel Dolly						
1100 lb.	42 in	0 to 42	-8° to 15°	62 3/4 in H 47 1/4 in L 48 3/16 in W	5105B	38EG39
Hydraulic Wheel Dolly						
1500 lb.	12 in	4	24.4°	27 17/100 in H 9 in L 44 in W	1580	19XY27
1500 lb.	—	5	4°	36 1/2 in H 39 in L 36 in W	1770A	48XV57
Lever Wheel Dolly						
300 lb.	—	5	—	33 1/2 in H — L 26 in W	5096A	48XV62

19XY20



Electric and Air/Hydraulic Pumps

3GZU3 includes remote 2-way, 2-position control valve. 19XY20 features a 2-stage release mechanism and internal relief valve.

Description	Mfr. Model	Item No.
Electric, 1/2 HP, 115VAC, 2. gal. Reservoir Capacity	4044	3GZU3
Air/Hydraulic	4020	19XY20