



Tiller/Cultivator—Features reversible, hardened-steel tines that provide a smooth tilling action. Worm gear-type transmission provides high torque and high tine rpm. Throttle control and water-resistant stop switch are easy for operator to reach.

Cultivator—Lightweight mini cultivator features 2 rear, 7" plastic wheels and a 3-pc. folding handle.

Rear Tine Tiller—Features forward and reverse gear drive. Includes 13" solid rubber tires and foldable, pistol grip handles. Fuel system oil mix to gasoline is not required.

| Description               | Tilling<br>D | Tine<br>L | Working<br>W  | Brand     | Item<br>No. |
|---------------------------|--------------|-----------|---------------|-----------|-------------|
| Tiller/Cultivator         |              |           |               |           |             |
| Two-Cycle 21.2cc Engine   | 10 in        | 4 in      | 9 in          | Echo      | 44X219      |
| Cultivator                |              |           |               |           |             |
| Two-Cycle 43cc Engine     | 5 in         | 8 in      | 6 in to 10 in | Southland | 6FWJ0       |
| Rear Tine Tiller          |              |           |               |           |             |
| 4-Stroke 212cc OHV Engine | 8 in         | 11 in     | 18 in         | Southland | 494P16      |



### MEGHO.

## **Gas-Powered Hole-Making Drill** and Pot Auger Bit

52DD78 cordless drill has an allposition diaphragm with purge pump carburetor, for heavy-duty performance at any angle. Two-cycle, 25.4cc engine has a trigger throttle and reverse function. Keyed chuck holds drill shanks up to 1/2". Electronic ignition provides quick, easy starts. 31ER79 auger bit works for planting gallon potted plants, shrubs or smaller trees

| Description                   | No.    |
|-------------------------------|--------|
| Gas-Powered Hole-Making Drill | 52DD78 |
| Gallon Pot Auger Bit          | 31ER79 |



#### **Garden Hand Tools**

Ergonomic handle design

Feature heavy-duty stainless steel blades and polyethylene handles. Tools offer soft gel-grip inserts for comfortable all-day use.

| Description  | Shank     | Blade Type  | Blade<br>W | Blade<br>L | Item<br>No. |
|--------------|-----------|-------------|------------|------------|-------------|
| Trowel       | Drop Down | Round Point | 3 in       | 5 ¾ in     | 415M70      |
| Transplanter | Drop Down | Round Point | 2 ½ in     | 5 % in     | 415M71      |
| Cultivator   | Straight  | 3 Prong     | 313/64"    | 3½"        | 415M72      |



## **Manual Post Hole Diggers**

Feature straight handles for driving into hard, heavy gravel soils. 49DG94 has a safety green, premium fiberglass handle with comfort grip and 3M retroreflective tape. The 11-ga. blades are hardened and sharpened. 793PT4 15-ga. blades are sharpened.

| Handle<br>L                     | Dist. Between<br>Blade Tips | Blade Size | Head<br>Size | Brand                     | ltem<br>No. |
|---------------------------------|-----------------------------|------------|--------------|---------------------------|-------------|
| Fiberglass H                    | landle                      |            |              |                           |             |
| 48 in                           | 6 1/4 in                    | 11 in      | 5 % in       | Ability One               | 52CD22      |
| 48 in                           | 6 1/4 in                    | 11 in      | 6 in         | Seymour Midwest Structron | 49DG94      |
| 48 in                           | 6 ½ in                      | _          | _            | Nupla                     | 3MD47       |
| 72 in                           | 6 in                        | 9 ½ in     | 6 1/4 in     | Hisco                     | 796MZ8      |
| Nonconductive Fiberglass Handle |                             |            |              |                           |             |
| 48 in                           | 6 ½ in                      | _          | _            | Nupla                     | 4GFF3       |
| Hardwood Handle                 |                             |            |              |                           |             |
| 72 in                           | 5 in                        | 9 in       | 5 in         | Seymour Midwest           | 793PT4      |



# **Earth/Ice Auger**

Max. Drilling Torque: 48.97 ft/lb

Clockwise rotation

Ideal for most earth, snow, and ice drilling operations and is suitable for a variety of auger diameters. 2-cycle, 42.7cc engine offers variable throttle control. 30.2:1 gear ratio allows for fast cutting speeds. Frame assembly and heavy-duty handle help reduce vibration for greater operator comfort and allows for 2-person operation.

| Description                                   | Dia.        | L     | Item<br>No. |
|---|-------------|-------|-------------|
| Gas-Powered Earth/Ice Auger                   | _           |       | 44Y641      |
| Earth/Ice Auger Bit with Point                | 4 in        | 36 in | 44Y644      |
| Forth/lee Auger Dite with                     | 6 in        | 34 in | 44Y645      |
| Earth/Ice Auger Bits with<br>Point and Spring | 8 in        | 34 in | 44Y646      |
| ruill allu spillig                            | 10 in       | 34 in | 44Y647      |
| Dual-Blade Ice Auger Bits                     | 8 in        | 40 in | 44Y656      |
| Dual-blade ice Augel bits                     | 10 in       | 40 in | 44Y657      |
| Replacement Earth<br>Auger Point Bit          | 2 in        | _     | 44Y654      |
| Earth Auger Extension Shafts                  | 7⁄8 in      | 12 in | 44Y649      |
| Earth Auger Extension Sharts                  | 7% in       | 18 in | 44Y648      |
| Earth Auger Adapter                           | 7/s to 1 in |       | 44Y660      |